



SLACK LOOP REQUIREMENTS:
 3' TO 5' SLACK LOOP REQUIRED AT HOUSE PULL BOX AND AT LAST PULL BOX BEFORE EXITING FOR FIELD EQUIPMENT, SLACK LOOP NOT REQUIRED FOR THROUGH CABLES

NOTES:

1. PLACE A LAYER OF DRAINAGE ROCKS AT A MINIMUM OF 6" BELOW AND EXTENDING 12" FROM EACH SIDE OF THE PULL BOX. ROCKS SHALL BE COMPACTED PRIOR TO PLACEMENT OF PULL BOX
2. NATIVE MATERIAL SHALL BE USED FOR BACKFILLING CONDUIT. ROCK AND DEBRIS LARGER THAN 3 INCHES IN DIAMETER SHALL BE REMOVED. BACK FILL COMPACTION SHALL BE 95-PERCENT IN 8" LIFTS
3. PULL BOX SHALL BE DESIGNED FOR H-20-44 BRIDGE LOADING AND EQUIPPED WITH COVER DESIGNED FOR VEHICULAR TRAFFIC. MINIMUM NOMINAL SIZE OF PULL BOX SHALL BE 2' X 3' LARGER PULLS BOXES SHALL BE FURNISHED WHERE MINIMUM BEND RADIUS OF CABLE IS A FACTOR. TOP OF PULL BOX SHALL BE LEVEL WITH FINAL GRADE
4. FOR CONTROL POINT, OR CROSSING SIGNAL HOUSE THIS COVER ASSEMBLY SHALL BE USED WITH A 4' X 4' PULL BOX WITH "NOTE 3" DESIGN SPECS. COVER IS DESIGNED WITH AN OPENING FOR THE SIGNAL HOUSE CABLE CHUTE. THE SIDE OF THE COVER WITH THE CABLE CHUTE OPENING IS RATED FOR PEDESTRIAN TRAFFIC ONLY
5. ALL PULL BOXES SHALL BE PROTECTED FROM DAMAGE UNTIL FINAL PLACEMENT IN SERVICE
6. SEAL CONDUIT / CABLE WELLS WITH PLASTER OF PARIS OR OTHER SUITABLE MATERIAL

PENINSULA CORRIDOR JOINT POWERS BOARD

STANDARD DRAWINGS

APPROVED BY:
Bernard Anagnostis *Steph Chen*
 ENGINEERING MANAGER DEPUTY DIRECTOR OF ENGINEERING



SIGNAL AND COMMUNICATION
 GENERAL SIGNAL
 PULL BOX
 TYPICAL PULL BOX INSTALLATION

CADD FILE NO.: SD-5123	
REV 0	DATE 093011
SIGNAL	
STANDARD NO.: SD-5123	

REV	DATE	BY	CHK	APP	DESCRIPTION