



NOTES:

1. AUXILIARY PED GATE ARM CONFIGURATION IS NOT FOR NEW CONSTRUCTION
2. CENTER MEDIAN IS PREFERRED WHERE DISTANCE OF GATE MAST TO CENTERLINE OF STREET IS GREATER THAN 32'-6", A 9' MEDIAN WITH FLASHER AND GATE SHALL BE INSTALLED. IF OVER TWO LANES PER DIRECTION, CANTILEVER AND GATES ARE REQUIRED. MAXIMUM GATE LENGTH 32'.

| REV | DATE | BY | CHK | APP | DESCRIPTION | REV | DATE | BY | CHK | APP | DESCRIPTION |
|-----|------|----|-----|-----|-------------|-----|------|----|-----|-----|-------------|
| | | | | | | | | | | | |

PENINSULA CORRIDOR JOINT POWERS BOARD

APPROVED BY:




ENGINEERING MANAGER DEPUTY DIRECTOR OF ENGINEERING



STANDARD DRAWINGS

SIGNAL AND COMMUNICATION
 HIGHWAY GRADE CROSSING APPARATUS
 HIGHWAY GRADE CROSSING NO MEDIAN
 TYPICAL 3-LANE WITH AUXILIARY GATE ARM

| | | |
|----------------|--------|---------|
| CADD FILE NO.: | | SD-5425 |
| REV | DATE | |
| 0 | 093011 | |
| SIGNAL | | |
| STANDARD NO.: | | SD-5425 |