



NOTES:

1. FLAGS SHALL BE MANUFACTURED FROM 14 GAUGE SHEET ALUMINUM MILL FINISH SIMILAR TO ALCOA 6061-T6. MOUNT WITH 3 3/8" X 2" HEXAGON BOLTS WITH WASHER AND WING NUT
2. FACE OF SIGNS SHALL BE COATED WITH WIDE ANGLE SILVER-WHITE REFLECTIVE SHEETING
3. POST SHALL BE HOT-DIPPED GALVANIZED STEEL (ASTM 526-690) "U" CHANNEL. POSTS FURNISHED WITH 3/8" HOLES ON 1" CENTERS FOR THE ENTIRE LENGTH OF THE POST AND A POINTED END. DIMENSIONS - DEPTH 1 7/16", WIDTH 3 1/16", THICKNESS 11 GAUGE. STANDARD LENGTH IS 10'-0", LONGER LENGTHS AVAILABLE
4. FOR LETTERS, SEE SD-9101

STOP SIGN

REV	DATE	BY	CHK	APP	DESCRIPTION

PENINSULA CORRIDOR JOINT POWERS BOARD

APPROVED BY:

ENGINEERING MANAGER

DEPUTY DIRECTOR OF ENGINEERING

1250 San Carlos Avenue
San Carlos, CA 94070

STANDARD DRAWINGS		CADD FILE NO.: SD-9104
RIGHT-OF-WAY SIGNAGE	STOP SIGN	REV 0 DATE 093011 RIGHT-OF-WAY STANDARD NO.: SD-9104