



NOTES:

- SIGN SHALL BE LOCATED TO THE RIGHT OF THE TRACK AS VIEWED FROM AN APPROACHING TRAIN
- SIGN POST SHALL BE LOCATED 15 FEET (10' MIN; 20' MAX) FROM THE CENTER LINE OF TRACK. POSTS SHALL BE PLACED TO THE EAST OF MAIN TRACKS 1 OR 3 AND WEST OF MAIN TRACKS 2 OR 4.
- WHISTLING BOARD SHALL BE PLACED AS NEARLY AS PRACTICABLE ONE QUARTER MILE (1320') DISTANT FROM CROSSING OR OTHER OBSTRUCTION. WHERE THERE ARE MULTIPLE PUBLIC CROSSINGS NOT MORE THAN ONE QUARTER MILE (1320') APART, SIGN BEARING LETTER "X" LOCATED ONE QUARTER MILE (1320') IN ADVANCE OF FIRST CROSSING SHALL DISPLAY A FIGURE WHICH REPRESENTS THE NUMBER OF CROSSINGS INVOLVED
- STATION ONE MILE SIGN SHALL BE PLACED ONE MILE (5280') IN ADVANCE OF A PASSENGER STATION
- THE SIGN PANELS SHALL BE METALLIC IN CONSTRUCTION; BAKED POWER-COATED FINISH, SILK-SCREENED AND SEALED NUMERALS/LETTERS, REFLECTIVE PAINT SURFACES, UV PROTECTION COATING, AND AN ANTI-GRAFFITI COATING. SUBMIT FOR CALTRAIN APPROVAL A FULL DESCRIPTION OF MATERIALS, COATING/FINISHES AND PROCESSES UTILIZED IN THE MANUFACTURE OF THE PROPOSED SIGN
 - SIGN PANELS: 0.135" THICK MILL FINISH ALUMINUM, ALCOG 6016-T6
 - NUMBERS AND LETTERS: BLACK COLOR
 - PAINT ALL SIDES WITH LINEAR POLYURETHANE
 - SHEETING SHALL BE RETRO-REFLECTIVE PRISMATIC, ASTM 4956 CLASS III OR HIGHER
 - ANTI-GRAFFITI: COATING: EXTERIOR GRADE, SENSITIVE CLEAR MYLAR, 3M-1160
- HARDWARE: ALL HARDWARE SHALL BE VANDAL RESISTANT, AND HOT DIPPED GALVANIZED
 - BOLTS: 5/16" X 2 3/4" LONG ALUMINUM CARRIAGE BOLTS, 2024-T4 ALLOY.
 - NUTS: TAMPER RESISTANT, ALCOA OR ENGINEER APPROVED EQUAL
 - WASHERS: FLAT ALUMINUM
 - POSTS: "U" CHANNEL POST FURNISHED WITH 3/8" HOLES ON 1" CENTERS FOR THE ENTIRE LENGTH OF THE POST
- FOR TEXT AND NUMBERS, SEE SD-9101

REV	DATE	BY	CHK	APP	DESCRIPTION

PENINSULA CORRIDOR JOINT POWERS BOARD

APPROVED BY:




ENGINEERING MANAGER DEPUTY DIRECTOR OF ENGINEERING



STANDARD DRAWINGS		CADD FILE NO.:
RIGHT-OF-WAY SIGNAGE		SD-9107
WHISTLING BOARD AND STATION ONE MILE SIGN		
REV	DATE	
0	093011	
STANDARD NO.:		SD-9107