1	Chapter 4
2	Other CEQA-Required Analysis
3	This chapter identifies cumulative impacts, significant and unavoidable impacts, significant
4	irreversible environmental changes, and growth-inducing impacts.

5 4.1 Cumulative Impacts

6 CEQA defines cumulative impacts as "two or more individual effects which, when considered
7 together, are considerable," and suggests that cumulative impacts may "result from individually
8 minor but collectively significant projects taking place over a period of time" (State CEQA Guidelines
9 Section 15355). CEQA documents are required to include a discussion of potential cumulative effects
10 when those effects would be significant, and the State CEQA Guidelines suggest two possible
11 methods for assessing potential cumulative effects: 1) the "list" approach and 2) the "projection"
12 approach (State CEQA Guidelines Section 15130).

13 The focus of analysis is to identify the Proposed Project's contribution to cumulative impacts that are 14 significant and to assess whether the Proposed Project's contribution would be considerable. Where 15 the Proposed Project would have no impact on a resource or can be clearly shown to have a less-16 than-considerable contribution to potential cumulative impacts, the discussion of cumulative 17 impacts is brief. Where cumulative impacts can be shown to be less than significant in the area 18 where the Proposed Project would contribute, the discussion is also brief. Where the Proposed 19 Project has a potential to contribute considerably to a significant cumulative impact, the analysis is 20 more detailed but remains focused on the Proposed Project's potential contribution rather than 21 articulating the cumulative impact comprehensively.

22 Under CEQA, the Peninsula Corridor Joint Powers Board (JPB) is not responsible to mitigate the 23 overall cumulative impact. Specifically, the High-Speed Rail (HSR) Blended Service (described fully 24 in Section 4.1.3.1. Rail Projects Planned within the Caltrain Corridor) is not the Proposed Project 25 being analyzed in this EIR or that is being considered by the JPB for potential approval. The JPB is 26 responsible for analyzing potentially feasible mitigation to address the Proposed Project's 27 considerable contributions to identified significant cumulative impacts only. Thus, the obligation to 28 assess mitigation is limited to the "fair share" portion of a significant cumulative impact that is due 29 to the Proposed Project's considerable contribution. Other cumulative projects have a similar 30 obligation for their contributions to significant cumulative impacts. Thus, for example, in any future 31 environmental evaluation of Blended Service, the California High-Speed Rail Authority (CHSRA) 32 would be responsible for assessing feasible mitigation for its direct project impacts as well as any 33 considerable contributions to significant cumulative impacts.

34 4.1.1 Approach and Methodology

- 35 CEQA Guidelines Section 15130(b) states that the discussion of cumulative impacts should include:
- Either 1) a list of past, present, and probable future projects producing related or cumulative
 impacts or 2) a summary of projections contained in an adopted general plan or similar

1 document, or in an adopted or certified environmental document, that described or evaluated 2 conditions contributing to a cumulative impact. 3 • A discussion of the geographic scope of the area affected by the cumulative impact. 4 • A summary of expected environmental effects to be produced by these projects. 5 • Reasonable, feasible options for mitigating or avoiding the project's contribution to any 6 significant cumulative effects. 7 This EIR used a hybrid approach, explained below, to best disclose different cumulative impacts. 8 • *Projections*: This approach is used to disclose broad regional cumulative impacts related to 9 regional air quality, greenhouse gas emissions, public services and utilities, and 10 transportation/traffic (for general growth driving traffic and transit use). 11 *List Approach*: Specific projects in or adjacent to the Caltrain corridor from San Francisco to San • 12 Jose were examined for the potential, along with the Proposed Project, to result in cumulatively 13 significant localized impacts. This analysis considered transportation projects proposed for the 14 Caltrain Corridor, as well as land development projects that are planned directly adjacent to the 15 Caltrain Corridor. The list approach was used for analyzing impacts related to aesthetics, local 16 air quality, biological resources, cultural resources, electromagnetic fields and electromagnetic 17 interference (EMF/EMI), geology, soils and seismicity, hazards and hazardous materials, hydrology and water quality, land use and recreation, noise and vibration, and 18 19 transportation/traffic (for analysis of construction transportation and traffic effects and for 20 transportation improvements assumed for cumulative ridership and traffic analysis). 21 Table 4-1 summarizes the methodology used for each cumulative subject analysis as well as the 22 geographic area of analysis. 23 As described in Section 3.0, Approach to Impact Analysis, the Proposed Project would have no impact

As described in Section 3.0, Approach to Impact Analysis, the Proposed Project would have no impact
 on mineral resources or agricultural resources. Because the Proposed Project would have no impact,
 it cannot contribute to any potential cumulative impacts and these resource areas are not discussed
 further in the cumulative impact analysis.

27 4.1.2 Projections/Regional Growth Characteristics

The Association of Bay Area Governments (ABAG) projections of land use and population growth were used to estimate overall growth in San Francisco, San Mateo and Santa Clara Counties. These projections are shown in Table 4-2. The Santa Clara Valley Transportation Authority (VTA) travel demand forecasting model (VTA Model¹) VTA was used to develop the travel forecasts for development and growth through the year 2040 in the corridor. The ridership estimates² and the ABAG projections of land use and growth were also used to model traffic conditions along the corridor.

¹ VTA's transportation model is an analytical tool that predicts travel patterns based upon spatial relationship between socio-economic characteristics of population and employment locations, tripmaking and economic-related activities in those areas and interconnecting transportation facilitates, including roadway, transit and bicycle and pedestrian modes of travel. The VTA *Local Transportation Model Consistency Guidelines* (2009) outlines how the model may be used by local jurisdictions to develop the local transportation models.

² <u>As noted in Section 3.14, ridership is reported using boardings in this EIR, not boardings plus alightings.</u>

Resource Issue	Cumulative Method	Geographic Area of Impact
Aesthetics	List	Caltrain ROW and vicinity
Air Quality	Projection (Criteria Pollutants)	Criteria pollutants: San Francisco Bay Area Air Basin
	List (Toxic Air Containnants)	Toxic air contaminants: Caltrain ROW and immediate vicinity
Biological Resources	List	Terrestrial species: Caltrain ROW and immediate vicinity
		Aquatic species: ROW, vicinity and downstream
Cultural Resources	List	Caltrain ROW and adjacent
EMF/EMI	List	Caltrain ROW and adjacent
Geology, Soils and Seismicity	List	Caltrain ROW and adjacent
GHG Emissions and Climate	Projection (GHG emissions)	The planet (GHG emissions)
Change	List (vulnerability to Climate change impacts)	San Francisco Peninsula (vulnerability to climate change Impacts)
Hazards and Hazardous Materials	List	Caltrain ROW and adjacent
Hydrology and Water Quality	List	Caltrain ROW and downstream water bodies
Land Use and Recreation	List	Caltrain ROW and adjacent
	Projection (recreation demand)	
Noise and Vibration	List	Caltrain ROW and adjacent
Population and Housing	Projection	San Francisco, San Mateo, and Santa Clara Counties
Public Services and Utilities	List (Construction Disruption)	Caltrain ROW and adjacent (Construction)
	Projection (Operations)	Service areas of regional providers to project sites (Operations)
Transportation/ Traffic	List (Construction Analysis and Transportation Improvements) Projection (Operational Traffic)	Caltrain ROW, roadways crossing ROW and roadways near stations (traffic level of service, bicycle and pedestrian facilities)
		San Francisco Peninsula (regional traffic, regional transit systems)

1 Table 4-1. Summary of Cumulative Impact Methodology

2

	Total Population				Occupied Housing Units			Employment (Total Jobs)				
								%				%
Area	2010	2040	Change	% Diff	2010	2040	Change	Diff.	2010	2040	Change	Diff.
San Francisco County	805,235	1,076,305	271,070	34	345,811	447,248	101,437	29	568,730	760,230	191,500	34
San Mateo County	718,451	899,169	180,718	25	257,837	316,868	59,031	23	346,320	462,870	116,550	34
Santa Clara County	1,781,642	2,411,704	630,062	35	604,204	819,607	215,403	36	906,270	1,263,834	1357,564	40

1 Table 4-2. 2010–2040 Population, Housing and Employment Growth in the Counties of the Caltrain 2 Corridor

Note: The data for 2040 is based on data derived used in the VTA system ridership model. As explained in Appendix I, the socioeconomic data used for the ridership model was based on available ABAG SCS forecasts in late 2012 when project EIR analysis began. The ABAG 2013 projections released in fall 2013 are slightly different, but the differences are not large enough to have a significant influence on the ridership forecasts or on the EIR traffic analysis. Source: U.S. Census 2010; Appendix I, *Ridership Technical Memorandum*.

3

4 **4.1.3 Projects Considered**

Reasonably foreseeable future projects are defined as the projects that have been adopted or have
otherwise demonstrated likelihood to occur based on documentation from project sponsors.

7 There are three types of cumulative projects considered: rail projects planned within the Caltrain

8 Corridor, other regional transportation improvements, and land development adjacent to the

9 Caltrain ROW. For land development along the Caltrain ROW, the JPB requested lists of reasonably

10 foreseeable projects from cities along the Caltrain and additional projects were added based on

11 general knowledge. The geographic areas considered for cumulative impact analyses vary by

12 individual resource, and can include different scales of impact (such as for criteria pollutants or

13 greenhouse gases). The geographic area is noted in the beginning of each subject analysis.

14 Table 4-3 presents the applicable planning jurisdictions, the potential cumulative impact areas, the

15 estimated construction schedule associated with each cumulative project, and the distance of the

16 cumulative project to the Caltrain ROW. The project numbers in Table 4-3 correspond to the project

17 numbers in Figure 4-1. Figure 4-1 shows the approximate location of each project with respect to

18 the Caltrain ROW and proposed project components. The column titled "Potential Cumulative

19 Impact Areas" generally summarizes the anticipated cumulative impact areas known at this time.

20 Project information listed in Table 4-3 is based on information supplied by the cities the

- 21 surrounding Caltrain ROW and available environmental documents and information posted on
- agency websites.

The source of cumulative project information, unless otherwise noted in text below, is the
 references noted at the end of Table <u>4-3</u> 4-2.



- 3700 Bayshore Boulevard 21
- 1225 Floribunda Avenue 22
- 23 Mi Rancho Market
- Gas and Shop 24
- Sadigh Mixed Use 25
- Nazareth Terrace 26
- 27 Cal Water Office
- 28 800 & 888 N. San Mateo Drive Apartments
- 29 2090 Delaware Apartments
- San Carlos Transit Village 30
- Wheeler Plaza Redevelopment 31
- 32 145 Monroe Street
- 33 Classics at Redwood City
- 34 Finger Avenue
- 35 201 Marshall Street
- 36 Lathrop PARC

- 43 145 Hawthorne
- 44 195 Page Mill Road (Park Plaza)
- 3445 Alma Street (Alma Plaza) 45
- 100 Moffett Boulevard 46
- 47 209-405 West Evelyn
- 100-200 West Evelyn 48
- 49 902 Villa Street
- 871 West Evelyn 50
- 51 San Antonio Station
- 52 Northpark Apartments
- South Whisman Precise Plan 53
- 54 **Tripointe Homes**
- Pacific Press Courtyard 55
- 56 Carmel Lofts
- Santa Clara Station Area Plan 57
- 58 Earthquakes Stadium

- 59 Former FMC site, aka Coleman Highline (PDC98-104, PD12-019)
- 60 Alameda (PD12-017)
- Morrison Park Townhomes (PD06-094) 61
- 785-807 The Alameda (PDC13-007) 62
- Baseball Stadium (PP05-214) 63
- Park Avenue Senior and Family Housing (PDC13-012) 64
- OSH West San Carlos (H13-008) 65
- Lawrence Station Area Plan 66
- Atherton Town Hall Complex 67
- 68 Millbrae BART Station TOD
- El Camino Real/Downtown Specific Plan (Menlo Park) 69
- 389 El Camino Real 71
- 72 Diridon Station Area Plan
- Hillsdale Station Area Plan 75
- 76 North Fair Oaks Community Plan

Note: This figure replaces Figure 4-1 from the Draft EIR.

Figure 4-1 **Projects Considered in the Cumulative Analysis**

Peninsula Corridor Electrification Project

N

Miles

Table 4-3. Projects Considered In the Cumulative Analysis

Project Number	Jurisdiction	Project Title	Potential Cumulative Impact Areas	Estimated Construction Schedule	Location relative to the Proposed Project (miles)	Potential Conflicts between Proposed Project and Cumulative Project?
Rail Pro	jects Planned within th San Jose – San Francisco	California High- Speed Rail Phase 1 Blended Service (including Transbay Terminal Center and Downtown Extension Project)	Construction : Separated in time; but overlap from San Jose to San Francisco. Air Quality; Biological Resources, Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality; Noise; Public Services and Utilities; Transportation and Traffic. Operations : Aesthetics; Air Quality; Biological Resources; EMF/EMI; GHG emissions; Hydrology and Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.	Estimated completion by sometime between 2026 and 2029; assumed construction sometime after <u>2020</u> 2019 but before 2026/2029.	In the Caltrain corridor from San Francisco to San Jose and the 1.3 miles from San Francisco Transbay Transit Center to the San Francisco 4th and King Station	None, but dDesign of passing tracks, and Diridon and Millbrae Stations may require realignment of some Proposed Project OCS poles and wires (as well any proposed grade separations).Track upgrades and reconfiguration to increase line speeds up to 110 mph and potential improvements at the 4 th and King Street station and system improvements depending on revenue service date and systems to be determined.
<u>1b</u>	<u>San Francisco</u>	<u>Transbay Transit</u> <u>Center and</u> <u>Downtown</u> <u>Extension Project</u>	 <u>Construction:</u> Separated in time; but overlap from north of 16th street to 4th and King Street in San Francisco. Air Quality; Biological Resources, Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality; Noise; Public Services and Utilities; Transportation and Traffic. <u>Operations:</u> Aesthetics; Air Quality; Biological Resources; EMF/EMI; GHG emissions; Hydrology and Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic. 	TTC in construction now. <u>Assumed DTX</u> construction sometime after 2020 but before 2026/2029.	In the Caltrain corridor from north of 16 th Street to 4 th and King and the 1.3 miles from 4 th and King to the San Francisco Transbay Transit Center	<u>Construction within 4th and King</u> <u>station/yard for DTX may disrupt</u> <u>Caltrain service and will require</u> <u>coordination between TJPA and</u> <u>Caltrain. As DTX no longer includes full</u> <u>platform reconfiguration at 4th and</u> <u>King, this is no longer a DTX issue.</u>
2	San Jose – Merced	San Jose to Merced High-Speed Train (as part of Phase 1 blended system)	 Construction: Separated in time but overlap at Diridon Station only. Air Quality; Biological Resources, Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology & Water Quality; Noise, Public Services and Utilities; Transportation and Traffic. Operations: Aesthetics, Air Quality; Biological Resources; EMF/EMI; GHG emissions; Hydrology and Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic. 	2021-2026	Overlap with Caltrain corridor only at San Jose Diridon Station; project then heads southeast away from Caltrain ROW	None, but design of Diridon Station may require realignment of some Proposed Project OCS poles and wires.
3	San Jose – San Francisco	Future Full Electrified	Construction: No construction impacts, only replacement of rolling stock. Operations: Air Quality, EMF/EMI, GHG Emissions, Noise and Vibration.	Complete between 2020 and 2026/2029	Caltrain ROW	None
4	Santa Clara, San Jose	Caltrain South Terminal (Phase II and III)	 Construction: Overlap between Santa Clara and Tamien Stations and in time. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology & Water Quality; Noise, Public Services and Utilities; Transportation and Traffic. Operations: Service increases included in other projects so impacts only related to permanent physical improvements. Aesthetics, Hydrology and Water Quality; and Land Use and Recreation. 	2017-2023	Caltrain ROW	None but construction will require coordination.
5	City of Menlo Park, City of East Palo Alto, City of Union City, City of Fremont, City of Newark, City of Redwood City	Dumbarton Rail Corridor	 Construction: No construction in Caltrain corridor, but construction east of corridor in Redwood City. No overlap in time or location. Air Quality; Biological Resources, Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology & Water Quality; Noise, Public Services and Utilities; Transportation and Traffic. Operations: Air Quality; GHG emissions; Noise and Vibration; Public Services and Utilities; Transportation and Traffic. 	Sometime after 2020	Caltrain ROW	None

Project Number	Jurisdiction	Project Title	Potential Cumulative Impact Areas	Estimated Construction Schedule	Location relative to the Proposed Project (miles)	Potential Conflicts between Proposed Project and Cumulative Project?
6	Stockton – San Jose and Stockton – Merced	ACEforward Program	Construction: No construction in Caltrain ROW (covered by South Terminal Project) so no overlap in area, but potential overlap in time. Nearest potential area of construction would be Alviso wetlands area. Air Quality; Biological Resources, Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology & Water Quality; Noise, Public Services and Utilities; Transportation and Traffic. Operations: Overlap from Santa Clara to San Jose only. Air Quality: GHG emissions: Noise and Vibration:	2018–2022 or after	Within Caltrain ROW from San Jose to Santa Clara; then forks east towards City of Fremont along Union Pacific Rail Road track	None
			Public Services and Utilities; Transportation and Traffic.			
7	City of San Jose, City of Fremont, City of Santa Clara, City of Emeryville, City of Oakland	Capital Corridor Oakland to San Jose, Phase 2	Construction: No construction in Caltrain ROW (covered by South Terminal Project) so no overlap in area. Nearest area of construction would be Santa Clara double track area. Potential overlap in time. Air Quality; Biological Resources, Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology & Water Quality; Noise, Public Services and Utilities; Transportation and Traffic.	2016–2023 or after	Within Caltrain ROW from Santa Clara to San Jose only	None
			Operations: Overlap from Santa Clara to San Jose only. Air Quality; GHG emissions; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.			
8	City of San Jose, City of Santa Clara	BART Silicon Valley Extension	Construction: Overlap in time and in area from Santa Clara Station to Diridon Station. Air Quality; Biological Resources, Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology & Water Quality; Noise, Public Services and Utilities; Transportation and Traffic.	2012-2023	Caltrain ROW at Santa Clara Station	None but connections between BART and Caltrain stations at Diridon and Santa Clara will require coordination
			Operations: Overlap in adjacent operations from Santa Clara to San Jose only. Aesthetics; Air Quality; EMF/EMI; GHG emissions; Noise and Vibration; Public Services and Utilities.			
9	San Jose – San	California State Rail	Construction: No construction in corridor.	No construction in	Caltrain ROW from San	None
	Francisco	<i>Plan</i> (Coast Daylight)	Operations: Air Quality, GHG emissions, Noise and Vibration, Transportation and Traffic.	corridor; Service date start by 2020	Jose to San Francisco	
10	San Jose – San Francisco	Freight Rail Future Plans	Construction: No construction needed for current freight trains; Use of taller trains in future <u>could</u> may require construction to provide clearances at bridges and tunnels. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology & Water Quality; Noise, Public Services and Utilities; Transportation and Traffic.	Incremental over time; specific timing unknown	Caltrain ROW	Trains taller than current trains <u>could</u> may -require construction to provide clearances at bridges and tunnels. New freight will have to comply with FRA
			Operations: Air Quality; GHG emissions; Noise and Vibration; Public Services and Utilities.			temporal separation requirements.
11	City of San Bruno	San Bruno Grade Separation Project	Construction: No overlap in time but overlap in location in San Bruno. Air Quality; Biological Resources, Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology & Water Quality; Noise, Public Services and Utilities; Transportation and Traffic.	2010-2014	Caltrain ROW	None; project will be completed before Proposed Project.
			Operations: Aesthetics; Noise and Vibration; Transportation and Traffic.			
12	Cities of San Mateo, Santa Clara, and San	Other Caltrain Planned Corridor	Construction: Would overlap in location and some improvements would overlap in time. Air Quality; Biological Resources, Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous	2013 onward	Caltrain Corridor and project vicinity	None, but may require coordination during construction.
	Jose and other location	Improvements	Operations: Aesthetics; Air Quality; GHG emissions; Noise and Vibration; Public Services and Utilities			Potential OCS pole and wire relocation depending on timing of platform improvements at 4 th and King.
70	City of Millbrae	BART Millbrae Tail Tracks	Construction: Overlap south of Millbrae Station. Potential overlap in time. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology & Water Quality; Noise, Public Services and Utilities; Transportation and Traffic.	Assumed by <u>2020</u> 2019	Caltrain ROW	May require coordination on placement of OCS poles and wires south of Millbrae BART station.
			Operations: Aesthetics; Air Quality; EMF/EMI; GHG emissions; Noise and Vibration; Public Services and Utilities.			

Project Number	Jurisdiction	Project Title	Potential Cumulative Impact Areas	Estimated Construction Schedule	Location relative to the Proposed Project (miles)	Potential Conflicts between Proposed Project and Cumulative Project?
Other Re	gional Transportation	Improvements				
13	City and County of San Francisco	Central Subway	Construction: Overlap in time and adjacent area at San Francisco 4th and King Station. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology & Water Quality; Noise, Public Services and Utilities; Transportation and Traffic.	2010-2019	Caltrain ROW	None but construction coordination may be required if both projects are active near San Francisco 4th and King
			Operations: Air Quality; EMF/EMI; GHG emissions; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.			Station at same time.
14	City and County of San Francisco	San Francisco Municipal Railway Bay Trolley Coach	Construction: Overlap at 16th Street crossing of Caltrain ROW and possibly in time. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology & Water Quality; Noise, Public Services and Utilities; Transportation and Traffic.	Sometime before 2019	Passes over Caltrain tunnel ROW	Potential conflict requires technical solution to resolve crossing of two incompatible OCS power systems at
		Re-Routing	Operations: Air Quality; EMF/EMI; GHG emissions; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.			16 th Street crossing
15	Caltrans, VTA (Various jurisdictions)	Major Highway Improvements on the Peninsula	Includes following projects: VTA Silicon Valley Express Lanes Program; U.S. Highway 101 improvements including HOV/T lane from San Francisco county line to Whipple Avenue; express lanes between Whipple Ave. and Cochrane Road, and auxiliary lanes from Marsh Road to Embarcadero Road to State Route 85; and U.S. Highway 101 corridor interchange improvements at Candlestick Point (San Francisco), Produce Avenue (South San Francisco), SR 92 (San Mateo), Oregon Expressway (Palo Alto), and Zanker Road (San Jose).	Varies	Less than 0.2	None
			Construction: Possible overlap in time but no overlap in location. Air Quality; Biological Resources; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality; Noise, Public Services and Utilities; Transportation and Traffic.			
			Operations: Air Quality; GHG emissions; Hydrology & Water Quality; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.			
16	Caltrans, VTA (Various jurisdictions)	RTP Major Non- Highway Improvements on the Peninsula	Includes following projects: Embarcadero Streetcar (San Francisco); Southern Intermodal Terminal and MUNI T-Line Extension (San Francisco); Future grade separations in San Mateo County; Bus Rapid Transit along El Camino Real; Palo Alto Caltrain Station and Bus Transit Center Expansion; Grade separation at Rengstorff Avenue; Tasman Express Long T double tracking: Mineta San Jose International Airport Automated People Mover Connector.	Varies	Caltrain ROW; and 1.0 ^a	Coordination needed between grade- separation projects and OCS pole and wire design.
			Construction: Possible overlap in time and location. Air Quality; Biological Resources; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Noise, Public Services and Utilities; Transportation and Traffic.			
			Operations: Air Quality; EMF/EMI; GHG emissions; Hydrology & Water Quality; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.			
73	City and County of San Francisco	I-280 Teardown/ "Boulevard"/ 4th and King	Construction: No overlap in time but overlap in location at 4th and King Station, Caltrain ROW south to 23 rd Street. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology & Water Quality; Noise, Public Services and Utilities; Transportation and Traffic.	Unknown	4th and King Station, Caltrain ROW south to 24rd Street, I-280 in San Francisco and additional areas	Yes. Project likely to be after <u>2020</u> 2019 based on current status of planning. May require new tunnel for
		underground station	Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.			Caltrain/HSR from 23 rd to 4 th and King and/or complete rebuild of 4 th and King Station.
<u>74</u>	City of Brisbane	Geneva Avenue to US 101/Candlestick Point Interchange	Construction: Overlap in location at Tunnel Avenue and proposed extension of Geneva Avenue, and in time. Air Quality: Cultural Resources: GHG emissions: Hazards and Hazardous Materials: Hydrology & Water Quality: Noise, Transportation and Traffic.	2015-2020	Caltrain ROW	Coordination require for OCS poles and grade separation at Tunnel Avenue.
			Operations: Aesthetics. Air Quality: GHG emissions: Hydrology & Water Quality: Noise and Vibration: <u>Transportation and Traffic.</u>			

Project Number	Jurisdiction	Project Title	Potential Cumulative Impact Areas	Estimated Construction Schedule	Location relative to the Proposed Project (miles)	Potential Conflicts between Proposed Project and Cumulative Project?
Land Dev	velopment in the Vicin	ity and Adjacent to Ca	altrain ROW			, , ,
17	City and County of San Francisco	4th and King Railyards Redevelopment	Construction: No overlap in time but overlap in location at 4th and King. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology & Water Quality; Noise, Public Services and Utilities; Transportation and Traffic.	Unknown (likely after <u>2020</u> 2019)	Adjacent, and in OCS/ESZ area outside ROW.	Potentially depending on station configuration. Project likely to be after <u>2020</u> 2019 based on current status of
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.			planning. May require relocation of OCS pole at wires at station.
18	City of Brisbane	Brisbane Baylands Specific Plan	Construction: Overlap in location and directly adjacent. Air Quality; Biological Resources, Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	Phased over 20 years (2015–2035)	Adjacent, and in OCS/ESZ area outside ROW	Proposed Project will have minor encroachments on land included in specific plan which won't change
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.			overall plans but may require minor adjustments.
19	City of Brisbane	Opus Office	Construction: No overlap in location. Air Quality; Biological Resources, Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	Unknown; likely before 2020 2019	0.10	None
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.			
20	City of Brisbane	3710–3760 Bayshore Boulevard	Construction: No overlap in location. Air Quality; Biological Resources, Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	<u>Unknown; likely before</u> 2020 2019	0.02	None
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.			
21	City of Brisbane	3700 Bayshore Boulevard	Construction: No overlap in location. Air Quality; Biological Resources, Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	<u>Unknown; likely before</u> 2020 2019	0.02	None
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.			
68	City of Millbrae	Millbrae BART Station TOD	Construction: No overlap in location but directly adjacent. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	<u>Unknown; likely before</u> 2020 2019	Adjacent	None, but may require coordination during construction.
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.			
22	City of Burlingame	1225 Floribunda Avenue	Construction: No overlap in location. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	<u>Unknown; likely before</u> 2020 2019	0.08	None
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.			
23	City of San Mateo	Mi Rancho Market	Construction: No overlap in location. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	<u>Unknown; likely before</u> 2020 2019	0.02	None
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.			

Project Number	Jurisdiction	Project Title	Potential Cumulative Impact Areas	Estimated Construction Schedule	Location Propose (miles)
24	City of San Mateo	Gas and Shop	Construction: No overlap in location. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	<u>Unknown: likely before</u> 2020 2019	0.13
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.		
25	City of San Mateo	Sadigh Mixed Use	Construction: No overlap in location. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	<u>Unknown; likely before</u> 2020 2019	0.03
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.		
26	City of San Mateo	Nazareth Terrace	Construction: No overlap in location. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	<u>Unknown: likely before</u> 2020 2019	0.06
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.		
27	City of San Mateo	Cal Water Operations Office	Construction: No overlap in location. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	<u>Unknown; likely before</u> 2020 2019	0.11
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.		
28	City of San Mateo	800 & 888 N. San Mateo Drive Apartments	Construction: No overlap in time or location. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	2012-2013	0.11
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.		
29	City of San Mateo	2090 Delaware Apartments	Construction: No overlap in time or location. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	2013-2014	0.10
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.		
30	City of San Carlos	San Carlos Transit Village	Construction: Overlap in location. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	To be determined	Adjacen OCS/ES ROW
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.		
31	City of San Carlos	Wheeler Plaza Redevelopment	Construction: No overlap in location. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	Unknown; possibly before <u>2020</u> 2019	0.10
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.		

tion relative to the osed Project	Potential Conflicts between Proposed
es)	Project and Cumulative Project?
	None
	None
	None
	None
	None
	None
	None
cent and in	Caltrain coordinating with project
ESZ area outside	regarding OCS/ESZ location and
 7	project landscaping/vegetation.
	None

Project Number	Iurisdiction	Project Title	Potential Cumulative Impact Areas	Estimated Construction Schedule	Locatio Propose (miles)
32	City of Redwood City	145 Monroe Street	Construction: No overlap in time or location. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	2013-2014	0.07
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.		
33	City of Redwood City	Classics at Redwood City	Construction: No overlap in location. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	2013-2015	0.08
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.		
34	City of Redwood City	Finger Avenue	Construction: No overlap in location. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	<u>Unknown: likely before</u> 2020 2019	0.11
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.		
35	City of Redwood City	201 Marshall Street	Construction: No overlap in location or time. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	2012-2014	0.03
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.		
36	City of Redwood City	Lathrop PARC	Construction: No overlap in time but overlap in location and directly adjacent. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	2011-2014	Adjacen ESZ are
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.		
37	City of Redwood City	Crossing/900	Construction: No overlap in location but directly adjacent. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	2013-2015	Adjacen
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.		
67	Town of Atherton	Atherton Town Hall Complex	Construction: No overlap in location but directly adjacent. Air Quality; Biological Resources, Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	Unknown; possibly by <u>2020-2019</u>	Adjacen
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.		
71	City of Menlo Park	389 El Camino Real	Construction: No overlap in location or time. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	2013/2014	0.06
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.		

tion relative to the osed Project es)	Potential Conflicts between Proposed Project and Cumulative Project?
	None
	None
	None
	None
	None
cent, and in OCS/	Proposed Project will have minor
area outside ROW	encroachment for OCS/ESZ which may constrain uses directly along Caltrain
	ROW but should not affect project
cent	during construction
cent	None but may require coordination
	None

Project Number	Iurisdiction	Proiect Title	Potential Cumulative Impact Areas	Estimated Construction Schedule	Location Propose (miles)
38	City of Menlo Park	500 El Camino Real	Construction: No overlap in location. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	<u>Unknown: likely before</u> 2020 2019	0.05
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.		
39	City of Menlo Park	1300 El Camino Real	Construction: No overlap in location. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	<u>Unknown; likely before</u> 2020 2019	0.08
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.		
40	City of Menlo Park	1460 El Camino Real	Construction: No overlap in time or location. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	2012-2014	0.11
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.		
41	City of Menlo Park	1706 El Camino Real Medical Office	Construction: No overlap in time or location. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	2012-2013	0.14
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.		
69	City of Menlo Park	El Camino Real/ Downtown Specific Plan	Construction: Overlap in time, location and adjacent. Air Quality; Biological Resources, Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	Next 30 years	Adjacen ESZ area
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.		
42	City of Palo Alto	395 Page Mill Road	Construction: No overlap in location. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	Applicant withdrew application. Construction unknown.	0.12
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.		
43	City of Palo Alto	145 Hawthorne	Construction: No overlap in location. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	Unknown; possible before <u>2020</u> 2019	0.07
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.		
44	City of Palo Alto	195 Page Mill Road (Park Plaza)	Construction: Overlap in location and adjacent. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	In construction 2013 – 2014, Unknown; likely before 2019	Adjacen OCS/ESZ ROW
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.		

tion relative to the osed Project es)	Potential Conflicts between Proposed Project and Cumulative Project?
	None
	None
	None
	None
cent, and in OCS/ area outside ROW	Proposed Project would have minor encroachments on land included in Specific Plan, which would not change overall plans but may require minor adjustments.
	None
	None
cent, and in ESZ area outside	Proposed Project would have <u>minor_no</u> encroachments on <u>private</u> land included in project , which would not change overall plans but may require <u>minor adjustments</u> . PS5 Option 2 is a lso adjacent to this project. <u>As noted</u> <u>in Section 3.1, coordination between</u> <u>the projects may be necessary</u> <u>concerning vegetative screening.</u>

Project Number	Jurisdiction	Project Title	Potential Cumulative Impact Areas	Estimated Construction Schedule	Propose (miles)
45	City of Palo Alto	3445 Alma Street (Alma Plaza)	Construction: No overlap in time or location. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	2009-2013	0.08
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.		
46	City of Mountain View	100 Moffett Boulevard	Aesthetics, Air Quality; Cultural Resources; Geology, Soils, and Seismicity, Greenhouse Gas Emission and Climate Change, Hazards and Hazardous Materials, Land Use and Recreation; Noise and Vibration; Public Services and Utilities, and Transportation and Traffic.	<u>Unknown; likely before</u> 2020 2019	0.03
47	City of Mountain View	209–405 West Evelyn	Construction: No overlap in time or location. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	2013-2014	0.03
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.		
48	City of Mountain View	100–200 West Evelyn	Construction: No overlap in time but overlap in location and adjacent. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	2012-2014	Adjacer Propos OCS/ES
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.		ROW
49	City of Mountain View	902 Villa Street	Construction: No overlap in time or location. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	2013-2014	0.08
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.		
50	City of Mountain View	871 West Evelyn	Construction: No overlap in time but directly adjacent. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	2012-2013	Adjacer
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.		
51	City of Mountain View	San Antonio Station	Construction: No overlap in location but directly adjacent. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	Unknown; possibly before <u>2020</u> 2019	Adjacer
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.		
52	City of Mountain View	Northpark Apartments	Construction: No overlap in time or location. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	2013-2014	0.09
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.		
53	City of Mountain View	South Whisman Precise Plan	Construction: No overlap in location. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	Unknown; possibly before <u>2020</u> 2019	0.20
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.		

tion relative to the osed Project es)	Potential Conflicts between Proposed Project and Cumulative Project?
	No
	No
	No
cent and in osed Project ESZ area outside	Proposed Project would have minor encroachments on land included in project, which would not change overall plans but may require minor adjustments
	No
cent	No
cent	No, but may require coordination during construction.
	No
	No

Project Number	Jurisdiction	Project Title	Potential Cumulative Impact Areas	Estimated Construction Schedule	Location relative to the Proposed Project (miles)	Potential Conflicts between Proposed Project and Cumulative Project?
54	City of Mountain View	Tripointe Homes	Construction: No overlap in location. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	2013-2015	0.08	No
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.			
55	City of Mountain View	Pacific Press – Courtyard	Construction: Overlap in location. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	Unknown; possibly before <u>2020</u> 2019	Adjacent and in Proposed Project OCS/ESZ area outside	Proposed Project would have minor encroachments on land included in project, which would not change
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.		ROW	overall plans but may require minor adjustments.
56	City of Sunnyvale	Carmel Lofts	Construction: No overlap in time or location. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	2012-2014	0.08	No
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.			
66	City of Sunnyvale, City of Santa Clara	Lawrence Station Area Plan	Construction: Overlap in location. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	Unknown; possibly before <u>2020</u> 2019	Adjacent and in Proposed Project OCS/ESZ area outside ROW	Proposed Project would have minor encroachments on land included in Area Plan, which would not change overall plans but may require minor adjustments.
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.			
57	City of Santa Clara	Clara Santa Clara Station Area Plan	Construction: Overlap in location. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	Unknown; likely before <u>2020 2019</u>	Adjacent and in Proposed Project OCS/ESZ area outside	Proposed Project will have minor encroachments on land included in Area Plan which won't change overall
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.		ROW	plans but may require minor adjustments.
58	City of San Jose	Earthquakes Stadium	Construction: No overlap in time or location but directly adjacent. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	2012-2014	Adjacent	None
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.			
59	City of San Jose	Former FMC site, aka Coleman Highline	Construction: No overlap in location but directly adjacent. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	Construction to start in 2014 or 2015	Adjacent	None but may require coordination during construction.
		(PDC98-104, PD12- 019)	Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.			
60	City of San Jose	Alameda (PD12- 017)	Construction: No overlap in location. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	Construction to start in 2015	0.06	None
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.			

Project Number	Jurisdiction	Project Title	Potential Cumulative Impact Areas	Estimated Construction Schedule	Location relative to the Proposed Project (miles)	Potential Conflicts between Proposed Project and Cumulative Project?
61	City of San Jose	Morrison Park Townhomes (PD06- 094)	Construction: No overlap in time or location. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	2012-2014	0.08	None
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.			
62	City of San Jose	785-807 The Alameda (PDC13- 007)	Construction: No overlap in location. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	2014–2015	0.11	None
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.			
63	City of San Jose	Baseball Stadium (PP05-214)	Construction: Overlap in location and adjacent. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	Unknown	Adjacent and in Proposed Project OCS/ESZ area outside ROW	Proposed Project would have minor encroachments on land included in project, which would not change
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.			overall plans but may require minor adjustments.
64	City of San Jose	Park Avenue Senior and Family Housing (PDC13-012)	Construction: No overlap in location. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	2015-2017	0.02	None
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.			
65	City of San Jose	an Jose OSH West San Carlos (H13-008) (Now Lowe's)	Construction: Overlap in location and directly adjacent. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	Approved; construction planned; date unknown	Adjacent and in Proposed Project OCS/ESZ area outside	Proposed Project would have minor encroachments on land included in project, which would not change
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.		ROW	overall plans but may require minor adjustments.
72	City of San Jose	Diridon Station Area Plan	Construction: Overlap in location and adjacent. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic.	Over next 2–3 decades	Adjacent and in Proposed Project OCS/ESZ area outside	Proposed Project would have minor encroachments on land included in Area Plan, which would not change overall plans but may require minor adjustments.
			Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic.		ROW	
75	<u>City of San Mateo</u>	<u>Hillsdale Station</u> <u>Area Plan</u>	 Construction: Air Quality, Aesthetics, Transportation and Traffic, Noise and Vibration, GHG emissions, Geology and Soils, Hydrology and Water Quality: Hazards and Hazardous Materials Operations: Aesthetics, Air Quality, GHG Emissions, Noise and Vibration, Public Services and Utilities; Public Services, Transportation and Traffic: Hazards and Hazardous Materials 	2011-2031	<u>Adjacent and in</u> <u>Proposed Project</u> <u>OCS/ESZ area outside</u> <u>ROW</u>	<u>Current plan only applies to Caltrain is</u> <u>Caltrain requests redesignation of</u> <u>Caltrain ROW. Proposed Project would</u> <u>require minor reconfiguration of</u> <u>current vision for development on site</u> <u>if PS4. Option 1 or Option 2 but would</u> <u>not be major obstacle to plan</u> <u>implementation. PS4. Option 4 would</u> <u>require no reconfiguration.</u>

Project Number	Jurisdiction	Project Title	Potential Cumulative Impact Areas	Estimated Construction Schedule	Location relative to the Proposed Project (miles)	Potential Conflicts between Proposed Project and Cumulative Project?
<u>76</u>	<u>San Mateo County</u>	<u>North Fair Oaks</u> <u>Community Plan</u>	 Construction: Adjacent. Air Quality: Cultural Resources: Geology & Soils: GHG emissions: Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic. Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic. 	<u>Next 25 to 30 years</u>	<u>Adjacent to OCS/ESZ</u> <u>and adjacent to SWS1,</u> <u>Option 1</u>	<u>Proposed Project is not located in plan</u> <u>area, but in adjacent Samtrans-owned</u> <u>land. Would not require any</u> <u>reconfiguration of land uses. May</u> <u>increase chance of commercial/light</u> <u>industrial near tracks. but will not</u> <u>preclude residential.</u>
77	<u>City and County of San</u> <u>Francisco</u>	<u>Mission Bay</u> <u>Redevelopment Plan</u>	 Construction: Adjacent. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality, Noise, Public Services and Utilities; Transportation and Traffic. Operations: Aesthetics, Air Quality; GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic. 	<u>Much completed but</u> <u>development will</u> <u>continue in following</u> <u>decades</u>	<u>Adjacent to OCS/ESZ</u>	<u>Plan designates rail ROW for public use</u> <u>including rail uses. PCEP is consistent</u> <u>with plan.</u>
78	<u>City and County of San</u> <u>Francisco</u>	<u>Visitacion</u> <u>Valley/Schlage Lock</u> <u>Plan</u>	 Construction: Adjacent. Air Quality; Cultural Resources; Geology & Soils; GHG emissions; Hazards and Hazardous Materials; Hydrology and Water Quality. Noise. Public Services and Utilities; Transportation and Traffic. Operations: Aesthetics. Air Quality: GHG emissions; Hydrology & Water Quality; Land Use and Recreation; Noise and Vibration; Public Services and Utilities; Transportation and Traffic. 	<u>Next 10 to 20 years</u>	<u>Adjacent to OCS/ESZ</u> and adjacent to PS2	Plan covers area around Bayshore Station and designated residential on Schlage Lock site next to JPB ROW (project helps residential by reducing diesel emissions/noise). PS-2 adjacent to light industrial designated area on UPRR land that may also be park or light industrial. PS-2 would not be inconsistent with plan designations of adjacent area.

^a The 1.0 mile distance corresponds to the San Jose Airport – VTA Connector PRT System Project. The Caltrain ROW is 1.0 mile from Mineta San Jose International Airport.

Sources: ABAG and MTC. 2013a; ABAG and MTC, No date; BART 2013; Brisbane Baylands 2010; LTK 2013; Caltrain 2013b; Caltrain 2013b; CCJPA 2013; CHSRA 2012a; CHSRA 2012c; CHSRA 2012c; CHSRA 2012d; CHSRA 2012c; CHSRA 2010c; CHSRA 2013c; City of San Jose 2012; City of Palo Alto 2013c; City of San Jose 2013c; City of San Mateo 2013c;

Peninsula Corridor Joint Powers Board

This page intentionally left blank.

Other CEQA-Required Analysis

1 **4.1.3.1** Rail Projects Planned within the Caltrain Corridor

2 High-Speed Rail Blended Service from San Jose to San Francisco

Blended service will include a number of different actions by different parties. The CHSRA is
 responsible for high-speed rail service planning. The TJPA is responsible for the Transbay Transit
 Center and Downtown Extension which would serve both Caltrain and HSR, in addition to other
 transit providers at the TTC. The JPB is responsible for Caltrain electrification to Fourth and King
 and ultimately for Caltrain service to TTC once DTX and TTC are completed. Both HSR blended
 service and the TTC/DTX project are discussed together below for the ease of reader review of
 blended service improvements overall.

10 This project-<u>HSR Blended Service</u> is Project #1<u>a</u> on Table 4-3 and in Figure 4-1.

11 The CHSRA previously prepared a final program-level environmental analysis of a statewide HSR 12 system (CHSRA 2005). The program-level analysis included an evaluation of various alignments for 13 high-speed service. In 2008, the CHSRA issued a final program-level environmental analysis of the 14 Bay Area to Central Valley alignments. This analysis identified the Pacheco Pass and the Caltrain 15 alignment as its preferred alternative. There were several legal challenges to the final program-level 16 environmental analysis of the environmental analysis for the Bay Area to Central Valley alignments 17 that resulted in court orders to make certain revisions to the Final Program EIR. Revisions to the 18 Final Program EIR were completed in 2010 and 2012. Subsequent to certification of the 2012 19 revisions, the CHSRA confirmed that the selected route for the California HSR system is the Pacheco 20 Pass alignment from the Central Valley to the Bay Area and the Caltrain corridor for the Bay Area 21 segment from San Jose to San Francisco.

In 2009, CHSRA began project-level analysis of a grade-separated, four-track system from San Jose
 to San Francisco, including an alternatives analysis and a supplemental alternatives analysis. The
 four-track proposals by CHSRA were controversial along the Peninsula corridor, with a diversity of
 opinions about the project. Taking into account these concerns, CHSRA decided in 2012 to change its
 approach for the Peninsula corridor and embrace a Blended Service concept in which Caltrain and
 CHSRA would share operations on the corridor and CHSRA would primarily be located within the
 Caltrain right of way (CHSRA 2012a).

- Blended Service would consist of electrified Caltrain trains³ and HSR trains mostly using the same
 tracks from San Francisco to San Jose, with a section of passing tracks for scenarios with up to four
 HSR trains per peak hour per direction (pphpd). There would be no Blended Service south of Santa
 Clara. Caltrain and CHSRA have engaged in planning level studies of Blended Service to demonstrate
 its viability. The details of Blended Service are not available at this time. Additional planning and
- 34 design will be done later and evaluated in a separate environmental evaluation of Blended Service
- 35 by the CHSRA. For purposes of this cumulative analysis, two representative Blended Service
- 36 scenarios are considered: the "6-2" scenario and the "6-4" scenario:

³ The Peninsula Corridor Electrification Project would replace approximately 75 percent of the revenue service fleet with EMUs for service from San Francisco to San Jose. Additional funding would need to be secured beyond that available for the Proposed Project to provide sufficient rolling stock to have 100 percent electrified service from San Francisco to San Jose. Diesel service would continue from Gilroy to San Jose under all scenarios.

- Under the "6-2" scenario, up to two HSR trains pphpd in addition to the six Caltrain trains pphpd
 planned under the Proposed Project has been analyzed by Caltrain. This scenario would not
 require passing tracks.
- Under the "6-4" scenario, up to four HSR trains pphpd in addition to six Caltrain trains pphpd
 planned under the Proposed Project has been analyzed by Caltrain. This scenario would require
 one section of passing track (see discussion below).

7 Additional "Core Capacity" projects (as described in the nine-party MOU⁴ for the High Speed Rail 8 Early Investment Strategy For a Blended System in the San Francisco to San Jose Segment Known as 9 the Peninsula Corridor of the Statewide High-Speed Rail System) including needed upgrades to 10 stations, tunnel, bridges, potential passing tracks, other track modifications and rail crossing 11 improvements including selected grade separations will be required to accommodate the mixed 12 traffic capacity requirements of high-speed rail service and commuter services on the Caltrain 13 corridor. However the specific Core Capacity projects have not been identified or defined at this 14 time. These projects would be identified in future discussions and evaluations between CHSRA and 15 Caltrain and other agencies. Core Capacity projects would be subject to separate, project-level 16 environmental evaluation by the implementing agency/agencies.⁵

- Table 4-4 presents some key conceptual assumptions that have been studied by Caltrain about
 Blended Service at this time. These assumptions are used in the cumulative impact analysis in this
 EIR.
- As noted in Table 4-4, the cumulative analysis in this EIR presumes speeds for Blended Service up to
 110 mph in light of the following considerations:
- The blended system has been simulated by Caltrain at speeds of up to 110 mph and shows a
 blended system to be viable.
- The 2012 Partially Revised Program EIR for the Bay Area to Central Valley states the following:
 "The HST could operate at maximum speeds of 100–125 mph along the Peninsula providing 30minute express travel times between San Francisco and San Jose." (CHSRA 2012f)
 - CHSRA has confirmed that with speeds up to 110 mph, a 30-minute express travel time can be achieved between San Jose and San Francisco as required by Prop 1A (CHSRA 2013a).
 - If it is determined to be necessary to analyze speeds greater than 110 mph in the future, additional simulations will be performed to understand the viability and implications of the speed range identified by CHSRA in the 2012 Partially Revised Program EIR.
- If speeds beyond 110 mph are ultimately proposed by CHSRA for the Caltrain corridor, track
 improvements may be necessary on the route to allow for an increase in top speed as well as
 any FRA-mandated safety improvements, and they will be evaluated in the separate
 environmental document for evaluating HST service on the San Francisco Peninsula.

27

28

29

30

31

⁴ Memorandum of Understanding (MOU). *High Speed Rail Early Investment Strategy for a Blended System in the San Francisco to San Jose Segment known as the Peninsula Corridor of the Statewide High-Speed Rail System*. City and County of San Francisco, San Francisco County Transportation Authority, Transbay Joint Powers Authority, San Mateo County Transportation Authority, Santa Clara Valley Transportation Authority, City of San Jose, and MTC. See discussion in Chapter 1, *Introduction*.

⁵ <u>Core Capacity projects do not include DTX/TTC, which is a separate project that has already been reviewed under CEQA and NEPA and TTC is already under construction.</u>

Subject	Assumption	Source	
Number of HSR trains (per peak hour per direction)	Up to 4 ^a	CHSRA 2012 Business Plan, <i>Estimating High-Speed Train Operating and Maintenance Cost for the CHSRA 2012 Business Plan</i> (CHSRA 2012b)	
		CHSRA 2014 Business Plan Ridership and Revenue Technical Memorandum, Draft 2 014 Business Plan. (CHSRA 2014b)	
Number of trains/day for 2040	Up to 40 round trips (80 trains <u>) up to</u> <u>53 round trips (106 trains) ^b</u>	CHSRA 2012 Business Plan, Estimating High-Speed Train Operating and Maintenance Cost for the CHSRA 2012 Business Plan (CHSRA 2012b).	
		CHSRA 2014 Business Plan, Service Planning Methodology, CHSRA 2014c)	
Hours of operation	5 a.m. to 12:30 a.m.	San Francisco to San Jose Preliminary Alternatives Analysis Report Appendix K (CHSRA 2010a)	
Study Speeds	Up to 79 mph and up to 110 mph ^c	Caltrain/California HSR Blended Operations Analysis (LTK 2012)	
Ridership Forecasts	See Table 4-5		
Merging HSR tracks from Diridon to Santa Clara	Two tracks from San Jose Diridon Station to Santa Clara Station	Conceptual locations described in <i>Caltrain/California HSR Blended</i> Operations Analysis (LTK 2012) and <i>Caltrain/HSR Blended Service Plan</i> Operations Considerations Analysis (LTK 2013)	
Potential number of passing tracks	One location (see description in text)	Same as above.	
Storage yards and maintenance facilities	Specific location(s) not known (see text discussion)	Caltrain/HSR Blended Service Plan Operations Considerations Analysis (LTK 2013)	
HSR Station Descriptions	Transbay Terminal <u>Transit Center</u> (San Francisco)	Transbay Transit Center Program Final SEIS/EIR (2004) and subsequent addenda. (TJPA 2004 and subsequent)	
	<u>4th and King Interim Station (San</u> <u>Francisco), if necessary</u> Millbrae	<u>CHSRA 2014 comment letter on the PCEP DEIR (see Volume II)</u> San Francisco to San Jose Supplemental Alternatives Analysis Report (CHSRA 2010b).	
	Redwood City (to be determined)	California High-Speed Rail Program Revised 2012 Business Plan: Building California's Future (CHSRA 2012a)	

Table 4-4. Key Assumptions in High-Speed Rail Blended Service Conceptual Description

Peninsula Corridor Joint Powers Board

Subject	Assumption	Source
	San Jose Diridon	San Francisco to San Jose Supplemental Alternatives Analysis Report (CHSRA 2010b)
		San Jose Visual Design Guidelines (CHSRA/City of San Jose 2012)
		San Jose to Merced Preliminary Alternatives Analysis (CHSRA 2010e)
Planned grade separations	Center Street (if Millbrae Station constructed as in SF–SJ Supplemental Alternatives Analysis Report) Other grade separations ^d (to be determined)	San Francisco to San Jose Supplemental Alternatives Analysis Report (CHSRA 2010b)

Notes:

^a The <u>CHSRA 2012 Revised Business Plan Ridership and Revenue Forecasting (CHSRA 2012c) and the Draft</u> 2014 Business Plan Ridership and Revenue Technical Memorandum, (CHSRA 2014b) presumes Phase 1 Blended Service would have up to four trains per peak hour and up to four trains per off-peak hour. This EIR presumes up to 40 to 53 daily round-trip high-speed trains in 2040 based on the CHSRA 2012 Business Plan, *Estimating High-Speed Train Operating and Maintenance Cost for the CHSRA 2012 Business Plan* (CHSRA 2012b) which assumed 40 round-trip trains per day and the CHSRA 2014 Business Plan Service Planning Methodology (CHSRA 2014c) which assumes up to 53 round-trip trains per day. There is no explicit statement in the 2014 Business Plan of the daily number of HSR trains for the San Francisco to San Jose segment. The Draft 2014 Business Plan Service Planning Methodology document (CHSRA 2014c) includes an assumption of 53 daily round trip trains starting in 2029 and continuing beyond 2040. Caltrain's Blended Service planning to date. The ridership included in this EIR is based on the latest 2014 CHSRA Business Plan has not studied the 2014 Business Plan estimates because the plan was released on February 7, 2014 and conceptual Blended Service studies completed in 2012 and 2013. Thus, this Draft EIR is based on the 40 daily round-trip high-speed trains consistent with Blended Service studies completed by Caltrain. The exact number of HSR trains along the corridor is unknown. The subsequent CHSRA project-level environmental evaluation will address proposed high-speed train service levels along the San Francisco Peninsula.

^b As noted in the prior footnote, this Draft EIR presumes 40 to 53 daily round-trip high-speed trains up to 2040.

^c As described in text above, Caltrain has simulated Blended Service operations for speeds up to 79 mph and up to 110 mph and thus this EIR evaluates these two speed scenarios in this cumulative analysis. If it is determined to be necessary to analyze speeds greater than 110 mph in the future, additional simulations will be performed to understand the viability and implications of the 100 to 125 mph speed range identified by CHSRA in the 2012 Partially Revised Program EIR (CHSRA 2012f). If speeds beyond 110 mph are ultimately proposed by CHSRA for the Caltrain corridor, they will be evaluated in the separate environmental document for evaluating HST service on the San Francisco Peninsula.

^d Blended Service is not defined as a fully grade-separated system. See discussion in text about other potential grade separations.

The blended system will be part of the roughly 540-mile HST system travelling between San
 Francisco and Los Angeles.

3 Ridership

- 4 HSR ridership has been evaluated by CHSRA for 2030 under low and high ridership scenarios. Table
- 5 4-5 shows Blended Service ridership estimates for 2030 under the low and high scenarios for the
- 6 Peninsula corridor stations. These estimates are for HSR ridership only; no joint HSR/Caltrain
- 7 service ridership modeling has been completed. No estimate of blended system ridership with a
- 8 Redwood City HSR station was included in the *2012 Revised Business Plan* (CHSRA 2012a) or the
- 9 Draft *2014 Business Plan* (CHSRA 2014a). For the purposes of this EIR, all HSR ridership is assumed to be in addition to Caltrain ridership to analyze maximum potential traffic and other impacts due to
- to be in addition to Caltrain ridership to analyze maximum potential traffic and oth
 increased ridership at combined HSR/Caltrain stations.
- 12 CHSRA released its Draft *2014 Business Plan* (CHSRA 2014a) in early February 2014 which presents
- higher ridership estimates than in the 2012 Revised Business Plan; these estimates, which were draft
- 14 at the time of the Draft EIR, have since been finalized and are shown in These estimates are provided
- 15 in-Table 4-5 below.

16Table 4-5. Projected Blended Service High-Speed Rail 2029/2030 Weekday Daily Boardings at17Peninsula Corridor Stations without Optional Redwood City HSR Station

Station	Revised 2012 Business Plan (CHSRA 2012c)		Draft <u>Final</u> 2014 (CHSRA	Draft <u>Final_</u> 2014 Business Plan (CHSRA 2014a)	
	2030-Low Scenario	2030-High Scenario	2029 -Phase 1 Blended	<u>2040 – Phase 1</u> <u>Blended</u>	
San Francisco (TTC)	11,500	20,500	15,400	<u>19,700</u>	
Millbrae	2,600	4,200	6,900	<u>8,500</u>	
San Jose	3,300	6,100	8,200	<u>10,200</u>	
Note: This table reports boardings, not boardings plus alightings					

18

19 Station Improvements

Station design is at a preliminary conceptual level except for the Transbay Transit Center (TTC). The
 concepts for station improvements at San Francisco (TTC), Millbrae, Redwood City, and San Jose
 Diridon Stations to accommodate HSR/Caltrain Blended Service are described below.

23 San Francisco Transbay Transit Center (TTC) and Downtown Rail Extension (DTX)

24 <u>This is Project 1b in Table 4-3.</u> The Transbay Joint Powers Authority (TJPA), consisting of the City
 25 and County of San Francisco, the State of California, Alameda-Contra Costa Transit District, the JPB,
 26 and Caltrans (ex officio) is leading the planning and implementation of the TTC and Downtown Rail
 27 Extension (DTX) projects.

- 28 The TTC/DTX is an independent project with multiple purposes of supporting Caltrain extension to
- 29 <u>downtown, improved transit services and coordination, as well as facilitating future high-speed rail</u>
- 30 <u>service to the TTC. However, because it is an integral part of Blended Service, it is discussed in</u>
- 31 <u>concert with the discussion of blended service.</u>

A Final EIS/EIR for the DTX and TTC projects and the related redevelopment project (collectively,
 the Transbay Program) was completed in 2004. A number of addenda have been completed since

- 3 2004. TIPA is presently preparing a Supplemental EIS/EIR for certain changes to the Transbay
- 4 Program as noted below.
- 5 The Transbay Program consists of three components.
- A new, multi-modal transportation facility (the TTC) at the site of the former Transbay Terminal at First and Mission Streets, which is currently under construction.
- A <u>1.3 2</u>-mile extension (the DTX) of Caltrain commuter rail service from its current San
 Francisco terminus at 4th and King Streets to the new TTC.
- Development of a mix of new and transit-oriented uses on publicly-owned property in the
 vicinity of the new TTC, including an estimated 3,000 new homes and mixed-use commercial
 development.
- Other features analyzed in the 2004 Final EIS/EIR are an off-site bus storage facility, new bus ramps
 connecting to the Bay Bridge, a temporary bus facility for use during the construction of the TTC,
 and a reconfigured Caltrain layover yard. The new TTC has also been designed to serve the proposed
 HSR system. As part of the DTX project, the track between Caltrain's existing 4th and King Street
 terminal and the new downtown terminal would be electrified.
- Phase 1 of the project consists of the TTC and is presently under construction with expectedcompletion in approximately 2017.
- Phase 2 consists of the <u>1.3</u>2-mile extension of Caltrain service to the TTC from the existing Caltrain
 terminal at Fourth and King Street. The Supplemental EIS/EIR currently being prepared by TJPA will
 analyze proposed modifications to Phase 2, including the DTX track curvature entering the TTC,
 extension of platform rail levels to accommodate HSR requirements, an intercity bus facility, vent
 shaft enlargements and other minor refinements. The DTX work is on hold due to a funding gap and,
 thus, it appears likely that DTX will be completed after the Proposed Project. Scheduling is
 depending on funding availability.
- The prolonged delay of the DTX may require an interim high-speed rail terminal station at the 4th
 and King Station. As necessary, the CHSRA would evaluate this interim terminal station in a
 subsequent, project-level environmental impact analysis and document.
- 30 The critical aspects for Blended Service are as follows:
- HSR service (up to four trains pphpd) would terminate or originate at the TTC with multiple
 dedicated platforms.
- The new line between the 4th and King Caltrain Station and TTC would be electrified as part of
 the DTX project.
- Caltrain service, once electrified, would extend to the TTC with the completion of the DTX. In
 concept, Caltrain service has been studied with split service between the 4th and King Caltrain
 Station and TTC, with some trains terminating at each station.

38 San Francisco 4th and King Station and Approach

Based on current planning, the HSR service would not stop at either the San Francisco 4th and King
 Caltrain Station or the future 4th and Townsend underground station (unless, as noted above, DTX)

- 1is delayed beyond the point that interim HSR service to 4th and King is possible in which case an2interim terminal would operate at 4th and King). It would continue underground through the 4th2Image: A service of the service o
- and Townsend Station to the TTC. The surface station at 4th and King would be for Caltrain service
 terminating at that point. The underground 4th and Townsend Station would be a stop for Caltrain
 service terminating at the TTC. The platforms of the two stations would be connected vertically by
 stairs, escalators, and elevators to an underground mezzanine.
- Pursuant to current DTX designs, DTX tracks would begin just north of 16th Street with new tracks
 and sidings as the alignment approaches the 4th and Townsend and the 4th and King Stations. The
- 9 surface tracks and underground tracks would separate at approximately Berry Street.⁶
- 10 The Proposed Project would electrify the 4th and King Station and yard, including the existing six
- platforms and 12 tracks. This would allow for electrified operations to start in <u>2020 2019</u>. At present, the Proposed Project does not include funding to reconfigure the station and yard.
- 13 The station configuration <u>at the Fourth and King Station assumed covered</u> in the TJPA 2004 EIS/EIR
- 14 and approved by the TJPA would reconstruct the storage yard with included three surface platforms
- and six tracks on the southern portion of the existing facility and add a new one-platform
- 16 underground station on the northern portion near Townsend and Fourth Street. TJPA indicated in
- 17 its comment on the PCEP Draft EIR that full platform reconfiguration is not part of DTX. Although
- 18 the station reconfiguration was assumed in the original 2004 EIS/EIR project description, TJPA
- 19 clarified that full platform reconfiguration is assumed to be a separate project by others. A potential
- 20 <u>future project (currently unfunded) to reconfigure the 4th and King platforms is described separately</u>
- 21 <u>below under discussion of Caltrain projects.</u>
- 22 The schedule for completion of the DTX has not yet been determined <u>and funding for platform</u>
- 23 reconfiguration is uncertain at this time, thus, it is possible that station reconfiguration, if
- 24 appropriate, will occur sometime after 2020 2019, when funding is available. Should funding
- become available prior to 2020 2019, it may be possible to reconfigure the station and yard prior to
 electrification.

27 Millbrae Station

- 28 The most recent design for a HSR station at Millbrae was presented in the 2010 HSR Alternatives
- Analysis for the Peninsula corridor and would include two dedicated HSR tracks and platforms atgrade. The Caltrain station would be split level with one platform at-grade and one below-grade (CHSRA 2010c). A grade separation at Center Street in Millbrae would be necessary because of the changes at the Millbrae Station (CHSRA 2010a). The station design will need to be reevaluated to ensure appropriate scale for the blended system.
- -----

34 **Redwood City Station**

- 35 No decision has been made by CHSRA or Caltrain or any other party that there will be a Redwood
- City Station. Based on the designs in the 2010 HSR Alternatives Analysis, the Redwood City Station
- 37 could be either elevated or below-grade in a trench. If there is a Redwood City HSR station that is
- 38 elevated or below-grade, then there would also be grade separations at the nearby street crossings
- 39 (CHSRA 2010a). The station design will need to be reevaluated to ensure appropriate scale for the
- 40 blended system.

⁶ The Mission Bay Drive crossing would remain at-grade based on current designs.

1 San Jose Diridon Station

- 2 The San Jose Diridon Station would have dedicated platforms for HSR. The design of the station
- improvements has been the subject of prior and ongoing study. CHSRA is currently in the process of
 refining design alternatives for the HSR alignment through San José. These alternatives will be
 evaluated by the CHSRA when they prepare the San José to Merced and/or San Francisco to San José
- 6 HSR EIR/EIS documents.
- 7 At present, potential designs for the San Jose Diridon Station show either an elevated or a below-
- grade station. Depending on the vertical placement of the station, the approaches from the south and
 the north to the station could be in a tunnel or on an aerial structure. The approaches would likely
 transition from two tracks to four tracks as they approach the station to allow for four tracks in the
 station (CHSRA 2010a, 2010b, 2010e).
- 12 Additional Trackage

13 Merging HSR Tracks from Diridon to Santa Clara

Blended Service would include two new dedicated HSR tracks between the San Jose Diridon Station
and just north of the Santa Clara Caltrain Station (CHSRA 2010b). The dedicated tracks would
proceed northward on either an aerial structure or in a tunnel from the San Jose Diridon Station and
merge into middle of the Caltrain mainline at grade north of Control Point (CP) De La Cruz which is
just north of the Caltrain Santa Clara Station (CHSRA 2010b).

19 Passing Tracks

- 20 As described above, the "6-4" scenario would require passing tracks. It is important to note that no 21 decisions have been made about the locations of passing tracks; the subsequent design and 22 environmental process will define the actual proposed passing track locations. The locations studied 23 to date are identified to support a "proof of concept" approach only. Proposed passing track 24 locations could include other variations than those studied to date. However, because the locations 25 analyzed in the capacity studies completed to date are the only locations that have been studied, these locations are used in this EIR to disclose at a very general level what the impacts of passing 26 27 tracks may be with Blended Service.
- Passing tracks would be added to the existing tracks in limited segments of the corridor to be used
 by HSR trains to bypass Caltrain trains stopping at stations. The conceptual information used in this
 EIR about passing tracks comes from two planning studies completed in 2012 and 2013.
- Caltrain/California HSR Blended Operations Analysis (LTK 2012).
- Caltrain/California HSR Blended Operational Analysis Supplemental Analysis Requested by
 Stakeholders: Service Plan/Operations Considerations Study (LTK 2013).
- Passing tracks required for operational overtakes (i.e., one same-direction train passing another) would improve the integration of Caltrain and HSR services, avoid either service being substantially delayed at a passing track location by the other service, and are required to support the "6/4" scenario. The operational studies completed by Caltrain (LTK 2012; LTK 2013) provide further information on the overtake's operational requirements; the reader is referred to those studies for further detail.
- 40 Five potential overtake locations have been conceptually defined and are shown in Figure 4-2.:



Figure 4-2 Potential Passing Track Locations Studied to Date Peninsula Corridor Electrification Project

1	•]	Մhe North 4-Track։
2 3	C	10.2-mile-long, 4-track segment of tracks from milepost (MP) 5 (San Francisco) to MP 15.2 (Burlingame), including existing four-track configuration at Bayshore Station.
4	C	Includes four Caltrain stations: Bayshore, South San Francisco, San Bruno, and Millbrae.
5	C	Includes one HSR station: Millbrae.
6	• 1	The Long-Middle 4-Track:
7 8	C	9.1-mile-long, 4-track segment of tracks from MP 18.1 (San Mateo) to MP 27.2 (south part of Redwood City), including existing 4-track configuration south of Redwood City.
9 10	C	Includes five Caltrain stations: Hayward Park, Hillsdale, Belmont, San Carlos, and Redwood City.
11	•]	The Short-Middle 4-Track:
12	C	6.1-mile-long, 4-track segment of tracks from MP 18.1 (San Mateo) to MP 24.2 (San Carlos).
13	C	Includes four Caltrain stations: Hayward Park, Hillsdale, Belmont, and San Carlos.
14	• [The Middle 3-Track:
15 16	C	15.6-mile-long, 3-track segment of tracks from MP 18.1 (San Mateo) to MP 33.7 (southern part of Palo Alto)
17 18	C	Includes ten Caltrain stations: Hayward Park, Hillsdale, Belmont, San Carlos, Redwood City, Atherton, Menlo Park, Palo Alto, Stanford, and California Avenue.
19	• [The South 4-Track:
20 21 22	C	7.8-mile-long, 4-track segment of tracks from MP 33.8 (Mountain View) to MP 41.6 (Santa Clara south of Lawrence Station), including existing 4-track configuration at Lawrence Station.
23	C	Includes four Caltrain stations: San Antonio, Mountain View, Sunnyvale and Lawrence.
24 25 26 27 28	The f corri HSR half train	four-track overtake options allow two dedicated tracks for HSR for a limited segment of the dor—one track per direction. The three-track overtake option allows one dedicated track for for a limited segment of the corridor—one track that must be shared in both directions. One- of the three-track overtake supports northbound trains and the other half supports southbound as.
29 30 31	The perfo Thos	operational studies completed by Caltrain (LTK 2012; LTK 2013) evaluated HSR and Caltrain ormance of different passing tracks options; the reader is referred to those studies for details. se operational studies are incorporated by reference into this EIR.
32	Othe	er Trackage Improvements
33	At pi	resent the Caltrain corridor is rated for speeds of up to 79 mph. Blended Service at speeds

greater than 79 mph up to 110 mph will require additional track improvements that could include
 upgrades of tracks, trackbeds, ties, interlockings as well as possible curve realignments and other

- 1 improvements.⁷ Potential improvements have not been identified at this time but would be
- 2 identified as part of subsequent Blended Service design.
- 3 CHSRA Storage Yards and Maintenance Facilities
- 4 When the four-track, fully grade-separated HSR system was contemplated in the Peninsula corridor,
- 5 a storage/maintenance facility of approximately 100 acres was contemplated at several locations,
- 6 including San Francisco, Brisbane/Bayshore, San Francisco International Airport and Santa Clara.
- 7 The Brisbane/Bayshore site was described as the most feasible (CHSRA 2010a).
- Given that Caltrain and CHSRA are now committed to a blended system on the Peninsula, previous
 assumptions for HSR operations and maintenance facilities have changed. The CHSRA will be reevaluating the Peninsula for site-specific and operationally feasible locations that would meet the
 needs for maintenance and storage of high speed train sets. Suitable potential sites will be identified
 and evaluated through the blended system environmental process, a later process that is separate
 and distinct from this EIR.

14 Grade Crossing Improvements/Grade Separations

- 15 Apart from the grade separation assumed in the 2010 HSR Alternatives Analysis at Center Street in
- Millbrae and the grade separations that would be necessary for the HSR aerial section from San Jose
 Diridon Station to north of the Santa Clara Caltrain Station (described previously above), no
 decisions have been made regarding the potential additional at-grade crossing improvements or
 grade separations necessary for Blended Service. To date, Blended Service has been defined as a
 partially grade-separated system, not a fully grade-separated system.
- FRA's regulatory requirements for at-grade crossings greater than 79 mph are as follows (FRA
 2014):
- For 110 mph or less: At-grade crossings are permitted. States and railroads cooperate to
 determine the needed warning devices, including passive crossbucks, flashing lights, two
 quadrant gates (close only "entering" lanes of road), long gate arms, median barriers, and
 various combinations. Lights and/or gates are activated by circuits wired to the track (track
 circuits).
- For 110 to 125 mph: FRA permits crossings only if an "impenetrable barrier" blocks highway
 traffic when train approaches.
- 30 Above 125 mph: No at-grade crossings permitted.
- As noted above, at this time, Caltrain has only studied Blended Service operations up to 110 mph which have been shown to meet Prop 1A required timeframes for HSR service. For speeds greater than 79 mph up to 110 mph, there may be a need for additional at-grade crossing improvements; specific improvements would need to be identified during subsequent Blended Service design.
- Additional grade separations may also be desirable for operational purposes. Further, when
 combining HSR service with Caltrain and other tenant railroads, cumulative localized traffic and

⁷ As described above, Caltrain has evaluated Blended Service for speeds up to 79 mph and up to 110 mph; thus these two scenarios are evaluated in this EIR. Any consideration of speeds in excess of 110 mph would need to be evaluated in subsequent Blended Service design for viability and evaluated in the separate environmental evaluation by CHSRA for Blended Service.

- noise impacts are likely at many locations along the corridor and grade separations at some
 locations may be considered in the environmental analysis for Blended Service as mitigation.
- 3 The separate environmental process for the Blended Service will need to analyze all impacts related
- 4 to Blended Service including noise and traffic impacts related to increased train trips along the
- 5 Caltrain corridor as well as the impacts of any proposed passing tracks and any proposed at-grade
- 6 crossing or grade-separation improvements.

7 Other Core Capacity Projects

In addition to the improvements described above concerning stations, passing tracks, other track
 improvements and grade separations, there will be additional Core Capacity projects including
 improvements to tunnels and bridges or other improvements needed to accommodate mixed traffic
 capacity requirements of HSR service and Caltrain commuter rail service. These other projects
 would be identified as part of subsequent Blended Service design and would be evaluated in the

13 separate environmental document prepared by CHSRA.

14 Trackage Rights

- 15 <u>Union Pacific owns intercity passenger rail rights along the Caltrain Corridor. While the PCEP does</u>
- 16 not propose intercity rail, HSR service would be intercity rail. The TRA between the PCJPB and
- 17 <u>Union Pacific contemplates that additional parties may seek to share the right of way to provide</u>
- 18 intercity passenger service and requires the parties to negotiate with such third parties in good faith
- 19 (Section 2.7(b)). According to the 2014 Business Plan, CHSRA does propose to use the Caltrain
- 20 <u>Corridor as part of future blended service. If high-speed intercity rail operations are to occur along</u>
- 21 the Caltrain corridor, then CHSRA would need to obtain intercity passenger rail rights from Union
- 22 Pacific. Given that current CHSRA plans are to operate in the Caltrain Corridor, it is appropriate that
- 23 <u>the PCEP EIR conceptually analyze blended service operations in the Caltrain Corridor.</u>⁸

24 Schedule

- Based on the CHSRA *Revised 2012 Business Plan* (and the Draft *2014 Business Plan*), HSR service
 could be extended to San Jose by 2026 and to San Francisco by sometime between 2026 and 2029. It
 is possible, but unknown at this time, that San Jose Diridon would serve as a temporary northern
 terminus for the HSR system between the time service is provided to San Jose and the time that
 service is provided to San Francisco.
- 30 As noted above, while TTC is under construction, the exact timing for the DTX and Core Capacity
- 31 projects is not known at present.

⁸ If CHSRA is not able to obtain the intercity passenger rights to operate in the Caltrain Corridor, then there would be no blended service on the tracks that Caltrain shares with freight today. In concept, CHSRA would then be required to operate on separate tracks from those covered by the TRA, which may have different environmental impacts than the proposed blended service. This issue is more appropriately addressed in the project-level environmental analysis of high-speed rail operations on the Caltrain Corridor. It would be highly speculative for the IPB to analyze an alternative high-speed rail system for the corridor that has neither been designed nor is proposed by CHSRA at this time in the cumulative analysis for the PCEP EIR. The IPB has analyzed cumulative impacts based on the current concept for blended service by CHSRA (as well as the other cumulative projects) at this time; if any subsequent change in the blended service concept is ultimately considered, any resulting impacts are best addressed in the separate environmental review process for blended service.

1	San Francisco Transbay Transit Center (TTC) and Downtown Rail Extension (DTX)
2	This project is Project #1b on Table 4-3 and in Figure 4-1.
3	<u>The Transbay Joint Powers Authority (TJPA), consisting of the City and County of San Francisco, the</u>
4	<u>State of California, Alameda-Contra Costa Transit District, the JPB, and Caltrans (ex officio) is leading</u>
5	<u>the planning and implementation of the TTC and Downtown Rail Extension (DTX) projects.</u>
6 7 8 9	<u>A Final EIS/EIR for the DTX and TTC projects and the related redevelopment project (collectively, the Transbay Program) was completed in 2004. A number of addenda have been completed since 2004. TJPA is presently preparing a Supplemental EIS/EIR for certain changes to the Transbay Program.</u>
10	The Transbay Program consists of three components.
11	• <u>A new, multi-modal transportation facility (the TTC) at the site of the former Transbay Terminal</u>
12	at First and Mission Streets, which is currently under construction.
13	• <u>An approximately 1.3-mile extension (the DTX) of Caltrain commuter rail service from its</u>
14	<u>current San Francisco terminus at 4th and King Streets to the new TTC and a new underground</u>
15	<u>Caltrain station at 4th and Townsend.</u>
16 17 18	• Development of a mix of new and transit-oriented uses on publicly-owned property in the vicinity of the new TTC, including an estimated 3,000 new homes and mixed-use commercial development.
19	Other features analyzed in the 2004 Final EIS/EIR are an off-site bus storage facility, new bus ramps
20	connecting to the Bay Bridge, a temporary bus facility for use during the construction of the TTC,
21	and a reconfigured Caltrain layover yard. The new TTC has also been designed to serve the proposed
22	HSR system. As part of the DTX project, the track between Caltrain's existing 4th and King Street
23	terminal and the new downtown terminal would be electrified.
24	<u>Phase 1 of the project consists of the TTC and is presently under construction with expected</u>
25	<u>completion in approximately 2017.</u>
26	<u>Phase 2 consists of the 1.3-mile extension of Caltrain service to the TTC from the existing Caltrain</u>
27	<u>terminal at Fourth and King Street.</u>
28	A Supplemental EIS/EIR currently being prepared by TJPA will analyze proposed modifications to
29	Phase 2, including the DTX track curvature entering the TTC, extension of platform rail levels to
30	accommodate HSR requirements, an intercity bus facility, vent shaft enlargements and other minor
31	refinements. The DTX work is on hold due to a funding gap and, thus, it appears likely that DTX will
32	be completed after the Proposed Project. Scheduling is depending on funding availability.
33	California High-Speed Rail San Jose to Merced (as part of Phase 1 Blended System)
34	This is project number 2 in Table 4-3 and Figure 4-1.
35	The San Jose to Merced section of the California HSR system is a 125-mile corridor running from the
36	Diridon Station in Downtown San Jose to Merced, where the system would connect to the Central

- Valley section (Merced to Fresno).⁹ From the Diridon Station in San Jose, trains in the San Jose to
 Merced section would travel south to Gilroy, east through the Pacheco Pass, and then to Chowchilla
 before turning north to Merced.
- San Jose to Merced will be the linkage between San Francisco/San Jose corridor and the Central
 Valley portion of the HST system and upon completion would be part of the 540-mile Phase 1
- 6 Blended System.

The proposed stations are Diridon Station in San Jose, a station in Gilroy, and a downtown Merced
station. The San Jose to Merced section of the California HSR system would overlap with the
Proposed Project at Diridon Station in San Jose. Capital costs for the San Jose to Merced section are
estimated to be \$5.4 billion dollars. The purpose of this project and the entire California HSR System
is to provide a new mode of high-speed intercity travel that would link major metropolitan areas of
the state and provide added capacity to meet increases in intercity travel demand in California.

- 13 Environmental review for the San Jose to Merced section began in 2009 and a Draft EIS/EIR is
- 14 currently being developed. A Preliminary Alternatives Analysis was prepared in 2010 and a
- 15 Supplemental Alternatives Analysis Report, which evaluated potential route alignments that will be
- 16 considered in the Draft EIR/EIS, was prepared in 2011. The Preliminary Alternatives Analysis
- (CHSRA 2010X) evaluated multiple options for the San Jose Approach subsection and recommended
 the SR 87/I-280 Alignment Alternative. This alignment would be on an aerial structure heading
- southward from the Diridon Station along the Caltrain ROW to approximately Park Avenue and then
 would depart from the Caltrain ROW to cross the I-280/SR 87 interchange and then come parallel to
- 21 the Caltrain ROW next to the Tamien Station. For the Monterey Highway subsection, the alignment 22 would continue south from the Tamien Station along the Caltrain ROW on an aerial structure to
- would continue south from the Tamien Station along the Caltrain ROW on an aerial structure to
 Almaden Road, then be an at-grade section from Almaden Road to near Pullman Way and transition
 back to an aerial structure from near Pullman Way to just north of the Capitol Expressway. While the
 San Jose to Merced section proceeds further south, the project limits for the Caltrain Peninsula
 Corridor Electrification Project end just south of Pullman Way. Unlike the Blended Service, there
 would be no shared track between Caltrain and HSR for the HSR San Jose to Merced segment as HSR
- would have dedicated tracks.
- The San Jose to Merced HSR Project EIR/EIS will tier from the Final Statewide Programs EIR/EIS
 and the Final Bay Area to Central Valley HSR EIR/EIS. Service is planned to commence along this
 segment in 2026.

32 Caltrain Projects

33 Future Full Electrified (San Francisco to San Jose)

- 34 This is project number 3 in Table 4-3 and Figure 4-1.
- 35 As described in Chapter 2, *Project Description*, the Proposed Project budget of \$440 million for
- 36 rolling stock would provide for electrification of approximately 75 percent of the revenue service
- 37 fleet from San Francisco to San Jose. It is the JPB's long-term plan to fully electrify the service from
- 38 San Francisco to San Jose for the same reasons supporting the Proposed Project. In addition, to
- 39 accommodate Blended Service (as described above), the Caltrain service between San Jose and San

⁹ North of San Jose, the California High-Speed Rail system would connect to San Francisco through Blended Service, discussed above.

- 1 Francisco must be fully electrified. The Proposed Project would install the electrical infrastructure
- necessary to support a fully electrified service, but Caltrain would need to purchase additional EMU
 rolling stock to support this service.
- 4 As shown in Table 4-6, full electrification would require approximately 40 to 50 additional EMU
- 5 vehicles. Based on the 2009 estimated budget of \$440 million for 96 EMUs, the additional EMUs
- 6 could require an additional \$193 to \$248 million in funding that has not been secured at this time.
- 7 As funding becomes available, the JPB intends to replace retiring diesel locomotives with EMUs. If
- 8 Blended Service is realized by sometime between 2026 and 2029, Caltrain would need to be fully
- 9 electrified at that time to maintain the levels of service called for in the Proposed Project.

10Table 4-6. Fleet Requirements of the Peninsula Corridor Electrification Project (2020 2019) and a11Future Fully Electrified Service (San Jose – San Francisco)

Year	Diesel Locomotives	EMUs	Diesel-Hauled Vehicles	Total Vehicles
2020 2019 ^a (Six trains per peak hour/direction)	9	96	45	150
2040 ^b (Six trains per peak hour/direction)	6	138 to 150	31	175 to 187

^a The majority of vehicles would be replaced <u>by 2020</u> in 2019 as they reach the end of their design life. Additional vehicles would be replaced after <u>2020</u> 2019 as they reach the end of their design life.

^b Diesel operation limited to San Jose–Gilroy shuttle service. 2040 EMU estimate is a conceptual estimate.

12

13 Caltrain South Terminal Project

14 This is project number 4 in Table 4-3 and Figure 4-1.

15The South Terminal Project is a multi-phased project to improve the South Terminal Area (STA)16portion of the Caltrain corridor between Santa Clara and San Jose to adequately accommodate17potential future rail traffic levels. Where constraints with existing infrastructure are identified,18improvements are recommended to address the operational needs of Caltrain and its tenants:19Altamont Commuter Express (ACE), Capitol Corridor, and Amtrak Long Distance Coast Starlight20service. Phase 1 of the project is already complete. Table 4-7 summarizes Phase II and Phase III of21the South Terminal Project is

21 the South Terminal Project

1
-

2

3

4

5

Table 4-7. Projects Identified as Improvements to South Terminal Area

Segment	Improvement
CP Shark to CP Alameda ^a	South Terminal Phase II—Fourth main track, CEMOF to Diridon. This additional fourth track would be approximately 2,000 feet long and would require minor right of way acquisition. To incorporate the 4th track, the existing track systems would require rearrangement. Associated signal control work would be included.
CP Bird to Tamien Station	South Terminal Phase III— This project includes the construction of an additional track south of the South Terminal, between the San Jose Diridon Station and the I-280 crossing. Additionally, associated signal work is included and a new control point would be constructed between the Auzerais Avenue crossing and the I-280 crossing. The Auzerais crossing would be reconstructed. This additional track would be approximately 2,000 feet long and would run across the widened portion of the newly constructed Los Gatos Creek Bridge.
^a CP Shark and CP Alameda are in San Jose. CP Alameda extends north from Diridon Station to north of Santa Clara street and connects to CP Shark, immediately west of SAP Center in San Jose. CP Shark extends to north of Iulian Street.	
CEMOF = Central Equipment Maintenance Operations Facility.	
CP = control point.	
I-280 = Interstate 280.	
There are no schedules as of yet for these projects.	
San Bruno Grade Separation	
This is project number 11 in Table 4-3 and Figure 4-1.	

6 The San Bruno Grade Separation Project, which is currently in construction, will elevate Caltrain

7 tracks above three existing at-grade street crossings at San Bruno, San Mateo, and Angus Avenues to

8 improve safety for pedestrians and motorists, and to help reduce traffic congestion from U.S.

- 9 Highway 101 in San Bruno. Additionally, a new elevated Caltrain station will be constructed
- 10 between San Bruno and San Mateo Avenues to replace the existing station at Sylvan Avenue. There
- 11 will be 201 parking spaces and a "kiss-and-ride" lot.

The project will include three pedestrian underpasses, one near Sylvan Avenue, one at the new
 station, and one between Euclid Avenue and Walnut Street. The elevated station will have elevators
 to provide easy access for Caltrain riders. The surrounding streets and sidewalks will be improved,
 including those at Posy Park. Construction is expected to be completed in April 2014 (Caltrain

16 2013b).

17 Caltrain Planned Corridor Improvements

18 This is project number 12 in Table 4-3 and Figure 4-1.

19 Caltrain Communications Based Overlay Signal System Positive Train Control

- 20 The Caltrain Communications Based Overlay Signal System (CBOSS) Positive Train Control (PTC)
- 21 Project will provide a new advanced signal system. The project, which is in construction now,
- 22 involves installation of PTC which is a requirement by the FTA on all commuter and freight

- 1 railroads. The project will help eliminate train-to-train collisions and over-speed mistakes and
- 2 provide additional safety measures for railroad workers. The Caltrain CBOSS PTC Project will meet
- 3 the federal mandate to implement PTC by 2015 and increase system capacity to allow for future
- 4 increase in ridership and demand. The project components are compatible with Caltrain's existing
- diesel-based trains, and will also be compatible with the future Caltrain electric powered fleet. In
 addition, the Caltrain's CBOSS PTC project is being designed to ensure interoperability with HSR as
- well as existing passenger and freight tenants (Caltrain 2013).
- 8 Other Caltrain Improvements
- 9 Caltrain improvements that are being planned other than CBOSS PTC, the Proposed Project, the STA
 10 improvements, and the San Bruno project include the following:
- Rehabilitation of the Existing System—long-term repairs, reconstruction, and modernization of
 the existing tracks, signals, bridges, stations, rolling stock, and other systems.
- Bridge replacements in San Francisco, San Mateo¹⁰ and at Los Gatos Creek.
- The modernization of stations such as removing the hold-out rule.
- At-grade crossing improvements and a system-wide fencing program to improve safety.
- South San Francisco Station Improvement Project, which would remove the holdout rule and improve access to station platforms.
- 18 Station security improvements.
- 19 Trackwork rehabilitation improvements consist of the following:
- Replacing jointed rail track with continuous welded rail track.
- At-grade crossing improvements.
- Drainage improvements.
- Planned rehabilitation improvements include tunnel rehabilitation, retrofit of existing structures to
 current seismic safety standards, new bridge decks, and new foundations where needed.
- 25 Rehabilitation improvements at stations include the following:
- Station security improvements.
- Provision of 600-foot-long (or longer) side platforms.
- Wide center platforms at selected locations.
- 29•At the Fourth and King Station, this work could include reconfiguration of the platforms30from the current 6 platform, 12-track configuration to a 3 platform, 6-track configuration31similar to that originally included in the TJPA 2004 EIS/EIR or some other configuration for32a surface terminal. This would require realignment of tracks leading to the platforms as well33within the 4th and King Yard. Platform reconfiguration is not currently funded and thus it is34unknown if and when this proposal might be advanced.

¹⁰ Bridges are presently being replaced in San Mateo at the East Poplar, East Santa Inez Avenue, Monte Diablo, and Tilton Avenue underpasses. The bridge replacement will be completed by 2016. The bridge replacement project has already been environmentally cleared.

- 1 Improved lighting, shelters, and communications facilities at station waiting area.
- Facilities to meet Americans with Disabilities Act (ADA) requirements.
- 3 Underpasses for pedestrians.
- Inter-track fencing to keep passengers from attempting to cross the tracks.
- 5 Bridge rehabilitation.

6 **Dumbarton Rail Corridor**

7 This is project number 5 in Table 4-3 and Figure 4-1.

8 The Dumbarton Rail Corridor project will extend rail service between the Redwood City Caltrain 9 Station and the Union City BART Station by reconstructing a 20.5-mile existing rail corridor. The 10 purpose of the Dumbarton Rail Corridor Project is to improve transbay public transportation service 11 and interconnections to reduce roadway congestion, improve travel reliability, improve air quality, 12 and address greenhouse gas reduction goals from transportation and development. In the East Bay, 13 the service would use the Union Pacific Railroad's Centerville Line and Oakland Subdivision to reach 14 Union City. The service would then utilize the Dumbarton Line, including crossing the currently out-15 of-service Dumbarton Rail Bridge across the San Francisco Bay (located east of the SR 84 highway 16 bridge). The Dumbarton Rail Corridor service would operate on the Caltrain mainline beginning at 17 Redwood Junction in Redwood City, with service continuing north to San Francisco and south to San 18 Jose. The extension will connect to existing public transportation services such as BART, ACE, 19 Amtrak's Capital Corridor, Caltrain, and regional bus service.

- 20 The reconstruction of the rail corridor will include track improvements, new moveable rail bridges, 21 new train stations in Menlo Park (Willow Road), at Newark's Dumbarton Transit-Oriented
- 21 new train stations in Menio Fark (Winow Road), at Newark's Dumbarton <u>Traisit</u>-oriented
 22 Development area, and adjacent to the Union City BART Station, upgrading the Centerville Station in
 23 Fremont, a centralized train signal control system, and a layover yard in the East Bay, among other
 24 improvements. Depending on the alternative selected, some of these improvements may be within
 25 the Caltrain corridor.
- An Alternatives Study was completed in March 2011 and an environmental review of the project
 was initiated. However, Alameda County Measure B, which would have provided funding, did not
 pass in November 2013. As a result, the JPB and the Federal Transit Administration (FTA) have
 placed the project on hold until new funding is identified.
- A number of different alternatives have been considered for the Dumbarton Rail Corridor. For the
 purpose of this EIR, the analysis assumed that six diesel locomotive trains will travel from Union
 City during the AM peak commute period. Three of these trains will travel to San Francisco and
 three to San Jose. In the PM peak period, these trains will make the reverse trip from San Francisco
 and San Jose back to Union City.

35 ACEforward Program

- 36 This is project number 6 in Table 4-3 and Figure 4-1.
- 37 The ACE forward Program is an initiative of the San Joaquin Regional Rail Commission (SJRRC) to
- 38 expand ACE service. The project is intended to improve ACE service between Stockton and San Jose
- 39 and to extend service to Modesto and Merced. The purpose of the project is to enhance commuter
- 40 and intercity rail service for riders in the northern San Joaquin Valley and the eastern and southern

5

- 1 parts of the Bay Area. ACE commenced its environmental process for the ACE forward Program in
- 2 June 2013 and intends to complete an EIR/EIS for the program by 2016.
- 3 Infrastructure improvements currently under study by ACE would provide for:
- Operation of a fifth and sixth round trip between Stockton and San Jose by 2018.
 - Operation of 10 or more round trips between Stockton and San Jose by approximately 2022.
- Operation of six round trips between Stockton and Merced by approximately 2022.

Within the Caltrain project area, the ACE service operates on the Caltrain ROW between Santa Clara
and San Jose. The ACE forward program includes increases of up to six round trips on this segment
by 2018 and up to 10 round trips or more by approximately 2022. As noted above, this is one of the
projects that depends on the improvements to the south terminal area. Further improvements in the
south terminal may be needed and are being studied. Additionally, beyond the south terminal area,
the ACE forward Program presumes capital improvements east of the Caltrain corridor at certain
locations between Stockton and Santa Clara.

14 Capitol Corridor Oakland to San Jose, Phase 2

- 15 This is project number 7 in Table 4-3 and Figure 4-1.
- 16 The Capitol Corridor service is operated by the Capitol Corridor Joint Powers Authority (CCJPA).
- Initially, the service provided six daily trains between Sacramento and San Jose. Between 2002 and
 2006, the CCJPA increased service multiple times in response to the growing demand. The CCJPA is
 now working on the Capitol Corridor Oakland to San Jose Project.
- Phase 1 of the Oakland to San Jose track improvements and the Yolo Causeway main track,
 completed in 2004, allowed the Capitol Corridor to reach its current service level. The Capitol
 Corridor currently runs 32 weekday (22 weekend) trains between Sacramento and San Jose, and 14
 daily trains between Oakland and San Jose. (Capitol Corridor Joint Powers Authority 2013 2010)
- 24 Phase 2 of the Oakland to San Jose track improvements will increase frequency of Capitol Corridor 25 service from 14 daily trains to 22 daily trains between Oakland and Santa Clara/San Jose. CCJPA has 26 identified a list of track infrastructure projects to allow for the expansion of the Capitol Corridor rail 27 service, and is moving forward with design plans and environmental review. As noted above, this is 28 one of the projects that depends on the improvements to the south terminal area. Further 29 improvements in the south terminal may be needed and are being studied. The project does not 30 include any capital improvements within the Additionally, beyond the south terminal area, the 31 Phase 2 Oakland to San Jose project presumes capital improvements east of the Caltrain corridor at 32 certain locations between Oakland and Santa Clara.
- 52 certain locations between bakand and santa

33 BART Silicon Valley Extension

- 34 This is project number 8 in Table 4-3 and Figure 4-1.
- 35 The VTA and Bay Area Rapid Transit (BART) District are planning a 16.1-mile extension of the BART
- 36 system to serve Santa Clara County. The extension would extend from Fremont to the Santa Clara
- 37 Caltrain Station. The extension will be constructed in phases. The first phase, the Warm Springs
- 38 Extension, covers 5.4 miles beginning just south of the planned BART Warm Springs Station in
- 39 Fremont. The second phase, Berryessa Extension, will extend along the Union Pacific Rail Road
- (UPRR) line through Milpitas to the Berryessa District of San Jose, near Las Plumas Avenue. The
 third phase, Santa Clara Extension, would be from Berryessa to Santa Clara.
- Major construction on the Warm Springs Extension began in August of 2009. The Warm Springs
 Extension is expected to open for revenue service in the fall of 2015.
- 5 The Berryessa Extension is also under construction and is scheduled to be open in 2018. BART
- 6 trains are expected to run every 15 minutes during peak commute periods on two BART lines: Green

7 line (Berryessa–Daly City) and the Orange Line (Berryessa–Richmond). The projected opening day

- 8 ridership is approximately 23,000 average weekday riders.
- 9 The Santa Clara Extension is in the environmental review phase and is expected to be in service by
- 10 2023. The Santa Clara Extension is the only part of the project that would be located in and adjacent
- 11 to the Caltrain corridor. The Santa Clara Extension includes potential stations at Diridon and Santa
- 12 Clara connected to the Caltrain stations and a subway or at-grade alignment between Diridon and
- 13 Santa Clara. BART would be in its own ROW separate from Caltrain.

14 Coast Daylight

- 15 This is project number 9 in Table 4-3 and Figure 4-1.
- 16 The *California State Rail Plan* establishes strategies and priorities for the Department of
- Transportation to improve passenger and freight rail service for the public. Part of this plan
 proposes new intercity rail routes. The proposed intercity route, the Coast Daylight, would connect
 San Francisco, San Jose, Salinas, San Luis Obispo, Santa Barbara, Ventura, and Los Angeles. Currently
 the Coast Starlight, an Amtrak route, provides service from between Los Angeles and the Pacific
 Northwest, serving markets in California. The route operates once per day in each direction between
 Los Angeles and the Bay Area. The proposed Coast Daylight route would have twice as many stops at
 the Coast Starlight.
- 24 Coast Daylight service would support several statewide transportation objectives (Caltrans 2013):
- Providing additional capacity to serve corridor growth in a cost-effective manner with minimal impacts on local communities, natural resources, and air quality and GHG emissions.
- Increasing use of intercity passenger rail service as part of a multi-modal strategy identified in regional and county goals and plans.
- Improving rail operations by reducing travel times and increasing reliability and safety.
- Providing early implementation of a "one-seat" ride from downtown San Francisco to downtown
 Los Angeles.
- The present proposal is to run two daily roundtrips from San Francisco to Los Angeles. No capital
 improvements are proposed within the Caltrain corridor for this project. The feasibility of this
 project is yet to be determined and is dependent on its compatibility with a blended system in the
 Peninsula Corridor
- Pending that feasibility assessment, for the purposes of this EIR cumulative analysis only, this
 service is assumed to start by 2020.

1

2

3

4

5

6

7

8

Freight Rail Future Plans

This is project number 10 in Table 4-3 and Figure 4-1. As described in Section 3.14, *Transportation and Traffic*, levels of freight operations in the corridor as of late 2012 were estimated at approximately seven round trips per day. San Francisco to South San Francisco freight yard—one round trip daily during daytime ("South City" Local) South San Francisco freight yard to Redwood City—one round trip daily during nighttime ("Broadway")

- 9 South San Francisco freight yard to San Jose (Newhall Yard)—one round trip daily during nighttime ("Mission Bay")
- South Terminal Area (South of CP Coast) four round trips daily ("Salinas", "Granite Rock 1",
 "Granite Rock 2", and "Permanente") and one one-way daily ("MRVSJ").
- In addition to this routine daily traffic, freight operators also run periodic trains to serve non routine episodic freight needs along the Caltrain corridor.
- UPRR and various freight rail operators and users along the Caltrain corridor expect freight service
 to grow over time to accommodate demands from their various customers for freight deliveries.
- 17 Port of San Francisco: The annual numbers of rail cars for the past 3 years has grown from 475 • 18 railcars in 2010, to 1,165 railcars in 2011, to 1,950 railcars in 2012 (Greenway, pers. comm.). 19 The port projects year-on-year growth from 2012 forward to be 15 percent (Greenway, pers. 20 comm.). Richmond Mining Limited (now Nevada Mining) has identified potential use of port 21 facilities at Piers 90–96 to handle its iron ore (Richmond Mining, undated) and provided a letter 22 of intent in 2010 identifying the Port of San Francisco as its favored port of loading (Richmond 23 Mining Limited 2010). If this project were to be realized, then, starting in 2016, iron ore could 24 start moving at a rate of 500 additional railcars/month initially and then potentially grow to as 25 many as 1,700/month by 2018 (Greenway, pers. comm.). Assuming 75 iron ore railcars per train 26 consist¹¹, 1,700 railcars/month would correspond to approximately 23 additional trains per 27 month or less than one train/day on average. It should be noted that no environmental analysis 28 has been commenced or completed for the proposed expansion of Piers 90–96 operations for 29 iron ore export or the associated increase in freight rail operations. There are also other 30 potential port options in Oakland and Richmond that could be utilized for iron ore shipping. 31 Thus, for the likelihood for a large-scale increase in iron ore shipments along the Peninsula 32 corridor is unknown at this time.
- Union Pacific Railroad: Representatives of UPRR informed Caltrain that they expect general freight growth of 4 percent per year. Representatives of UPRR also noted that if the Monterey Shale oil deposit is developed substantially in the future, there might be an increase in oil shipments through the South Terminal Area to oil refineries in the East Bay and Benicia. The potential for a large increase in Monterey Shale exploitation is a subject of intense concern and controversy at present; the potential for increased oil shipments through the Caltrain project area is unknown at this time.

 $^{^{11}}$ Estimates of iron ore consists in Utah range from 75- to 100-car consists. See: http://utahrails.net/mining/iron-mountain.php

- Freight Operators: The Peninsula Freight Rail Users Group, a collection of freight rail operators and users in the Caltrain Corridor including the Ports of Redwood City and San Francisco, the San Francisco Bay Railroad, CEMEX, Granite Rock, and a number of other rail users, identified in their scoping letter on the Proposed Project EIR that "it is foreseeable that freight volumes will expand significantly over the coming decades, even without any expansion of infrastructure."
 (Peninsula Freight Rail Users Group 2013).
- California State Rail Plan: The Draft California State Rail Plan (Caltrans 2013) estimates that
 tonnage at the ports of Oakland and San Francisco is expected to increase 2.5 times between
 2007 and 2040. However, the plan does not provide a separate estimate for how much of this
 growth is expected for the Port of San Francisco or an estimate of freight rail increases along the
 Caltrain Corridor.
- With continued economic growth on the Peninsula corridor from the present to 2040 and beyond, there will be an expanded demand for the transport of bulk cargoes and bulky materials, which could be met by expanded freight rail. Should large-scale bulk carriers decide to ship materials either in or out of the Ports of Redwood City or San Francisco, such as the proposal to expand iron ore shipments described above, there could be a substantial demand for freight shipments through the Caltrain corridor.
- 18 As discussed in Section 3.14, *Transportation and Traffic*, freight operations are primarily limited to
- 19 operational hours of 8 p.m. to 5 a.m. with limited slots available outside of this period at present.
- 20 With the Proposed Project, the FRA waiver allowing the use of light-weight EMUs on the Peninsula
- 21 Corridor requires freight traffic to be limited to the hours between midnight and 5 a.m. to provide
- 22 temporal separation between light-weight passenger trains and heavy freight trains. The FRA is
- 23 currently engaged in a rule-making process that may alter the requirements for temporal separation
- which may allow larger freight operational hours. Unless FRA modifies the temporal separation
 requirement, any increases in freight traffic would be assumed to occur between midnight and 5
- a.m. If FTA determines that temporal separation is not required, then freight increases would be
 assumed to occur between 8 p.m. and 5 a.m.
- 28 <u>As discussed in Chapter 2. Project Description</u>, the Project now assumes that temporal separation of
- 29 <u>the EMUs and freight equipment will not be required and thus that freight operational windows will</u> 30 not substantially change from today. Freight trains today avoid the peak hours at present, which is
- 31 the period of most substantial change with the PCEP.
- Freight train consists vary substantially in length. Bulk carriers, such as those that could be
 associated with transport of iron ore, can be particularly lengthy.

34 BART Millbrae Tail Tracks

- 35 This is project number 70 in Table 4-3 and Figure 4-1.
- BART anticipates extending the Millbrae tail track by an additional 200–300 feet southerly into
 Burlingame to accommodate all 10-car trains on these tail tracks in the near future (BART 2013).

38 **Summary of Assumed Cumulative Rail Service**

Table 4-8 describe cumulative rail service assumed along the Caltrain corridor by 2040 based on
 review of project documents for the cumulative rail projects described above.

1 Table 4-8. Cumulative Existing and Future (2040) Daily Train Service Along the Caltrain Corridor

	Tamien - Diridon	Diridon - Santa	Santa Clara -	Redwood City - San	
System	Diffuoli	Clara	City	Francisco	Source
Existing (2013)	Service				
Caltrain	40	92	92	92	Existing Caltrain Schedule
ACE	8	8			ACE Schedule (ACE trains layover at Tamien yard)
Capitol Corridor		14			CCJPA Schedule
Coast Starlight	2	2			AMTRAK schedule
Freight	4	9	2	6	Caltrain dispatch data
Total	54	125	94	98	
Future (2040) S	ervice				
Caltrain	48	114	114	114	Proposed Project NOP (Appendix A)
High-Speed Rail			80 <u>to 106</u>	80 <u>to 106</u>	CHSRA <i>Revised 2012 Business</i> <i>Plan</i> (CHSRA 2012a)ª
ACE	20	20			ACEforward NOP (SJRRC 2013)
Capitol Corridor		30			CCJPA Draft 2013 Vision Plan (CCJPA 2013)
Coast Daylight	4	4	4	4	2013 California State Rail Plan (Caltrans 2013)
Dumbarton Rail Corridor		6	6	6	2013 California State Rail Plan (Caltrans 2013)
Coast Starlight	2	2			No change
Freight	8	19	4	12	108% increase based on assumed 4% per annum increase
Cumulative Total	80	195	208 <u>to 224</u>	216 <u>to 242</u>	
Change from 2013	26	70	114 <u>to 140</u>	118 <u>to 144</u>	

^a As noted above, the Draft 2014 Business Plan *Service Planning Methodology* document (CHSRA 2014c) includes an assumption of 53 daily round trip trains starting in 2029 and continuing beyond 2040 <u>but</u> the prior 2012 CHSRA Business Plan assumed 40 daily round-trip trains. Caltrain's Blended Service planning to date has not studied the 2014 Business Plan estimates because the plan was released on February 7, 2014 and conceptual Blended Service studies were completed in 2013. Thus, this Draft EIR is based on the 40 to 53 daily round-trip <u>HSR</u> trains, that have been studied by Caltrain to date. If more than 40 daily round-trip high-speed trains operate on the Caltrain corridor, then some operational noise impacts, such as noise, vibration, or localized traffic congestion, may be worse than disclosed in this analysis. The exact number of HSR trains on the corridor in the future is unknown at this time. The subsequent CHSRA project-level environmental evaluation will address proposed high-speed train service levels along the San Francisco Peninsula.

2

1 4.1.3.2 Other Regional Transportation Improvements

2 Central Subway

3 This is project number 13 in Table 4-3 and Figure 4-1.

4 The Central Subway Project is a 1.7-mile extension of Muni's T Third Line from the 4th Street 5 Caltrain Station to Chinatown, with a street-level stop at 4th and Brannan, and three underground 6 stops at Yerba Buena (4th and Folsom Streets), Union Square (Stockton Street at Union Square), and 7 Chinatown (Stockton and Washington Streets). The station to be located at Stockton Street at Union 8 Square will be connected to the Powell Street BART/Muni Station to allow for convenient transfers 9 to BART, Muni Metro lines, the Powell Street Cable Car, and Muni bus lines in the area. The extension 10 will provide a direct connection from the Bayshore and Mission Bay areas to the South of Market, 11 Union Square, downtown, and Chinatown areas. The extension will also provide connection from 12 locations along the new 1.7-mile corridor to the 4th and King Caltrain Station through the already 13 existing 4th and King/Berry T-Third line station.

- The Central Subway Project is Phase 2 of San Francisco Municipal Transportation Agency's (SFMTA)
 Third Street Light Rail Transit Project. Phase 1 of the SFMTA Third Street Light Rail Transit Project,
- 16 included a 5.1-mile light rail line along the Third Street corridor that opened in 2007. The Central
- 17 Subway segment of the T-Third Line is expected to be open to the public in 2019. (SFMTA 2013)

18 San Francisco Municipal Railway 22-Fillmore Electric Trolley Bus Coach Re-Routing

19 This is project number 14 in Table 4-3 and Figure 4-1.

SFMTA proposes to move the 22-Fillmore Trolley route off of 17th and 18th Streets and onto 16th
Street between Kansas Street and 3rd Street in order to between connect to the growing Mission
Bay neighborhood and to provide continuous transit service along 16th Street. A revised 33-Stanyan
would replace the 22-Fillmore on Connecticut and 18th Streets. SFMTA is also proposing other
improvements along the 22-Fillmore route in order to reduce travel time, increase average
operating speed, and improve service reliability.

- 26 This proposed realignment would mean that the trolley would cross the Caltrain tracks at-grade at
- 27 16th Street. With the proposed electrification under the Proposed Project, there would be a conflict
- between the overhead wires for the electric trolley coach (which is a direct current 600 volt system)
- and the Proposed Project (which is an alternating current 25 kV system). These electrification
- 30 systems are not compatible. At discussed in the cumulative analysis of transportation below,
- Caltrain has identified two technical solutions that would facilitate both the Proposed Project and the 22 Fillment to use the at grade 16th Street gragging with out conflict
- 32 the 22-Fillmore to use the at-grade 16th Street crossing without conflict.

33 Major Highway Improvements on the Peninsula

- 34 This is project number 15 in Table 4-3 and Figure 4-1.
- 35 In the face of rapid growth on the Peninsula and San Francisco, a variety of highway improvements
- 36 are planned. Major planned highway improvements within several miles of the Caltrain corridor
- that would cost more than \$100 million apiece and that are listed in *Plan Bay Area* include the
 following (ABAG and MTC 2013a, no date):

2

3

- 1 • VTA Silicon Valley Express Lanes Program will convert existing carpool lanes to express lanes and add new lanes along SR 237, SR 85, and U.S. Highway 101 corridors throughout Santa Clara County (including express lanes along I-880 between U.S. Highway 101 and I-280).
- 4 U.S. Highway 101 improvements including a high-occupancy vehicle lane from the San Francisco • 5 county line to Whipple Avenue (Redwood City); conversion of HOV lane to express lane between 6 Whipple Avenue and Santa Clara County line; and auxiliary lanes from Marsh Road (Menlo Park) 7 to Embarcadero Road (Palo Alto) to SR 85 (Mt. View).
- 8 • U.S. Highway 101 corridor interchange improvements at Candlestick Point (San Francisco), 9 Produce Avenue (South San Francisco), SR 92 (San Mateo), Oregon Expressway (Palo Alto), and 10 Zanker Road (San Jose).
- Some of these projects are fully funded; others are not yet fully funded but are assumed to be funded 11 12 in future years. These projects and other projects included in *Plan Bay Area* are not enough to solve 13 the transportation problems in the corridor. The *Plan Bay Area* Final EIR (ABAG and MTC 2013b) 14 indicates that even with these projects in place, there will be more peak period congestion and more 15 total vehicle hours of delay in the region. Thus, there is a need for additional transit in the corridor to reduce future congestion and improve travel opportunities. Improved Caltrain service would help 16 17 meet this need.

18 Other Major Non-Highway Improvements on the Peninsula

- 19 This is project number 16 in Table 4-3 and in Figure 4-1.
- 20 Major planned non-highway transportation improvements within several miles of the Caltrain corridor that would cost more than \$100 million apiece and that are listed in *Plan Bay Area* include 21 22 the following (ABAG and MTC 2013a, no date):
- 23 • Embarcadero Streetcar: Extend historic streetcar service from Fort Mason to Caltrain's San 24 Francisco 4th and King Station.
- Southern Intermodal Terminal and MUNI T-Line Extension: Extend MUNI T-Line from 25 26 Bayshore/Sunnydale to Caltrain Bayshore Station (San Francisco).
- 27 Future grade separations in San Mateo County: Grade separations at approximately two or three • 28 high-priority candidate locations along the Caltrain corridor to separate vehicular and rail traffic 29 for safety purposes. The locations are not yet known.
- 30 • Bus Rapid Transit (BRT) along El Camino Real: Provide BRT along El Camino Real from Palo Alto 31 to Daly City.
- 32 • Palo Alto Caltrain Station and Bus Transit Center Expansion: Improve bus transit capacity, 33 amenities and access to downtown Palo Alto, the Stanford campus and Stanford Shopping 34 Center (Palo Alto).
- 35 • Grade separation at Rengstorff Avenue: Depress Rengstorff under the Caltrain tracks (Mountain 36 View).
- 37 • Tasman Express Long T double tracking: Double-tracking of VTA's Mountain View light rail line 38 (Mountain View/Sunnyvale, Santa Clara, San Jose).

- Mineta San Jose International Airport Automated People Mover (APM) Connector: Provide
 direct service from the airport to VTA's Guadalupe light-rail station, and the Santa Clara Caltrain
 station, and future Santa Clara BART Station.
- Some of these projects are fully funded; others are not yet fully funded but are assumed to be funded
 in future years.

San Francisco Interstate I-280 Teardown/Boulevard/4th and King Underground Station Conceptual Planning

- 8 This is project number 73 in Table 4-3 and Figure 4-1.
- 9 The City and County of San Francisco will be conducting a study (entitled the Railyard Alternatives
- 10 and I-280 Boulevard Feasibility Study) that will evaluate the feasibility of removing the end of the I-
- 11 280 freeway after Mariposa Street, extending the Caltrain (and future HSR) tracks underground,
- 12 creating a surface boulevard that would connect the cross-streets of Potrero Hill and SOMA
- 13 neighborhoods to Mission Bay, reconnecting the adjacent neighborhoods at the San Francisco 4th
- 14 and King Station, and potentially redeveloping the 4th and King Station.
- 15 Key potential elements of this concept include the following:
- The City is exploring the potential removal of I-280 north of Mariposa Street and the replacing it
 with an at-grade boulevard. A similar concept was completed along Octavia Boulevard with the
 removal of the Central Freeway and along the Embarcadero with the removal of the
 Embarcadero Freeway following the 1989 Loma Prieta earthquake. Planning is at an early phase
 but may involve a new boulevard with vehicle, bicycle, and pedestrian lanes and access, as well
 as commercial and residential development of areas adjacent to the boulevard, and new
 connections between areas east and west of the existing I-280.
- As part of the evaluation of the removal of I-280, the City is also exploring the potential to
 underground or realign the northern portion of the Caltrain corridor from somewhere north of
 Mariposa Street to the 4th and King Station.
- In addition, the City is also exploring the potential for either reconfiguring or replacing the existing 4th and King Station to allow for potential redevelopment providing housing and employment in the area.
- 29 • Other components of the City of San Francisco Railyard Alternatives and I-280 Boulevard 30 Feasibility Study currently underway are considering the alignment and construction methods 31 of the Downtown Tunnel-Extension (DTX) to the Transbay Transit Center (TTC); the possibility 32 of constructing a loop track out of the north end of the TTC which may allow for a two-track, 33 rather than a three-track section, through the 4th and Townsend Station area; and the funding 34 and financial opportunities from potential development that could be designated as a potential 35 funding source for future improvements in the area, a dedicated funding stream for Caltrain, and/or general City funds. 36
- The anticipated study schedule is from June 2014 to July 2016.
- This project is not part of any approved City planning document, has not been environmentally
 reviewed, and project funding has not been identified. Given this project is at a very early phase of
- 40 development, it cannot be analyzed in any detail in this cumulative impact analysis.

- 1 If such a project were to advance, development would occur after the Proposed Project is complete.
- 2 To complete such a project could require substantial changes to the Caltrain alignment in San
- 3 Francisco and the 4th and King Station. While the removal of Proposed Project's electrical
- 4 infrastructure (wires and poles) in the vicinity would require additional construction effort and cost,
- 5 the electrical infrastructure would not pose a physical impediment to future development and the
- costs of removal would be minor in comparison with the cost of the potential improvements
 described above.
- 8 Geneva Avenue to US 101/Candlestick Point Interchange
- 9 <u>This is project number 74 in Table 4-3 and Figure 4-1.</u>
- 10 The San Francisco-San Mateo Bi-County area analyzed the Geneva Avenue extension project in the
- 11 <u>Bi-County Transportation Study (SFCTA 2013). The study was an effort to develop a priority project</u>
- 12 list and funding strategy for new transportation improvements to support the needs and anticipated
- 13 growth in the area. This is a priority project for San Mateo and San Francisco counties. The
- 14 <u>timeframe for the project is 2015–2020.</u>
- 15 This project would extend Geneva Avenue from Bayshore Boulevard to the new proposed US 101
- 16 <u>Candlestick Point Interchange, connecting to Harney Way, and include a grade-separated Caltrain</u>

17 <u>crossing at Tunnel Avenue. This new local street connection would provide access to US 101 from</u>

18 Brisbane Baylands as well as existing adjacent neighborhoods that would use the new street as a

19 more direct route to US 101 than existing routes. The design would accommodate six travel lanes.

20 <u>two bicycle lanes, sidewalks, and potentially bus rapid transit exclusive lanes (SFCTA 2013).</u>

21 **4.1.3.3** Land Development Adjacent to Caltrain ROW

Planned, proposed, and under-construction land development projects adjacent or within 0.15 miles
 of the Caltrain ROW have the potential to be affected by the Proposed Project. Table 4-9 describes all
 land use projects, in various stages of development, within approximately 0.15 miles of the Caltrain
 ROW.

26 **4.1.4 Cumulative Impact Analysis**

- This section discusses the cumulative impact analysis. Table 4-10 summarizes the cumulativeimpact analysis findings.
- 29 In general, if Project Variant 1 is implemented, there would be fewer cumulative construction
- 30 <u>impacts south of Tamien Station because there would be no construction activities in this area.</u>
- 31 <u>Cumulative operational impacts would generally remain the same as described in the impact</u>
- 32 analyses below. Similarly, there would be fewer cumulative construction impacts near the 4th and
- 33 <u>King Station because electrification of the 4th and King storage yard would be deferred and</u>
- 34 <u>cumulative operational impacts would generally remain the same. There would be no change to the</u>
- 35 <u>cumulative impact analyses if Project Variant 3 is implemented.</u>

Table 4-9. Land Use Development Projects Adjacent to the Caltrain ROW

Project Name (Ref #)	Description	Location	Status	Location Relative to Proposed Project
San Francisco			Status	
4th and King Railyards Redevelopment (#17)	Existing and planned high-density residential, commercial and office uses (San Francisco Planning Department 2012)	San Francisco 4th and King Caltrain Station	Early planning	Within Caltrain ROW, Adjacent, and in OCS/ ESZ area outside ROW
Brisbane				
Brisbane Baylands Specific Plan (#18)	684-acre, 12-million-square-foot development to include a variety of uses (UPC 2010)	Between U.S. Highway 101 and Bayshore Boulevard	Proposed	Adjacent and in OCS/ ESZ area outside ROW
Opus Office (#19)	Two buildings with 448,000 square feet of office uses (City of Brisbane 2013)	3000–3500 Marina Boulevard	Proposed	0.10 mi from ROW
3710–3760 Bayshore Boulevard (#20)	2.9-acre development of two buildings with 30 residential units (City of Brisbane 2013)	3710–3760 Bayshore Boulevard	Approved. Building permit application submitted in 2010.	0.02 mi from ROW
3700 Bayshore Boulevard (#21)	3.6 <u>1.3</u> -acre development with <u>386</u> <u>36</u> condominiums and a 4.5-acre development with 21 single-family lots (City of Brisbane 2013)	3700 Bayshore Boulevard	Tentative subdivision map submitted	0.02 mi from ROW
Millbrae				
Millbrae BART Station TOD (#68)	350 residential units and approximately 160,000 square feet of office and commercial space. (Note: The Station Area Plan provides a long-term framework for more substantial development over time.)	El Camino Real and Millbrae Avenue	Planning	Adjacent
Burlingame				
1225 Floribunda Avenue (#22)	3-story, 6-unit residential condominium (City of Burlingame 2013)	1225 Floribunda Avenue	Proposed	0.08 mi from ROW
San Mateo				
Mi Rancho Market (#23)	2-story, 12,500-square-foot market with 25 parking spaces (City of San Mateo 2013e)	80 North B Street	Proposed	0.02 mi from ROW
Gas and Shop (#24)	New fuel island, curb cut, and canopy at existing gas station (City of San Mateo 2013d)	609 East 4th Avenue	Proposed	0.13 mi from ROW

Project Name (Ref #)	Description	Location	Status	Location Relative to Proposed Project
Sadigh Mixed Use (#25)	Mixed-use building with 4,000 square feet of retail and 10 residential condominiums (City of San Mateo 2013g)	4300 S. El Camino Real	Approved	0.03 mi from ROW
Nazareth Terrace (#26)	Mixed-use building including 3,010 square feet of retail, 7,273 square feet of office, and 11 residential units (City of San Mateo 2013f)	234 7th Avenue	Approved	0.06 mi from ROW
Cal Water Office (#27)	2-story, 18,184-square-foot office building (City of San Mateo 2013c)	341 and 345 N. Delaware Street	Approved	0.11 mi from ROW
800 & 888 N. San Mateo Drive Apartments (#28)	3.08-acre development of 155 apartments units (City of San Mateo 2013a)	SE corner of Peninsula Avenue and North San Mateo Drive	Under construction	0.11 mi from ROW
2090 Delaware Apartments (#29)	2.38-acre development of 111 apartment units (City of San Mateo 2013b)	NW corner of S. Delaware Street and Pacific Boulevard	Under construction	0.10 mi from ROW
<u>Hillsdale Station Area</u> <u>Plan (#75)</u>	Station Plan area is for 150 acres in the southern area of the City of San Mateo. Plan proposes a mix of residential and commercial land uses in the area (City of San Mateo 2011)	<u>S El Camino Real between</u> 28 th and 31 st Avenues	<u>Approved</u>	<u>Adjacent</u>
<u>North Fair Oaks</u> Community Plan (#76)	<u>Community plan encompasses 798 acres. Plan</u> <u>sets land use for the area. Plan proposed mixed</u> <u>residential/commercial/industrial use for the</u> <u>Redwood Triangle area (San Mateo County 2011)</u>	<u>Unincorporated San Mateo</u> <u>County between Redwood</u> <u>City and Menlo Park</u>	<u>Approved</u>	<u>Adjacent</u>
San Carlos				
San Carlos Transit Village (#30)	Eight new buildings that would house 407,298 square feet of residential uses including 280 multiple-family dwelling units, 23,797 square feet of office uses, and 14,326 square feet of retail uses (City of San Carlos 2012)	North of San Carlos Caltrain Station	Approved	Adjacent and in OCS/ ESZ area outside ROW
Wheeler Plaza Redevelopment Project (#31)	2.65-acre redevelopment of city-owned parcel including 9,855 square feet of commercial uses and 108 residential units above a 3-level parking garage (Lamphier-Gregory 2011)	1 block west of El Camino Real and southwest of the San Carlos Avenue/Laurel Street	Proposed	0.10 mi from ROW
Redwood City				
145 Monroe Street (#32)	2.27-acre, 6-story development of 305 residential units (City of Redwood City 2013a)	Franklin Street/Monroe Street	Proposed	0.07 mi from ROW

				Location Relative to
Project Name (Ref #)	Description	Location	Status	Proposed Project
Classics at Redwood City (#33)	0.5-acre, 3-story development with 18 residential units and 35 subterranean parking stalls (City of Redwood City 2013c)	755 Brewster Avenue	Proposed	0.08 mi from ROW
Finger Avenue (#34)	1.7-acre development of 9 residential units	80 Finger Avenue	Proposed	0.11 mi from ROW
201 Marshall Street (#35)	0.7-acre development with 116 residential units and parking (City of Redwood City 2013b)	201 Marshall Street	Under construction	0.03 mi from ROW
Lathrop PARC (#36)	0.7-acre, 60,000-square-foot nursing facility with 114 beds (City of Redwood City 2013d)	134 Maple Street	Under construction	Adjacent and in OCS/ ESZ area outside ROW
Crossings/900 (#37)	296,000-square-foot office development with 904 parking stalls (City of Redwood City 2013e)	950 Middlefield Road	Under construction	Adjacent
Atherton				
Atherton Town Hall Complex (#67)	Update the existing town complex	91 Ashfield Road	In planning phase; Construction timing unknown	0.03 mi from ROW
Menlo Park				
389 El Camino Real (#71)	Demolition of an existing single-family house and residential triplex, and construction of 26 residential units	389 El Camino Real	Under construction	0.06 mi from ROW
500 El Camino Real (#38)	8.43-acre redevelopment with 170 housing units, 10,000 square feet pf retail space, and 199,500 square feet of office space (City of Menlo Park 2013a)	500 El Camino Real	Proposed	0.05 mi from ROW
1300 El Camino Real (#39)	3.4-acre development with 110,065 square feet of office uses and 424 parking spaces (City of Menlo Park 2013b)	1300 El Camino Real	Approved	0.08 mi from ROW
1460 El Camino Real (#40)	26,800-square-foot, 2-story office building with submerged parking and 16 two-story townhouse units with partially submerged parking (City of Menlo Park 2013c)	1452 &1460 El Camino Real and 1457 & 1473 San Antonio Street	Approved	0.11 mi from ROW
1706 El Camino Real Medical Office (#41)	2-story, 10,148 square-foot office building for medical/dental office use (City of Menlo Park 2013d)	1706 El Camino Real	Approved	0.14 mi from ROW

Project Name (Ref #)	Description	Location	Status	Location Relative to Proposed Project
El Camino Real/	Redevelopment over the next 30 years of the El	Caltrain station, downtown	Approved	Adjacent and in OCS/
Downtown Specific Plan	Camino Real corridor, the downtown area and the	area, and areas east and		ESZ area outside ROW
(#69)	rail station area	west of El Camino Real		
Palo Alto				
395 Page Mill Road (#42)	Two 4-story buildings with 311,000 square feet of R&D/office uses, in addition to existing 3-story building with 1,329 parking stalls (City of Palo Alto 2013b)	395 Page Mill Road	Proposed	0.12 mi from ROW
145 Hawthorne (#43)	10,503-square-foot development of three detached residential units (City of Palo Alto 2013)	145 Hawthorne Avenue	Planning	0.07 mi from ROW
195 Page Mill Road (Park Plaza) (#44)	3-story mixed-use building with 82 residential rental units (104,174 square feet) and 47,917 square feet of ground floor commercial and retail use (City of Palo Alto 2013a)	195 Page Mill Road	Under construction	Adjacent and in OCS/ESZ area outside ROW
3445 Alma Street (Alma Plaza) (#45)	20,000-square-foot grocery store and an additional 6,000 square feet of commercial space (City of Palo Alto 2013c)	3445 Alma Street	Under construction	0.08 mi from ROW

Project Name (Def #)	Description	Location	Status	Location Relative to
Mountain View	Description	Location	Status	Proposed Project
100 Moffett Poulovard	20 agra development of three 2 to 4 story	100 Maffatt Daulaward	Dlamaina	0.02 mi from DOW
(#46)	buildings with 190 units (ICF International 2012)	100 Monett Boulevard	Planning	0.03 ml from KOW
209-405 West Evelyn (#47)	4.2-acre development of 65 residential units (Grand Boulevard Initiative 2012)	209–405 West Evelyn	Under construction	0.03 mi from ROW
100-200 West Evelyn (#48)	4.33-acre development with 48,738 square feet of office space (Grand Boulevard Initiative 2013)	100–200 West Evelyn	Under construction	Adjacent and in OCS/ESZ area outside ROW
902 Villa Street (#49)	4-story building with 21,745 square feet of office space (Grand Boulevard Initiative 2013)	902 Villa Street	Under construction	0.08 mi from ROW
871 West Evelyn (#50)	4-story building with 65,000 square feet of office space.	871 West Evelyn	Under construction	Adjacent
San Antonio Station (#51)	Remove Heritage Trees	100 Mayfield Avenue	Planning	Adjacent
Northpark Apartments (#52)	Addition of 134 residential units to an existing 188 residential unit apartment complex (Environmental Planning Commission 2012)	111 North Rengstorff Avenue	Under construction	0.09 mi from ROW
South Whisman Precise Plan (#53)	New, 38-acre residential community with 1,210 housing units and 37,000 square feet of commercial space (Mountain View City Council 2009)	Ferguson Road, Near Whisman Station	Phased over time	0.20 mi from ROW
Tripointe Homes (#54)	Four rowhouses	129 Ada Avenue	Planning	0.08 mi from ROW
Pacific Press – Courtyard (#55)	Precise Plan Amendment	1200 Villa Street	Inactive	Adjacent and in OCS/ ESZ area outside ROW
Sunnyvale				
Carmel Lofts (#56)	Two buildings with 133 apartment units in 4 stories and 8,000 square feet of ground floor retail space (City of Sunnyvale 2013)	Adjacent to Plaza del Sol off of Frances Avenue and Olson Way	Under construction	0.08 mi from ROW
Lawrence Station Area Plan (Sunnyvale and Santa Clara) (#66)	Planning document for the vicinity of the Lawrence Station that includes mixed-use development	106 Lawrence Station Road	Planning	Adjacent and in OCS/ ESZ area outside ROW
Santa Clara/San Jose				

Project Name (Ref #)	Description	Location	Status	Location Relative to Proposed Project
Santa Clara Station Area Plan (#57)	Plan for 432 acres surrounding Santa Clara Transit Center for future transit-oriented development (VTA 2010)	Santa Clara Caltrain Station	Approved. Incremental construction over time	Adjacent and in OCS/ ESZ area outside ROW
San Jose				
Earthquakes Stadium (#58)	18,000-seat professional sports stadium.	1105-1125 Coleman Avenue	Under construction	Adjacent
Former FMC site, also called Coleman Highline (PDC98-104, PD12-019) (#59)	Up to 3 million square feet of office/R&D space next to Earthquakes stadium	1115 Coleman Avenue	Construction in 2014/ 2015	Adjacent
Alameda (PD12-017) (#60)	2.19-acre development of a 33,900-square-foot grocery store (Whole Foods) (San Jose Planning Commission 2012)	155 Stockton Avenue	Construction in 2013/2014	0.06 mi from ROW
Morrison Park Townhomes (PD06- 094) (#61)	4.44-acre multi-family attached residential development with 250 townhome units, 425 parking stalls, and 1.16 acres of open space (Civil Engineering Associate 2006)	Cinnabar and Stockton Streets	Under construction	0.08 mi from ROW
785-807 The Alameda (PDC13-007) (#62)	1.04-acre development with 98 residential units and 22,660 square feet of commercial use (City of San Jose 2013b)	785-807 The Alameda	Planning	0.11 mi from ROW
Baseball Stadium (PP05-214) (#63)	1.5-million-square-foot baseball stadium with a capacity of 45,000 and 1,200 space parking garage (LSA Associates 2007)	245 S. Montgomery Street	EIR certified	Adjacent and in OCS/ ESZ area outside ROW
Park Avenue Senior and Family Housing (PDC13- 012) (#64)	2.15-acre development of 181 family and senior apartments (City of San Jose 2013c)	777 Park Avenue	Planning	0.02 mi from ROW
OSH West San Carlos (H13-008) (#65)	48,000-square-foot commercial building (City of San Jose 2013a)	720 W. San Carlos Street	Construction Summer 2013	Adjacent and in Proposed Project OCS/ ESZ area outside ROW
Diridon Station Area Plan (#72)	Plan for expansion of and development around the Diridon Transit Station (approximately 500 acres)	At and adjacent to Diridon Station	Planning	Adjacent and in OCS/ ESZ area outside ROW
Sources: See Table 4-2.				

1 Table 4-10. Summary of Cumulative Impacts Analysis

		Rail Projects Planned in the Caltrain RC			ROW	OW Other Regional Transportation		Land Development Adjacent to		Cumulative Impact		Is Proposed Project's		
		CAHSR Blen	ded Service	Other P	rojects	Impro	ovements	Caltr	ain ROW	(including Pre	oposed Project)	Contribution	Considerable?	
Resource Issue	Geographic Area of Impact	Construction	Operation	Construction	Operation	Construction	Operation	Construction	Operation	Construction	Operation	Construction	Operation	
Aesthetics	Caltrain ROW and vicinity	LTSM	PS	LTSM	PS	LTSM	PS	LTSM	PS	LTSM	PS	LCCM	CCU	
esource Issue esthetics ir Quality iological Resources ultural Resources MF/EMI eology, Soils and Seismicity HG Emissions and Climate hange azards and Hazardous aterials ydrology and Water Quality oise and Vibration	Criteria pollutants: San Francisco Bay Area Air Basin	LTSM	Beneficial	LTSM	Beneficial	LTSM	PS	LTSM	LTSM	LTSM	LTSM	LCCM	Beneficial	
All Quality	Toxic air contaminants: Caltrain ROW and immediate vicinity	LTSM	LTS	LTSM	LTSM	LTSM	LTSM	LTSM	LTSM	LTSM	LTSM	LCCM	Beneficial	
Biological Resources	Terrestrial species: ROW and adjacent Aquatic species: ROW and downstream	LTSM	LTSM	LTSM	LTSM	LTSM	LTSM	LTSM	LTSM	LTSM	LTSM	LCCM	LCCM	
							Histo	orical Resource	es		8			
		PS/UNK	NI	PS/UNKN	NI	PS/UNK	NI	PS/UNK	NI	PS/UNK	NI	LCCM	NI	
Cultural Resources	Coltrain DOW and adjacent to DOW		Archaeological Resource											
	Caltrain ROW and adjacent to ROW	LTSM	NI	LTSM	NI	LTSM	NI	LTSM	NI	LTSM	NI	LCCM	NI	
			Human Remains											
		LTSM	NI	LTSM	NI	LTSM	NI	LTSM	NI	LTSM	NI	LCCM	NI	
	Caltrain ROW and adjacent to ROW	Electromagnetic Fields												
EME/EMI		LTS	LTS	LTS	NI	LTS	NI	LTS	NI	LTS	LTS	LCC	LCC	
		Electromagnetic Interference												
Air Quality Biological Resources Cultural Resources EMF/EMI Geology, Soils and Seismicity GHG Emissions and Climate Change Hazards and Hazardous Materials Hydrology and Water Quality Land Use and Recreation Noise and Vibration		LTS	LTSM	LTS	NI	LTS	NI	LTS	NI	LTS	LTSM	LCC	LCCM	
Geology, Soils and Seismicity	Caltrain ROW and adjacent to ROW	LTSM	NI	LTSM	NI	LTSM	NI	LTSM	NI	LTSM	NI	LCCM	NI	
	The Planet (GHG emissions)	Greenhouse Gas												
GHG Emissions and Climate	San Francisco Peninsula	Benet	ficial	LTS	M	LTSM		I	LTSM		LTSM		Beneficial	
Change	(vulnerability to climate change						Climate Change	(excluding Sea	a Level Rise) ^a					
	impacts, excluding sea level rise)	NI	LTS	NI	LTS	NI	LTS	NI	PS	NI	PS	NI	LCC	
Hazards and Hazardous Materials	Caltrain ROW and adjacent to ROW	LTSM	LTSM	LTSM	LTSM	LTSM	LTSM	LTSM	LTSM	LTSM	LTSM	LCCM	LCCM	
					H	lydrology and	Water Quality (other than Flo	oding due to Sea	Level Rise)				
Hudrology and Water Quality	Caltrain BOW and downstroom	LTSM	LTSM	LTSM	LTSM	LTSM	LTSM	LTSM	LTSM	LTSM	LTSM	LCCM	LCCM	
Hydrology and water Quality	Califani Row and downstream						Flooding	due to Sea Lev	el Rise					
		NI	PS	NI	PS	NI	PS	NI	PS	NI	PS	NI	CCU	
Land Use and Recreation	Adjacent to Caltrain ROW	LTSM	PS	LTSM	PS	LTSM	PS	LTSM	PS	LTSM	PS	LCCM	LCCM	
								Noise						
Noise and Vibration	Caltrain ROW and adjacent to ROW	PS	PS	PS	PS	PS	PS	PS	LTSM	PS	PS	CCU	CCU	
								Vibration						
		LTSM	LTSM	LTSM	LTSM	LTSM	LTSM	LTSM	LTSM	LTSM	LTSM	LCCM	LCCM	
Population and Housing	Project counties	LTSM	LTSM	LTSM	NI	LTSM	LTSM	LTSM	NI	LTSM	NI	NI	NI	

		Rail Projects Planned in the Caltrain ROW			Other Regional Transportation		Land Development Adjacent to		Cumulative Impact		Is Propose	ed Project's	
		CAHSR Blended Service		Other Projects		Improvements		Caltrain ROW		(including Proposed Project)		Contribution Considerable?	
Resource Issue	Geographic Area of Impact	Construction	Operation	Construction	Operation	Construction	Operation	Construction	Operation	Construction	Operation	Construction	Operation
		Disruption to Utilities											
Public Services and Utilities	Caltrain ROW and adjacent to ROW	LTSM	NI	LTSM	NI	LTSM	NI	LTSM	NI	LTSM	NI	LCCM	LCC
	(Construction) Service areas of regional providers to project sites (Operations)		Public Services										
		LTSM	LTS	LTSM	LTS	LTSM	LTS	LTSM	LTSM	LTSM	LTSM	LCCM	LCC
		Landfill Capacity											
		LTSM	LTS	LTSM	LTS	LTSM	LTS	LTSM	LTSM	LTSM	LTSM	LCC	LCC
Transportation and Traffic	Caltrain ROW, roadways crossing ROW, and roadways near stations (traffic level of service, bicycle and pedestrian facilities) San Francisco Peninsula (regional traffic, regional transit systems)	LTSM	PS	LTSM	PS	LTSM	PS	LTSM	PS	LTSM	PS	LCCM	CCU

^a Flooding related to sea level rise is included in the hydrology and water quality impacts.

LTS = Less than significant.

LTSM = LTS with mitigation.

PS = Potentially significant.

NI = No impact.

UNK = Unknown.

NA =Not applicable. LCC = Less than considerable contribution.

LCCM = LCC with project mitigation.

CCU = Cumulatively considerable and unavoidable.

1

14.1.4.1General Characteristics of Cumulative Projects for the2Cumulative Analysis

3 Construction

- 4 There is the potential for cumulative construction impacts where cumulative projects and the
- 5 Proposed Project overlap in location or are adjacent (affecting the same resource/receptor but
- 6 potentially at different times), or if they overlap in time (affecting the same resource/receptor at the
- 7 same time).

8 Blended Service

- 9 Construction of the San Jose to Merced section of the HSR system would occur sometime after 2020
 10 and be completed by 2026.
- 11 Construction associated with Blended Service between San Jose and San Francisco would include
- 12 passing tracks, station development at Diridon and Millbrae (and possibly Redwood City), trackage
- 13 improvements, at-grade crossing improvements and a maintenance facility. Construction would
- 14 occur sometime after 2020 after the Proposed Project construction is completed.
- 15 Thus, construction of the Proposed Project and HSR improvements would not overlap in time.
- 16 However, with a 4-year construction schedule for Proposed Project and then a multi-year
- 17 construction period for HSR, there would be potential for cumulative construction impacts that
- 18 would be longer in duration with both projects than with only the Proposed Project.

19 Other Rail Projects in or Adjacent to the Caltrain ROW

As described in Table 4-3, only some of the other rail projects would have actual construction in or
adjacent to the Caltrain ROW, specifically, Caltrain South Terminal (#4), BART Silicon Valley
Extension (#8), bridge or tunnel work if needed to accommodate higher freight service in the future
(#10), San Bruno Grade Separation project (#11), other Caltrain improvements (#12), and the BART
Millbrae tail tracks (#70). Some of these projects would be constructed prior to Proposed Project
construction, some during, and some after the Proposed Project is completed.

26 **Other Transportation Projects**

- As described in Table 4-3, only some of the other transportation projects would have actual construction in or adjacent to the Caltrain ROW, specifically, Central Subway (#13), Muni 22-
- Fillmore re-route (#14); some of the non-highway improvements (#16), and San Francisco's
- 30 potential future project related to I-280 teardown (#73). Some of these projects would be
- 31 constructed prior to Proposed Project construction, some during, and some after the Proposed
- 32 Project is completed.

33 Land Development Projects Adjacent to the Caltrain Row

- As shown in Table 4-3, none of the land development projects, with the exception of potential future
- redevelopment of the 4th and King Station and yard (#17) is located within the Caltrain ROW.
- 36 However, a number of these projects are adjacent to the Caltrain ROW and some of them are located
- 37 in areas of minor encroachment by the Proposed Project for OCS or ESZ requirements. Some of these

projects would be constructed prior to Proposed Project construction, some during, and some after
 the Proposed Project is completed.

3 **Operations**

4 Blended Service

- 5 Operation of a statewide HST will yield transportation and environmental benefits, including:
- 6 enhanced inter-regional mobility from a new transportation mode; reductions in statewide and Bay
- 7 Area vehicle miles travelled; reduced energy consumption for transportation; air quality
- 8 improvements; and reduced emissions of greenhouse gases (CHSRA 2005).
- 9 CHSRA plans for operational HSR service to San Jose by as early as 2026 (pursuant to the 2014
- 10 <u>CHSRA Business Plan</u>; thus there could be potential cumulative effects after that date of the San
- 11 Jose to Merced section of HSR where it is parallel to the Caltrain ROW between San Jose Diridon
- 12 Station and south of the Tamien Station. The earliest date for potential Blended Service between San
- 13Jose and San Francisco would be sometime between 2026 and 2029. Thus, there would be no
- 14 cumulative operational impacts of the Proposed Project and Blended Service until those dates.

15 **Other Rail Projects in the Caltrain ROW**

- The other rail projects have various planned in-service dates. Some, such as ACEforward (#6),
 Capitol Corridor improvements (#7), and the Coast Daylight project (#9), would increase service in
- 18 the Caltrain corridor by 2020. Freight service could increase, as well. Once the Proposed Project is
- operational (first full year expected to be 2020), there is potential for cumulative operational
 impacts to occur as other passenger and freight rail service increases over time. To analyze the
 potential full impact of such proposed increases, this analysis uses the service increases shown in
- potential full impact of such proposed increases, this analysis uses the service increases shown in
 Table 4-8 for 2040.

23 Land Development Projects Adjacent to the Caltrain Row

As shown in Table 4-3, none of the land development projects, with the exception of potential future
redevelopment of the 4th and King Station and yard (#17) is located within the Caltrain ROW.
However, a number of these projects are adjacent to the Caltrain ROW and some of them are located
in areas of minor encroachment by the Proposed Project for OCS or ESZ requirements. Some of these
projects would be constructed prior to Proposed Project construction, some during, and some after
the Proposed Project is completed.

30 **Operations**

31 Blended Service

- Operation of a statewide HST will yield transportation and environmental benefits, including:
 enhanced inter-regional mobility from a new transportation mode; reductions in statewide and Bay
 Area vehicle miles travelled; reduced energy consumption for transportation; air quality
 improvements; and reduced emissions of greenhouse gases (CHSRA 2005).
- 36 CHSRA plans for operational HSR service to San Jose by as early as 2026 (pursuant to the 2014
- 37 <u>CHSRA Business Plan</u>); thus there could be potential cumulative effects after that date of the San
- Jose to Merced section of HSR where it is parallel to the Caltrain ROW between San Jose Diridon
- 39 Station and south of the Tamien Station. The earliest date for potential Blended Service between San

- 1 Jose and San Francisco would be sometime between 2026 and 2029. Thus, there would be no
- 2 cumulative operational impacts of the Proposed Project and Blended Service until those dates.

3 Other Rail Projects in the Caltrain ROW

- 4 The other rail projects have various planned in-service dates. Some, such as ACEforward (#6),
- 5 Capitol Corridor improvements (#7), and the Coast Daylight project (#9), would increase service in
- 6 the Caltrain corridor by 2020. Freight service could increase, as well. Once the Proposed Project is
- operational (first full year expected to be 2020), there is potential for cumulative operational
 impacts to occur as other passenger and freight rail service increases over time. To analyze the
- 8 impacts to occur as other passenger and freight rail service increases over time. To analyze the
 9 potential full impact of such proposed increases, this analysis uses the service increases shown in
- 10 Table 4-8 for 2040.

11 Other Transportation Projects

- 12 Other transportation projects concerning highways, light rail, or other transit systems would not
- 13 result in cumulative operational impacts along the Caltrain ROW itself. However, there is potential
- 14 for cumulative operational impacts at areas where light rail or transit projects intersect with
- 15 Caltrain stations or the Caltrain ROW and for traffic overall with roadway projects that may facilitate
- 16 increased traffic.

17 Land Development Projects Adjacent to the Caltrain ROW

- 18 Land development projects would not affect rail service itself, but could result in cumulative
- 19 operational impacts related to general traffic, air quality, noise and other operational issues in
- 20 combination with the Proposed Project. In addition, land development projects adjacent to the
- 21 Caltrain ROW would result in additional residential and commercial receptors of operational train
- 22 noise impacts resultant from Proposed Project and other rail projects.

23 **4.1.4.2** Aesthetics

24 Impact CUMUL-1-AES: Cumulative impacts on visual aesthetics

The geographical context area for the analysis of potential cumulative aesthetic impacts consists of the areas adjacent to, within, and in the vicinity of the Caltrain ROW. The existing setting for the Proposed Project is presented in Section 3.1, *Aesthetics*. Cumulative projects within this geographic context include all projects listed in Table 4-3, but the cumulative impact area is limited to the extent of cumulative projects in or adjacent to the Caltrain ROW. The Proposed Project would not contribute to any potential cumulative aesthetic impacts that occur at distance from the Caltrain

31 ROW, such as the potential impacts of HSR between San Jose and Merced.

32 Construction

33 Scenic Vistas

34 The Caltrain ROW and adjacent areas are primarily located in the midst of urban and suburban

- development on the Peninsula corridor. As discussed in Section 3.1, *Aesthetics*, while some of the
- 36 area has a high localized visual quality, there are very limited long-range scenic vistas that include
- 37 the Caltrain ROW, due to the developed character of the ROW and vicinity, its location at-grade in a
- 38 generally flat area and due to the intervening vegetation and buildings blocking scenic vistas.

- 1 Visual signs of construction of the Proposed Project, Blended Service improvements, HSR San Jose to
- 2 Merced, and other construction along the Caltrain ROW would include construction equipment and
- 3 stockpiling of soils, as well as new structures. During this phase, construction activity would be
- 4 highly noticeable to residents and others in the immediate vicinity.
- 5 The view from bridges would be fleeting for crossing motorists, bicyclists, and pedestrians, and 6 construction would not affect their long-range views because viewers would be elevated above the 7 Caltrain ROW and other construction activities. The view from adjacent multi-level buildings of the 8 Santa Cruz Mountains, San Francisco Bay, or San Bruno Mountain would not be blocked by
- 9 cumulative construction activities. Cumulative construction activities would not likely be seen from
- 10 distant hillsides because of intervening features and activities except for substantial elevated
- 11 structures. Elevated structures could be associated with HSR north and south of the San Jose Diridon 12 Station if an aerial station option is selected.
- 13 Ground level views from adjacent residential, commercial, and park areas would be affected by 14 construction where the Caltrain ROW is visible from these adjacent areas, but these views are short-15 range in character, not long-range scenic vistas.
- 16
- Cumulative construction activities although of a longer duration when combining Proposed Project 17 and cumulative projects would, thus, have less-than-significant impacts on scenic vistas. Thus, the
- 18 Proposed Project would have a less-than-considerable contribution to cumulative aesthetic impacts
- 19 relative scenic vistas.

20 Scenic Resources within or along a Designated Scenic Roadway

21 As discussed in Section 3.1, *Aesthetics*, there are no designated scenic roadways directly adjacent to 22 the Caltrain ROW between San Jose and San Francisco except I-280 in San Francisco. Given that I-23 280 is elevated where it crosses the Caltrain ROW and Proposed Project, and that Blended Service 24 and other rail projects would use the Caltrain ROW itself, construction of cumulative rail service is 25 not likely to affect any scenic resources associated with I-280. The Proposed Project would not affect 26 any scenic resources within a designated scenic roadway during construction. While other 27 cumulative projects may affect scenic resources along a designated scenic roadway during 28 construction, the Proposed Project would not make any contribution to such potential impacts that 29 are not in or adjacent to the Caltrain ROW itself. Therefore, the Proposed Project's contribution to 30 potential cumulative construction impacts on scenic resources along a designated scenic roadway 31 would be less than considerable

32 Visual Character

- 33 This impact concerns temporary visual changes during construction. Cumulative construction of 34 concern for this analysis would occur in or adjacent to the Caltrain ROW. As described in Section 3.1,
- 35 Aesthetics, the character of the areas adjacent to the Caltrain corridor vary from residential to 36 commercial to industrial and includes a number of park areas as well. Cumulative construction
- 37 would be most out of character in residential and park areas and less out of character in commercial
- and industrial areas or in transportation corridors (like the Caltrain ROW). Where construction 38
- 39 activities are present for an extended period of time in or directly adjacent to residential or park
- 40 areas, there could be a temporarily significant aesthetic impact.
- 41 For the Proposed Project, Mitigation Measure AES-2a is required to minimize the Proposed Project's temporary impacts on residential and park areas outside the Caltrain ROW. Although other 42

- 1 cumulative projects may also result in a temporary change of visual character of areas adjacent to
- 2 the Caltrain ROW during construction, with the recommended mitigation measure, the Proposed
- Project's contribution to cumulative temporary changes in visual character would be less than
 considerable.
- 5 Light and Glare
- 6 Both the Proposed Project and Blended Service improvements would require night-time
- 7 construction. Other railway and transportation projects and possibly some of the land use projects
- 8 may also require night-time construction as well. This could result in light spill over into adjacent
 9 residential areas, which if uncontrolled could be significant.
- 10 During Proposed Project nighttime construction, pursuant to Mitigation Measure AES-4a, the JPB
- 11 will require the project contractor to ensure that construction crews working at night direct any
- 12 artificial lighting onto the work site, to minimize spill over light or glare in adjacent residential
- 13 areas. With this mitigation, the project's contribution to a potential cumulative impact on light and
- 14 glare during construction is not considerable.

15 **Operation**

16 Scenic Vistas

17 Blended Service

- As noted above, the Caltrain ROW is not a readily observable part of a scenic vista due to its setting
 in an urban and suburban context with few long-range scenic views of the ROW itself. In the San Jose
- 20 to Merced HSR segment, the approaching aerial tracks between the Caltrain Tamien Station and the
- 21 San Jose Diridon Station would elevated and would be highly observable as part of long range views
- 22 of downtown San Jose. For Blended Service improvements north of Diridon, potentially elevated
- 23 structures between San Jose to Santa Clara and for grade separations elsewhere would have the
- 24 greatest potential to affect scenic vistas. The maintenance yard, if proposed at the
- Brisbane/Bayshore location close to U.S. Highway 101, may also be readily observable by passing
 motorists, although this area at present consists of formerly used industrial and landfill property
 and is not particularly of a high visual quality. Passing tracks will be noticeable to local communities,
 but if at-grade, would not disrupt scenic vistas.

29 All Other Projects

- Cumulative projects along the Caltrain ROW could also affect scenic vistas from buildings, hillsides,
 and bridges and other locations, particularly where new highly elevated structures are proposed
 that are discimilants quisting development along the POW
- 32 that are dissimilar to existing development along the ROW.

33 **Proposed Project Cumulative Contribution**

- 34 While cumulative projects could affect scenic vistas where new structures affect long-range views of
- 35 the Santa Cruz Mountains, San Francisco Bay, or other visual resources, the Proposed Project itself
- 36 would only have minimal impacts on long-range views because the Proposed Project improvements
- 37 would be difficult to distinguish among the developed areas along the Caltrain ROW. Moreover, the
- 38 Proposed Project improvements installed as part of the Caltrain ROW would be consistent with the
- 39 character of the ROW as a rail corridor such that they would not substantially change this part of a

- long-range view. Consequently, the Proposed Project's contribution to the cumulative impact on
 scenic vistas would be less than considerable.
- 3 Scenic Resources within or along a Designated Scenic Roadway
- 4 As noted above, the Proposed Project would not affect any scenic resources within a designated
- 5 scenic roadway. While other cumulative projects may affect scenic resources along a designated
- 6 scenic roadway, the Proposed Project would not make any contribution to such potential impacts
- 7 that are not in or adjacent to the Caltrain ROW itself. Therefore, the Proposed Project's contribution
- 8 to potential cumulative operational impacts on scenic resources along a designated scenic roadway
- 9 would be less than considerable.

10 Visual Character

11 Blended Service

12 The aerial structures and new trackage proposed for HSR for the San Jose to Merced segment

- 13 approaching San Jose from north of SR 82 and the Diridon Station would be located along the
- 14 Caltrain ROW and would affect the visual character of existing areas along the ROW, particularly
- 15 where the Caltrain ROW is adjacent to residential areas in San Jose. A potential aerial structure from
- 16 the Diridon Station to Santa Clara would also change the visual character of this area although much
- 17 of the Caltrain ROW is adjacent to commercial and industrial areas to the east.
- 18 The Blended Service proposed improvements between Santa Clara and San Francisco could affect 19 the visual character of areas along the passing tracks, at Diridon and Millbrae Stations (and possibly 20 Redwood City Station), at the maintenance yard location, and potentially in other areas where grade 21 separations or other improvements are proposed. While station changes could be substantial, given 22 that these are existing stations, the new stations would be generally consistent with existing visual 23 character. However, depending on the specific design, though compatible with current uses, the 24 actual character could be substantially changed. This would be more acute at a historic station (such 25 as Diridon) than a station with extensive recent visual changes (such as Millbrae).
- The impact of the passing tracks on visual character would depend on their location and design. The
 general visual setting of the preliminary 5 locations studied to date is as follows
- The North 4 Track (San Francisco to Burlingame): Areas adjacent to the northern part of this section are primarily industrial and commercial in Brisbane and South San Francisco. Areas adjacent to the southern part of this section are dominated by adjacent residential areas in San Bruno (including two parks), a mix of residential and commercial uses in Millbrae and Burlingame.
- The Long-Middle 4 Track (San Mateo to Redwood City): Areas adjacent to the northern part of
 this section contains a mix of adjacent commercial and residential areas in San Mateo,
 transitioning to primarily residential areas in Belmont, primarily commercial areas in San
 Carlos, with a mix of commercial and residential areas in Redwood City. Several parks are
 adjacent in San Mateo and Redwood City.
- The Short-Middle 4 Track (San Mateo to San Carlos): Areas adjacent to the northern part of this section contain a mix of adjacent commercial and residential areas in San Mateo (including one adjacent park), transitioning to primarily residential areas in Belmont and commercial areas in San Carlos.

- The Middle 3 Track (San Mateo to Palo Alto): Areas adjacent to the northern part of this section
 contain a mix of adjacent commercial and residential areas in San Mateo, transitioning to
 primarily residential areas in Belmont, commercial areas and San Carlos and a mix of
 commercial and residential areas in Redwood City. The southern part of this section includes
 adjacent residential areas in Atherton, Menlo Park, and Palo Alto, with commercial areas in
 downtown Menlo Park and Palo Alto. Several parks are adjacent in San Mateo, Redwood City,
 Atherton and Palo Alto.
- The South 4-Track (Mountain View to Santa Clara): Areas adjacent to this section contains a mix
 of residential and commercial areas including several parks in Mountain View.

Within areas where adjacent land uses are commercial or industrial in character, additional passing
 tracks, even if outside the ROW, would not have a significant impact on visual character. In
 residential areas or areas with parks, expansion outside the ROW for passing tracks, where
 necessary, could change the visual character of the land immediately adjacent to the existing
 Caltrain ROW itself.

- 15The impact of a new maintenance yard and any grade separations or other improvements would16also depend on their location. The previously studied maintenance yard location in Brisbane/17Bayshore (in the 2010 CHSRA alternatives analysis) is in an area of historic industrial, railroad and18landfill use, but the area is proposed for redevelopment with residential, commercial, industrial and19park use by the Brisbane Baylands project. Depending on the uses extant at the time of Blended20Service, the addition of maintenance yard at the Brisbane/Bayshore location may or may not be21consistent with the visual character at that time.
- As indicated in Table 4-8, the corridor is presently used by nearly 100 trains per day between Santa
 Clara and San Francisco and 125 trains per day between Santa Clara and San Jose. Thus, the addition
 of HST trains themselves (in combination with other rail increases) will not change the visual
 character of the Caltrain corridor as a transportation corridor. The changes in noise and vibration
 due to additional trains on adjacent land uses is discussed separately below.
- Overall aesthetic impacts of new HSR facilities for the San Jose to Merced segment and for Blended
 Service facilities between San Jose and San Francisco are considered potentially significant
 depending on their ultimate location and design. The highest potential for significant visual
- 30 character impacts would be for any elevated grade separations or passing tracks outside the Caltrain
- 31 ROW if located in sensitive visual areas such as residential areas or parks.

32 All Other Projects

- During operation, the cumulative projects could change the visual character in the project area due
 to permanent structures and changes in landscaping.
- 35 Cumulative transportation projects would introduce new features such widened roadways, bridges
- 36 and interchanges, aerial and at-grade tracks, overhead power lines and grade separations.
- 37 Cumulative transportation projects would also increase passenger and freight rail, light rail, and
- 38 roadway use as well although such increase in use would not change the aesthetic character of
- 39 existing roadway, rail, and light rail corridors unless facilities in new locations are proposed. In
- 40 some cases, cumulative transportation projects would affect Caltrain station aesthetics (such as at
- Diridon, Santa Clara, 4th and King, Millbrae, and Palo Alto, among others) that are also affected by
- 42 the Proposed Project.

- Other passenger and freight service increases would contribute to the change in intensity of the
 Caltrain corridor combined with increased Caltrain and HSR rail service due to the more than
- 3 doubling of overall number of trains by 2040.
- 4 Cumulative land use development would introduce new building structures which may or may not 5 be consistent with the current visual character. Many locations along the Caltrain ROW, particularly in downtown areas and near many Caltrain stations are seeing increased density of residential and 6 7 commercial development including transit-oriented development. In many of the more suburban 8 communities, this increased density and diversity of land use represents a change from the single-9 family residential visual character of some of these communities. In more urbanized areas, such as 10 San Francisco or downtown San Jose, the change in character is more one of intensity in that these 11 areas are substantially developed at present with new development only increasing the existing 12 densities and heights of development.
- PS4, Options 1 and 2 would be located within an area envisioned for Transit Oriented Development
 and a Transit Center and associated improvements as part of the Hillsdale Station Area Plan. As
 concluded in Section 3.10, these two options would require minor reconfiguration of the plan, and
- may be adjacent to potential future residential or park/plaza uses. If PS4, Options 1 or 2 are selected
 and the adjacent areas are actually proposed for residential and/or park/plaza use, then Mitigation
 Measure AES-2b would be implemented for these locations. If PS4, Option 3 is selected, then no
 mitigation would be required.
- As described in Section 3.3. Caltrain will coordinate with the City of San Carlos in regards to
 potential tree plantings associated with the San Carlos Transit Village and will apply Mitigation
 Measure BIO-5 as appropriate to project tree effects.
- 23 SWS Option 1 would be located adjacent to, but not in an area proposed for mixed 24 residential/commercial/lightindustrial use in the Redwood Triangle portion of the North Fair Oaks 25 Community Plan. Given the mixed-use designation, it is more likely that future residential redevelopment would not happen directly adjacent to the Caltrain mainline but would rather likely 26 27 occur on the north part of Redwood Triangle, closer to Middlefield Road to separate residential 28 development from the active mainline and to provide residential development close to services and 29 transit connections along Middlefield Road. The area north of the active tracks is used and will likely 30 continue to be used for laydown of equipment and supplies; a use that will continue whether or not 31 the PCEP switching station is placed at the proposed location. If commercial or light industrial 32 development occurs along the southern perimeter of Redwood Triangle, the switching station would 33 be obscured from view from other areas within Redwood Triangle, similar to current conditions. 34 Nevertheless, if in the future, the switching station is constructed at the proposed location and there is a viable proposed residential development on the site that would have an unobstructed view of 35 the switching station with no intervening development, then Caltrain is willing to apply Mitigation 36 37 Measure AES-2b to the switching station location and provide vegetative screening, as feasible on 38 the north side of the switching station in order to ensure that aesthetic impacts would be less than 39 significant in that situation. This mitigation will only be required if adjacent areas are actually 40 proposed to be developed for residential use and will not be required until that is a reality. The JPB 41 has also identified a second option, SWS1, Option 2, located north of the JPB tracks adjacent to the 42 Orchard Supply Hardware and Costco in Redwood City just to the west of Redwood Junction that 43 would not be adjacent to the proposed mixed use area.

- 1 <u>As described in Section 3.1, there are overlapping vegetative screening requirements relative to the</u>
- 2 mixed use development at 195 Page Mill Road in Palo Alto and the mitigation requirement for
- Mitigation Measure AES-2b for PS5, Option 2. As required in the mitigation measure, the JPB will
 coordinate with the project developer during design.

5 **Proposed Project Cumulative Contribution**

- 6 As discussed in Section 3.1, *Aesthetics*, the Proposed Project would have permanent effects on 7 aesthetics along the Caltrain ROW due to the OCS, the TPFs, and tree removal/trimming.
- 8 The addition of the OCS would affect the visual character of some visually sensitive areas, including
- 9 adjacent residential areas, parks and Caltrain historic stations. Implementation of Mitigation
- 10 Measure AES-2b would ensure that OCS poles recede into the visual landscape as much as feasible.
- 11 Because the OCS would be limited to along the Caltrain ROW itself and would be a linear feature
- consistent with existing railroad ROW visual character and Mitigation Measure AES-2b would help
 to reduce the visual obviousness of the OCS, the Proposed Project's OCS would make a less-than-
- 14 considerable contribution to potential cumulative impacts on visual character.
- 15 However because of permanent tree removal for the OCS/ESZ requirements, the Proposed Project 16 may have a localized significant and unavoidable impact on visual character in specific locations 17 where implementation of required mitigation (Mitigation Measure BIO-5) for tree replacement 18 would not avoid a significant change in localized visual character. Where cumulative projects also 19 substantially change visual character in areas where the Proposed Project would also have 20 permanent aesthetic effects, there may be a cumulatively significant impact on localized visual 21 character. In such areas, albeit localized, the Proposed Project is considered have a cumulatively 22 considerable and unavoidable impact on visual character.

23 Light and Glare

24 Blended Service

- Blended Service could introduce new lighting at stations at Diridon, Millbrae, and possibly Redwood
 City, as well as at any new maintenance areas. If uncontrolled such additional lighting could spill
 over into adjacent residential areas; however such lighting is usually readily controllable through
 appropriate lighting controls.
- 29 In addition, the HSR trains, when running at night would increase train light along the Caltrain ROW
- 30 itself. Because the Caltrain ROW already has train light as part of the existing setting at night, the
- 31 addition of more train light is not considered a significant impact.

32 All Other Projects

- 33 Other cumulative projects could introduce new lighting as part of residential, commercial, or
- 34 transportation projects. If uncontrolled, additional structural lighting could spill over into adjacent
- 35 residential areas; however such lighting is usually readily controllable through appropriate lighting
- 36 controls. Transportation projects would likely increase train and vehicle light along existing
 37 transportation corridors, including the Caltrain ROW. Where this occurs on existing rail and
- 38 roadway corridors, the addition of more train or vehicle light is not considered a significant impact.

1 Proposed Project Cumulative Contribution

- 2 The Proposed Project could introduce new lighting or glare associated with the TPFs and OCS that
- could affect the visual character of the area along the Caltrain ROW if uncontrolled and this could
 contribute to cumulative light and glare impacts. However, with the implementation of Mitigation
 Measures AES-2b and AES-4b, the Proposed Project's contribution to potential cumulative light and
- 6 glare impacts would be reduced to a less-than-considerable level.

7 **4.1.4.3** Air Quality

As discussed in Section 3.2, *Air Quality*, the Proposed Project would be consistent with regional air
 quality plans and would only result in routine construction odors, and would reduce operational
 odors. Thus these issues are not the focus of this cumulative analysis which focused on criteria
 pollutants and toxic air contaminants.

- 12 The geographic context for the analysis of cumulative criteria pollutant impacts is the San Francisco
- 13 air basin as criteria pollutant emissions are a regional concern. Past, present and probable future
- cumulative projects within this geographic context include all projects listed in Table 4-3 as well as
 the general growth included in Table 4-1.
- 16 The geographic context for the analysis of cumulative toxic air contaminants impacts is the
- 17 immediate area along the Caltrain ROW that is presently affected by diesel emissions and would be
- 18 changed with the Proposed Project. Past, present and probable future cumulative projects within
- 19 this geographic context include only those projects listed in Table 4-3 that are in, adjacent to the
- 20 Caltrain ROW or within a short distance from the Caltrain ROW.
- 21 Impact CUMUL-2-AQ: Cumulative effects on air quality

22 Construction

23 Criteria Pollutants

- 24 During construction of the cumulative projects listed in Table 4-3 and the overall growth shown in 25 Table 4-1, criteria pollutants that could impact air quality in the San Francisco air basin would be 26 emitted. Construction of the cumulative projects may emit criteria pollutants singularly that could 27 exceed the allowable threshold for criteria pollutants in the basin or could exceed these thresholds 28 for the combined effect of cumulative construction that occurs at the same time. Therefore, the 29 cumulative projects would have a significant cumulative impact on air quality due to construction. In 30 the Bay Area, all discretionary projects evaluate their construction air quality emissions and usually 31 compare them to the BAAQMD's construction daily or annual thresholds for criteria pollutants. The 32 BAAQMD's thresholds are designed so that if all projects meet those thresholds, then regionally 33 construction would not have a significant effect on regional air quality. Through the CEQA process, 34 lead agencies usually require that individual projects that exceed the thresholds provide mitigation 35 to reduce emissions to the threshold levels, where feasible. However, for some large projects, it may 36 not be feasible to always reduce to the adopted thresholds.
- 37 For the San Jose to Merced HSR segment and for Blended Service improvement construction, CHSRA
- 38 would employ the project design features that it has included in prior project-level documents, such
- 39 as fugitive dust controls. The project-level environmental documents for the HST Merced to Fresno
- 40 segment (CHSRA 2012d) and the HST Fresno-Bakersfield segment (CHSRA 2012e) both concluded

- 1 that project construction criteria pollutants would be significant before mitigation, but could be
- 2 reduced to a less than significant levels with project mitigation (including reduction of exhaust
- 3 emissions from construction equipment and on-road vehicles and purchase of offsets where onsite
- mitigation was insufficient to lower construction emissions below relevant thresholds). A similar
 conclusion is likely for San Jose to Merced HSR segment and Blended Service improvements
- conclusion is likely for San Jose to Merced HSR segment and Blended Service improvements
 construction, although construction emissions along the Caltrain corridor should be lower than
- 7 these Central Valley segments.
- 8 As described in Section 3.2, *Air Quality*, the Proposed Project would have a significant impact on
- 9 criteria pollutant emissions before mitigation for construction. However, with the implementation of
 10 Mitigation Measures AQ-2a through AQ-2c, the Proposed Project's criteria pollutant emissions
 11 would be reduced below the BAAQMD thresholds. Thus, the Proposed Project's contribution to
 12 potential cumulative impacts on air quality related to criteria pollutants would be reduced to a less13 than-considerable level.

14 **Toxic Air Contaminants**

- Construction of the Blended Service improvements and a portion of the HSR San Jose to Merced segment would occur along the Caltrain ROW with the possible exception of the maintenance yard (depending on location) and would result in toxic air contaminant emissions (in the form of diesel
- 18 particulate matter (DPM)) due to construction equipment and vehicles.
- 19 Construction of other rail improvements and other cumulative projects along the Caltrain ROW 20 could emit TACs (primarily in the form of DPM) that could impact public health of sensitive 21 receptors along the Caltrain ROW. The TACs would be emitted from construction equipment and 22 exhausts of workers' vehicles. The project-level environmental documents for the HST Merced to 23 Fresno segment (CHSRA 2012d) and the HST Fresno-Bakersfield segment (CHSRA 2012e) both 24 concluded that project construction TAC pollutants would be not be significant for alignment 25 construction but would be significant for certain sensitive receptors close to a station or concrete 26 batch plant. These impacts were found to be reduced to a less than significant level with project 27 mitigation. A similar conclusion is likely for the construction of the San Jose to Merced HSR segment 28 and the Blended Service improvements, although construction emissions along the Caltrain corridor 29 should be lower than these Central Valley segments.
- Therefore, the cumulative projects could have a potential significant cumulative impact on public
 health from TAC emissions on sensitive receptors along the Caltrain ROW.
- As described in Section 3.2, *Air Quality*, the Proposed Project would not have a significant impact
 related to TAC/DPM emissions for construction. Implementation of Mitigation Measures AQ-2b
 through AQ-2c as mitigation for criteria pollutants would further reduce the Proposed Project's
 TAC/DPM emissions. Thus, the Proposed Project's contribution to potential cumulative impacts on
- 36 air quality related to TAC/DPM emissions for construction would be less than considerable.
- 37 **Operation**
- 38 Criteria Pollutants

39 Blended Service

40 Operationally, HSR trains would not add any local criteria pollutant emissions due to train
 41 operation, since HSR trains would use electricity and not use diesel fuel. Indirect criteria pollutant

- 1 emissions would occur at power plants providing the electricity for HSR (depending on fuel
- 2 source¹²), but such plants are highly regulated under state and federal law to be consistent with the
- 3 air basin plans for areas in which they are located to not result in significant impacts to regional air
- quality. There would be some criteria pollutant emissions associated with maintenance yard
 operations and maintenance of HSR facilities as well as worker commutes, but such emissions are
 not ownerted to be substantial
- 6 not expected to be substantial.
- 7 On a broader scale, Blended Service would offset vehicular and air travel criteria pollutant emissions
- 8 for individuals choosing to take the high speed train for regional or state-wide travel instead of
- 9 driving or flying. The Program EIS/EIR for the state-wide HST system (CHSRA 2005) concluded that 10 statewide criteria pollutants would be reduced by 0.5 to 1.4 percent with the HST system compared
- 11 with the No Project conditions overall.

12 All Other Projects

- 13 During operation of the other cumulative rail projects, there would be criteria pollutant emissions
- from diesel-based rail services such as ACE, Dumbarton Rail Corridor (DRC), Capitol Corridor, and
 Amtrak, as well as from freight rail. Due to federal regulations, emissions associated with diesel
- 16 Anitrak, as wenas noninneght ran. Due to reder an egulations, emissions associated with dieser 16 trains will dramatically decline over time which will reduce present and future emissions associated
- 17 with rail service. Light-rail systems such as VTA's system are electrically powered and thus have no
- direct emissions, but have indirect emissions due to electricity provision. Both light and heavy-rail
 services provide alternatives to vehicular travel and freight rail provides an alternative to trucking
 and thus usually result in a net reduction in criteria pollutant emissions relative to vehicular travel
- 21 or trucking. A similar conclusion applies to bus transit projects, like BRT or shuttles.
- During operation of the cumulative highway projects, there may be an increase in vehicular
 emissions if such projects result in induced traffic. If such projects result in a net decrease in vehicle
 miles traveled (through high-occupancy vehicle lanes for example), then they would reduce criteria
 pollutant emissions. All major highway projects receiving federal funding must be consistent with
 the regional air quality plans.
- During operation of the cumulative land use projects, there could be an increase in criteria pollutant
 emissions from increased vehicular travel. Over time, state and federal regulations are seeking to
 dramatically reduce the emissions of new vehicles through increased gas mileage as well as
 emission controls. Whether or not there will be an increase in criteria pollutant emissions due to
 land use development along the Peninsula corridor will depend on the rate of growth, vehicle
 technology, transit options, alternatives to vehicle travel such as bicycle use, and air quality
 regulation over time.

34 Proposed Project Cumulative Contribution

As discussed in Section 3.2, *Air Quality*, the Proposed Project would switch from diesel to electrically powered trains, and thus decrease the amount of criteria pollutants emitted during operation. In addition, by increasing service, the Proposed Project would provide increased alternatives to vehicle travel and thus reduce vehicle emissions as well. As a result, the Proposed Project's contribution to cumulative criteria pollutant impacts would be beneficial.

¹² CHSRA is exploring the potential to power the HSR with 100 percent renewable power (CHSRA 2013b).

1 Toxic Air Contaminants

2 Blended Service

Operationally, HSR operations would not add any DPM emissions along the Caltrain ROW due to
 train operation, since HSR trains would not use diesel fuel. There may be some diesel emissions
 associated with maintenance yard operations and maintenance of HSR facilities as well but the
 impact will depend on the proximity of the maintenance yard to sensitive receptors. The previously

- 7 proposed Bayshore/Brisbane location is presently an industrial area that would be less sensitive
- 8 than alternative locations that may be closer to residential areas, however this area is proposed to
- 9 be converted to residential, commercial and other uses by the Brisbane Baylands project.

10 All Other Projects

- 11 During operation of the other cumulative rail projects, there could be increased DPM emissions from
- 12 diesel-based rail services such as ACE, DRC, Capitol Corridor, AMTRAK as well as freight rail. Due to
- 13 federal regulations, emissions associated with diesel trains will dramatically decline over time
- 14 which will reduce present and future DPM emissions associated with rail service. Light-rail systems
- 15 such as VTA's system are electrically powered and thus have no DPM emissions. Freight rail
- 16 provides an alternative to trucking and thus can result in a net reduction in DPM emissions,
- although the location of the freight rail emissions (along the Caltrain ROW) and the displaced
 trucking (generally along freeways and major arterials) are different meaning that different
- 19 sensitive receptors will have different impacts.
- During operation of the cumulative highway projects, there may be an increase in truck DPM
 emissions if such projects result in induced truck traffic. Due to federal regulations, emissions
 associated with diesel trucks will also dramatically decline over time which will reduce present and
 future DPM emissions associated with trucking.
- 24 During operation of most cumulative land use projects, substantial TAC or DPM emissions are not 25 expected as most residential and commercial traffic is presently with gasoline vehicles which do not 26 result in substantial TAC/DPM emissions. However, materials delivery to such development will be 27 via truck, most of which are diesel trucks and thus some minor increases in DPM emissions will also 28 occur (although truck DPM emissions will decline over time due to regulation).
- 29 **Proposed Project Cumulative Contribution**
- 30 As discussed in Section 3.2, *Air Quality*, the Proposed Project would switch from diesel to electrically
- 31 powered trains, and thus decrease the amount of TAC/DPM pollutants emitted during operation, 32 thus improving health conditions along the entire Caltrain corridor between San Iose and San
- thus improving health conditions along the entire Caltrain corridor between San Jose and San
 Francisco. As a result, the Proposed Project's contribution to cumulative TAC impacts would be
- 34 beneficial.

35 **4.1.4.4 Biological Resources**

36 Impact CUMUL-3-BIO: Cumulative effects on biological resources

- 37 This analysis focused on potential cumulative loss of sensitive biological resources, which is defined
- 38 as including special-status species, riparian habitats or other sensitive natural communities,
- 39 protected wetlands or waters, and wildlife migration or nursery sites. This analysis also examines

- potential cumulative conflicts with local biological protection ordinances or adopted habitat
 conservation plans.
- 3 The geographic context for the analysis of cumulative biological resources impacts includes the
- 4 Caltrain ROW and immediate vicinity. For potential impacts to terrestrial species, the Caltrain ROW
- 5 is the geographic context and for aquatic species the geographic context includes the streams
- 6 traversed by the ROW and downstream. The cumulative projects included in this cumulative
- 7 analysis include all projects listed in Table 4-3.

8 Construction

- 9 As discussed in Section 3.3, *Biological Resources*, the Caltrain ROW is primarily an urban and
- 10 suburban rail corridor with only limited areas of sensitive biological habitat. Construction of HSR
- 11 San Jose to Merced and Blended Service improvements along the Caltrain corridor could potentially
- 12 affect the same biological resources affected by the Proposed Project. Blended Service
- 13 improvements construction could also affect biological resources not affected by the Proposed
- 14 Project due the maintenance yard (depending on location). Additional tree removal may also need to
- 15 occur for the San Jose to Merced construction and where Blended Service passing tracks are located
- 16 outside of existing Caltrain tracks for the additional OCS and ESZ for those passing tracks. Aquatic
- 17 habitat could also be degraded from an increase in erosion and sedimentation during construction.
- 18 The project-level environmental documents for the HST Merced to Fresno segment (CHSRA 2012d) 19 and the HST Fresno-Bakersfield segment (CHSRA 2012e) both concluded that project construction 20 impacts to biological resources would be significant before mitigation, but could be reduced to a less 21 than significant levels with project mitigation. A similar conclusion is likely for construction of the 22 San Jose to Merced and Blended Service improvements, although given the urban/suburban nature 23 of the Caltrain Corridor, there are far less areas of biological sensitivity potentially affected along the 24 Caltrain ROW and thus impacts would be less than on the Central Valley segments (or on natural 25 lands crossed by the San Jose to Merced HSR segment).
- 26 Construction activities for other cumulative projects could also result in the loss of biological
- 27 resources due to grading, paving and tree removal where sensitive biological resources are present.
 28 Aquatic habitat could be degraded from an increase in erosion and sedimentation during
 29 construction. However, in most cases, project-level mitigation will be able to reduce impacts to a less
- 30 than significant level.
- 31 As described in Section 3.3, *Biological Resources*, the Proposed Project could have significant impacts 32 to special-status species, riparian habitats or other sensitive natural communities, protected 33 wetlands or waters and to trees along the Caltrain ROW without mitigation. However, with 34 implementation of Mitigation Measure BIO 1a-1h (special-status species), BIO-2 (sensitive natural 35 communities), BIO-3 (wetlands and waters), BIO-5 (tree avoidance, minimization, and replacement) 36 and BIO-6 the Proposed Project's project-level impacts on biological resources due to construction 37 would be reduced to a less-than-significant level. The Proposed Project construction would not 38 occur in pristine areas, but, rather, in a developed rail corridor; thus, impacts would be to remnant 39 biological resources within that context. Given that context, with mitigation, the Proposed Project's 40 residual construction impacts would be limited in scale and extent. Consequently, Proposed Project 41 construction, with mitigation, would make a less than considerable contribution to any potential
- 42 cumulative impacts on biological resources due to construction.

1 **Operation**

2 Blended Service

While increased train traffic would occur with HSR operations and the Proposed Project, operational
 conditions are not expected to be significantly different from pre-project conditions relative to
 biological resources. Routine tree maintenance would be conducted along the Caltrain ROW for all
 areas where OCS clearance is required, but these activities would be similar to existing maintenance
 practices albeit they would be conducted in more expansive areas and more frequently than at
 present.

9 HSR tracks south of Diridon for the San Jose to Merced segment and additional station space at

10 Diridon, Millbrae, and potentially Redwood City would require additional impervious spaced which

- 11 would result in additional runoff generation. In addition, a new maintenance facility would also have
- new impervious spaces as well as the operational use of fuels and other materials. Any new facilities
 would need to comply with applicable state and federal water quality requirements concerning
 stormwater runoff and control of fuels and other materials with potential to pollute downstream
- 15 waters.

16 All Other Projects

17 For the most part, impacts to biological resources along the Caltrain corridor from the cumulative 18 projects would occur during the construction phase; however there could be new impacts related to 19 operations of some of the cumulative projects. Where development occurs on existing vacant sites, 20 there could be increases in the stormwater runoff which could degrade water quality in surface 21 waters downstream of the Caltrain ROW corridor and affect aquatic species. However, current water quality regulations implemented through the countywide stormwater NPDES permits requires 22 23 treatment of stormwater runoff for substantial new projects precisely to manage the cumulative 24 impact on water quality of new development in the corridor. Some of the projects may also handle 25 fuel or other hazardous materials.

26 **Proposed Project Cumulative Contribution**

27 As described in Section 3.3, Biological Resources, the Proposed Project could have significant impacts 28 to nesting bird or bat species during tree maintenance along the Caltrain ROW without mitigation. 29 However, with implementation of Mitigation Measure BIO-1j, impacts due to disruption of bird 30 nesting or bat roosting would be reduced to a less-than-significant level. The additional permanent 31 project facilities (traction power substations, switching station, and paralleling stations) would have 32 limited areas of new impervious surfaces that would result in limited increases in stormwater 33 generation potential. As discussed in Section 3.9, *Hydrology and Water Quality*, these facilities would 34 comply with the respective countywide stormwater programs, which would result in less-than-35 significant indirect impacts on the water quality and hydrology of waters and wetlands. 36 Consequently, with mitigation Proposed Project operation would make a less-than-considerable

37 contribution to potential cumulative impacts on biological resources due to operations.

1 **4.1.4.5** Cultural Resources

2 Impact CUMUL-4-CUL: Cumulative effects on cultural resources

3 Methodology

4 **Historical Resources**

5 The geographical context area for architectural historical resources was defined to include the area directly adjacent to the Caltrain ROW, the parcels surrounding the proposed traction power facility 6 7 sites and the Caltrain ROW. The project APE/study area includes a variety of historical structures 8 considered historic resource under CEQA and eligible for the national or California registers. Table 9 3.4-3 in Section 3.4, *Cultural Resources*, lists the 25 eligible and listed properties within Proposed 10 Project APE. Cumulative projects within this geographic context include all projects within and 11 adjacent to the Caltrain ROW. An adverse change to an eligible and listed property in the NRHP and 12 CRHR during the construction phase of a cumulative project could result in significant cumulative 13 impacts on historical archeological resource.

14 Archaeological Resources

15The geographic context for the analysis of potential cumulative impacts on archeological resources16includes areas where cumulative projects overlap with the Proposed Project to affect a single17resource. Present and probable future cumulative projects within this geographic context include all18projects within and adjacent to the Caltrain ROW. If known or unknown archeological resources are19disturbed, the identified cumulative projects could result in significant cumulative impacts on20archaeological resources.

21 Human Remains

22 The geographic context for the analysis of potential cumulative impacts on human remains includes

areas where cumulative projects overlap with the Proposed Project site to affect a single resource.
 Present and probable future cumulative projects within this geographic context include all projects
 within and adjacent to the Caltrain ROW. If known or unknown human remains are disturbed, the
 identified cumulative projects could result in significant cumulative impacts on a cultural resource.

27 Construction

28 Historic Resources

29 Construction of the HSR improvements would include improvements at the Diridon Station and

- 30 Millbrae Station, both of which are NRHP and CRHP listed structures. In addition, it is possible that 31 there may be historic resources (including historic buildings as well as any historic tree groves if
- 31 there may be historic resources (including historic buildings as well as any historic tree groves if 32 present) located in areas ultimately proposed for passing tracks or a maintenance yard (or possibly
- 33 for other improvements like grade separations) that might be affected by HSR construction.
- 34 Some of the other cumulative projects (including projects Nos. 4, 5, 12, 16, 30, 57, 67, 68, 69, and 72)
- 35 could also affect historic Caltrain stations at Millbrae, San Carlos, Atherton, Menlo Park, Palo Alto,
- 36 Santa Clara, and San Jose or historic underpassings. The San Mateo Bridge Project will remove and
- 37 replace the four historic underpasses in San Mateo and, thus, the Proposed Project would not have
- 38 an effect on those underpasses because they will be removed by another project prior to the

- 1 completion of the Proposed Project. If freight rail service requires additional height clearances,
- 2 modifications could affect historic railroad tunnels in San Francisco as well as the historic bridge 3 over San Francisquito Creek.
- 4 While cumulative projects may affect other historic resources away from the Caltrain ROW, the
- 5 Proposed Project would not affect such resources and thus such resources are not discussed further 6 in this analysis.
- 7 There could be significant cumulative impacts to the historic resources noted above.
- 8 As discussed in Section 3.4, *Cultural Resources*, the implementation of Mitigation Measures CUL-1a
- 9 through CUL-1f would reduce the Proposed Project's effects on historic tunnels, stations, and
- 10 underpasses along the Caltrain ROW with the possible exception of San Francisco Tunnel 4. While
- 11 other cumulative projects may have significant impacts on the same historic resources affected by
- 12 the Proposed Project and their impact may or may not be mitigable, the Proposed Project's residual
- 13 impacts on these resources after Proposed Project mitigation would be minimal, except possibly at
- 14 Tunnel 4. Therefore, the Proposed Project's potential contribution to cumulative impacts on
- 15 historical resources due to construction would be less than considerable.

16 **Archaeological Resources**

- 17 Based on the cultural resource evaluation for the Proposed Project, construction of the HSR San Jose 18 to Merced segment and Blended Service improvements along the Caltrain ROW could impact 19 archeological resources in the City of San Francisco, City of San Jose, and identified sensitive 20 archeological zones in or adjacent to the study area and within the Caltrain ROW. Blended Service 21 improvements construction could also affect other archeological resources at the maintenance area 22 or in passing track locations outside the Caltrain ROW.
- 23 During construction, earth moving activities for other cumulative projects in or adjacent to the 24 Caltrain ROW could also impact archaeological resources that may be affected by the Proposed
- 25
- Project. An overlap in the construction area for some of these projects increases the likelihood of 26 finding unknown or impacting known archeological resources. Construction activities for
- 27 cumulative projects that are not adjacent to the Caltrain ROW could impact archeological resources
- 28 but the site disturbance areas for these projects would not overlap with Proposed Project.
- 29 Thus, there is a potential for cumulative impacts on archaeological resources due to potential 30 multiple disturbances of resources that may be encountered in or along the Caltrain ROW.
- 31 As discussed in Section 3.4, *Cultural Resources*, the implementation of Mitigation Measures CUL-2a, 32 CUL-2b, CUL-2c, CUL-2d, CUL-2e, and CUL-2f would reduce the Proposed Project's effects on 33 archaeological resources along the Caltrain ROW to a less-than-significant level. While other
- 34 cumulative projects may have significant impacts on the same archaeological resources affected by
- 35 the Proposed Project, the Proposed Project's residual impacts on these resources after Proposed
- 36 Project mitigation would be minimal. Therefore, the Proposed Project's potential contribution to
- 37 cumulative impacts on archaeological resources due to construction would be less than
- 38 considerable.

39 Human Remains

- 40 Construction activities for the cumulative projects could impact human remains and result in
- 41 cumulative impacts where project disturbance areas overlap. However, with implementation of

1 Mitigation Measures CUL-3, the Proposed Project's contribution to any potential cumulative impacts 2 on human remains would be less than considerable.

3 Operation

- 4 For the most part, cumulative projects would not require further ground disturbance or disturbance
- 5 to historic structures after construction. As discussed in Section 3.4, Cultural Resources, the
- 6 Proposed Project would have no impact on cultural resources during operations. Therefore, there
- 7 would be no cumulative cultural resource impacts resulting from Proposed Project operation, and
- 8 the Proposed Project would make no contribution to any impact.

9 4.1.4.6 EMF/EMI

10 Impact CUMUL-5-EMF: Cumulative increase in electromagnetic fields or electromagnetic 11 interference

- 12 The geographic context for the analysis of potential cumulative impacts of electromagnetic fields
- 13 (EMF) and electromagnetic interference (EMI) includes the Caltrain ROW and the area adjacent to 14 the Caltrain ROW.
- 15 The only cumulative projects that could change EMFs in this area are electrified rail projects 16
 - including: Blended Service (#1), San Jose Merced High Speed Train (#2), Caltrain Full
- Electrification (#3), BART Silicon Valley (#8), BART Millbrae Tail Tracks (#70), Central Subway 17 18 (#13), the re-routing of the 22-Fillmore trolley (#14) and several light-rail projects (#16). Land
- 19 development projects would not involve substantial generation of EMFs at concern levels but may 20 introduce new receptors along the Caltrain ROW.
- 21 The concern with EMFs is potential health risks to receptors along the Caltrain ROW. The concern 22 with EMI is potential interference with sensitive electrical equipment along the Caltrain ROW due to 23 increased EMF levels.

24 Construction

- 25 Construction activities from cumulative projects along the Caltrain ROW would temporarily increase
- 26 the amount of EMF. As discussed in Section 3.5, *Electromagnetic Fields and Electromagnetic*
- 27 Interference, all construction equipment generates a small amount of EMF but not at levels
- 28 considered to be a potential health risk concern. As a result, cumulative EMF/EMI impacts resulting 29 from construction would be less than significant, and the contribution of the Proposed Project would 30 be less than considerable.

31 Operation

- 32 The location of potential cumulative increases in EMF levels along the Caltrain ROW due to 33 cumulative projects are as follows:
- 34 Proposed Project: from south of Tamien Station to San Francisco (AC EMF field, 60 Hz). •
- 35 • Blended Service and HSR San Jose to Merced: San Jose (from 2 miles south of Tamien Station) to 36 San Francisco (AC EMF field, 60 Hz).
- 37 • Caltrain Full Electrification: San Jose to San Francisco (due to larger number of electrified trains) 38 (AC EMF field, 60 Hz).

1

- BART Silicon Valley: San Jose to Santa Clara (DC EMF field).
- BART Millbrae Tail Tracks: 200–300 feet south of the current BART yard in Millbrae (DC EMF field).
- Central Subway Project: near the San Francisco 4th and King station (surface effects attenuated by being underground due to additional light trains on surface streets) (DC EMF field).
- Re-routing of the 22- Fillmore trolley: along 16th Street (DC EMF field).
- Extension of the MUNI T-Line: near the Caltrain Bayshore Station (DC EMF field).
- Tasman Express Long T double-tracking: near the Mountain View Caltrain Station (due to additional light rail trains) (DC EMF field).
- Mineta San Jose International Airport APM Connector: near the Santa Clara Caltrain Station
 (unknown design; unknown EMF field generation).

12 As noted above, only some of the cumulative projects use alternating current (AC) systems and 13 generate AC EMF fields like the Proposed Project. Cumulative projects that use direct current (DC) 14 systems generate static DC EMF fields, which have higher health thresholds than those for variable 15 AC EMFs. As described in the final EIS for the BART Silicon Valley Extension, because BART uses DC 16 traction power, contributions from BART to the magnetic field levels of the ambient power 17 frequency (60 Hz AC) were described as negligible (VTA 2010). Thus, EMFs from DC systems should 18 not be simply added to those from AC systems and compared with a single standard. Instead, one 19 should compare DC EMF levels with DC thresholds and AC EMF levels with AC thresholds. Because 20 the Proposed Project OCS would have an AC system, the focus of this cumulative analysis in regards 21 to health concerns is on potential cumulative EMF impacts from AC systems.

- 22 For HSR San Jose to Merced operations and Blended Service from San Jose to San Francisco, 23 potential EMF levels associated with HSR can be estimated based on assessment of other sections of 24 the HSR project. In the Final EIR/EIS for the Merced to Fresno segment of the HSR project, the EMF 25 levels were estimated. When the California HSR project is complete, the predicted HSR-generated 26 EMF/EMI levels to which the general public is expected to be exposed would be lower than the 27 applicable HSR project Maximum Permissible Exposure (MPE) standards¹³ for humans in 28 uncontrolled (open) environments used for HSR evaluations. Specifically, it was estimated that 29 fenceline EMF levels would be 177 milligauss (mG) (CHSRA 2012d). As described in Section 3.5, 30 *Electromagnetic Fields and Electromagnetic Interference*, the Proposed Project's EMF levels along the 31 Caltrain ROW were estimated at up to 41 mG. With full electrification, EMF levels for Caltrain 32 electrified service could increase by perhaps 25 percent. The EMF levels along the fenceline for 33 Blended Service should be well below the threshold used in this EIR of 833 mG. Thus, the Proposed 34 Project would make a less than considerable contribution to potential health risks associated with 35 EMFs.
- Concerning EMI, the projects specified above could also result in interference with electrical
 equipment along the Caltrain ROW. Both DC and AC systems could contribute to potential
 interference concerns.
- For HSR service, analysis in the Fresno to Bakersfield Revised Draft EIR/EIS (CHSRA 2012e) was
 used to examine potential HSR EMI impacts. In that document, potentially significant impacts were

¹³ The CHSRA Merced-Fresno EIR/EIS (CHSRA 2012d) MPE for the EMF health risks for the general public are the same as the EMF thresholds used in this EIR: 833 mG for magnetic fields and 4.2 kV/m for electrical fields.

- 1 identified where the HSR route crossed adjacent to at least one facility with sensitive equipment
- such as medical imaging systems and mitigation was proposed that would lower potential EMI
 impacts to a less than significant level.

4 Prior to mitigation, there is the potential for cumulative EMI effects due to HSR Service, the 5 Proposed Project and other projects. As discussed in Section 3.5, Electromagnetic Fields and 6 *Electromagnetic Interference*, the Proposed Project was identified as having potentially significant 7 EMI impacts on sensitive equipment and adjacent freight and passenger rail system signals and 8 equipment, and Mitigation Measure EMF-2 would require system design to minimize EMI effects and 9 to coordinate with adjacent facilities with potential sensitive equipment and with freight and 10 passenger rail operators.¹⁴ With implementation of Mitigation Measure EMF-2, the Proposed 11 Project's contribution to any potential cumulative EMI effects would be reduced to a less-than-

12 considerable level.

134.1.4.7Geology, Soils and Seismicity

14 Impact CUMUL-6-GEO: Cumulative exposure of people or structures to geologic or seismic 15 hazards or destruction of unique paleontological/geologic resources

- 16 Geology and soil-related impacts are typically site-specific and depend on the local geologic and soil
- 17 condition. The geographic context for the analysis of cumulative construction geologic, soil, and
- 18 paleontological resource impacts includes areas within and adjacent to the Caltrain ROW. Past,
- 19 present, and probable future cumulative projects within this geographic context include the projects
- 20 listed in Table 4-3 that are within the Caltrain ROW or adjacent.

21 Construction

- Construction impacts are limited to the potential for increased erosion and potential damage to
 paleontological resources. Impacts related to other geological, seismic, and soil hazards for new
- 24 structures are discussed under operations.

25 Erosion

- 26 Construction of cumulative projects could result in cumulative erosion impacts unless controlled. All
- 27 major projects, including the Proposed Project, must comply with the Construction General Permit
- 28 NPDES, which requires substantive controls on project erosion such that significant cumulative
- 29 impacts due to erosion are not expected. Therefore, the Proposed Project's contribution to potential
- 30 cumulative erosion impacts would be less than considerable.

31 Paleontological Resources/Unique Geologic Features

- 32 Cumulative construction projects may encounter paleontological resources. However, as discussed
- 33 in Section 3.6, *Geology, Soils and Seismicity*, the Caltrain ROW and adjacent areas are highly
- 34 disturbed urban areas that are unlikely to contain intact unique geologic or paleontological features.
- 35 In addition, the below-ground disturbance associated with the Proposed Project is limited overall in
- 36 extent. Consequently, the potential for the Proposed Project to contribute to potential cumulative
- 37 impacts on paleontological resource or unique geologic features is less than considerable.

¹⁴ Similar mitigation may be required for Blended Service.
1 **Operation**

2 New transportation, residential, commercial and other facilities and services could increase 3 exposure of people or structures to geologic, seismic and soil hazards could result in a significant 4 cumulative impact. The project area is likely to experience a strong seismic activity and geologic 5 instability (e.g., soil liquefaction or collapse) that could damage structures or expose people to 6 greater risks of loss of life and injury. In addition, there could be cumulative exposure due to 7 construction in areas of expansive soils. Therefore, there could be a significant cumulative impact 8 from the increase exposure of structures and people to risks and damage associated with geologic, 9 seismic and soil hazards. All cumulative projects would be subject to comply with applicable state 10 and local codes, including design standards (e.g., California Building Code), which address these 11 impacts.

As discussed in Section 3.6, *Geology, Soils and Seismicity*, the Proposed Project could also result in
 various impacts related to geologic, seismic or soil hazards. With implementation of Mitigation
 Measures GEO-1, 4a, and 4b would reduce the Proposed Project's exposure to risks of geologic,

- 15 seismic and soil hazards. Therefore, the Proposed Project's contribution to the increase of exposure
- 16 to these hazards would be less considerable.

17 **4.1.4.8** Greenhouse Gas Emissions and Climate Change

Impact CUMUL-7-GHG: Cumulative greenhouse gas emissions or exposure of people or structures to reasonably foreseeable impacts of climate change

- The geographic context for the analysis of cumulative construction and operation related impacts to
 greenhouse gas emissions is the planet. All of the projects in Table 4-3 are included in the analysis as
 well as cumulative GHG emissions from California, the United States, and the rest of the world.
- For the analysis of potential exposure of people or structures to reasonable foreseeable impacts of
 climate change, the geographic context is the San Francisco Peninsula and is only analyzed for
 operational conditions. Past, present, and probable future cumulative projects within this
 geographic context consist of all projects listed in Table 4-3.

27 Greenhouse Gas Emissions

During construction, all cumulative projects would emit GHGs due to construction equipment and
 vehicles. Construction activities are temporary, but the lifespan of the most emitted greenhouse gas,
 carbon dioxide, can be up to 100 years and many of the other GHGs can last for decades.

31 HSR Operations

32 Operationally, HSR would not add any GHG direct local emissions due to train operation, since HSR 33 trains would use electricity and not use diesel fuel. Indirect GHG emissions would occur at power 34 plants providing the electricity for HSR. There will also be some GHG emissions associated with 35 maintenance yard operations and maintenance of HSR facilities as well as worker commutes, but 36 such emissions are not expected to be substantial. On a broader scale, HSR service would offset 37 vehicular and air travel GHG emissions for individuals choosing to take the high speed train for 38 regional or state-wide travel instead of driving or flying. The effects of high-speed rail service on 39 GHG emissions were estimated by considering the GHG analysis in the Final EIS/EIR for the Merced 40 -Fresno HSR segment (CHSRA 2012d), which concluded that operational GHG emission reduction in

- 1 the segment region (due to car and plane trips removed in the Merced-to-Fresno area) would offset
- 2 segment construction GHG emissions within less than six months. Overall, the statewide HST
- 3 system, with Phase 1 blended system operations would result in reductions of 0.79 to 1.40 million
- 4 metric tons of CO2e in 2029 and 1.15 to 1.85 million MT CO2e in 2035 (CHSRA 2013b).

5 All Other Projects

- 6 During operation of the other cumulative rail projects, there would be GHG emissions from diesel-
- 7 based rail services such as ACE, DRC, Capitol Corridor, and Amtrak, as well as from freight rail. Light-
- 8 rail systems such as VTA's system are electrically powered and thus have no direct GHG emissions,
- 9 but have indirect GHG emissions due to electricity provision. Both light and heavy-rail services
- provide alternatives to vehicular travel and freight rail provides an alternative to trucking and thus
 usually result in a net reduction in GHG emissions relative to vehicular travel or trucking. A similar
 conclusion applies to bus transit projects, like BRT or shuttles.
- During operation of the cumulative highway projects, there may be an increase in vehicular GHG
 emissions if such projects result in induced traffic. If such projects result in a net decrease in vehicle
 miles traveled (through high-occupancy vehicle lanes for example), then they would reduce GHG
 pollutant emissions.
- 17 During operation of the cumulative land use projects, there could be an increase in GHG pollutant
- 18 emissions from increased vehicular travel as well as building energy consumption, waste
- 19 generation, water and waste treatment and other sources. Over time, local, state and federal plans
- 20 are seeking to dramatically reduce GHG emissions overall. Many of the communities along the San
- Francisco Peninsula have adopted local Climate Action Plans to reduce GHG emissions under their
- control and AB 32 mandated GHG emission reductions at a state level. According to the state's latest
 inventory data, the state is on track to reduce GHG emissions by 2020 to 1990 levels.

24 **Proposed Project Cumulative Contribution**

25 As discussed in Section 3.7, Greenhouse Gas Emissions and Climate Change, the Proposed Project 26 would switch Caltrain from diesel to electrically powered trains, and, thus, decrease the amount of 27 GHG emissions during Caltrain operation. In addition, by increasing service, the Proposed Project 28 would provide increased alternatives to vehicle travel and thus reduce vehicle GHG emissions as 29 well. While the Proposed Project would result in GHG emissions during construction, it is expected 30 that the operational reduction of GHG emissions would offset the construction GHG emissions within 31 less than one year and the Proposed Project would result in a net reduction of GHG emissions. As a 32 result, the Proposed Project's contribution to cumulative GHG emissions would be beneficial.

Exposure of People or Structures to Reasonably Foreseeable Impacts of Climate Change (other than Sea Level Rise)

As discussed in Section 3.7, *Greenhouse Gas Emissions and Climate Change*, even with the efforts of the municipalities along the San Francisco Peninsula, in the greater San Francisco Bay Area, and in California as a whole, a certain amount of climate change is unavoidable due to existing and unavoidable future GHG emissions. With respect to central western California, including the project site, climate change effects could be substantial including, but not limited to hotter and drier climates, more frequent and intense wildfires, changes in water supplies, and a number of other effects.

- 1 All of the cumulative projects would be subject to some of the potential impacts related to climate
- 2 change in the future whether it is temperature increases, changes in storm characteristics, or
- wildfire potential though individual effects will depend on the nature of project, use by people,
 location and vulnerability to climate change effects.
- As described in Section 3.7, *Greenhouse Gas Emissions and Climate Change*, with the exception of sea
 level rise, the Proposed Project is not expected to result in increased risk to people or structures
 from foreseeable climate change effects.
- 8 Risks due to flooding associated with sea level rise are addressed separately in discussion of
 9 Hydrology and Water Quality below.

10 **4.1.4.9** Hazards and Hazardous Materials

11 Impact CUMUL-8-HAZ: Cumulative effects related to hazards and hazardous materials

12 Potential hazard impacts are generally site specific and thus the geographic context for the analysis

13 of cumulative hazards impacts includes the Caltrain ROW and the adjacent area. Hazards relative to

14 hazardous materials and emergency response/evacuation are analyzed for both construction and

15 operations. Hazards relative to airports and wildand wildland fire are only analyzed for operations.

- 16 Past, present, and probable future cumulative projects within this geographic context consist of all
- 17 cumulative projects listed in Table 4-3 that are adjacent to the Caltrain ROW.

18 Construction

19 Hazardous Materials

During construction of cumulative projects, people could be exposed to a risk to human health and
 spillage of hazardous materials such as gasoline, oil paint and solvents could. Water quality
 contamination could occur from accidental spillage of hazardous materials and mixture of
 contaminated water with non-contaminated water. Excavation activities could expose construction
 crew members to hazardous materials that could pose a risk to health and safety.

- Some of the cumulative projects are proposed in areas with known existing contamination. Several
 examples are described below (not a comprehensive list of sites with known contamination):
- The previously considered location for a HSR maintenance yard at the Brisbane/Bayshore
 location is a former landfill with known contamination.
- The Brisbane Baylands Specific Plan which is proposed in part at the same location previously
 considered for a HSR maintenance yard also contains known contamination from a former
 landfill, railroad yard, and industrial activity.
- The 395 Page Mill Road Project in the City of Palo Alto is proposed on a contaminated site
 undergoing remediation for contaminated soil and groundwater.
- These are only a few examples; other project may also encounter contamination issues. Thus, the
 construction of cumulative projects would have cumulative significant impact related to hazardous
 conditions and exposure to hazardous materials.
- The construction of HSR San Jose to Merced and Blended Service improvements would encounter
 similar hazardous materials conditions as that described for the Proposed Project for the Caltrain

- 1 ROW, however hazardous material conditions could be different for the maintenance yard,
- 2 depending on location. The previously considered maintenance yard site in Brisbane has
- 3 contamination issues due to its former industrial use. The greatest amounts of excavation for the
- 4 Blended Service improvements (when hazardous material is more likely to be encountered) would
- 5 be for station improvements, passing tracks and the maintenance yard.
- 6 As discussed in Section 3.8 *Hazards and Hazardous Material*, contaminated soil and groundwater 7 may be encountered during Proposed Project construction. In addition, construction would involve
- may be encountered during Proposed Project construction. In addition, construction would involve
 use of petroleum and other hazardous materials. Compliance with local, state and federal
- 9 regulations for handling of materials and implementation of the mandatory Stormwater Pollution
- 10 prevention Plan will address impacts associated with construction handling of petroleum and other
- 11 materials. For encountered contamination, the Proposed Project would require implementation of
- 12 Mitigation Measures HAZ-2a and HAZ-2b, which require preconstruction investigation of potentially
- contaminated areas and appropriate containment, handling and disposal of any encountered
 contaminated soil and groundwater. While multiple cumulative projects will handle petroleum and
- 15 hazardous materials and are likely to encounter existing soil and groundwater contamination
- 16 present in and adjacent to the Caltrain ROW, the existing regulatory requirements place strict
- 17 controls on how such materials are handled and how contamination is to be addressed. Thus, the
- 18 Proposed Project's contribution to any potential cumulative impact related to hazardous materials
- 19 during construction would be reduced to a less-than-considerable level with the implementation
- 20 Mitigation Measures HAZ-2a and HAZ-2b.

21 Emergency Response/Evacuation

During cumulative project construction, there may be temporary obstruction of access and egress
 from construction sites and on adjacent roads due to construction. Such obstruction would affect the
 ability of emergency responders to timely reach their destinations and impede the ability to
 evacuate constrained areas in the event of an emergency. Where one or more cumulative projects
 would be in construction at the same time in the same area, there could be cumulative impacts on
 emergency response or evacuation capacity.

- 28 As discussed in Section 3.8, Hazards and Hazardous Materials, the Proposed Project could have such 29 effects if an emergency occurs at the time when the Proposed Project construction limits access to 30 the Caltrain ROW or at at-grade crossings. As described in Section 3.14, Transportation and Traffic, 31 Mitigation Measure TRA-1a will require the preparation of a traffic control plan to help ensure 32 continued emergency access to Caltrain ROW, at-grade crossings, and all nearby properties. Caltrain 33 would coordinate with local public works departments, local emergency providers, and Caltrans in 34 the development of the traffic control plan to specifically address emergency response concerns. 35 Potential issues associated with multiple projects in construction at the same time may be
- 36 addressed through development of the traffic control plan. Thus, with mitigation, the Proposed
- Project's contribution to a potential cumulative impact related to emergency response or evacuation
 would be less than considerable.

39 **Operation**

40 Hazardous Materials

- 41 Release of and exposure to hazardous materials during operation of cumulative projects could result
- 42 in a cumulative significant impact. Because both HSR service and the Proposed Project would
- 43 involve electrically powered trains, spills of diesel petroleum products would not occur during

- 1 operation. However, operation of HSR service and the Proposed Project would involve handling of
- hazardous materials including batteries in EMUs, fluids in transformers and other electrical
 equipment, and maintenance materials and cleaning fluids.
- 4 Operation of the other cumulative projects would also involve the use and handlings of petroleum 5 and other hazardous materials including during maintenance. The use and handling of such 6 materials is highly regulated by local, state, and federal requirements that are applicable universally. 7 Therefore, routine operation and maintenance of the cumulative projects is not likely to have a 8 significant cumulative impact from the release of or exposure to hazardous materials. There is 9 always the possibility of an unforeseen accident involving petroleum or other hazardous materials, 10 but local, state, and federal regulations also specify operating procedures to minimize the potential 11 for such accidents and remedial response necessary in the event of such accidents or spills to
- 12 contain and cleanup hazardous material releases.
- As discussed in Section 3.8, *Hazards and Hazardous Materials*, the Proposed Project would comply
 with all applicable regulations concerning use, handling, storage, and disposal of petroleum and
 hazardous materials. Further, with the substantial reduction in diesel fuel use, the potential for
 diesel spills with the Proposed Project would be far lower than the existing potential for spills
 during current operations and maintenance.
- Although the Proposed Project would increase the amount of trains on the Caltrain corridor,
 conflicts with freight trains would be managed through temporal separation (pursuant to the
 current FRA waiver requirements), through train scheduling and dispatch, and with the use of
 Positive Train Control enabled by the CBOSS PTC project to minimize the potential for conflicts (if
- 22 the FRA waiver is modified to allow blending of EMUs and freight traffic).
- 23 <u>Although the Proposed Project would increase the amount of trains on the Caltrain corridor</u>,
- 24 conflicts with freight trains would be managed through train scheduling and dispatch, and with the
 25 use of Positive Train Control enabled by the CBOSS PTC project to minimize the potential for
- 26 <u>conflicts.</u>
- Thus, Proposed Project operations would result in a less-than-considerable contribution to any
 potential cumulative impacts related to hazardous materials.

29 Locations Relative to an Airport Land Use Plan

30 There are a number of airports along the Caltrain corridor, specifically, San Francisco International, 31 Mineta San Jose International, the federal airfield at Moffett Field, and municipal airports at San 32 Carlos and Palo Alto. Cumulative projects could result in potential hazards if they propose elevated 33 structures within the safety prism for landing and departing aircraft or if they place substantial 34 numbers of people within safety zones around the airports that might be subject to injury or death 35 in the event of a near-airport plane emergency landing or crash. Blended Service improvements may include elevated structures north of the San Jose Diridon Station (if an aerial station is selected) that 36 37 will need to be designed to avoid encroachment in safety zones of the San Jose International Airport. 38 Blended Service improvements at the Diridon Station, Millbrae Station and possibly at the Redwood 39 City Station would be sufficiently far from nearby airports that they are unlikely to result in any 40 safety zone encroachments. While the location of a potential HSR maintenance yard is unknown, it is 41 not likely to have substantially elevated structures that would be likely to conflict with safety zone

42 requirements.

- 1 As discussed in Section 3.8, *Hazards and Hazardous Materials*, the Proposed Project's TPFs and the
- 2 OCS would not conflict with any airport land use plan or airport safety zones. Thus, the Proposed
- 3 Project would result in a less-than-considerable contribution to any potential cumulative impacts on
- 4 airport land use plans or airport safety zones.

5 Emergency Response/Evacuation

6 Cumulative projects would affect existing emergency response times or evacuation capacity if they

- 7 result in constrictions on the ability for emergency responders to reach their destinations or the
- 8 egress ability from constrained areas in the event of an emergency. This could occur due to physical
- 9 constraints and/or generation of traffic congestion which could impede emergency vehicles.
- 10 As discussed below in the analysis of cumulative transportation and traffic impacts, the increase of 11 cumulative rail traffic along the Caltrain ROW from HSR, ACE, Capitol Corridor, Amtrakand freight 12 could result in increased gate-down times at the at-grade crossings along the Caltrain ROW. Because 13 of cumulative growth in traffic over time due to the land development projects included in Table 4-3 14 and general growth in the region, traffic conditions are expected to substantially decline over the 15 next few decades at the at-grade crossings of the Caltrain ROW and generally throughout the region 16 (in spite of substantial investments in transit). With this cumulative growth in traffic, emergency 17 response times during peak hours may be adversely affected, as could the ability to evacuate areas 18 via vehicles.
- 19 An additional cumulative concern with cumulative travel demand growth over time and increased 20 transit service for HSR, BART, VTA, Muni, SamTrans, and Caltrain is that transit stations, especially 21 underground stations, will exceed their currently designed capacity to allow for safe egress in the 22 event of an emergency. BART, for example, in its scoping comment letter on the Proposed Project, 23 specifically noted that several segments of the BART system, especially downtown San Francisco 24 stations, are currently near capacity. Thus cumulative travel demand could result in significant 25 impacts on evacuation plans for transit stations with constrained egress conditions, especially 26 underground transit stations.
- As discussed in Section 3.14, *Transportation and Traffic*, the Proposed Project would result in
 significant increases in traffic delays at a number of at-grade crossings along the Peninsula corridor
 due to increased gate-down time during peak hours. The Proposed Project would also impact traffic
 near some of the Caltrain stations. Project mitigation measure (described in Section 3.14, *Transportation and Traffic*) would reduce traffic impacts at many locations and would include
 requirements for coordination with local emergency providers to minimize increase in response
 times as feasible but would not reduce all traffic delays to a less-than-significant level.
- 34 Emergency response times are function of the conditions between the responder base location and 35 the incident location overall, not only a function of conditions at any one point along the response 36 path. As discussed in Section 3.14, Transportation and Traffic, the Proposed Project overall would 37 substantially reduce overall vehicle miles traveled (VMT) in the Peninsula corridor by 38 approximately 235,000 miles/day in 2020 and 619,000 miles/day in 2040 (compared with No 39 Project conditions), which would substantially improve congestion on a broad general basis. Most of 40 the VMT reductions would be during peak hours, which is especially important in reducing 41 congestion. The broad-based congestion improvement is expected to more than offset the localized 42 effects on at-grade crossings and near Caltrain stations and result in a net improvement (compared
- 43 with No Project conditions) in the emergency response times and in the ability to evacuate

- constrained areas by vehicle. Thus, the impact on emergency response times would be less than
 significant.
- As discussed in Section 3.8, *Hazards and Hazardous Materials*, the Proposed Project's new OCS
 would not pose an impediment to routine emergency equipment access.

5 Regarding transit stations emergency evacuation, as discussed in Section 3.14, Transportation and 6 Traffic, the Proposed Project is not expected to substantially increase the ridership of other transit 7 systems on the Peninsula. In specific, relative to No Project conditions, the Proposed Project is 8 expected to result in a slight decrease in BART ridership, a slight increase in Muni Metro (rail) 9 ridership in 2020 but a slight decline in 2040, and a slight increase in VTA light rail ridership. As a 10 result, station evacuation would be primarily a concern for controlled access BART stations and 11 underground Muni Metro stations. There is less concern for evacuation from at-grade Muni Metro 12 and VTA light-rail stations and all bus stations and stops given the open architecture of such 13 facilities. While some BART and underground Muni Metro stations may reach capacity because of 14 cumulative transit ridership, the Proposed Project would not contribute considerably to potential 15 cumulative impacts related to evacuation capacity at these locations because the Proposed Project's

16 long-term effect on these systems (e.g., in 2040) would be a slight reduction in ridership.

17 Wildland Fires

The Caltrain ROW and adjacent areas are highly developed urban and suburban areas with very few
 areas of adjacent wildlands. The only areas of wildlands along the Caltrain ROW are San Bruno
 Mountain and Communications Hill in San Jose. Cumulative projects adjacent to wildland areas
 might result in increased wildland fire risk by either placing activities with greater potential to

- ignite wildfires or by placing increased numbers of people and structures adjacent to wildland areas
- that might be subject to wildland fires. As discussed in Section 3.8, *Hazards and Hazardous Materials*,
 the Proposed Project is not located in any high fire risk areas and the Proposed Project would
- 25 maintain an electrical safety zone around all its electrical equipment to minimize the risk of fires due
- 26 to contact with live electrical wires. While cumulative projects might increase the risk or
- consequence of wildland fires, the Proposed Project's contribution to any potential cumulative
 impact regarding wildlife fires would be less than considerable.

29**4.1.4.10**Hydrology and Water Quality

30 Impact CUMUL-9-HYD: Cumulative impacts related to hydrology and water quality

The geographic context for the analysis of cumulative construction and operation-related hydrology
 and water quality impacts consists of the Caltrain ROW and adjacent areas, and downstream areas.
 Past, present, and probable future cumulative projects within this geographic context consist of all

- 34 projects listed in Table 4-3. The focus of the construction analysis is on water quality. The
- operational analysis of impacts includes water quality, groundwater recharge, drainage patterns and
 flooding.

37 Construction

38 Earth moving activities from cumulative projects such as grading and excavating could degrade

- 39 water quality from an increase in sediment-load, alteration to drainage patterns and increased
- 40 surface runoff. During construction, earth moving activities could degrade the water quality of
- 41 streams that cross the Caltrain ROW as well as San Francisco Bay downstream. In addition, during

- 1 excavation activities, shallow groundwater could be degraded from the introduction of
- 2 sedimentation and spillage of construction hydraulic fluid and there is also the potential of release
- 3 of contaminated groundwater during dewatering activities. Construction activities for many of
- 4 cumulative projects listed in Table 4-3 would each involve earth moving activities that collectively
- would impact on water quality. All major projects (with disturbance of more than 1 acre) are
 required to comply with the Construction General NPDES Permit which mandated preparation of a
- 7 Stormwater Pollution Prevention Plan (SWPPP) to address all of the above water quality concerns.
- 8 While smaller projects are not required to comply with the Construction General NPDES Permit, it is
- 9 routine practice for local jurisdictions to require erosion and sedimentation at all projects with
- 10 grading or excavation and thus most projects implement some form of stormwater pollution
- 11 prevention controls during construction.
- As described in Section 3.9, *Hydrology and Water Quality*, the Proposed Project would comply with
 the Construction General NPDES permit and prepare and implement a SWPPP. In addition, because
- 14 the Proposed Project has the potential to encounter contaminated groundwater during OCS pole
- 15 foundation excavation and other project excavation, Mitigation Measure HYD-1 would be
- 16 implemented to control dewatering discharges appropriately. With compliance with the
- 17 Construction General NPDES permit and mitigation measure, the Proposed Project's contribution to
- 18 any cumulative impacts on water quality during construction would be reduced to a less-than-
- 19 considerable level.

20 Operation

21 Water Quality and Runoff

22 Operation of the cumulative projects could impact water quality from an increase in impervious 23 surfaces, increased handling of petroleum or other hazardous materials, and other activities (such as 24 maintenance) that might result in contaminated stormwater runoff. HSR San Jose to Merced and 25 Blended Service improvements would increase the total imperviousness in the area from proposed 26 station improvements, passing track additions, and a new maintenance yard. Other cumulative 27 projects would also increase the impervious surfaces in the area where developed on areas that 28 currently allow for infiltration, thus increasing stormwater runoff. An increase in stormwater runoff 29 can cause erosion and increases turbidity in downstream depending on local stream condition and 30 can also result in increased pollutant loading due to contact with petroleum and other materials. In 31 addition to these changes, the cumulative increase in diesel locomotive rail traffic (all cumulative 32 rail services other than HSR, Proposed Project, and light rail) would increase the potential for 33 leakage of diesel that could degrade surface water quality.

34 As described in Section 3.9, Hydrology and Water Quality, the Proposed Project would have a 35 beneficial water quality impact by substantially reducing the use of diesel fuel for the Caltrain 36 system and the potential for spills as well as diesel exhaust deposition into water systems. While the 37 Proposed Project would add limited amount of new impervious surface, these additions are in areas 38 where additional impervious surface is not likely to result in additional sediment loading in streams. 39 Routine housekeeping practices and maintenance would control the potential for polluted runoff 40 from new facilities. As a result, the Proposed Project's contribution to any potential cumulative 41 water quality effects.

1 Groundwater Recharge

- 2 Cumulative increase in impervious surface could hinder groundwater recharge across the Peninsula.
- 3 However, as described in Section 3.9, *Hydrology and Water Quality*, groundwater along the Caltrain
- 4 ROW is not a substantial source of water supply. Nevertheless, cumulative increases impervious
- 5 surfaces might affect local groundwater supplies. As described in Section 3.9, *Hydrology and Water*
- 6 *Quality*, the Proposed Project would have limited effects on groundwater recharge. Considering the
- 7 limited effect, and given the limited importance of local groundwater supplies, the Proposed
- 8 Project's contribution to any potential cumulative impacts on groundwater recharge would be less
- 9 than considerable.

10 Change in Drainage Patterns

11 Cumulative projects could result in changes to drainage patterns that might affect erosion or 12 downstream sedimentation, polluted runoff, or affect stormwater drainage systems. However, in 13 most cases, local planning requirements include analysis of project impacts on drainage systems and 14 require fair-share contributions toward facility improvements over time. In addition, countywide 15 stormwater pollution prevention programs focus on addressing substantial sources of increased 16 runoff and require such projects to provide for both retention of water on-site and treatment of 17 stormwater runoff.

As described in Section 3.9, *Hydrology and Water Quality*, the Proposed Project would not alter
drainage patterns of existing drainage channels or streams. The additional impervious surface areas
at TPFs would not significantly increase the rate or volume of surface runoff, particularly given the
location of the two TPSs (which are the largest Proposed Project TPFs) in areas that are not of
concern for runoff affecting water quality due to erosion of downstream channels. Thus, the
Proposed Project's contribution to any potential cumulative drainage pattern impacts would be less
considerable.

25 Flooding, including Flooding Resultant from Predicted Sea Level Rise

- As shown in Figure 3.9-4 in Section 3.9, *Hydrology and Water Quality*, areas of the Peninsula close to
 San Francisco Bay are subject to coastal flooding at present and some areas along certain creeks and
 rivers, particularly in San Jose, are subject to flooding under 100-year event conditions.
- 29 HSR San Jose to Merced and Blended Service improvements, where located in the Caltrain ROW or 30 adjacent, would be subject to similar flooding impacts as the Proposed Project both now and in the 31 future. The Diridon, Millbrae and Redwood City Stations are not in current 100-year flood zones, but 32 limited portions of the passing tracks (depending on location) might be. Flooding impacts for the 33 maintenance yard would depend on location. Other cumulative projects could also be affected by 34 flooding particularly if close to San Francisco Bay or along riverine flooding zones. All projects take 35 into account flooding impacts when going through project review and approvals and in most cases 36 take action to protect their facilities from substantial flooding. Where projects encroach on the 100-37 year floodplain, most projects implement project-level mitigation where necessary to avoid 38 substantial increases in upstream or downstream flooding.
- 39 As described in Section 3.9, *Hydrology and Water Quality*, the Proposed Project could have some
- 40 effect on flooding due to proposed locations of some of the TPFs in current floodplains. Mitigation
- 41 Measure HYD-4 would require minimization of new impervious space for any TPFs proposed in
- 42 floodplain areas, relocation of facilities, and/or use of TPF site locations outside the 100-year

floodplain. With this mitigation, the Proposed Project would not contribute considerably to potential
 cumulative flooding impacts of cumulative projects.

3 As described in Section 3.9, *Hydrology and Water Quality*, sea level rise is a particular concern in 4 areas near San Francisco Bay as sea level rise is expected to rise up to 2 feet by 2050 and up to 5.5 5 feet by 2100. Parts of the Caltrain corridor are subject to coastal flooding at present and, with 6 expected sea level rise in the future, this risk of coastal flooding will increase. As shown in Figure 7 3.9-5 in Section 3.9, *Hydrology and Water Quality*, with future sea level rise, more areas of the 8 Peninsula close to San Francisco Bay will be subject to coastal flooding than at present and flooding 9 along tidal channels will increase. Relative to areas near the Caltrain ROW, flood areas will expand 10 from San Francisco to Redwood City. South of Redwood City, coastal flooding will also increase but 11 the area of flooding is further away from the Caltrain ROW. Cumulative projects located in areas of 12 potential increased coastal flooding in the future shown in Figure 3.9-5 could be subject to 13 inundation causing risk to people and structures.

14 For future coastal flooding resultant from increased sea level rise, additional portions of the Caltrain 15 ROW could be affected by flooding. Mitigation Measure HYD-7 requires Caltrain to adopt and 16 implement a sea level rise vulnerability assessment and adaptation plan and work with other local 17 partners to identify and implement adaptation measures to protect people and structures. However, 18 as noted in Section 3.9, *Hydrology and Water Quality*, at this time, the feasibility of implementing all 19 measures necessary to avoid future inundation associated with 100-year floods influenced by sea 20 level rise is not known given that assessment of such solutions will be an ongoing, long-term, and 21 multi-agency process. Consequently, because the Proposed Project would place additional people 22 and structures in areas that could be affected by coastal flooding influenced by sea level rise and 23 definitive mitigation to protect all parts of the Caltrain ROW and facilities is infeasible, the Proposed 24 Project's contribution to potential cumulative risks of flooding would be considerable.

25 **4.1.4.11** Land Use and Recreation

26 Impact CUMUL-10-LUR: Cumulative effects related to land use and recreation

The geographic context for the analysis of land use and recreation cumulative impacts consists of the areas within and adjacent to the Caltrain ROW. Physical division of an established community, conflict with applicable land use policies or plan adopted for the purpose of avoiding or mitigation an environmental effect, increase in the demand for or degradation of recreational facilities requiring construction or expansion of recreational facilities that would have an adverse effect on the environment would result in a significant cumulative impact.

- Cumulative construction impact analysis focused on temporary impacts on existing land uses and
 recreation. Operational impact analysis addressed potential division of communities, land use
 policy/plan consistency, and direct/indirect changes in recreational facilities.
- Cumulative projects included within this geographic context are all projects listed in Table 4-3. For
 analysis of recreation demand, cumulative growth in the three counties was also considered.

38 **Construction**

- 39 Construction of HSR San Jose to Merced and Blended Service improvements could impact land use
- 40 and recreational facilities because of temporary disruptions on or adjacent to existing other land
- 41 uses. Where construction occurs at or near the Tamien, Diridon, Millbrae (and possibly at the

- 1 Redwood City) Station, this would only be a concern for station use itself and would not impede 2 adjacent land uses. Construction of passing tracks, if inside the Caltrain ROW would not disrupt 3 adjacent uses. For construction of San Jose to Merced segment construction or Blended Service 4 passing track locations outside the ROW, this could result in disruption of existing land uses as well 5 as possibly adjacent uses, depending on access and staging. Construction of the maintenance yard 6 would depend on locations; at the previously considered location in Brisbane, it presently consists 7 of previously industrial land that is not in present use. Staging and access could also disrupt existing 8 land uses temporarily, although staging and access are usually conducted on areas with open land 9 (such as vacant lots and parking lots) wherein temporary disruption of existing use can be 10 minimized.
- 11 Construction of other cumulative projects could also temporarily impact existing land uses adjacent 12 to the Caltrain ROW, although most projects will either occur on vacant land or will displace the 13 existing land uses prior to construction of the new use by limiting use and demolishing existing 14 structures. Most projects would not displace adjacent existing uses during construction, except in 15 the case of needs for substantial off-site staging or access.
- 16 The Proposed Project would be constructed within the Caltrain ROW, with the exception of the two 17 TPSs (except for TPS2, Option 3 which is in the ROW), limited areas where the OCS alignment would 18 be outside the Caltrain ROW, and areas where the ESZ would extend outside the Caltrain ROW and 19 require vegetation clearance. Construction within the Caltrain ROW would not displace other land 20 uses outside the ROW. As discussed in Section 3.10, Land Use and Recreation, the TPS location 21 options, with the exception of TPS2 Option 2 and TPS2 Option 3, are vacant parcels surrounded by 22 industrial or commercial areas. TPS2 Option 2 would displace existing industrial use and parking 23 currently on the site; however, there are numerous alternative locations for industrial use in the 24 vicinity. TPS3 Option 3 would be in a parking lot/open area at the CEMOF that is used for parking and as a lavdown area. The construction of the OCS poles would primarily occur within the Caltrain 25 26 ROW; however, in some locations the OCS poles would be erected on adjacent commercial, 27 industrial and residential land. Some tree removal or pruning may be necessary on areas outside the 28 Caltrain ROW, which could disrupt existing land uses. Temporary staging and access could also 29 result in use of vacant lots inside and outside of the Caltrain ROW, but would not result in new land 30 uses that might be inconsistent with adjacent land uses.
- 31 As discussed in Section 3.1, *Aesthetics*, construction activity in residential and park areas would be 32 anomalous, and the visual character of such areas would be partially degraded during construction. 33 The duration of OCS construction at any one location would be limited to the time necessary to 34 install pole foundations and then later to install poles and string wires. The change in visual 35 character would only occur for a limited period and the perception of the visual quality of such areas 36 would not be altered once construction is complete. To ensure that the duration of construction 37 disruption and activities are limited in areas of greater visual sensitivity, Mitigation Measure AES-2a 38 would be implemented to avoid using residential or park areas for access or staging areas, to 39 minimize the duration of construction activity in such areas (to the extent feasible) and to remove 40 all construction equipment and materials immediately following completion of construction on such 41 sites. Because the disruption of existing land uses during construction would be temporary, would 42 not ultimately result in a conversion of land use (except at TPS2 Option 2, for which there are ample 43 industrial sites for the displaced use and TPS3 Option 3 for which alternative sites can be identified 44 for parking and laydown areas within the Caltrain ROW) and because Mitigation Measure AES-2a 45 would ensure that disruption to individual residential areas or park areas is minimal, the

contribution of Proposed Project's construction to the cumulative significant impact on land use and
 recreation would be less than considerable.

3 Operation

4 **Physically Divide a Community**

Blended Service and other cumulative train service increases would occur along the existing Caltrain
Corridor between San Jose and San Francisco. As such, operation of additional train service would
not physically divide communities. The San Jose to Merced HSR segment would include new aerial
and at-grade segments in San Jose along the Caltrain ROW from south of Tamien Station to the San
Jose Diridon Station. This segment would not physically divide communities due to overhead aerial
structures and the at-grade segments in the San Jose approach section are all along existing roads or
rail rights of way and thus would not introduce new community divisions.

12 The Blended Service improvements at the Diridon, Millbrae and, potentially, Redwood City Stations 13 would be an expansion of existing facilities given the existing railroad line at each location. A new 14 maintenance yard would not likely physically divide a community given that feasible locations for 15 such a yard are likely to be in commercial or industrial locations. If the new passing tracks are 16 located in the Caltrain ROW at-grade, they would not change existing divisions of the community. 17 Where passing tracks might encroach outside the Caltrain ROW, they would expand the width of the 18 existing railroad ROW but would not prevent access from east to west at existing crossings. Where 19 grade separations are proposed as part of Blended Service improvements, connections across the 20 Caltrain ROW would be improved over existing conditions.

- 21 Most of the other cumulative projects are not likely to result in physical division of communities as 22 they consist of residential, commercial and mixed use projects that are integrated into existing 23 communities. However, large, elevated land development projects that are much higher than 24 adjacent development can be perceived by some as dividing a community by creating a vertical 25 separation, even though there may be no physical barriers between development at the ground 26 level. Most transportation projects are proposed along existing transportation corridors, but if new 27 large transportation facilities are proposed at-grade or elevated in new locations, they could 28 physically divide communities and affect access between communities.
- As described in Section 3.10, *Land Use and Recreation*, the Proposed Project would not physically divide existing communities. The OCS poles and wires would add additional infrastructure in the Caltrain ROW but would not physically impede access across the Caltrain ROW. There may be increased delays at some at-grade crossings, but the delays would be temporary and would not physically divide communities on either side of the Caltrain ROW. Thus, the contribution of the Proposed Project's operation to any potential cumulative impacts related to physically dividing a community would be less than considerable.

36 Land Use Plan and Policy Consistency

Conflicts of a project with land use policies do not, in and of themselves, constitute significant
 environmental impacts. Policy conflicts are considered environmental impacts only when they
 would result in direct environmental effects.

The Blended Service improvements at the Diridon, Millbrae and, potentially, Redwood City Stations
 would be consistent with long-term planning for transit uses at these locations. The consistency of a

- 1 new maintenance yard with existing land use plans and policies would depend on the proposed
- location. If the new passing tracks are located in the Caltrain ROW at-grade, they would be
 consistent with existing land use planning.
- 4 If HSR San Jose to Merced facilities or Blended Service passing tracks are placed outside the Caltrain 5 ROW, they may or may not be consistent with local land use planning. If passing tracks are proposed
- 6 outside the Caltrain ROW, they would likely be inconsistent with land use plans and policies of
- 7 jurisdictions where land is designated for residential, commercial, open space or recreational uses.
- 8 All of the five preliminarily identified passing track locations are adjacent to a mixture of residential,
- 9 commercial, industrial, roadway, park and open space land uses. Because industrial use often
- 10 includes railroad access tracks, the use of such areas for passing tracks may not result in significant
- 11 environmental impacts different from those possible with allowed industrial uses.
- Grade separations can often require large footprints and may require additional ROW acquisition
 and displacement of land uses as well as changing the land use character adjacent to existing land
 uses.
- 15 In addition to the inconsistency with local land use plans, passing tracks placed outside the Caltrain 16 ROW may result in additional noise and aesthetic impacts during operation on land uses that are not 17 presently adjacent to the Caltrain ROW. These impacts would represent additional inconsistencies 18 with local land uses and policies. Further, passing track improvements that result in displacement of 19 existing residential, commercial, or industrial land uses may increase pressure for residential, 20 commercial, or industrial development at alternative locations, which may result in secondary 21 physical environmental impacts. Given that the design and location of the passing tracks, the 22 maintenance yard, and any other necessary improvements (which may include grade separations) 23 are unknown at present, a definitive conclusion regarding the consistency of Blended Service 24 improvement with land use plans and policies cannot be made. In the event that substantial Blended 25 Service improvements are placed outside the ROW in non-industrial areas, the inconsistency with 26 plans and policies could be a significant and unavoidable impact.
- 27 Other cumulative projects may or may not be consistent with local land use policies and plans. Many 28 projects are proposed consistent with current local land use planning; some projects seek general 29 plan and zoning amendments to allow uses that are not consistent with current local planning. All 30 local land use projects must be approved by land use jurisdictions. Thus, if projects are inconsistent 31 with local land use plans and policies and the city or county decides to approve them, the city or 32 county is required by law to amend local land use plans and policies or make the appropriate 33 findings prior to approving inconsistent uses. Most other cumulative transportation projects are 34 proposed along existing transportation corridors. However, as with potential Blended Service 35 passing tracks outside the Caltrain ROW, large transportation facilities in new locations outside transportation corridors could result in significant conflicts with local land use plans and policies. 36
- 37 As described in Section 3.10, Land Use and Recreation, the Proposed Project would generally be 38 consistent with the local plans and policies, including land use designations and zoning, except at 39 some of the TPF sites. The majority of the Proposed Project, including OCS poles and wires, the 40 paralleling stations, and the switching station would be located within the existing Caltrain ROW 41 and would, therefore, not impact adjacent land use plans. The Proposed Project would result in 42 several inconsistencies with local plans and policies, specifically, at the location of TPS1 Option 2, 43 and at locations where the OCS alignment and ESZ would be outside rail or road ROW. However, the 44 Proposed Project would not displace existing or potential future development (except the existing

- 1 industrial/warehouse use, which can be readily absorbed at other San Jose industrial sites, at the
- 2 TPS2 Option 2 site) and, thus, would not result in significant secondary environmental impacts as a
- 3 result of the inconsistencies with local land use plans and policies.
- 4 <u>At TPS1, Option 3 there is a pending hotel application under evaluation by the City of South San</u>
- 5 Francisco for which an EIR will be released in 2015. If approved and constructed, then construction
- 6 <u>of TPS1 at this location may be in conflict with the hotel, depending on the remaining developable</u>
- land at the site. As described in Section 3.11, there are noise impacts of locating a TPS at this site
 adjacent to an existing hotel but mitigation would lower the potential noise impact to less than
- adjacent to an existing hotel but mitigation would lower the potential noise impact to less than
 significant. Similarly, if the new hotel is built and there were still remaining land at the site for a TPS.
- 10 then the noise mitigation would still apply. If the hotel is built, the costs of land acquisition would
- increase, and may be a consideration for Caltrain in deciding on which potential site to locate the
 TPS. An additional option, Option 4 was added by Caltrain at the request of the City of South San
 Francisco in order to increase the options for Caltrain as Option 3 may be more conflicted in the
- 14 <u>future than in 2013 at the start of the CEQA process.</u>
- 15 PS4, Options 1 and 2 would be located within an area envisioned for Transit Oriented Development
- 16 and a Transit Center and associated improvements as part of the Hillsdale Station Area Plan. As
- 17 concluded in Section 3.10, these two options would require minor reconfiguration of the plan, but
- 18 would not hinder the ability to develop TOD overall, provide a Transit Center, or relocate the
- 19 Caltrain Hillsdale Station and thus development would not be displaced from the site. PS4, Option 3
- 20 would not require the minor reconfiguration. Also, see discussion under cumulative aesthetics.
- 21 <u>SWS Option 1 would be located adjacent to, but not in an area proposed for mixed</u>
- residential/commercial/lightindustrial use in the Redwood Triangle portion of the North Fair Oaks
 Community Plan. Because SWS, Option 1 is outside of the plan area, it would not displace any
 potential other land uses in the plan area. The mixed-use development can be fully realized within
 the plan area. Also, see discussion under cumulative aesthetics.
- Thus, contribution of the Proposed Project operation to any potential cumulative impacts related to
 land use policy or plan conflicts (and resultant secondary physical impacts on the environment)
 would be less than considerable.

29 Damage to or Demand for Recreational Facilities

- The San Jose to Merced HSR segment (where along the Caltrain ROW in San Jose) would avoid Fuller
 Park but may affect Kurte Park as this park is directly adjacent to the Caltrain Row.
- The Blended Service improvements at the Diridon, Millbrae and, potentially, Redwood City Stations
 would have no impacts on parks or recreation facilities. The new maintenance yard's impact on
 parks or recreation facilities would depend on location, although it is highly unlikely that the facility
- would be proposed at or adjacent to an existing park or open space location (the previously studied
- 36 Brisbane/Bayshore site is a former landfill site not used for recreation).
- 37 Where Blended Service passing tracks are located within the Caltrain ROW, they would not result on
- 38 encroachment onto park lands. However, if passing tracks are proposed outside the Caltrain ROW,
- 39 they could affect park or open space directly adjacent the Caltrain ROW. Based on Table 3.10-2 in
- 40 Section 3.10, *Land Use and Recreation*, all of the five preliminarily identified passing track locations
- 41 would be adjacent to parks.

6

- The North 4 Track (San Francisco to Burlingame): Lions Park and Lomita Park (both in San Bruno).
- The Long-Middle 4 Track (San Mateo to Redwood City): Trinta Park (San Mateo); John S. Roselli
 Memorial Park (Redwood City): Main Street Park (Redwood City); and Broadway-Arguello Park
 (Redwood City).
 - The Short-Middle 4 Track (San Mateo to San Carlos): Trinta Park (San Mateo).
- The Middle 3 Track (San Mateo to Palo Alto): Trinta Park (San Mateo); John S. Roselli Memorial
 Park (Redwood City): Main Street Park (Redwood City); Broadway-Arguello Park (Redwood
 City); Holbrook-Palmer Park (Atherton); El Camino Park (Palo Alto); El Palo Alto Park (Palo
 Alto); Embarcadero Bike Path (Palo Alto); and Peers Park (Palo Alto).
- The South 4-Track (Mountain View to Santa Clara): Rengstorff Park and Resident Park
 (Mountain View).

13 Whether any of these parks would actually be affected would depend on the width of the Caltrain 14 ROW, the feasibility to stay within the ROW, and the alignment of any passing tracks outside the 15 ROW. The design of passing tracks is unknown and, thus, no definitive conclusion can be made about 16 whether any parks would actually be affected or not. However, pursuant to the mandatory 17 requirements of Section 4(f) of the Department of Transportation (DOT) Act of 1966, CHSRA will 18 first consider options for avoiding park impacts in design of any passing tracks. If park impacts 19 cannot be avoided, then Section 4(f) requires mitigation to provide additional park space so that no 20 overall loss of park space and recreational opportunities results.

21 Most other cumulative transportation projects are proposed along existing transportation corridors, 22 but if new large transportation facilities are proposed outside transportation corridors, this could 23 affect existing park or recreation areas. Large transportation projects are also subject to the 24 requirements of Section 4(f) if they are federally funded or authorized (which is most large 25 transportation projects). Other non-transportation projects are less likely to physically encroach on 26 existing park or recreational areas. Cumulative projects that propose new housing units would 27 increase population and would increase the demand for recreational facilities. While there are many 28 park areas throughout the San Francisco Peninsula, it is possible that continued growth will start to 29 result in overuse of existing park and recreational facilities and create pressure for new park and 30 recreational facilities.

31 As described in Section 3.10, Land Use and Recreation, the Proposed Project may require tree 32 removal at Broadway-Arguello Park (Redwood City), Holbrook-Palmer Park (Atherton) and at Peers 33 Park (Palo Alto). Mitigation Measure BIO-5 requires replacement of removed trees and, as discussed 34 in Section 3.10, Land Use and Recreation, it is feasible to replace trees removed at parks at the parks 35 themselves to maintain their visual screening function from the Caltrain ROW without loss of 36 substantial portions of the parks. Given that Blended Service improvements or other cumulative 37 transportation projects would be required to avoid and/or mitigate for park impacts per the Section 38 4(f) requirements, other cumulative projects are unlikely to affect parks, and the Proposed Project's 39 park impacts would be mitigated, cumulative impacts are likely to be mitigable to a less than 40 significant level. Given the project-level mitigation described above, the Proposed Project's 41 contribution to any potential cumulative impacts would be less than considerable with mitigation.

1 4.1.4.12 Noise and Vibration

2 Impact CUMUL-11-NOI: Cumulative increase in noise or vibration

3 The geographic context for the analysis of potential cumulative construction- and operation-related

4 noise and vibration impacts consists of the Caltrain ROW, the adjacent areas, and areas adjacent to

- 5 access and haul routes (i.e., nearby locations with sensitive noise receptors) used by cumulative
- 6 projects and the Proposed Project. Present and probable future cumulative projects with the
- 7 potential for cumulative impacts related to noise and vibration are listed in Table 4-3.

8 Construction

- 9 During construction, an increase in noise and vibration levels, could impact the sensitive receptors
- 10 in the project vicinity. Cumulative noise and vibration impacts would primarily result from
- 11 simultaneous construction of different projects in the same location at the same time; however
- 12 where construction occurs in quick succession in the same area, there could also be a cumulative
- 13 impact due to the extended duration of construction disruption.
- Construction of the Proposed Project would occur years before prior to the construction of the HSR
 San Jose to Merced and Blended Service improvements and thus there would no simultaneous
 construction noise or vibration effects.
- Construction of the Transbay Terminal Transit Center is currently under way, but the TTC is located
 more than one mile from the San Francisco 4th and King Station, so there would be no cumulative
 noise effects resulting from simultaneous construction of the TTC and the Proposed Project.
 Construction of the DTX would occur after completion of the Proposed Project, so there would be no
 simultaneous construction noise impacts at their overlap at the 4th and King Station and yard.
- Construction of the Proposed Project would overlap in time and location with the projects specified
 as having such overlap in Table 4-3, including the following substantial transportation projects:
- Caltrain South Terminal Improvements (Santa Clara San Jose).
- BART Silicon Valley Extension, if construction starts by <u>2020</u> 2019 (Santa Clara San Jose).
- Other Caltrain Improvements (various locations).
- BART Millbrae Tail Tracks (south of Millbrae Station).
- Central Subway (near San Francisco 4th and King Station).
- Muni 22-Fillmore Electric Trolley Bus Re-Routing (16th Street in San Francisco).
- Other grade separations (Rengstorff, possibly others in San Mateo County).
- Muni T-Line Extension southern extension to the Caltrain Bayshore station, if construction starts
 by 2019 (Caltrain Bayshore Station).
- Palo Alto Caltrain Station/Bus Transit Center Expansion, if construction starts by 2020 2019
 (Caltrain Palo Alto Station).
- Tasman Express Long T Double-tracking (Mountain View Station).
- In addition, as noted in Table 4-3, there are numerous land use development projects that have
 planned or potential construction periods that could overlap with Proposed Project construction.

- With multiple cumulative construction projects in close adjacency, there is the potential for
 significant cumulative construction noise and vibration impacts.
- 3 As discussed in Section 3.11, *Noise and Vibration*, the Proposed Project construction would have
- 4 potentially significant noise and vibration impacts during construction. Mitigation Measure NOI-1a
- 5 would require development and implementation of a noise control plan to reduce potential
- 6 construction noise impacts but would not necessarily reduce all noise impacts at all times during
- 7 construction to a less than significant level, particularly with the likelihood of substantial night-time
- 8 construction expected with the Proposed Project. Because there will be other cumulative projects in
- 9 construction adjacent to the Caltrain ROW at the same time, the Proposed Project could result in a 10 cumulatively considerable contribution to cumulative construction noise impacts. Even with
- 11 mitigation, these cumulative impacts could be significant and unavoidable
- 12 Proposed Project construction vibration impacts would be reduced to a less than significant level
- 13 with Mitigation Measure NOI-2a. Given this mitigation and the fact that vibration levels due not 14 accumulate (like noise levels can), the Proposed Project would not contribute considerably to
- 15 cumulative construction vibration impacts.

16 **Operational**

17 **Operational Noise**

18 Cumulative Rail Projects

19 As shown in Table 4-8 above, if Blended Service and other cumulative freight and passenger rail 20 service increases all come to fruition as hoped by project proponents, there would be a substantial 21 increase in the number of daily trains using the Caltrain corridor itself by both 2020 and 2040. For 22 example in the segment between Santa Clara and San Jose, which is the most heavily used segment 23 by passenger services other than Caltrain and by freight service today, by 2040 there could be an 24 increase from approximately 116 passenger trains and nine freight trains today to perhaps as many 25 as 176 passenger trains and 19 freight trains daily in 2040. Between Santa Clara and Redwood City, 26 there could be an increase from approximately 94 passenger trains and two freight trains today to 27 perhaps as many as 204 to 230¹⁵ passenger trains and four freight trains daily in 2040. Between 28 Redwood City and San Francisco, there could be an increase from approximately 92 passenger trains 29 and six freight trains today to perhaps as many as 204 to 230 passenger trains and 12 freight trains 30 daily in 2040. Increased passenger and freight rail service would increase noise levels along the 31 Caltrain ROW as well as at any maintenance facilities for Caltrain, HSR, freight, or other tenant rail 32 services.

- 33 In addition to an increase in train service, Blended Service operations (for both HST and Caltrain) up
- to 110 mph, up from the present maximum of 79 mph would also increase potential cumulativenoise levels.
- 36 The HSR San Jose to Merced from San Jose Diridon to south of the Tamien Station would be along the
- 37 Caltrain ROW on aerial structures to south of the Tamien Station, then at-grade to south of Pullman
- 38 Way, then on aerial south to just north of Capitol Expressway. While HSR service south of the

¹⁵ The range indicated includes 40 to 53 daily round-trip (80 to 106 one-way) HSR trains from Table 4-8, but the noise analysis was completed for 53 daily round trip HSR trains as this is consistent with CHSRA 2014 Business Plan.

Diridon Station was not included in the cumulative noise modeling (because it would not be on the
 same tracks as Caltrain), HSR operations in this segment where parallel to the Caltrain ROW would
 add additional noise in this part of San Jose.

4 Modeling of Cumulative Rail Noise Levels

The potential cumulative rail noise using the Caltrain corridor due to the increases levels of service
 shown in Table 4-8¹⁶ were modeled by WIA for the following cumulative scenarios:

- 2020 Cumulative without project scenario: In this scenario, Caltrain service would include 92
 trains between San Jose and San Francisco using diesel locomotives and the cumulative
 increases of other rail services would be as shown in Table 4-8.
- 2020 Cumulative with project scenario: In this scenario, Caltrain service would include 114
 trains between San Jose and San Francisco of which 75 percent would be EMUs and 25 percent
 would be diesel service and the cumulative increases of other rail services would be as shown in
 Table 4-8.
- 2040 Cumulative without project scenario: In this scenario, Caltrain service would include 92
 trains between San Jose and San Francisco using diesel locomotives and the cumulative
 increases of other rail services would be as shown in Table 4-8 without High Speed Rail.
- 2040 Cumulative with Full Caltrain Electrification scenario: In this scenario, Caltrain service
 would include 114 trains between San Jose and San Francisco using EMUs and the cumulative
 increases of other rail services would be as shown in Table 4-8 without High Speed Rail.
- 20 2040 Cumulative with Blended Service, 79 mph Scenario: In this scenario, Caltrain service
 21 would include 114 trains between San Jose and San Francisco using EMUs and the cumulative
 22 increases of other rail services would be as shown in Table 4-8 including High Speed Rail
 23 Blended Service operating up to 79 mph.
- 24 2040 Cumulative with Blended Service, 110 mph Scenario: In this scenario, Caltrain service
 25 would include 114 trains between San Jose and San Francisco using EMUs and the cumulative
 26 increases of other rail services would be as shown in Table 4-8 including High Speed Rail
 27 Blended Service operating up to 110 mph.
- 28This noise modelling was done on a worst-case basis assuming that all of the service levels identified29in Table 4-8 occur ¹⁷ and not assuming any improvements in trackage (such as new track, ties, or30trackbed treatments that may lower noise) or any new grade separations (except for those included31in the under construction San Bruno Grade Separation Project). As described above, for the32Cumulative Blended Service scenarios, there will be Core Capacity projects constructed to33accommodate the mixing of Caltrain and HSR service and thus noise levels for the Blended Service
- 34 scenarios will likely be less than those indicated in Table 4-11.
- 35

¹⁶ As noted above, the 2014 Business Plan: 2014 Service Planning Methodology (CHSRA 2014c) describes 53 daily round-trip trips (106 trains) to San Francisco which is the assumption used in the cumulative noise analysis. However, this Draft EIR analyzes 40 daily roundtrips (80 trains), based on the adopted 2012 Revised Business Plan because this level of service is consistent with Caltrain analysis of Blended Service to date. If more round-trips occur, then noise levels may be higher than those identified in this section.

¹⁷ As noted above, for HSR it was assumed that service levels would be 53 daily round trips per the 2014 CHSRA Business Plan.

1 Table 4-11. Cumulative Rail Noise Impacts, Overview

		Impacts per FTA Noise Criteria			
		No	Moderate	Severe	
Year	Scenario	Impact	Impact	Impact	
	Cumulative ^a without Project	34	15	0	
2020	Cumulative ^a with Project	<u>37 </u> 36	<u>12</u> 13	0	
2040	Cumulative ^b without Project	1	39	9	
	Cumulative ^b with Full Caltrain Electrification ^c	<u>5</u> -4	<u>38</u> 37	<u>6</u> 8	
	Cumulative ^b with Blended Service (79 mph scenario)	<u>1</u> 1	<u>17</u> 4	<u>31</u> 44	
	Cumulative ^b with Blended Service (110 mph scenario)	1	4	44	

Source: Appendix C, Noise and Vibration Technical Report

^a Cumulative 2020 scenarios include freight and other passenger rail service levels noted in Table 4-8 but do not include high speed rail.

^b Cumulative 2040 scenarios include freight and other passenger rail service levels noted in Table 4-8 and vary based on whether the Proposed Project, Caltrain Full Electrification, or Blended Service is included. San Jose to Merced HSR operations are not included in this analysis but could add additional noise at two locations in San Jose, although the HSR alignment is not parallel to the Caltrain ROW at these study locations.

^c Caltrain Full Electrification is not part of the Proposed Project but is considered the likely situation for 2040.

3 The cumulative noise change was characterized in comparison with existing noise levels along the 4 Caltrain corridor at 49 study locations (see discussion in Section 3.11, Noise and Vibration). The 5 change from existing noise levels with each cumulative scenario was then compared with the FTA 6 moderate and severe impact thresholds. 7 With cumulative train service increases, under the worst-case assumptions noted above, there could 8 be significant cumulative noise impacts in all 2020 and 2040 scenarios evaluated, compared with 9 existing conditions. As discussed in Appendix C, Noise and Vibration Technical Report, the most 10 substantial contributor to increases in cumulative noise over existing levels is freight service at most 11 locations. Although the number of additional freight trains is smaller than the cumulative passenger 12 trains included in the various cumulative scenarios, freight trains are heavier and longer than 13 passenger trains and thus for similar speeds, they generally result in greater noise levels. 14 The summary of results by scenario is presented in Table 4-11 and comparative results by study 15 location are shown in Table 4-12 (2020) and Table 4-13 (2040). 16 Figure 4-3 shows the average noise levels across the entire Caltrain corridor with different

- 17 cumulative scenarios and the contribution of different cumulative rail services.
- 18 Figure 4-4 shows the noise levels at the 49 different study locations comparing existing noise levels,
- 19 cumulative conditions without the project and cumulative conditions with Caltrain Full
- 20 Electrification in 2040. As shown in Table 4-13, in 2040 Caltrain Full Electrification would reduce
- 21 cumulative noise levels at <u>45</u>42 locations, while increasing noise levels at one location, with no
- 22 change at <u>four six</u> locations compared with Cumulative No Project Conditions.

23

²

	Setting	Change from Existing - 2020			
Site No	Location	City	Cumulative w/o Project ^a	Cumulative w/ Project ^a	Project Contribution
1	Oakdale Ave and Quint Ave	San Francisco	<u>0.9</u>	<u>0.7</u>	<u>-0.2</u>
2	Reddy St and Williams Ave	San Francisco	<u>0.8</u>	<u>0.5</u>	<u>-0.3</u>
3	Carr St and Paul Ave	San Francisco	<u>0.8</u>	<u>0.6</u>	<u>-0.2</u>
4	Tunnel Ave and Lathrop Ave	San Francisco	<u>0.6</u>	<u>0.6</u>	<u>0.0</u>
5	Herman St and Tanforan Ave	San Bruno	<u>0.8</u>	<u>0.4</u>	<u>-0.4</u>
6	Huntington Ave and San Bruno Ave	San Bruno	<u>-1.1</u>	<u>-1.3</u>	<u>-0.2</u>
7	Montgomery Ave and Walnut St	San Bruno	<u>-0.4</u>	<u>-0.6</u>	<u>-0.2</u>
8	1st Ave and Pine St	San Bruno	<u>-1.1</u>	<u>-1.4</u>	<u>-0.3</u>
9	Huntington Ave and Sylvan Ave	San Bruno	<u>-1.2</u>	<u>-1.5</u>	<u>-0.3</u>
10	San Antonio Ave and San Benito Ave	San Bruno	<u>0.9</u>	<u>0.7</u>	<u>-0.2</u>
11	Monterey St and Santa Paula Ave	Millbrae	<u>0.8</u>	<u>0.8</u>	<u>0.0</u>
12	Hemlock Ave and Hemlock Dr	San Mateo County	<u>0.8</u>	<u>0.8</u>	<u>0.0</u>
13	California Dr and Dufferin Ave	Burlingame	<u>0.9</u>	<u>0.7</u>	<u>-0.2</u>
14	California Dr and Mills Ave	Burlingame	<u>0.7</u>	<u>0.7</u>	<u>0.0</u>
15	California Dr and Palm Dr	Burlingame	<u>0.9</u>	<u>0.9</u>	<u>0.0</u>
16	Park Ave and Carolan Ave	Burlingame	<u>0.8</u>	<u>0.8</u>	<u>0.0</u>
17	Grand Blvd and San Mateo Blvd	San Mateo	<u>0.7</u>	<u>0.7</u>	<u>0.0</u>
18	Railroad Ave and Monte Diablo	San Mateo	<u>0.6</u>	<u>0.6</u>	<u>0.0</u>
19	B St and 9th Ave	San Mateo	<u>0.8</u>	<u>0.8</u>	<u>0.0</u>
20	South Blvd and 16th Ave	San Mateo	<u>0.6</u>	<u>0.2</u>	<u>-0.4</u>
21	Pacific Blvd and Otay Ave	San Mateo	<u>0.8</u>	<u>0.7</u>	<u>-0.1</u>
22	Country Rd and Dale View Ave	San Mateo	<u>0.8</u>	<u>0.5</u>	<u>-0.3</u>
23	Country Rd and Marine View	Belmont	<u>0.8</u>	<u>0.7</u>	<u>-0.1</u>
24	Country Rd and Springfield Ave	San Carlos	<u>0.6</u>	<u>0.6</u>	<u>0.0</u>
25	D St and Stafford St	Redwood City	<u>0.7</u>	<u>0.8</u>	<u>0.1</u>
26	Cedar St and Main St	Redwood City	<u>0.6</u>	<u>0.7</u>	<u>0.1</u>
27	198 Buckingham Ave	Redwood City	<u>0.9</u>	<u>0.6</u>	<u>-0.3</u>
28	Arrowhead Lane and 5th Ave	San Mateo County	<u>1.0</u>	<u>0.6</u>	<u>-0.4</u>
29	Lloyden Dr and Fair Oaks Lane	Atherton	<u>0.8</u>	<u>0.5</u>	<u>-0.3</u>
30	Felton Dr and Encinal Ave	Atherton	<u>0.9</u>	<u>0.6</u>	<u>-0.3</u>
31	Burgess Dr and Alma St	Menlo Park	<u>1.0</u>	<u>0.8</u>	<u>-0.2</u>

1 Table 4-12. 2020 Cumulative Rail Noise Levels, Change over Existing (dBA)

Setting			Change from E	Existing - 2020	
C: N			Cumulative	Cumulative	Project
Site No	Location	Lity	w/o Project ^a	w/ Project ^a	Contribution
32	Mitchell Lane and University Ave	Palo Alto	<u>0.9</u>	<u>0.7</u>	<u>-0.2</u>
33	Alma St and Lincoln Ave	Palo Alto	<u>0.8</u>	<u>0.5</u>	<u>-0.3</u>
34	Residences near Peers Park	Palo Alto	<u>0.8</u>	<u>0.4</u>	<u>-0.4</u>
35	Alma St and El Dorado Ave	Palo Alto	<u>1.0</u>	<u>0.6</u>	<u>-0.4</u>
36	4237 Park Blvd	Palo Alto	<u>1.1</u>	<u>1.2</u>	<u>0.1</u>
37	Central Exp and Thompson Ave	Mountain View	<u>1.1</u>	<u>0.8</u>	<u>-0.3</u>
38	Evelyn Ave and Bryant St	Mountain View	<u>0.9</u>	0.7	<u>-0.2</u>
39	Central Exp and Whisman Ave	Mountain View	<u>0.9</u>	<u>0.9</u>	<u>0.0</u>
40	S. Bernardo Ave and Evelyn Ave	Mountain View	<u>0.8</u>	<u>0.3</u>	<u>-0.5</u>
41	Asilomar Ave and Mary Ave	Sunnyvale	<u>1.0</u>	<u>0.8</u>	<u>-0.2</u>
42	332 Angel Ave	Sunnyvale	<u>0.8</u>	0.7	<u>-0.1</u>
43	Fair Oaks Ave and Evelyn Ave	Sunnyvale	<u>1.0</u>	<u>0.8</u>	<u>-0.2</u>
44	Agate St and Lawrence Exp	Santa Clara	<u>0.7</u>	<u>0.7</u>	<u>0.0</u>
45	Agate Dr and Bowers Ave	Santa Clara	<u>0.8</u>	<u>0.6</u>	<u>-0.2</u>
46	Alvarado Dr and San Thomas Exp	Santa Clara	<u>0.7</u>	<u>0.4</u>	<u>-0.3</u>
47	2109 Main St	Santa Clara	<u>0.7</u>	<u>0.4</u>	<u>-0.3</u>
48	782 Auzerais Ave	San Jose	<u>-0.4</u>	<u>-0.4</u>	<u>0.0</u>
49	456 Jerome St	San Jose	<u>-0.4</u>	<u>-1.4</u>	<u>-1.0</u>
Increases	S		43	43	<u>3</u> 8
Decrease	25		6	6	<u>33</u>
No chan	ge		0	0	138

Source: Appendix C, Noise and Vibration Technical Report

^a Cumulative 2020 scenarios include freight and other passenger rail service levels noted in Table 4-8 but do not include high speed rail.

1

1 Table 4-13. 2040 Cumulative Rail Noise Levels, Change over Existing (dBA)^a

			Change from l	Existing - 2040			
Site No.	Location	City	2040 Cumulative No Project	2040 Cumulative with Caltrain Full Electrification	Change with Caltrain Full Electrification	2040 Cumulative with Blended Service (79 mph)	2040 Cumulative with Blended Service (110 mph)
1	Oakdale Ave and Quint Ave	San Francisco	2.7	<u>2.5</u>	<u>-0.2</u>	<u>3.0</u>	<u>3.6</u>
2	Reddy St and Williams Ave	<u>San Francisco</u>	<u>2.5</u>	<u>2.2</u>	<u>-0.3</u>	<u>2.9</u>	<u>3.7</u>
3	Carr St and Paul Ave	<u>San Francisco</u>	<u>2.7</u>	<u>2.4</u>	<u>-0.3</u>	<u>2.9</u>	<u>3.6</u>
4	Tunnel Ave and Lathrop Ave	<u>San Francisco</u>	<u>2.0</u>	<u>1.7</u>	<u>-0.3</u>	<u>3.0</u>	<u>3.1</u>
5	Herman St and Tanforan Ave	<u>San Bruno</u>	<u>2.4</u>	<u>2.0</u>	<u>-0.4</u>	<u>2.6</u>	<u>2.6</u>
6	<u>Huntington Ave and San Bruno</u> <u>Ave</u>	<u>San Bruno</u>	<u>0.7</u>	<u>0.4</u>	<u>-0.3</u>	<u>0.9</u>	<u>1.5</u>
7	Montgomery Ave and Walnut St	<u>San Bruno</u>	<u>1.4</u>	<u>1.2</u>	<u>-0.2</u>	<u>1.5</u>	<u>2.0</u>
8	<u>1st Ave and Pine St</u>	<u>San Bruno</u>	<u>0.6</u>	<u>0.4</u>	<u>-0.2</u>	<u>0.8</u>	<u>1.5</u>
9	Huntington Ave and Sylvan Ave	<u>San Bruno</u>	<u>0.5</u>	<u>0.2</u>	<u>-0.3</u>	<u>0.8</u>	<u>1.5</u>
10	<u>San Antonio Ave and San Benito</u> <u>Ave</u>	<u>San Bruno</u>	<u>2.9</u>	<u>2.7</u>	<u>-0.2</u>	<u>3.1</u>	<u>3.5</u>
11	Monterey St and Santa Paula Ave	<u>Millbrae</u>	<u>2.6</u>	<u>2.5</u>	<u>-0.1</u>	2.7	<u>2.8</u>
12	Hemlock Ave and Hemlock Dr	<u>San Mateo</u> <u>County</u>	<u>2.3</u>	<u>2.2</u>	<u>-0.1</u>	<u>3.0</u>	<u>3.2</u>
13	California Dr and Dufferin Ave	<u>Burlingame</u>	<u>2.9</u>	<u>2.7</u>	<u>-0.2</u>	<u>3.1</u>	<u>3.5</u>
14	California Dr and Mills Ave	<u>Burlingame</u>	<u>2.4</u>	<u>2.3</u>	<u>-0.1</u>	<u>3.3</u>	<u>3.2</u>
15	California Dr and Palm Dr	<u>Burlingame</u>	<u>2.7</u>	<u>2.7</u>	<u>0.0</u>	<u>3.2</u>	<u>3.2</u>
16	Park Ave and Carolan Ave	<u>Burlingame</u>	<u>2.6</u>	<u>2.6</u>	<u>0.0</u>	<u>3.2</u>	<u>3.2</u>
17	Grand Blvd and San Mateo Blvd	<u>San Mateo</u>	<u>2.0</u>	<u>1.8</u>	<u>-0.2</u>	<u>3.0</u>	<u>3.2</u>
18	Railroad Ave and Monte Diablo	<u>San Mateo</u>	<u>1.8</u>	<u>1.5</u>	<u>-0.3</u>	<u>3.0</u>	<u>3.2</u>
19	<u>B St and 9th Ave</u>	<u>San Mateo</u>	<u>2.5</u>	<u>2.5</u>	<u>0.0</u>	<u>3.3</u>	<u>3.2</u>
20	South Blvd and 16th Ave	<u>San Mateo</u>	<u>2.0</u>	<u>1.4</u>	<u>-0.6</u>	<u>2.7</u>	<u>3.9</u>
21	Pacific Blvd and Otay Ave	<u>San Mateo</u>	<u>2.4</u>	<u>2.2</u>	<u>-0.2</u>	<u>3.0</u>	<u>3.4</u>

			Change from l	Existing - 2040			
Site No.	Location	City	2040 Cumulative No Project	2040 Cumulative with Caltrain Full Electrification	Change with Caltrain Full Electrification	2040 Cumulative with Blended Service (79 mph)	2040 Cumulative with Blended Service (110 mph)
22	Country Rd and Dale View Ave	San Mateo	<u>2.6</u>	<u>2.3</u>	<u>-0.3</u>	<u>3.0</u>	<u>3.7</u>
23	Country Rd and Marine View	<u>Belmont</u>	<u>2.6</u>	<u>2.4</u>	<u>-0.2</u>	<u>3.1</u>	<u>3.3</u>
24	Country Rd and Springfield Ave	<u>San Carlos</u>	<u>2.0</u>	<u>1.7</u>	<u>-0.3</u>	<u>3.0</u>	<u>3.2</u>
25	<u>D St and Stafford St</u>	<u>Redwood City</u>	<u>2.0</u>	<u>1.9</u>	<u>-0.1</u>	<u>3.1</u>	<u>3.0</u>
26	<u>Cedar St and Main St</u>	<u>Redwood City</u>	<u>1.9</u>	<u>1.8</u>	<u>-0.1</u>	<u>3.1</u>	<u>3.1</u>
27	<u>198 Buckingham Ave</u>	<u>Redwood City</u>	<u>2.1</u>	<u>1.7</u>	<u>-0.4</u>	<u>2.6</u>	<u>3.7</u>
28	Arrowhead Lane and 5th Ave	<u>San Mateo</u> <u>County</u>	<u>2.2</u>	<u>1.7</u>	<u>-0.5</u>	<u>2.6</u>	<u>3.7</u>
29	Lloyden Dr and Fair Oaks Lane	<u>Atherton</u>	<u>1.4</u>	<u>0.9</u>	<u>-0.5</u>	<u>2.6</u>	<u>3.5</u>
30	Felton Dr and Encinal Ave	<u>Atherton</u>	<u>1.6</u>	<u>1.1</u>	<u>-0.5</u>	<u>2.6</u>	<u>3.4</u>
31	Burgess Dr and Alma St	<u>Menlo Park</u>	<u>2.9</u>	<u>2.7</u>	<u>-0.2</u>	<u>3.1</u>	<u>3.5</u>
32	Mitchell Lane and University Ave	<u>Palo Alto</u>	<u>1.9</u>	<u>1.5</u>	<u>-0.4</u>	<u>2.7</u>	<u>3.5</u>
33	Alma St and Lincoln Ave	<u>Palo Alto</u>	<u>2.3</u>	<u>1.9</u>	<u>-0.4</u>	<u>2.8</u>	<u>3.7</u>
34	Residences near Peers Park	<u>Palo Alto</u>	<u>1.7</u>	<u>0.9</u>	<u>-0.8</u>	<u>2.4</u>	<u>3.9</u>
35	<u>Alma St and El Dorado Ave</u>	<u>Palo Alto</u>	<u>2.6</u>	<u>2.3</u>	<u>-0.3</u>	<u>2.8</u>	<u>2.8</u>
36	<u>4237 Park Blvd</u>	<u>Palo Alto</u>	<u>2.2</u>	<u>2.2</u>	<u>0.0</u>	<u>3.1</u>	<u>3.0</u>
37	Central Exp and Thompson Ave	<u>Mountain</u> <u>View</u>	2.7	<u>2.5</u>	<u>-0.2</u>	<u>2.9</u>	<u>2.8</u>
38	Evelyn Ave and Bryant St	<u>Mountain</u> <u>View</u>	<u>2.1</u>	<u>1.8</u>	<u>-0.3</u>	<u>2.7</u>	<u>2.6</u>
39	Central Exp and Whisman Ave	<u>Mountain</u> <u>View</u>	<u>3.3</u>	<u>3.2</u>	<u>-0.1</u>	<u>3.3</u>	<u>3.5</u>
40	S. Bernardo Ave and Evelyn Ave	<u>Mountain</u> <u>View</u>	<u>1.7</u>	<u>1.0</u>	<u>-0.7</u>	<u>2.4</u>	<u>3.8</u>
41	Asilomar Ave and Mary Ave	<u>Sunnyvale</u>	<u>2.0</u>	<u>1.7</u>	<u>-0.3</u>	<u>2.8</u>	<u>3.4</u>
42	<u>332 Angel Ave</u>	<u>Sunnyvale</u>	<u>2.1</u>	<u>1.9</u>	<u>-0.2</u>	<u>3.0</u>	<u>3.3</u>
43	Fair Oaks Ave and Evelyn Ave	<u>Sunnyvale</u>	2.7	<u>2.5</u>	<u>-0.2</u>	<u>3.0</u>	<u>3.6</u>

	Change from Existing - 2040						
Site No.	Location	City	2040 Cumulative No Project	2040 Cumulative with Caltrain Full Electrification	Change with Caltrain Full Electrification	2040 Cumulative with Blended Service (79 mph)	2040 Cumulative with Blended Service (110 mph)
44	Agate St and Lawrence Exp	<u>Santa Clara</u>	<u>2.2</u>	<u>2.0</u>	<u>-0.2</u>	3.2	<u>3.9</u>
45	Agate Dr and Bowers Ave	<u>Santa Clara</u>	<u>2.7</u>	<u>2.4</u>	<u>-0.3</u>	<u>3.0</u>	<u>3.6</u>
46	<u>Alvarado Dr and San Thomas Exp</u>	<u>Santa Clara</u>	<u>2.4</u>	2.0	<u>-0.4</u>	<u>2.8</u>	<u>3.8</u>
47	<u>2109 Main St</u>	<u>Santa Clara</u>	2.4	<u>2.0</u>	<u>-0.4</u>	<u>2.8</u>	<u>3.8</u>
48	782 Auzerais Ave	<u>San Jose</u>	<u>1.3</u>	<u>1.2</u>	<u>-0.1</u>	<u>1.2</u>	<u>1.2</u>
49	<u>456 Jerome St</u>	<u>San Jose</u>	<u>1.2</u>	<u>0.6</u>	<u>-0.6</u>	<u>0.6</u>	<u>0.6</u>
Increases			49	49	<u>0</u> 1	49	49
Decreases			0	0	<u>45</u> 4 2	0	0
No Change			0	0	<u>4</u> 6	0	0

Source: Appendix C, Noise and Vibration Technical Report

^a Cumulative 2040 scenarios include freight and other passenger rail service levels noted in Table 4-8 and vary based on whether the Proposed Project, Caltrain Full Electrification, or Blended Service is included. San Jose to Merced HSR operations are not included in this analysis but could add additional noise at study locations 48 and 49, although the HSR alignment is not parallel to the Caltrain ROW at these study locations.

^b Caltrain Full Electrification is not part of the Proposed Project but is considered the likely situation for 2040.

1





the existing noise levels shown have been lowered by the average noise reduction of 0.3 dBA for 2040 with the project compared to No Project conditions.

Note: This figure replaces Figure 4-3 from the Draft EIR.

Figure 4-3 Average Noise Levels along Caltrain Corridor by Cumulative Scenario (dBA) Peninsula Corridor Electrification Project



Note: This figure replaces Figure 4-4 from the Draft EIR.

- 1 Figure 4-5 shows the noise levels at the 49 study locations comparing existing noise levels with
- 2 different cumulative scenarios. As shown, in 2040, for the Cumulative with Blended Service
- 3 scenarios (both 79 mph and 110 mph), the largest share of increases (approximately 68 to 75
- 4 percent) over the FTA severe criteria are due to freight/other rail increases with the remainder
- 5 (approximately 25 to 32 percent) due to Blended Service.
- Noise modeling results are presented in greater detail in Appendix C, *Noise and Vibration Technical Report.*

8 All Other Projects

During operation, the non-rail cumulative projects could also increase noise levels and affect
 sensitive receptors in the vicinity of the Caltrain ROW. Operation of the land use developments and
 other regional transportation projects would increase noise levels by introducing more people,
 activities and traffic into the project vicinity. In addition, land development projects along the
 Caltrain ROW would also introduce more sensitive receptors that would be subject to the

14 cumulative noise levels from increased passenger and rail service described above.

15 Proposed Project Cumulative Contribution

16As described in Section 3.11, Noise and Vibration, the Proposed Project would result in both17beneficial and adverse noise effects compared with existing conditions. The Proposed Project would18replace diesel locomotives with EMUs, which are quieter. However, the Proposed Project would also19increase service, which would increase train horn noise. In 2020, the Proposed Project would lower20existing noise levels at <u>37 38</u> locations, increase noise levels at <u>4</u> 8 locations and have no change at 821study locations. All project level noise increases would be less than the FTA impact thresholds.

- Also as described in Section 3.11, *Noise and Vibration*, the Proposed Project would result in
 significant noise impacts due to noise from TPFs at one location. Mitigation Measure NOI-1b is
 proposed to require enclosures and site design to control noise at the one TPF location where
 needed to avoid significant impacts to nearby sensitive receptors. Relative to TPF noise alone, this
 mitigation would reduce any potential TPF noise contributions to potential cumulative impacts.
- 27 Where the Proposed Project would result in lower noise levels or the same noise levels compared
- 28 with No Project conditions, it would not contribute to cumulative rail noise impacts. As shown in
- 29 Table 4-12, in 2020, the Proposed Project would contribute to increased noise levels at <u>four</u> six
- 30 different study locations compared with 2020 Cumulative No Project conditions although, as shown
- in Figure 4-3, the Proposed Project would lower noise levels on average. <u>As shown in Table 4-12.</u>
 <u>only three of the four locations would have cumulatively significant noise increases in 2020, but all</u>
- 33 <u>four locations would have cumulatively significant noise increases in 2040 as shown in Table 4-13.</u>
- As shown in Table 4-13, under 2040 conditions, the combined effect of the Proposed Project and
 Caltrain Full Electrification would result in increased noise levels at only one no study locations
- 36 compared with 2040 No Project conditions. As shown in Figure 4-3, on average, the Proposed
- 37 Project and Caltrain Full Electrification would lower noise levels along the Caltrain corridor.
- 38 However, Caltrain Full Electrification is not part of the Proposed Project and thus under 2040
- conditions, the Proposed Project is assumed to contribute to increased noise levels at the same <u>four</u>
 six study locations identified for 2020 cumulative conditions.
- Thus, at the <u>four six</u> locations identified in Table 4-12 where the Proposed Project would result in
 noise increases, the Proposed Project would make a considerable contribution to the significant

- cumulative noise impacts shown in Table 4-11 and described further in Appendix C, *Noise and Vibration Technical Report.*
- 3 <u>There are several milestones for cumulative noise.</u>
- 4 The first is 2020 when the PCEP service would begin. In 2020, there are three locations with • 5 significant operational noise impacts: San Mateo near the 9th Avenue grade crossing (Receptor 6 #19); Redwood City near the Whipple Ave. grade crossing (Receptor #25); and Palo Alto near 7 the W. Charleston Road grade crossing (Receptor #36). Caltrain's contribution to cumulative 8 noise increase is only 0.1 dBA at each of these locations which represents 8 to 13 percent of the 9 noise increase. The freight increases are the most substantial in terms of noise generation. There 10 is a possibility that if the freight increases assumed in the EIR do not come to fruition that the 11 significant impacts at one or all three of these locations would not occur and the timing for the 12 <u>Coast Daylight is not certain. The PCEP noise increases at this location alone would not result in</u> 13 significant noise impacts.
- 14 The second is 2026 or after when HSR blended service commences. The noise analysis used a 15 2040 milestone, but cumulative noise would change with the combination of the PCEP, freight increases, other railroads, and high speed rail over the post-2020 period as rail service increases 16 17 actually occur. As shown in Figure 4-5, the noise contributions of freight rail and other 18 passenger rails are actually the largest source of increased noise but there would also be 19 contributions from HSR blended service, The PCEP contribution after 2026 will depend on 20 whether Caltrain is using all EMUs for the San Jose to San Francisco service; if so, then Caltrain 21 will not contribute to cumulative increases. If Caltrain is still operating a similar amount of 22 diesel locomotives as in 2020, then it would contribute approximately 0.1 dBA to the increases at these four locations: Burlingame near the Broadway grade crossing (Receptor #14): San 23 24 Mateo near the 9th Avenue grade crossing (Receptor #19); Redwood City near the Whipple Ave. 25 grade crossing (Receptor #25); and Palo Alto near the W. Charleston Road grade crossing 26 [Receptor #36]. These increases would represent only about 3 percent of cumulative noise 27 increases in 2040.
- 28 There are a number of different methods to reduce the noise impacts of cumulative trains:
- Wayside horns: Train horn noise can be reduced through use of a wayside horn, which is an automatically triggered horn located at the at-grade crossing itself that sounds upon approach of a train. Because the horns are located at the crossing itself, the area of effect is smaller than the area of effect due to train horns, but sensitive receptors near the at-grade crossing will still be affected by horn noise. Wayside horns are included as one option in Mitigation Measure NOI-CUMUL-1 described below but only as part of a quiet zone. Without the quiet zone designation, train operators could still use the train horn thus defeating the purpose of a wayside horn.
- 36 Building sound insulation: Another method of reducing the impact of train horn noise is building 37 sound insulation. Sound insulation of residences and institutional buildings improve the 38 outdoor-to-indoor noise reduction. Although this approach has no effect on noise in exterior 39 areas, it is a feasible method for sites where noise barriers are not feasible or desirable, for 40 buildings where indoor sensitivity is of most concern, or where the horn noise dominates the 41 noise environment. Improvements in building sound insulation can often be achieved by adding 42 an extra layer of glazing to the windows and by sealing any holes in exterior surfaces that act as 43 sound leaks. Building sound insulation is included as one option in Mitigation Measure NOI-44 CUMUL-1 described below.



Note: This figure replaces Figure 4-5 from the Draft EIR.

Figure 4-5 2040 Cumulative Noise Levels along Caltrain Corridor Peninsula Corridor Electrification Project

1

2

3

4

5

6

7

8

- *Quiet zone*: The FRA has established a process by which a local jurisdiction can designate a specific area containing at-grade crossings as a "quiet zone", provided that certain supplemental safety measures (SSM) are used in place of the locomotive horn to provide an equivalent level of safety at the at-grade crossing (FTA 2006).
 - The SSMs commonly used for quiet zones include 4-quadrant gates, gates with medians or channelization devices, one-way street with gates, and street closure. By adopting an approved SSM at each of the impacted at-grade crossings, a quiet zone at least 0.5 mile long can be established.
- 9 Only with local implementation of the quiet zone can Caltrain, freight operators and other 0 10 tenant railroad operations be relieved of the requirement to sound their horns when crossing at-grade crossings. However, following implementation of a quiet zone, if any 11 12 unsafe conditions were present at the time of train passage (such as a vehicle going around 13 the gates or pedestrians in the crossing), train operators would still have the discretion to 14 sound train horns. Although the quiet zone regulations are silent on the issue of liability, 15 local jurisdictions may perceived that the implementation of a quiet zone includes 16 acceptance of potential liability in the event of related accidents. It is possible that 17 jurisdictions may not wish to risk the potential liability associated with implementing a 18 quiet zone and decline to do so. In such a case, Caltrain, and freight and other rail operators 19 would continue to use train horns as a safety device in compliance with FRA requirements.
- Although funding for quiet zone improvements is not included in the current Proposed
 Project budget, funding for quiet zone improvements at all remaining 42 at-grade crossings
 between San Jose and San Francisco is considered feasible. Assuming that quiet zone
 improvements may range in cost up to \$1 million to \$2 million per crossing, the cost of
 implementing quiet zone improvements could range from \$42 million.
- Where quiet zones are implemented and accepted by local jurisdictions, cumulative noise
 levels may be reduced to a less than significant level at some but not necessarily all
 cumulatively affected locations.
- Quiet zones are included as one option in Mitigation Measure NOI-CUMUL-1 described
 below.
- 30 *Soundwalls*: Soundwalls are not considered a feasible mitigation to address horn noise because • 31 train horns are elevated and thus soundwalls would have to be as high or higher than the 32 locomotives themselves to be effective at shielding train horn noise. Along the Caltrain corridor, 33 such high walls would not likely be acceptable to local communities. Soundwalls cannot be 34 placed at the at-grade crossing which also reduces their effectiveness for horn noise reduction. 35 While lower soundwalls would help to reduce engine and wheel noise for adjacent receptors, 36 lower soundwalls are not considered cost-effective given that they would only be partially 37 effective at addressing train noise and would not address train horn noise which is the dominant 38 concern.
- Grade Separation: While grade separations are a technically feasible way to avoid the need for
 train horn use, it is a highly expensive mitigation strategy. Caltrain has supported prior grade
 separation efforts, such as the San Bruno Grade Separation project, led by Caltrain, which will be
 completed in 2014. As shown in the analysis in this EIR, the San Bruno Grade Separation would
 reduce noise levels by approximately 2 dB compared with existing conditions. Caltrain supports
 future efforts at grade separation where acceptable to local communities and where local, state,

1 and federal funding can be obtained to fund these improvements. Grade separations can cost 2 approximately \$50 million to \$100 million per crossing (grade separations can cost much more 3 sometimes), grade separating all existing 42 at-grade crossings would cost \$2.1 to \$4.2 billion. 4 The budget for the Proposed Project is \$1.225 billion by comparison. Thus, Caltrain cannot 5 commit to a comprehensive program of grade separations at this time. However, as described in 6 Mitigation Measure NOI-CUMUL-1, Caltrain will work with local jurisdictions, transportation 7 funding agencies, and state and federal agencies to support grade separations over time as 8 funding becomes available.

9 While the recommended mitigation below, where feasible to implement, would help to reduce noise,
10 it will take time to implement it and it may not be feasible to reduce all cumulative noise impacts to
11 a less than significant level. Therefore, the Proposed Project, without full Caltrain EMU operations
12 between San Jose and San Francisco, would make a considerable contribution to cumulative noise
13 impacts, with mitigation.

14 As to secondary environmental impacts of Mitigation Measure NOI-CUMUL-1, the environmental 15 effects of the different mitigation options would vary. Wayside horns and building sound insulation 16 would have limited to no secondary environmental impacts. Quiet zone improvements would 17 require additional construction, but the likely environmental impacts of such construction are 18 limited given the limited footprint of four-quadrant gates, active warning systems, medians and 19 street work. In general, construction impacts for quiet zone improvements would be similar to the 20 impacts disclosed for Proposed Project construction, would occur in previously developed and 21 disturbed areas, and would be temporary in nature. The applicable Proposed Project mitigation 22 described for construction impacts in this EIR, where relevant, would also be applied to quiet zone 23 improvements.

As to grade separations, the design and feasibility of a select number of future grade separations are
unknown and unstudied at this time, and thus the specific environmental impacts cannot be
identified. While they are statutorily exempt from CEQA review, grade separations may nevertheless
have substantial environmental impacts depending on their design and location, and their
construction can be highly disruptive. Therefore, as a conservative assumption, their secondary
environmental impacts are assumed to be significant and unavoidable.

30 Caltrain will work with other parties when implementing this measure to apply the relevant 31 construction mitigation measures identified in this EIR to these the implementation of future noise 32 mitigation improvements. Based on the analysis to date, the Proposed Project and Caltrain Full 33 Electrification are the minor sources of cumulative increases in noise compared with existing 34 conditions; therefore, pursuant to CEQA, Caltrain is only responsible for that portion of the 35 cumulative increases caused by the Proposed Project (or in the future with full electrification). Other 36 sources of cumulative increases including HSR, other passenger rail and freight services as well as 37 non-rail sources near the Caltrain corridor would also bear responsibility for cumulative noise 38 increases.

Mitigation Measure NOI-CUMUL-1 would address Caltrain's contribution to this cumulative impact.
 However, given the long-term nature of these improvements, the lack of current funding, the shared
 responsibility for cumulative impacts, and the lack of a collective agreement for a comprehensive
 noise mitigation program, it may not be possible to implement noise mitigation measures prior to
 cumulatively significant noise increases. In addition, the secondary environmental effects of some
 improvements, particularly for any grade separations constructed in the future, may be significant

and unavoidable. Thus, the Proposed Project is considered to contribute considerably to a
 cumulatively significant noise impact, even with mitigation.

Mitigation Measure NOI-CUMUL-1: Implement a phased program to reduce cumulative train noise along the Caltrain corridor as necessary to address future cumulative noise increases over FTA thresholds

- 6 The JPB, in cooperation with other rail operators, local jurisdictions, transportation funding 7 agencies, and state and federal agencies, will support incremental noise reduction measures at 8 the locations of cumulative noise impacts over time as funding becomes available for the 9 locations where the PCEP would contribute to cumulative noise impacts. Where the PCEP does 10 not contribute to cumulative noise impacts or where it would lower existing noise levels, then 11 the PCEP is not responsible to participate in mitigation, even if the cumulative noise impacts due 12 to other rail service increase is significant. Caltrain will work with local, state, and federal 13 partners to establish priorities for noise reduction measure to be implemented as funding 14 becomes available. Caltrain will also work with other rail operators to seek funding 15 participation from multiple parties on a fair-share basis in proportion to their cumulative noise contributions. 16
- 17The costs for implementing the phased program shall be borne by all rail operators in18proportion to their contributions to cumulative train noise increased over existing conditions.19Given that there are multiple contributors to cumulative rail noise, the JPB is only responsible to20fund its fair share for necessary noise mitigation with other rail services responsible to fund21their fair share as well. Fair share shall be determined by the noise contribution of each rail22service increase over existing conditions (2013) to cumulative noise levels as determined using23acceptable FTA noise modeling protocols.
- 24As noted above, the Proposed Project would result in increased increases noise at four six of the2549 study locations in the 2020 cumulative scenario (but only three locations would have26cumulatively significant noise increases in 2020), but if Caltrain implements full electrification27(e.g. 100 percent EMU service from San Jose to San Francisco), then the combined effect of the28Proposed Project and full electrification would only not result in noise increases at any one of29the 49 study locations and no fair-share contribution would be necessary from Caltrain.
- This program is expected to be implemented over a period of decades. Improvements will be
 phased as needed to address changes in cumulative rail service over time and cumulative rail
 noise.
- 33 The first cumulative milestone is 2020. The PCEP would contribute to significant cumulative • 34 impacts at three locations with PCEP contributions ranging from 8 to 13 percent: San Mateo 35 near the 9th Avenue grade crossing (Receptor #19); Redwood City near the Whipple Avenue grade crossing (Receptor #25); and Palo Alto near the W. Charleston Road grade crossing 36 37 (Receptor #36). At these locations, the cumulative noise increases identified in the EIR are 38 the combination of the PCEP, assumed freight increases, and potential Coast Daylight 39 service. Caltrain will monitor freight levels as well Coast Daylight planning in the time 40 leading up to 2020. Caltrain will work with UPRR and Amtrak, as necessary, to coordinate 41 fair-share contributions to cumulative mitigation and plan for implementation of feasible 42 improvements by 2020 or by such period that cumulative noise at the three locations above 43 is expected to exceed the FTA moderate threshold criteria. Since the PCEP increases are only 44 a small portion of the cumulative impact in 2020, the fair-share contributions of other

1

2

- parties will need to be secured to implement potential mitigation. If the other parties are not willing to contribute their fair-share, then mitigation may not be feasible.
- 3 The second cumulative milestone is 2026 or after when HSR blended service first • 4 commences along the Caltrain corridor. If Caltrain replaces all remnant diesel equipment by 5 that time, then the PCEP would make no contribution to cumulative noise increases and 6 would have no further mitigation responsibilities (operating up to 79 mph). If Caltrain is still 7 operating a similar amount of diesel locomotives in 2026 or after as in 2020, then it would 8 contribute approximately 3 percent to the increases at these four locations: Burlingame 9 near the Broadway grade crossing (Receptor #14): San Mateo near the 9th Avenue grade 10 crossing (Receptor #19); Redwood City near the Whipple Ave. grade crossing (Receptor #25); and Palo Alto near the W. Charleston Road grade crossing (Receptor #36). These four 11 12 locations would all be affected by the PCEP, HSR, freight, and the Coast Daylight and the Palo 13 Alto location could also be affected by Dunbarton Rail Corridor service. The subsequent 14 project-level analysis of blended HSR service may refine the noise increases due to HSR and 15 blended service when project level design details are taken into account. Caltrain's fair share 16 responsibility for blended service with Caltrain EMUs operating up to 110 mph may exceed 17 the PCEP's noise contribution since the PCEP is limited to 79 mph. Projected freight and other passenger rail increases may or may not occur. Caltrain will monitor freight levels 18 changes and will work with CHSRA, UPRR, and Amtrak (and DRC sponsors if DRC is 19 20 advanced) as necessary, to coordinate fair-share contributions to cumulative mitigation and 21 plan for implementation of feasible improvements by 2026 or by such period that 22 cumulative noise at the four locations above will exceed the FTA moderate threshold 23 criteria. Since the PCEP increases are only a small portion of the cumulative impact, the fair-24 share contributions of other parties will need to be secured to implement potential 25 mitigation. If the other parties are not willing or able to contribute their fair-share, then 26 mitigation may not be feasible, although it is assumed that CHSRA will be able to secure 27 sufficient funding to support mitigation to address HSR noise fair-share impacts.

28 Wayside horns and Residential building sound insulation.

- The, JPB, in cooperation with the other parties noted above, shall evaluate the potential to
 reduce cumulative noise impacts through the installation of wayside horns and building sound
 insulation improvements at residences projected to have a sound increase greater than the FTA
 moderate impact criteria. Building sound insulation methods may include extra wall insulation,
 window glazing and sealing of exterior surfaces.
- If this option is selected, a technical study shall be completed to evaluate the effectiveness of reducing cumulative impacts to less than the FTA moderate impact threshold through these methods. If the study shows that it is feasible to reduce the impact to less than the threshold at a cumulatively affected sensitive noise receptor, then no additional mitigation at that location will be required. Building sound insulation measures shall only be installed to the extent necessary to meet the impact threshold at the receptor location and shall only be installed if building owners are willing to accept such measures.

41 **Quiet Zones**

The lead agency for a quiet zone designation is the local jurisdiction (typically the City or
County) that is responsible for traffic control and law enforcement on the roads at the at-grade
crossings.

1 2 3 4 5 6	The JPB, in cooperation with the other parties noted above, and the affected local jurisdictions shall implement a phased program considering the potential establishment of quiet zones along the Caltrain corridor at all locations where cumulative train noise is predicted to exceed FTA moderate impact thresholds. The JPB and other cooperating railroad operators will work closely with local jurisdictions to prepare the engineering studies and coordination agreements to design, construct, and enforce potential quiet zones.
7 8	Options for establishing quiet zones could include implementation of the following FRA pre- approved supplemental safety measures (SSM):
9 10	• Four-quadrant gate system. This measure involves the installation of at least one gate for each direction of traffic to fully block vehicles from entering the crossing.
11 12 13	• Gates with medians or channelization devices. This measure keeps traffic in the proper travel lanes as it approaches the crossing, thus denying the driver the option of circumventing the gates by travelling in the opposite lane.
14 15 16	• One-way street with gates. This measure consists of one-way streets with gates installed so that all approaching travel lanes are completely blocked. This option may not be feasible or acceptable to local jurisdictions at all locations.
17 18	• Road closure. This measure consists of closing the road to through travel at the at-grade crossing. This option may not be feasible or acceptable to local jurisdictions at all locations.
19 20 21 22 23	In addition to these pre-approved SSMs, the FRA also identifies a range of other measures that may be used to establish a quiet zone. These could be modified SSMs or non-engineering measures which might involve law enforcement or public awareness programs. Such alternative safety measures must be approved by the FRA based on the prerequisite that they provide an equivalent level of safety as the sounding of horns.
24 25 26	<u>Wayside horns can also be utilized as part of a quiet zone. While not avoiding the sounding of a horn, wayside horns affect a smaller area than train-mounted horn. Wayside horns can be used when the other measures above are not adequate to avoid the use of a horn.</u>
27 28 29 30 31 32 33 34 35 36	The lead agency for a quiet zone designation is the local public authority which is the only authority that can implement a quiet zone. Caltrain or the other rail operators cannot on their own designate the quiet zone. However, only with the implementation of the quiet zone can Caltrain, other tenant railroads and freight operators be relieved of the requirement to sound their horns when crossing at-grade crossings. One key aspect of local jurisdiction acceptance of a quiet zone is acceptance of potential liability in the event of accidents related to not sounding a horn at an at-grade crossing after the installation of any required SSMs. Thus, if a local city does not accept the quiet zone, then even if the required SSMs are present, Caltrain, freight and other rail operators would continue to use train horns as a safety device in compliance with FRA requirements.
37	Grade Separations
38	Caltrain, in cooperation with other rail operators, local jurisdictions, transportation funding

agencies, and state and federal agencies, will support incremental grade separations at locations
 of cumulative noise impacts over time as funding becomes available. Caltrain will work with
 local, state, and federal partners to establish priorities for grade separations to be implemented

- as funding becomes available. Caltrain will also work with other rail providers to seek funding
 participation from multiple parties on a fair-share basis in proportion to noise contributions.
- 3 <u>Costs</u>
- The specific costs are not known for this mitigation. As noted in the EIR, grade separations can
 cost \$50 million to \$100 million or more per location (42 locations could cost \$2.1 to 4.2 billion)
 and quiet zone treatments can cost \$1 million to \$2 million per location (42 locations could cost
 \$42 to \$84 million). Building insulation costs have not been estimated.

8 **Operational Vibration**

9 The thresholds used for this analysis are the FTA annoyance thresholds for residential receptors (72
10 VdB) and institutional buildings (75 VdB) and the structural damage threshold (100 VdB). As
11 described by the FTA (2006), it is very rare for transportation-generated ground vibration to
12 approach building damage levels. Thus, the primary focus of this cumulative analysis is on the
13 annoyance thresholds.

- 14 Unlike noise, which is measured on a 24-hour day-night basis in which noise levels can increase
- 15 cumulatively, vibration levels do not accumulate. Thus cumulative impacts would not result in

higher vibration levels when combining multiple trains along the corridor. However, cumulative
 impacts can occur when multiple trains, each over the FTA vibration annoyance thresholds, pass a
 single sensitive receptor, resulting in an increase the number of annoyance events.

- 19As presented in Table 3.11-4 in Section 3.11, Noise and Vibration, existing vibration levels for20Caltrain's diesel service at 50 feet from the outermost track vary from 72 to 80 VdB, depending on21local site conditions and speed. This range would be representative of continued diesel operations22for Caltrain as well as predicted increases in cumulative diesel passenger rail operations for other23tenant railroads (ACE, Capitol Corridor, etc.). As presented in Table 3.11-5 in Section 3.11, Noise and24Vibration, existing vibration levels for freight at 100 feet from the outermost track vary from 73 to2581 VdB, which is considered representative for future freight service increases.
- These existing levels exceed FTA annoyance thresholds of 72 VdB for immediately adjacent
 residences and of 75 VdB for immediately adjacent institutional buildings, but none approach
 structural damage thresholds.

29 Blended Service Scenario (79 mph scenario)

30 As described in the Final EIS/EIR for the HSR Merced-Fresno segment, HSR projects typically 31 generate significantly fewer vibration impacts as compared with noise impacts (CHSRA 2012d). 32 Using FRA reference level of 83 VdB for 150 mph high-speed rail trains at 50 feet from track 33 centerlines (FRA 2012) and adjusting to a 79 mph speed, potential vibration levels are generically 34 estimated as 77 VdB which would be within the range of existing train vibration levels along the 35 corridor today. This estimate has not been adjusted for site trackage or soil conditions or any 36 potential track improvements that may come with Blended Service and thus may overestimate 37 actual vibration levels for HST trains. For example, for the HSR Merced – Fresno segment, vibration 38 levels for speeds up to 150 mph at 50 feet from the HSR track centerline were estimated as 39 approximately 72 VdB for (CHSRA 2012d). Based on the HSR Merced-Fresno vibration distance 40 curves and adjusting downward for 79 mph speeds, vibration levels could be 66 VdB instead if 41 similar vibration conditions (soil, trackage, etc.) were present along the Caltrain corridor as that 42 presumed for HSR for the Merced Fresno segment.

- 1 The additional cumulative diesel traffic (ACE, DRC, Capitol Corridor, Amtrak and freight) would not 2 increase vibration levels along the Caltrain ROW compared with existing conditions (which already 3 includes diesel freight and passenger rail operations). Over time, these services are likely to replace 4 their older equipment as it reaches the end of its design life and it is possible, but unknown, that 5 new equipment may be somewhat quieter than existing equipment.
- As noted in Section 3.11, *Noise and Vibration*, using FTA vibration reference levels (FTA 2006) for
 rapid transit trains (which FTA guidance recommends for electric commuter trains), vibration levels
 with Caltrain EMUs could be 73 Vdb at 50 feet from the outermost track at 50 mph. Adjusting to 79
 mph level, the vibration levels for the new Caltrain EMUs could be 77 VdB at 79 mph. This level is
 within the range of existing vibration levels along the Caltrain corridor noted above.
- Based on the information presented above, cumulative train service (including HSR, the Proposed
 Project, Caltrain Full Electrification, ACE, Capitol Corridor, DRC, Amtrak and freight) would not
 change the overall range of vibration levels along the Caltrain corridor.
- According to the FTA Noise and Vibration Manual (FTA 2006), in heavily used corridors, if the
- 15 existing train vibration exceeds the FTA annoyance impact criteria (as noted above), the project will
- 16 cause additional impact if the project significantly increases the number of vibration events defined
- 17 as approximately doubling the number of events. Thus, the analysis then examined whether the
- 18 increase in the number of cumulative vibration events is or is not significant.
- 19As noted in Table 4-8, if all the cumulative train service increases proposed would come to full20fruition, in 2040, the number of trains (including Blended Service) between Santa Clara and San21Francisco would more than double. Given the more than doubling of trains along the Santa Clara to22San Francisco segment of the Caltrain corridor, a potentially cumulative significant increase in the23number of vibration annoyance events for residential and institutional building receptors is24identified.
- 25 The number of trains between San Jose and Santa Clara using the Caltrain ROW itself would increase 26 by over 50 percent and between Tamien and Diridon by just under 50 percent under cumulative 27 2040 conditions, but these sections would not include HST operations since the HST would operate 28 on a dedicated separate track south of Santa Clara. Between Santa Clara and San Jose Diridon, HSR 29 would be on an aerial or in a tunnel. South of Diridon, HSR would be on an aerial structure to south 30 of Tamien Station, then on a mix of aerial and at-grade to Capitol Expressway. Where on aerial 31 structures, based on analysis in the HSR Merced-Fresno EIR/EIS (SCHRA 2012d), vibration levels 32 are much less that an at-grade section. Vibration from tunnels depends on soil conditions and tunnel 33 design and thus cannot be assessed at this time, but will be assessed by CHSRA for the Blended 34 Service environmental evaluation if a tunnel is used from San Jose to Santa Clara. For the at-grade 35 HSR segment south of the Tamien Station to Pullman Way where the HSR alignment is along the 36 Caltrain ROW, HSR vibration could also contribute additional vibration.
- Although HSR would operate on a separate dedicate<u>d</u> track south of Santa Clara, if one includes 80
 trains (one-way) per day and given the parallel alignment to the Caltrain ROW in some locations,
there is a possible doubling of vibration events, and potential cumulative vibration impacts are also
 identified south of Santa Clara.¹⁸

3 Blended Service Scenario (110 mph scenario)

In addition to train service level increases, HSR and Caltrain EMUs could operate at speeds up to 110
 mph with Blended Service.

6 Using FRA reference level of 83 VdB for 150 mph high-speed rail trains at 50 feet from track 7 centerlines (FRA 2012) and adjusting for 110 mph speeds, potential vibration levels for HSR trains 8 are generically estimated as 80 VdB. As noted above, this generic vibration level estimate has not 9 been adjusted for site trackage or soil conditions or any potential track improvements that may 10 come with Blended Service and thus may overestimate actual vibration levels for HST trains. For 11 example, for the HSR Merced – Fresno segment, vibration levels for speeds up to 150 mph at 50 feet 12 from the HSR track centerline were estimated as approximately 72 VdB for (CHSRA 2012d). Based 13 on the HSR Merced-Fresno vibration distance curves and adjusting downward for 110 mph speeds, vibration levels could be 69 VdB instead if similar vibration conditions (soil, trackage, etc.) were 14 15 present along the Caltrain corridor as that presumed for HSR in this segment.

- 16 Both the Merced to Fresno and Fresno to Bakersfield HST project-level environmental documents
- 17 identified significant vibration effects (related to exceedance of the annoyance thresholds, not
- structural damage) to a limited number of adjacent residences (close to the HST corridor) and
 included mitigation design measures that would be employed (options identified included increased
 maintenance, special trackwork, vehicle suspension design, track support systems, building
 modifications, trenches and buffer zones) (CHSRA 2012d, 2012e). However, since these segments
 are projected to operate at speeds in excess of 200 mph and Blended Service studied in this EIR is
- studied only up to 110 mph, the conclusions for much higher speeds in these prior studies are not
 considered representative for conditions for Blended Service for the Caltrain corridor.
- Based on the FTA Reference levels for rapid transit trains at 50 mph (FRA 2006) and adjusting for
 110 mph speeds, HSR EMUs could have vibration levels of 80 VdB at 50 feet from the outer track
- centerline which would be the same as the generic estimate for HSR trains described above and
 would be similarly at the top of the range of existing vibration levels along the corridor. This
 estimate also has not been adjusted for track improvements that will be necessary to operate at
 speeds up to 110 mph and thus may overestimate the actual value.
- Thus, at this time, it appears likely that Blended Service would not increase overall vibration levels
 compared with the range of vibration levels along the Caltrain corridor today and it is distinctly
 possible that vibration levels for Blended Service would be lower than the generic estimates
 presented above when specific trackage improvements required to allow 110 mph speeds are made
- 35 and when site-specific considerations are taken into account.
- 36 However, as noted above for the Blended Service 79 mph scenario, cumulative train events would
- 37 more than double between Santa Clara and San Francisco. Cumulative train events would also more
- 38 than double south of Santa Clara if including HST service on separate dedicated trackage where

¹⁸ Whether cumulative impacts would actually occur would depend on the specific design of tracks from south of Tamien Station to Santa Clara and the specific vibration characteristics of HSR trains and trackage. The identification of a potential cumulative vibration impact is preliminary and based on worst-case assumptions. As noted above, vibration levels for HST may be much lower than generic FTA reference level derived estimates and aerial structure vibration should be much less than at-grade segments.

- 1 along the Caltrain ROW. Thus, there is a potentially significant increase in annoyance due to
- cumulative vibration events for residents and institutional buildings immediately adjacent to the
 Caltrain ROW for the 2040 Blended Service 110 mph scenario.

4 Other Non-Rail Projects

5 Operation of the land developments would not likely have substantial effects on vibration levels due 6 to traffic generation involving light duty and passenger vehicles. Increased vibration along roadways 7 may occur in in locations in very close proximity to heavy-truck traffic but would not otherwise be 8 expected to be a significant impact. In addition, land development projects along the Caltrain ROW 9 would also introduce more sensitive receptors that would be subject to the cumulative vibration 10 levels resulting from increased passenger and rail service described above.

11 Proposed Project Cumulative Contribution

12 As discussed in Section 3.11, *Noise and Vibration*, the Proposed Project would not change existing 13 vibration levels along the Caltrain Corridor due to replacement of diesel trains with EMUs which, if 14 anything, would likely have less vibration than existing diesel-locomotive trainsets they replace. As 15 described in Section 3.11, Noise and Vibration, using FTA vibration reference levels (FTA 2006) for 16 rapid transit trains (which FTA guidance recommends for electric commuter trains), vibration levels 17 with EMUs could be 73 Vdb at 50 feet from the outermost track at 50 mph. Adjusting to 79 mph, the 18 vibration levels for the new EMUs could be 77 VdB at 50 feet which is in the middle of the range of 19 existing vibration levels along the Caltrain corridor noted above.

- As noted in Section 3.11, *Noise and Vibration*, the TPFs would not generate significant vibrations and
 thus would not contribute to any cumulative vibration impacts.
- 22 Although the Proposed Project would have vibration levels within the range of existing levels, the 23 Proposed Project would add 22 trains per day to the Santa Clara to San Francisco segment, which in 24 combination with cumulative rail increases (described above) would result in a more than doubling 25 of the train vibration events along this segment, which is considered a significant increase per the 26 FTA criteria. South of Santa Clara, cumulative train vibration event increases may also be significant 27 if including HST operations on separate dedicated track. Thus, the Proposed Project would have a 28 considerable contribution to a significant cumulative increase in train vibration effects for the 2040 29 Blended Service 79 mph scenario.
- 30 For the 2040 Blended Service 110 mph scenario, Caltrain EMUs with full electrification would have
- 31 vibration levels within the range of existing vibration levels along the Caltrain corridor and thus
- 32 would not increase vibration levels. However, similar to the conclusion for the 2040 Blended Service
- 33 110 mph scenario, the Proposed Project and Caltrain Full Electrification would contribute to a
- 34 significant increase number of train vibration events along the corridor.
- Potential vibration reduction measures identified in prior environmental evaluations for the high speed rail system are noted in Table 4-14.

Mitigation Procedure	Location of Mitigation	Description
Location and Design of Special Trackwork	Source	Careful review of crossover and turnout locations during the preliminary engineering stage. When feasible, relocate special trackwork to a less vibration-sensitive area. Installation of spring frogs eliminates gaps at crossovers and helps reduce vibration levels.
Vehicle Suspension	Source	Rail vehicle should have low unsprung weight, soft primary suspension, minimum metal-on-metal contact between moving parts of the truck, and smooth wheels that are perfectly round.
Special Track Support Systems	Source	Floating slabs, resiliently supported ties, high resilience fasteners and ballast mats all help reduce vibration levels from track support system (see further discussion of track support options in Appendix C, <i>Noise and Vibration Technical Report</i>).
Building Modifications	Receiver	For existing buildings, if vibration-sensitive equipment is affected by train vibration, the floor upon which the vibration-sensitive equipment is located could be stiffened and isolated from the remainder of the building. For new buildings, the building foundation should be supported by elastomer pads similar to bridge bearing pads.
Trenches	Along Vibration Propagation Path	A trench can be an effective vibration barrier if it changes the propagation characteristics of the soil. It can be open or solid. Open trenches can be filled with materials such as styrofoam. Solid barriers can be constructed with sheet piling, rows of drilled shafts filled with either concrete or a mixture of soil and lime, or concrete poured into a trench.
Buffer Zones	Receiver	Negotiate a vibration easement from the affected property owners or expand rail right-of-way.
Source: CHSRA 2012d		

1Table 4-14. Potential Vibration Mitigation Procedures and Descriptions from the CHSRA Merced to2Fresno EIS/EIR

3

4

5

6

7

8

Unlike the proposed Merced-Fresno HSR segment, the Caltrain corridor is an existing rail system and, thus, the applicability of these options to the Caltrain corridor will vary as discussed below:

- Location and Design of Special Trackwork: Relocation of existing special trackwork is not applicable to the Caltrain corridor because the locations of the existing crossovers and turnouts are determined by the existing track configuration.
- 9 Special Track Support Systems: These systems could be applied to the Caltrain corridor if
 10 needed, but these options are significant capital projects and funding would need to be secured.
- Vehicle Suspension: The vehicle suspension measure described in Table 4-14 is for high-speed
 rail vehicles only.
- Building Modifications: The building modification measure is feasible for the Caltrain corridor
 where needed.
- Trenches: As described in Appendix C, *Noise and Vibration Technical Report*, this is an
 experimental method and there are several major issues that must be overcome, including

- 1 structural concerns and the need for up to 60 feet of area adjacent to the tracks that would raise 2 substantial ROW concerns along the constrained Caltrain ROW. Further, as of the time of this 3 Draft EIR (February 2014), WIA is not aware of any successful installations in North America.
- 4 Buffer Zones: The applicability of the buffer zone option will need a site-specific assessment. • 5 There is a built environment generally up to the Caltrain ROW and buffer zones could be 6 disruptive to the existing environment in constrained locations.
- 7 While some of the measures in Table 4-14 are not applicable to the Caltrain corridor, as discussed 8 above, given the range of options available, there are feasible means to reduce the cumulative 9 vibration impacts. Thus, Mitigation Measure NOI-CUMUL-2 would help to reduce the Proposed 10 Project's contribution to a less-than-significant level.
- 11 Given the preliminary state of design for the Blended Service improvements, the specific vibration 12 treatments that may be necessary have not been identified at this time. Depending on the measures 13 actually proposed, there may be secondary physical impacts due to their construction, but these 14 impacts should be limited to the Caltrain ROW and the area of any passing tracks (if outside the 15 Caltrain ROW). Evaluation of potential secondary physical impact of track or other improvements necessary to address significant Blended Service vibration effects should be included in the separate 16 17 environmental evaluation of Blended Service by CHSRA.

18 Mitigation Measure NOI-CUMUL-2: Conduct project-level vibration analysis for Blended 19 System operations and implement vibration reduction measures as necessary and 20 appropriate for the Caltrain corridor

- 21 As noted above, the vibration analysis in this document uses worst-case assumptions. A project-22 level vibration analysis will be completed by CHSRA for both the San Jose to Merced segment 23 and the Blended Service segment north of San Jose. If subsequent environmental evaluation by 24 CHSRA shows that significant cumulative increases in vibration would not occur along the 25 Caltrain ROW when considering the specific track improvements and HSR and Caltrain EMU 26 design, then this mitigation would not be required or may only be required in certain locations.
- 27 A significant cumulative impact would only occur when the number of vibration events 28 approaches a doubling of existing conditions. These measures are only necessary to be in place 29 by the time Blended Service operates on the Caltrain corridor north of Santa Clara or when HSR 30 operates on dedicated track south of Santa Clara (to 2 miles south of Tamien Station).
- 31 Based on the 2014 Business Plan, the earliest date for HSR blended service operations on the 32 Caltrain corridor north of Santa Clara and south of Santa Clara on dedicated track would be 33 2026. Caltrain will coordinate with CHSRA during the subsequent environmental process for 34 blended service to examine the actual potential for significant cumulative vibration impacts to 35 actually occur and the need for mitigation.
- 36 If necessary If the subsequent environmental evaluation shows significant cumulative vibration 37 impacts taking into account the specific blended service track improvements, the JPB, in 38 cooperation with CHSRA and other rail operators will support incremental train vibration 39 reduction measures along the Caltrain ROW. Caltrain will work with CHSRA and other rail 40 operators to establish priorities for vibration reduction measure to be implemented as funding 41 becomes available. The timing for any necessary improvements should be combined with 42
- blended service track improvements and should occur prior to a doubling of vibration events

- Based on the 2014 Business Plan, HSR operations would commence in 2026 which would
 double the vibration events and thus mitigation should be in place at that time.
- Potential vibration reduction measures could include, but are not limited to, special track
 support systems, vehicle suspension (HSR vehicles only), building modifications, trenches (if
 feasible), and buffer zones.

6 The costs for implementing the phased program should be borne by all rail operators in 7 proportion to their contributions to increased vibration events and/or levels. Given that there 8 are multiple contributors to cumulative rail vibration events, the JPB is only responsible to fund 9 its fair share for necessary vibration reduction measures with other rail services responsible to 10 fund their fair share as well. However, if there is no governmental approval that triggers an 11 obligation to share such costs, it may be impossible to require other railroads to pay their fair-12 share. Fair-share shall be determined by the vibration train event increases over existing 13 conditions (2013).

14 **4.1.4.13 Population and Housing**

15 Impact CUMUL-12-POP: Cumulative impact to population and housing

As discussed in Section 3.12, *Population and Housing*, the Proposed Project would not have any
 impacts on population or housing during construction or operations; therefore, the Proposed
 Project would not contribute to housing and population impacts in the three counties.

19**4.1.4.14Public Services and Utilities**

20 Impact CUMUL-13-PSU: Cumulative impacts related public services and utilities

The geographic context for the analysis of cumulative construction impacts to public services and utilities is the Caltrain ROW and adjacent areas. The geographic context for the cumulative analysis of operation-related public services and utilities impacts includes the service areas of regional utilities and service providers to the project sites. For construction disruption to utilities and public services, only the cumulative projects in Table 4-3 are included in the analysis. For operational impacts to utilities and public services, the general growth projections summarized in Table 4-2 were used.

- Public services are defined to include schools, fire protection, police protection, wastewater
 treatment or other such public facilities. Utilities are defined to include water supply, electrical
 supply, and natural gas supply which are typically provided by utility agencies or companies.
 Landfill capacity is separately addressed
- 31 Landfill capacity is separately addressed.
- For construction, the analysis addressed potential for utility disruption, temporary public service
 demands and impacts to landfill capacity. For operations, the analysis addresses operational public
 service and utility demands relative to the potential need for new public service facilities and utility
 infrastructure as well as operational impacts to landfill capacity.
- Impacts regarding emergency response times are addressed separately above in the discussion of
 Hazards and Hazardous Materials.

1 **Construction**

2 **Disruption to utilities**

During construction, cumulative projects could disrupt utility service systems in a planned or
 unplanned manner. Standard construction practices and regulations require construction
 contractors to identify and avoid unplanned disruptions to utilities and to work with utility owners
 to coordinate construction to avoid damage and utility outages. However, there would remain a
 small potential for multiple utility disruptions due to construction activities resultant from
 cumulative projects that occur at the same time.

9 As discussed in Section 3.13, *Public Services and Utilities*, earth moving activities for the installation

- 10 of the OCS poles, and TPFs could temporarily disrupt utility service systems. However, with the
- 11 implementation of Mitigation Measures PSU-8a, PSU-8b, and PSU-8c, which require JPB coordination
- 12 with all utility providers, adjustment of OCS pole locations (as necessary to minimize utility
- 13 conflicts), and scheduling and notification requirements, the Proposed Project would minimize
- 14 potential disruptions to utilities and thus would make a less than considerable contribution to any
- 15 potential cumulative impacts during construction.

16 **Public Services**

- 17 During the construction of cumulative projects, there could be a temporary distributed increased 18 demand for public services across the San Francisco Peninsula. However, the region already 19 accommodates substantial construction projects across the entire Peninsula and the overall level of 20 construction, considered on a regional scale, is not expected to substantially change with the 21 cumulative projects compared with existing conditions. Therefore, the overall change in demand in 22 public services is not expected to result in the need for new or physically altered public facilities 23 and, thus, result in any potential secondary environmental impacts associated with construction of 24 new public facilities.
- As discussed in Section 3.13, *Public Services and Utilities*, because the Proposed Project would
 neither directly displace public facilities nor result in substantial changes in local population and
 demand for public services, construction of the Proposed Project would make a less-than considerable contribution to any potential cumulative impacts on public services and facilities
 during construction.

30 Landfill Capacity

- Construction of the cumulative projects would generate solid waste. Construction waste would include soils from grading and excavating activities, construction and demolition material, and other solid waste. Cumulative growth in the region will also result in increased solid waste generation. As explained in the EIR for *Plan Bay Area* (MTC/ABAG 2013b), all but four of the 17 landfills in the San Francisco Bay Area have an estimated closure date before the year 2040 and it is unlikely the four remaining landfills can handle the region's solid waste disposal. As a result, construction of cumulative projects would contribute to the reducing capacity of regional landfills over time.
- As described in Section 3.13, *Public Service and Utilities*, the only solid waste expected to result from
 project construction would be soil resulting from grading and excavation associated with
 construction of TPFs and OCS foundations as well as general packaging and other materials
- 41 associated with construction materials and construction workers. Any uncontaminated soil that is
- 42 not reused onsite would be recycled in accordance with the various state and local ordinances

- 1 governing recycling. Contaminated soil would be disposed at facilities approved to receive such soil,
- 2 as discussed in Section 3.8, *Hazards and Hazardous Materials*. While there are long-term concerns
- 3 for landfill capacity by 2040, as explained in the EIR for *Plan Bay Area* (MTC/ABAG 2013b), 12 of the
- 4 current 17 major landfills in the Bay Area will still be open through <u>2020</u> 2019, including the
- 5 Guadalupe Sanitary landfill and Kirby Canyon Landfill (both in Santa Clara County). Other
- 6 construction waste is expected to minimal and readily handled by existing landfill facilities in the 7 region, which have ample remaining capacity for such material in the aggregate. Thus, while long-
- 8 term growth in the region will require the construction of additional landfill by 2040 to
- 9 accommodate future solid waste, the Proposed Project's contribution to any cumulative impacts on
- 10 landfill capacity would be less than considerable.

11 **Operation**

12 Demand for Additional Utility Infrastructure

13 Operation of cumulative projects could increase demands for additional utility infrastructure 14 including water supply, electrical supply and natural gas supply. New transportation projects, 15 including Blended Service, BART Silicon Valley extension, and extension of light-rail systems would 16 increase cumulative demand for electricity. Land use projects and general regional growth will 17 increase water, electricity, and natural gas demands. The cumulative demands for utility service 18 could result in the need for additional utility infrastructure including electricity generation plants 19 and transmission facilities, development of additional water supplies and distribution infrastructure 20 as well as additional natural gas supply and transmission. Depending on where the new 21 infrastructure is required, this could result in significant impacts on the environment during 22 construction of such new facilities.

23 As discussed in Section 3.13, Public Services and Utilities, the Proposed Project will require the 24 relocation of some existing utilities crossing the Caltrain ROW or along the location of the ductbanks 25 connecting the TPSs to the Caltrain ROW and will also require construction of electrical 26 transmission connections from PG&E substations to the two TPSs. The relocation of these utilities or 27 the construction of electrical transmission connections could result in secondary environmental 28 impacts. At this time, the Proposed Project is not expected to result in the need for additional PG&E 29 power generation or transmission facilities upstream of the local substations that would connect to 30 the TPSs. Thus, the Proposed Project could contribute to cumulative demands for new utility 31 infrastructure relative to the local utility relocations and the local transmission facility extensions. 32 Under Mitigation Measure PSU-9, the JPB will work with utility owners and local jurisdictions to 33 apply the relevant applicable mitigation identified for construction of the Proposed Project when 34 conducting local utility relocations or local transmission line extensions made necessary by the 35 Proposed Project. With this mitigation, the Proposed Project would make a less-than-considerable

36 contribution to any potential cumulatively significant utility infrastructure demands.

37 Public Services

38 Operation of cumulative projects could increase demands for additional public services including

- 39 fire, police, schools and other public facilities. New transportation projects, including Blended
- 40 Service, BART Silicon Valley extension, and extension of light-rail systems would increase
- 41 cumulative demand for electricity. Land use projects and general regional growth will increase
- 42 demands for fire, police, schools and other local public community facilities. The cumulative
- 43 demands for public service could result in the need for additional public service facilities including

- 1 new police stations, fire stations, schools, or other public community facilities. Depending on where
- the new facilities are proposed, this could result in significant impacts on the environment during
 construction and operation of new public facilities.
- 4 As discussed in Section 3.13, *Public Services and Utilities*, the Proposed Project is not expected to
- 5 result in increased demand for police, fire, school, or other public facilities compared with existing
- 6 conditions because the Proposed Project would not result in population growth and would not
- 7 fundamentally change conditions of the Caltrain ROW in a way that increases demand for public
- 8 services. For these reasons, the contribution of the Proposed Project to any potential cumulatively
 9 significant on public service demands that might result in the need for construction of additional
- 10 public service facilities would be less than considerable.

11 Landfill Capacity

- General growth in the region would generate additional solid waste. As noted above, only a few
 (four) of the existing landfills have a closure before 2040 and it is unlikely these four can handle the
 region's solid waste disposal in 2040. As a result, cumulative project operations would contribute to
 reducing capacity of regional landfills over time.
- 16 Operation of cumulative transportation projects would have a limited increase in the demand for
- 17 landfill capacity because they generally do not generate large amount of solid waste overall.
- 18 However, operation of the cumulative land use developments would generate solid waste. Over
- 19 time, combined with general regional growth, there will be a need for new landfills, the construction
- 20 of which might result in significant environmental impacts.
- 21 As discussed in Section 3.13, Public Services and Utilities, with the Proposed Project, normal EMU 22 operations would not result in substantial new generation of solid waste above that associated with 23 servicing of diesel locomotives today. Similarly, maintenance of the OCS and TPFs would not involve 24 the generation of large amounts of solid waste. There would be a minor increase in solid waste 25 production associated with the Proposed Project from increased ridership (e.g., disposable coffee 26 cups, newspaper) but the volumes of waste would not be substantial relative to landfill capacity. 27 Therefore, Proposed Project operations would result in a less-than-significant solid waste 28 generation and would make a less-than-considerable contribution to any potential cumulatively impacts on landfill capacity. 29

30 **4.1.4.15** Transportation/Traffic

31 Impact CUMUL-14-TRA: Cumulative effects to transportation and traffic

- The geographic context for the analysis of cumulative construction and operation-related public varies by subject area. For construction disruption, the geographic area is the Caltrain ROW and vicinity. For operational impacts to traffic level of service, and bicycle and pedestrian facilities, the geographic focus of the analysis is the roadways/intersections at the at-grade crossings and near Caltrain stations. For regional impacts to traffic and transit systems, the geographic area is the San
- 37 Francisco Peninsula.
- 38 For construction disruption to transportation and traffic, only the cumulative projects in Table 4-3
- 39 are included in the analysis. For operational impacts to transportation and traffic, the general
- 40 growth projections summarized in Table 4-2 were used in combination with assumptions about

cumulative transportation improvements (see Appendix I, *Ridership Technical Memorandum*) to
 drive ridership, traffic modeling analysis, and other operational impact analysis.

3 Construction

4 Disruption of transportation facilities and systems

5 During construction, cumulative projects could disrupt roadway, transit, pedestrian, bicycle, parking 6 or access facilities in a planned or unplanned manner. Standard construction practices and 7 regulations require construction contractors to identify, avoid, and minimize unplanned disruptions 8 to transportation facilities and system and work with public works departments, transportation 9 agencies, and system operators to coordinate construction to avoid substantial delays or disruption 10 in access, service and travel.

11 Rail, transit, and vehicle access and movement could be disrupted during construction of Blended 12 Service station improvements, passing tracks, and other facilities (such as grade separations, if 13 proposed). Construction of the maintenance yard may also result in such disruption, although 14 disruptions at the previously studied Bayshore/Brisbane location would likely be minimal given the 15 lack of active use at the site at present (this would change if the site or the environs are developed as 16 proposed in the Brisbane Baylands project). Disruption will depend on the location. Construction of 17 the passing tracks could have the most substantial temporary disruptions to roadways, pedestrian, 18 and bike lanes that cross the Caltrain ROW.

Construction of other transportation projects could also result in disruptions to existing roadway,
 bicycle, pedestrian facilities as well as access depending on their routing and present transportation
 facilities. For other non-transportation cumulative projects, there is usually less potential for
 substantial disruption to transportation systems and facilities, except when existing facilities are
 proposed for temporary closure or rerouting during construction although temporary delays are
 always possible during delivery of large materials and construction of utility connections in local
 roadways.

26 As discussed in Section 3.14, Transportation and Traffic, with the Proposed Project, installation of 27 the OCS poles and construction of the TPFs would not generally disrupt existing transportation 28 systems or transit operations except in limited circumstances. However, construction at the at-grade 29 crossings to install OCS infrastructure and to update grade crossing warning devices would result in 30 temporary roadway closures (as well as bike and pedestrian crossings where present). Where OCS 31 infrastructure needs to be installed near other transit systems, such as at the Millbrae Station shared 32 by Caltrain and BART or in San Francisco at 16th Street where Muni plans to install Muni OCS 33 infrastructure for the re-routing of the 22-Fillmore Trolley Bus¹⁹, there is the potential for 34 temporary disruption of other transit systems. There is also the potential to disrupt freight service 35 operations during construction. Caltrain will coordinate with all affected transit operations to avoid 36 and minimize the duration and extent of any potential disruption. With the implementation of 37 mitigation measures identified in Section 3.14, *Transportation and Traffic*, the Proposed Project 38 would minimize potential disruptions to transportation facilities and transit services. Thus, with 39 mitigation, Proposed Project construction would make a less-than-considerable contribution to any 40 potential cumulative impacts on transportation facilities and systems.

¹⁹ See discussion below under Operations about proposed mitigation to allow simultaneous operations of the Caltrain 25 KVA AC OCS and the Muni 600 V DC OCS at the 16th Street crossing.

1 Emergency Vehicle Access

2 During cumulative project construction, there may be temporary obstruction of access and egress

- from construction sites and on adjacent roads due to construction. Such obstruction would affect the
 ability of emergency responders to timely reach their response destinations and/or impede the
 ability to evacuate constrained areas in the event of an emergency. Where one or more cumulative
 projects would be in construction at the same time in the same area, it is possible there could be
 cumulative impacts on emergency response or evacuation capacity.
- 8 As discussed in Section 3.8, Hazards and Hazardous Materials, the Proposed Project could have also 9 have such effects if emergency occurs at the time when the Proposed Project construction may 10 involve temporary access or egress limitations from the Caltrain ROW or at at-grade crossings along 11 the Caltrain ROW (when changing grade-crossing warning devices). As described in Section 3.14, 12 *Transportation and Traffic*, project mitigation measures will require the preparation of a traffic 13 control plan to help ensure continued emergency access to Caltrain ROW, at-grade crossings, and all 14 nearby properties. Caltrain will coordinate with local public works department, local emergency 15 providers, and Caltrans in the development of the traffic control plan to specifically address 16 emergency response concerns. Any potential issues associated with multiple projects in 17 construction at the same time can be addressed through development of the traffic control plan. 18 Thus, with mitigation, the Proposed Project's contribution to a potential cumulative impact related
- 19 to emergency response or evacuation would be less than considerable).

20 **Operation**

21 **Roadway Traffic Operations**

22 Regional and City Vehicle Miles Traveled

23 As presented in Appendix I, Ridership Technical Memorandum, regional growth will result in a 24 substantial increase in VMT even with the improvements in transit systems currently programmed 25 for the future, including the Proposed Project. However, compared with No Project conditions, the 26 Proposed Project will result in a substantial reduction in regional VMT of 235,000 miles per day in 27 2020. With full electrification and the Downtown Extension, the reduction in regional VMT in 2040 would be 619,000 miles per day as shown in Table 4-15. Thus, the Proposed Project would have a 28 29 beneficial regional effect on vehicle traffic by providing such a substantial reduction in regional 30 traffic.

31 Table 4-15. Average Regional Daily Vehicle Miles of Traveled

		Vehicle Miles of Trave	eled
Scenario	Peak Hours	Off-Peak Hours	Daily Total
Existing Condition	<u>96,260,000</u>	<u>82,401,000</u>	<u>178.660.000</u>
2040 No Project	120,676, <u>500</u>	105,846, <u>300</u>	226,522, <u>800</u>
2040 Project	120,159, <u>200</u>	105,744, <u>700</u>	225,903 <u>,900</u>

³²

Table 4-16 displays daily VMT within each city in the project area for 2040 No Project and Project

scenarios. City-level VMT is calculated by accounting for the total mileage of all vehicle trips that
 occur within each city's boundaries, which known as the "boundary method" calculation.

Peninsula Corridor Electrification Project EIR

- 1 In 2040, daily VMT in nearly cities would also be lower under the 2040 Project scenario than 2040
- 2 No Project scenario. The only exception is the City of San Mateo which would experience a very
- 3 small increase in VMT due to the Proposed Project, likely attributable to slight increases in
- 4 automobile traffic coming to and from San Mateo, Hayward Park and Hillsdale Stations. Total daily
- 5 VMT under the 2040 Project scenario is projected to decrease by an average of 0.7 percent in all
- 6 cities along the corridor compared with the 2040 No Project scenario.

7 Table 4-16. Weekday Daily Regional Vehicle Miles Traveled Within Each City, 2040 Scenario

	2	040 No Projec	t		2040 Project			
City	Peak ^a	Off-Peak ^b	All	Peak ^a	Off-Peak ^b	All		
San Francisco	4,676,000	3,931,000	8,607,000	4,625,000	3,919,000	8,544,000		
<u>Brisbane</u>	<u>492,000</u>	<u>464,000</u>	<u>956,000</u>	<u>486,000</u>	<u>460,000</u>	<u>946,000</u>		
South San Francisco	824,000	662,000	1,487,000	813,000	659,000	1,472,000		
San Bruno	587,000	415,000	1,003,000	576,000	414,000	989,000		
Millbrae	248,000	183,000	431,000	242,000	182,000	424,000		
Burlingame	609,000	529,000	1,138,000	596,000	526,000	1,122,000		
San Mateo	1,476,000	1,298,000	2,774,000	1,482,000	1,293,000	2,775,000		
Belmont	185,000	126,000	311,000	182,000	125,000	307,000		
San Carlos	383,000	315,000	698,000	377,000	314,000	690,000		
Redwood City	866,000	779,000	1,645,000	853,000	776,000	1,630,000		
Atherton	90,000	49,000	139,000	87,000	49,000	136,000		
Menlo Park	716,000	660,000	1,376,000	705,000	658,000	1,362,000		
Palo Alto	947,000	751,000	1,698,000	926,000	749,000	1,675,000		
Mountain View	1,157,000	953,000	2,110,000	1,137,000	951,000	2,088,000		
Sunnyvale	1,601,000	1,226,000	2,827,000	1,577,000	1,223,000	2,800,000		
Santa Clara	1,545,000	928,000	2,473,000	1,526,000	927,000	2,454,000		
San Jose	11,024,000	8,814,000	19,838,000	10,953,000	8,812,000	19,765,000		
TOTAL	27,426,000	22,083,000	49,511,000	27,143,000	22,037,000	49,179,000		

Source: Appendix D, Transportation Analysis.

^a Peak travel is defined as travel occurring from 5:00 a.m. to 9:00 a.m. and from 3:00 p.m. to 7:00 p.m.

^b Off-peak travel is defined as travel occurring from 9:00 a.m. to 3:00 p.m. and from 7:00 p.m. to 5:00 a.m.

8

While certain locations on the Caltrain corridor may experience increases in traffic due to more
 automobiles driving to and from stations, the total effect is that total vehicle miles in all cities other
 than San Mateo would decrease due to the Proposed Project.

12 Intersection level of Service - 2040

13 As discussed in Section 3.14, *Transportation and Traffic*, the Proposed Project would result in an

14 adverse effect at some localized intersections near at-grade crossings and Caltrain stations. The

15 cumulative effect of growth in the area combined with cumulative transportation improvements

16 included in the ridership model (see Appendix I), and the Proposed Project on traffic near at-grade

17 crossings and Caltrain stations was evaluated using traffic modeling (see Appendix D). As shown in

18 Table 4-17, compared with existing conditions, there are 39 study locations (out of 8291 total study

19 locations) where there will be significant cumulative increase in local traffic delays.

Table 4-17. Intersection Delay and Levels of Service, 2040 Cumulative Conditions with and Without the Project Alternatives

Changes since the Draft EIR are shown in italics given that underlining is used as part of the significance
 indication.

					204	0 No			
Int.			Peak	Intersection	Pro	oject	2040	Project	Change
ID	Intersection	Jurisdiction	Hour	Control	Delay	LOS	Delay	LOS	In Delay
	ZONE 1								
<u>1</u>	4th Street & King Street	SF	AM	Signal	>120	F	<u>>120</u>	<u>F</u>	<u>36.7</u>
			PM		>120	F	>120	F	-10.3
2	4th Street & Townsend	SF	AM	Signal	>120	F	>120	F	-20.3
	Street		PM		>120	F	>120	F	-0.3
3	Mission Bay Drive & 7th	SF	AM	Signal	12.5	В	16.6	В	4.1
	Street		PM	-	16.2	В	17.0	В	0.8
4	Mission Bay Drive &	SF	AM	Signal	3.7	А	2.1	А	-1.6
	Berry Street		PM	C	8.8	А	8.6	А	-0.2
5	7th Street & 16th Street	SF	AM	Signal	>120	F	>120	F	14.2
_			PM	0	119.9	F	>120	F	14.4
6	16th Street & Owens	SF	AM	Signal	11.3	В	10.6	В	-0.7
_	Street		PM	0	40.2	D	55.8	Е	15.6
7	22nd Street &	SF	AM	All-way Stop	13.5	В	14.2	В	0.7
	Pennsylvania Street		PM		9.6	А	11.2	В	1.6
8	22nd Street & Indiana	SF	AM	All-way Stop	7.4	А	7.1	А	-0.3
	Street		PM	5 I	6.4	А	6.4	А	0.0
9	Tunnel Avenue &	SF	AM	All-way Stop	>120	F	>120	F	<u>>60</u>
_	Blanken Avenue		PM	5 I	>120	F	>120	F	>60
10	Linden Avenue & Dollar	SSF	AM	Signal	81.8	F	>120	F	>60
	Avenue		PM	0	41.6	D	46.1	D	4.5
11	East Gr & Avenue &	SSF	AM	Signal	12.4	В	13.2	В	0.8
	Dubuque Way		PM		13.8	В	15.1	В	1.3
12	S Linden Avenue & San	SSF	AM	Signal	27.9	С	74.9	Е	47.0
	Mateo Avenue		PM		10.6	В	13.4	В	2.8
13	Scott Street & Herman	SB	AM	Side-Street	26.3	D	45.9	Е	19.6 ^a
	Street	55	PM	Stop	18.2	C	18.4	Ċ	0.2
14	Scott Street &	SB	AM	Side-Street	7.2	А	8.8	А	1.6
	Montgomery Avenue	02	PM	Stop	7.1	A	6.8	A	-0.3
15	San Mateo Avenue &	SB	AM	Signal	33.3	C	40.7	D	7.4
	San Bruno Avenue	55	PM	5-5-141	24.6	C	32.5	C	7.9

T .				T	2040 Pro	0 No ject	2040	Project	Change
Int. ID	Intersection	Iurisdiction	Реак Hour	Control	Delav		Delav	LOS	In Delay
	ZONE 2	Juitourouon	noui	00110101	Derug	100	Doraj	200	
<u>16</u>	El Camino Real & Millbrae Avenue	MB	AM PM	Signal	112.0 68.5	F E	<u>>120</u> <u>84.7</u>	<u>F</u> <u>F</u>	<u>11.1</u> <u>16.2</u>
<u>17</u>	Millbrae Avenue & Rollins Road	MB	AM PM	Signal	74.9 110.2	E F	<u>84.4</u> >120	<u>F</u> <u>F</u>	<u>9.5</u> 29.3
18	California Drive & Broadway	BG	AM PM	Signal	<u>154.1</u> <u>170.3</u>	<u>F</u> <u>F</u>	<u>138.5</u> <u>160.4</u>	<u>F</u> <u>F</u>	<u>-15.6</u> <u>-9.9</u>
<u>19</u>	Carolan Avenue & Broadway	BG	AM PM	Signal	<u>101.5</u> <u>92.4</u>	<u>F</u> <u>F</u>	<u>112.5</u> <u>97.4</u>	<u>F</u> <u>F</u>	<u>11.0</u> <u>5.0</u>
<u>20</u>	California Drive & Oak Grove Avenue	BG	AM PM	Signal	>120 76.9	F E	91.2 <u>99.1</u>	F <u>F</u>	-34.1 22.2
<u>21</u>	Carolan Avenue & Oak Grove Avenue	BG	AM PM	Side-Street Stop	>120 >120	F F	<u>>120</u> >120	<u>F</u> <u>F</u>	<u>>60</u> >60
22	California Drive & North Lane	BG	AM PM	Side-Street Stop	28.4 18.4	D C	20.4 21.4	C C	-8.0 3.0
23	Carolan Avenue & North Lane	BG	AM PM	Side-Street Stop	> 120 43.7	F E	>120 69.4	F F	>-60 25.7ª
24	Anita Road & Peninsula Avenue	BG	AM PM	Side-Street Stop	29.1 67.6	D F	31.9 36.1	D E	28 -31.5
<u>83</u>	<u>Broadway and Rollins</u> <u>Road</u>	<u>BG</u>	<u>AM</u> PM	<u>Signal</u>	<u>61.0</u> 57.5	<u>E</u> F	<u>64.5</u> 58.9	<u>E</u> F	<u>3.5</u> 1.4
<u>84</u>	<u>Rollins Road and</u> Cadillac Way	<u>BG</u>	<u>AM</u> PM	<u>Signal</u>	<u>9.0</u> 10.8	<u>–</u> <u>A</u> A	<u>11.3</u> 8.0	<u>–</u> <u>B</u> A	<u>2.3</u> -2.8
<u>84a</u>	Broadway and US 101 Southbound Ramps	<u>BG</u>	<u>AM</u> PM	<u>Signal</u>	<u>85.5</u> 48.8	<u>F</u> D	<u>88.1</u> 51.1	<u>F</u> D	<u>2.6</u> 2.3
<u>85</u>	<u>Bayswater Avenue and</u> California Drive	<u>BG</u>	<u>AM</u> PM	<u>Signal</u>	<u>44.7</u> 20.3	<u>D</u> C	<u>26.7</u> 23.1	<u></u> C	<u>-18.0</u> 2.8
25	Woodside Way & Villa Terrace	SM	AM PM	Side-Street Stop	5.1 5.5	A A	5.0 5.3	A A	-0.1
26	North San Mateo Drive & Villa Terrace	SM	AM PM	Side-Street Stop	12.2 17.2	B C	11.8 10.2	B B	-0.2
27	Railroad Avenue & 1st Avenue	SM	AM PM	Side-Street Stop	>120 >120	F F	15.0 >120	В F	>-60
<u>28</u>	S B Street & 1st Avenue	SM	AM PM	Signal	48.4 66.9	D F	20.7 >120	C F	-27.7 193 2
29	9th Avenue & S Railroad Avenue	SM	AM PM	Side-Street Stop	>120 >120	F F	>120 91.6	F F	<u>>60</u>
<u>30</u>	S B Street & 9th Avenue	SM	AM PM	Signal	34.3 51.5	C D	<u>67.7</u> 69.3	<u>E</u> E	<u>33.4</u>
31	Transit Center Way & 1st Avenue	SM	AM PM	Uncontrolled	49.0 88.2	F F	9.2 69.3	A F	-39.8 -18.9

					204) No	2040	Droioat	Change
Int. ID	Intersection	Iurisdiction	Peak Hour	Intersection	Delay		Delay		In Delay
32	Concar Drive & SR 92	SM	ΔΜ	Signal	20.8	LU3 C	25.3	LU3 D	14 5
52	Westbound Ramps	5141	PM	Signal	13.4	В	12.3	B	-1.1
33	S Delaware Street & E	SM	AM	Signal	55.7	Е	25.6	С	-30.1
	25th Avenue		PM	8	>120	F	>120	F	-5.3
34	E 25th Avenue & El	SM	AM	Signal	84.4	F	63.4	E	-21.0
	Camino Real		PM		>120	F	>120	F	-0.3
<u>35</u>	31st Avenue & El	SM	AM	Signal	77.7	E	32.6	C	-45.1
		0.4	PM		11/./	r	<u>>120</u>	<u>1</u>	<u>19.0</u>
<u>36</u>	E Hillsdale Boulevard &	SM	AM	Signal	<u>>120</u> 02.0	F F	45.6 >120	D F	<u>>-60</u>
27	E Uilladala Dirid 8	CM		Ci ave a l	<u>92.0</u>	F	225	<u> </u>	<u>>00</u>
<u>37</u>	Curtiss Street	2141	PM	Signal	55.0 66.7	E	>120	С F	-33.1 48 5
28	Paningula Avenue &	SM		Side-Street	22.0	 	24.3	<u>-</u> C	<u>40.5</u> 23
30	Arundel Road & Woodside Way	3141	PM	Stop	47.4	E	30.2	D	-17.2
<u>39</u>	El Camino Real &	BL	AM	Signal	>120	F	<u>>120</u>	<u>F</u>	<u>41.4</u>
	Ralston Avenue		PM		>120	F	>120	F	0.2
40	El Camino Real & San	SC	AM	Signal	20.0	В	24.5	С	4.5
	Carlos Avenue		PM		46.1	D	46.9	D	0.8
41	Maple Street & Main	RC	AM	Side-Street	42.7	E	22.2	C	-20.5
	Street ^b		PM	Stop	>120	F	>120	F	>60
42	Main Street & Beech	RC	AM	Side-Street	19.7	С	15.0	В	4.7
	Street		PM	Stop	>120	ľ	>120	F	>-60 <u>.0</u>
43	Main Street & Middlefield Readb	RC	AM	Signal	30.3	C	>120	F	>60.0
		Da	PM		>120	Г	>120	г	-1.6
44	Broadway Street &	RC	AM	Side-Street	>120	F F	>120	F	>-60.0
45		DC	PM	Stop	>120	r F	>120	r F	>-60.0
<u>45</u>	Whipple Avenue	KU	AM PM	Signal	/1./	E	<u>109.2</u> 88.3	r F	<u>3/.5</u>
16	Armallo Stroot &	DC		Signal	×120	F	00.5	L E	5.5 > 60.0
40	Brewster Avenue ^b	N.	PM	Sigilai	115.9	г F	112.1	г F	-3.8
47	El Camino Real &	RC	AM	Signal	>120	F	>120	F	-3.0
17	Broadway Street ^b	no	PM	orginal	>120	F	>120	F	1.3
48	Arguello Street &	RC	AM	Signal	>120	F	>120	F	>-60.0
	Marshall Street ^b		PM		>120	F	>120	F	14.1
49	El Camino Real & James	RC	AM	Signal	>120	F	>120	F	-22.8
	Avenue ^b		PM		>120	F	>120	F	4.6
	ZONE 3								
<u>50</u>	El Camino Real & Fair	AT	AM	Signal	>120	F	<u>>120</u>	<u>F</u>	<u>46.1</u>
	Oaks Lane		PM		104.2	F	103.5	F	-0.7

					204	0 No			
Int.			Peak	Intersection	Pro	ject	2040	Project	Change
ID	Intersection	Jurisdiction	Hour	Control	Delay	LOS	Delay	LOS	In Delay
51	El Camino Real &	AT	AM	Side-street	>120	F	>120	F	>-60.0
	Watkins Avenue		PM	stop	>120	F	>120	F	>-60.0
<u>52</u>	Fair Oaks Lane &	AT	AM	Side-Street	>120	F	<u>>120</u>	<u>F</u>	<u>>60.0</u>
	Middlefield Road		PM	Stop	>120	F	>120	F	>-60 <u>.0</u>
<u>53</u>	Watkins Avenue &	AT	AM	Side-Street	75.4	F	<u>>120</u>	<u>F</u>	<u>>60.0</u>
	Middlefield Road		PM	Stop	>120	F	>120	F	>-60 <u>.0</u>
54	Glenwood Avenue &	AT	AM	Side-Street	>120	F	>120	F	>-60 <u>.0</u>
	Middlefield Road		PM	Stop	>120	F	>120	F	>-60 <u>.0</u>
<u>87</u>	<u>Encinal Avenue and</u>	<u>AT</u>	<u>AM</u>	<u>Signal</u>	<u>26.4</u>	<u>C</u>	<u>33.5</u>	<u>C</u>	<u>7.1</u>
	<u>Middlefield Road</u>		<u>PM</u>		<u>20.5</u>	<u>C</u>	<u>19.0</u>	<u>B</u>	<u>-1.5</u>
<u>86</u>	<u>Encinal Avenue and El</u>	<u>MP</u>	<u>AM</u>	<u>Signal</u>	<u>29.9</u>	<u>C</u>	<u>39.8</u>	<u>D</u>	<u>9.9</u>
	<u>Camino Real</u>		<u>PM</u>		<u>96.0</u>	<u>F</u>	<u>56.2</u>	<u>E</u>	<u>-39.8</u>
55	El Camino Real &	MP	AM	Signal	93.9	F	<u>>120</u>	<u>F</u>	<u>>60</u>
	Glenwood Avenue		PM		>120	F	>120	F	>-60
<u>56</u>	El Camino Real & Oak	MP	AM	Signal	81.3	F	<u>96.9</u>	<u>F</u>	<u>15.6</u>
	Grove Avenue		PM		94.6	F	84.0	F	-10.6
<u>57</u>	El Camino Real & Santa	MP	AM	Signal	46.9	D	37.7	D	-9.2
	Cruz Avenue		PM		78.4	Ε	<u>>120</u>	<u>F</u>	<u>>60</u>
<u>58</u>	Merrill St & Santa Cruz	MP	AM	All-way Stop	14.5	В	9.8	А	-4.7
	Avenue		PM		>120	F	<u>>120</u>	<u>F</u>	<u>45.9</u>
59	Ravenswood Avenue &	MP	AM	Side-Street	75.8	F	66.4	F	-9.4
	Alma Street		PM	Stop	84.2	F	>120	F	>-60
60	El Camino Real &	MP	AM	Signal	120.1	F	99.1	F	-21.0
	Ravenswood Avenue		PM		>120	F	>120	F	-4.9
61	Ravenswood Avenue &	MP	AM	Signal	89.2	F	83.4	F	-5.8
	Laurel Street		PM		>120	F	>120	F	>-60
<u>88</u>	<u>Laurel Street and Oak</u>	<u>MP</u>	<u>AM</u>	<u>Sianal</u>	<u>11.2</u>	<u>B</u>	<u>33.8</u>	<u>C</u>	<u>22.6</u>
	Grove Avenue		PM		<u>33.5</u>	<u>C</u>	<u>18.3</u>	<u>B</u>	<u>-15.2</u>
<u>89</u>	Laurel Street and	<u>MP</u>	<u>AM</u>	<u>All-way Stop</u>	<u>11.2</u>	<u>B</u>	<u>13.7</u>	<u>B</u>	<u>2.5</u>
	<u>Glenwood Avenue</u>		<u>PM</u>		<u>37.9</u>	<u>E</u>	<u>13.4</u>	<u>B</u>	<u>-24.5</u>
<u>90</u>	Laurel Street and	<u>MP</u>	<u>AM</u>	<u>All-way Stop</u>	<u>6.8</u>	<u>A</u>	<u>9.3</u>	<u>A</u>	<u>2.5</u>
	<u>Encinal Avenue</u>		<u>PM</u>		<u>6.4</u>	<u>A</u>	<u>5.9</u>	<u>A</u>	<u>-0.5</u>
62	Alma Street & Palo Alto	PA	AM	Side-Street	39.5	E	21.9	С	-17.6
	Avenue		PM	Stop	24.3	С	28.5	D	4.2
<u>63</u>	Meadow Drive & Alma	PA	AM	Signal	>120	F	<u>>120</u>	<u>F</u>	<u>43.3</u>
	Street		PM		>120	F	<u>>120</u>	<u>F</u>	<u>8.5</u>
<u>64</u>	El Camino Real & Alma	PA	AM	Signal	62.1	Ε	<u>85.8</u>	<u>F</u>	<u>23.7</u>
	& Sand Hill Road		РМ		>120	F	<u>>120</u>	<u>F</u>	<u>28.0</u>
65	High Street &	PA	AM	Signal	10.1	В	13.6	В	3.5
	University Avenue		PM	-	24.5	С	24.5	С	0
<u>66</u>	Alma Street & Churchill	PA	AM	Signal	>120	F	>120	F	<u>10.5</u>
	Avenue		PM	2	>120	F	>120	F	-0.7

Int			Dook	Intersection	204 Pro	0 No ject	2040	Project	Change
ID.	Intersection	Jurisdiction	Hour	Control	Delay	LOS	Delay	LOS	In Delay
67	W Meadow Drive &	PA	AM	Side-Street	>120	F	>120	<u>F</u>	<u>></u> 60ª
	Park Blvd.		PM	Stop	>120	F	>120	<u>F</u>	22.6 ^a
<u>68</u>	Alma Street &	PA	AM	Signal	>120	F	<u>>120</u>	<u>F</u>	<u>>60</u>
	Charleston Road		PM		>120	F	>120	F	-30.4
69	Showers Drive &	MV	AM	Signal	5.2	А	5.2	А	0.0
	Pacchetti Way		PM		4.9	А	6.4	А	1.5
<u>70</u>	Central Expressway & N	MV	AM	Signal	>120	F	<u>>120</u>	<u>F</u>	<u>7.7</u>
	Rengstorff Avenue		PM		>120	F	>120	F	<u>-6.2</u>
<u>71</u>	Central Expressway &	MV	AM	Signal	>120	F	>120	F	<u>-3.1</u>
	Castro Street		PM		>120	F	<u>>120</u>	<u>F</u>	<u>>60</u>
72	W Evelyn Avenue &	MV	AM	Signal	2.8	А	2.6	А	-0.2
	Hope Street		PM		4.7	А	4.9	А	0.2
73	Rengstorff Avenue &	MV	AM	Signal	168.5	F	<u>196.8</u>	F	<u>28.3</u>
	California Street		PM	-	175.7	F	<u>263.2</u>	<u>F</u>	<u>>60</u>
<u>74</u>	Castro Street & Villa	MV	AM	Signal	41.6	D	<u>71.4</u>	<u>E</u>	<u>29.8</u>
	Street		PM		112.5	F	<u>116.8</u>	<u>F</u>	<u>4.3</u>
<u>75</u>	W Evelyn Avenue & S	SV	AM	Signal	92.1	F	<u>110.2</u>	<u>F</u>	<u>18.8</u>
	Mary Avenue		PM		88.8	F	<u>96.8</u>	<u>F</u>	<u>8.0</u>
<u>76</u>	W Evelyn Avenue &	SV	AM	Signal	47.5	D	<u>287.9</u>	<u>F</u>	<u>>60</u>
	Frances Street		PM		51.7	D	<u>98.1</u>	<u>F</u>	<u>46.4</u>
	ZONE 4								
<u>77</u>	Kifer Road & Lawrence	SCL	AM	Signal	>120	F	<u>>120</u>	<u>F</u>	<u>55.4</u>
	Expressway ^c		PM		>120	F	>120	F	-47.4
<u>78</u>	Reed Avenue &	SCL	AM	Signal	>120	F	<u>>120</u>	<u>F</u>	<u>9.1</u>
	Lawrence Expressway		PM		>120	F	>120	F	>-60
<u>79</u>	El Camino Real &	SCL	AM	Signal	20.4	С	<u>69.5</u>	<u>E</u>	<u>49.1</u>
	Rallroad Avenue		PM		35.5	D	39.2	D	3.7
80	W Santa Clara Street &	SJ	AM	Signal	<u>89.4</u>	F	84.5	F	<u>-4.9</u>
		<i>a</i>	PM		92.2	r	54.7	D	-37.5
81	S Montgomery Street	SJ	AM	Signal	<u>31.3</u>	C E	51.6 86.2	D F	<u>20.3</u>
	Street		PM		~120	Г	00.3	Г	>-60
<u>82</u>	Lick Avenue and W	SI	AM	Signal	24.6	С	<u>62.</u> 1	<u>E</u>	<u>37.</u> 5
	Alma Avenue	,	PM	5	65.5	Ε	63.0	Ē	-2.5

1

Int				Peak	Intersection	204 Pro	0 No oject	2040	Project	Change
ID	Intersection	Jurisdi	ction	Hour	Control	Delay	LOS	Delay	LOS	In Delay
Sourc	ce: Appendix D,									
Trans	sportation Analysis									
Juris	dictions:									
SF	San Francisco	SM	San	Mateo				MV	Mount	ain View
SSF	South San Francisco	BL	Belr	nont				SV	Sunny	vale
SB	San Bruno	SC	San	Carlos				SCL	Santa	Clara
MB	Millbrae	RC	Red	wood (City			SCC	Santa	Clara
BG	Burlingame	AT	Athe	erton				Count	7	
MP	Menlo Park	PA	Palo	o Alto				SJ	San Jo	se
AM =	AM = morning peak hour. PM = afternoon peak hour									
LOS	designation as per 2010 H	ighway (Capaci	ty Man	ual					
Delay	measured in seconds		-							
Bold	font represents an LOS th	nat is belo	ow the	e establ	ished threshold	d of sign	ificance as	per the	Significa	nce
Crite	ria compared with existin	g conditi	ons.					-		
<u>Bold</u>	Underline font represent	ts locatio	ons an	d condi	tions where the	e Propos	sed Project	t would	result in	а
signi	ficant impact relative to th	ne No Pro	oject c	onditio	ns					
^a Alt	hough the Proposed Proje	ect would	l incre	ease del	ay at LOS F cor	nditions,	the inters	ection v	vould not	: meet a
sig	nal warrant and thus per	the signi	ficanc	e criter	ia would not ha	ave a sig	nificant in	npact.		
^b Do (Po	wntown Redwood City ha blicy BE-29.4).	s no leve	el of se	ervice s	tandard for inte	ersection	is in the D	owntow	n Precise	<i>Plan</i> area
c Cit in S	^c City of Santa Clara level of service exemptions exist for new development, to facilitate alternate transportation in Station Focus Areas.									
ſ	The results in Table 4-17	do not i	nclud	le the lo	ocalized effects	s of incr	eased HSI	R riders	hip at HS	SR

2 3 stations for 2040 or the effects of potential increases in gate down time on intersections near at-4 grade crossings due to Blended Service and other non-project increases in passenger and freight rail 5 traffic indicated in Table 4-8 above. As discussed in Appendix D, the effect of increased rail service 6 on gate-down time is highly site specific and is dependent on very specific assumptions about train 7 schedules. Given the current level of planning for Blended Service, any assumptions about schedule 8 and service would be speculative. Similarly, there are no published schedule analyses or draft 9 environmental documents for other service improvement plans, such as for ACE, Capitol Corridor, 10 Amtrak, and DRC or freight increases, and it would also be speculative to make assumptions about 11 their schedules at this time as well. Nevertheless, given the substantial service increases shown in 12 Table 4-8, it would be reasonable to assume that the impacts around HSR stations and at at-grade 13 crossings shown in Table 4-17 may underestimate the potential cumulative traffic delays, perhaps 14 substantially.

- Based on the impact criteria from Section 3.14, *Transportation and Traffic*, in 2040 the Proposed
 Project will have a significant impact at 39 study intersections during the AM and/or PM peak hours
 compared with the 2040 No Project conditions as shown in Table 4-17. Mitigation options were
 evaluated for all of these intersections. The following criteria were used to determine if the
 identified mitigation option would reduce the Proposed Project's impact to a less-than-significant
 level.
- If the intersection operates at LOS A–D under the No Project conditions, the mitigation measures
 must allow the intersection to continue operating at LOS A–D under the project alternative.

- If the intersection operates at LOS E or F under the No Project conditions, the mitigation
 measures must ensure that the delay under the project alternative does not increase by 4
 seconds or more.
- 4 Mitigation Measure TRA-CUMUL-1 below provides feasible mitigation measures for a number of
- 5 these intersections. Of the 39 intersections noted as significantly affected, as shown in Table 4-18,
- 6 17 would have significant and unavoidable impacts under 2040 Project conditions either because,
- 7 there is no feasible mitigation available to reduce the impact to a less-than-significant level or
- 8 because the identified mitigation is insufficient to reduce the impact to a less-than-significant level.

Impact Significance after Int. Impacted Peak Hour(s) Mitigation Strategies ID Intersection Mitigation **Signalized Intersections** 1 4th Street and AM Adjust signal timings to better serve traffic Significant and after project implementation unavoidable (SU) King Street 5 7th Street and AM and PM Widen northbound approach to lengthen left Less-than-significant after 16th Street turn pocket mitigation (LTS) Revise signal timing and phasing to better coordinate with 16th Street and Owens Street. Pre-emption, pre-signals or queue cutters to prevent an increase in potential queue back to the grade crossing. 16th Street and Revise signal timing and phasing to better 6 PM Less-than-significant after **Owens Street** coordinate with 7th Street and 16th Street mitigation (LTS) 10 Linden Avenue AM Adjust signal timing to better serve traffic after Less-than-significant after and Dollar project implementation mitigation (LTS) Avenue Adjust signal timing to better serve traffic after Less-than-significant after 12 S Linden AM Avenue and San project implementation mitigation (LTS) Mateo Avenue 16 El Camino Real AM and PM Adjust signal timing to better serve traffic after Less-than-significant after and Millbrae project implementation mitigation (LTS) in AM Avenue Significant and unavoidable (SU) in PM Less-than-significant after 17 Millbrae Avenue AM and PM Adjust signal timing to better serve traffic after and Rollins project implementation mitigation (LTS) Road 19 Carolan Avenue AM and PM Include northbound right-turn overlap. Less-than-significant after and Broadway mitigation (LTS) Adjust signal timing to better serve traffic after project implementation 20 California Drive PM Adjust signal timing to better serve traffic after Less-than-significant after and Oak Grove project implementation mitigation (LTS) Avenue 28 S B Street and PM Adjust signal timing to better serve traffic after Less-than-significant after 1st Avenue project implementation mitigation (LTS)

9 Table 4-18. Summary of 2040 Cumulative Intersection Impacts and Mitigation Measures

Int. ID	Intersection	Impacted Peak Hour(s)	Mitigation Strategies	Impact Significance after Mitigation
30	S B Street and 9 th Avenue	AM and PM	Extend southbound left-turn pocket Remove parking to add eastbound left-turn pocket Adjust signal timing to better serve traffic after project implementation <u>Pre-emption. pre-signals or queue cutters to</u> <u>prevent an increase in potential queue back to</u> <u>the grade crossing.</u>	Less-than-significant after mitigation (LTS) in AM Significant and unavoidable ^a (SU) in PM
35	31 st Avenue and El Camino Real	РМ	Adjust signal timing to better serve traffic after project implementation	Less-than-significant after mitigation (LTS)
36	E Hillsdale Boulevard and El Camino Real	РМ	Reconfigure westbound to two through lanes and one shared through/right-turn lane Adjust signal timing to better serve traffic after project implementation	Less-than-significant after mitigation (LTS)
37	E Hillsdale Boulevard and Curtiss Street	РМ	Adjust signal timing to better serve traffic after project implementation	Less-than-significant after mitigation (LTS)
39	El Camino Real and Ralston Avenue	АМ	Restripe westbound shared through/left-turn lane into a through lane Revise signal timing and phasing to better serve traffic after project implementation	Less-than-significant after mitigation (LTS)
45	El Camino Real and Whipple Avenue	АМ	Adjust signal timing to better serve traffic after project implementation	Significant and unavoidable (SU)
50	El Camino Real and Fair Oaks Lane	АМ	Adjust signal timing to better serve traffic after project implementation	Less-than-significant after mitigation (LTS)
55	El Camino Real and Glenwood Avenue	АМ	Widen westbound approach to provide right- turn pocket Adjust signal timing to better serve traffic after project implementation	Significant and unavoidable (SU)
56	El Camino Real and Oak Grove Avenue	АМ	Adjust signal timing to better serve traffic after project implementation	Less-than-significant after mitigation (LTS)
57	El Camino Real and Santa Cruz Avenue	РМ	Adjust signal timing to better serve traffic after project implementation	Less-than-significant after mitigation (LTS)
63	Meadow Drive and Alma Street	AM and PM	No feasible mitigations exist ^b	Significant and unavoidable (SU)
64	El Camino Real and Alma Street and Sand Hill Road	AM and PM	Widen west leg of Sand Hill Road by adding one lane to allow southbound right turns on red Adjust signal timings to better serve traffic after project implementation	Significant and unavoidable (SU) in AM Less-than-significant after mitigation (LTS) in PM
66	Alma Street and Churchill Avenue	AM	No feasible mitigations exist ^b	Significant and unavoidable (SU)

Int. ID	Intersection	Impacted Peak Hour(s)	Mitigation Strategies	Impact Significance after Mitigation
68	Alma Street and Charleston Road	АМ	No feasible mitigations exist ^b	Significant and unavoidable (SU)
70	Central Expressway and N Rengstorff Avenue	AM	No feasible mitigations exist ^b	Significant and unavoidable (SU)
71	Central Expressway and Moffett Boulevard and Castro Street	AM and PM	No feasible mitigations exist ^b	Significant and unavoidable (SU)
73	Rengstorff Avenue and California Street	AM and PM	Revise signal timing and phasing to better serve traffic after project implementation	Significant and unavoidable (SU)
74	Castro Street and Villa Street	AM and PM	Remove five on-street parking spaces on the eastbound approach to add a left turn pocket Remove parking to stripe one left-turn pocket and one through lane for the eastbound and westbound directions Revise signal timing and phasing to better serve traffic after project implementation	Less-than-significant after mitigation (LTS)
75	W Evelyn Avenue and S Mary Avenue	AM and PM	No feasible mitigations exist ^c	Significant and unavoidable (SU)
76	W Evelyn Avenue and Frances Street	AM and PM	Stripe westbound as one through lane and one shared through/right-turn lane Revise signal timing and phasing to better serve traffic after project implementation	Significant and unavoidable (SU)
77	Kifer Road and Lawrence Expressway	АМ	No feasible mitigations exist ^d	Significant and unavoidable (SU)
78	Reed Avenue and Lawrence Expressway	АМ	No feasible mitigations exist ^d	Significant and unavoidable (SU)
79	El Camino Real and Railroad Avenue	АМ	Revise signal timing and phasing to better serve traffic after project implementation	Less-than-significant after mitigation (LTS)
82	Lick Avenue and W Alma Avenue	АМ	Revise signal timing and phasing to better serve traffic after project implementation	Less-than-significant after mitigation (LTS)
Uns	ignalized Interse	ctions		
9	Tunnel Avenue and Blanken Avenue	AM and PM	Signalize intersection	Less-than-significant after mitigation (LTS)
21	Carolan Avenue and Oak Grove Avenue	AM and PM	Signalize intersection <u>with the addition of</u> northbound and westbound left-turn pockets	Significant and unavoidable ^e (SU) in AM Less-than-significant after mitigation (LTS) in PM

Int. ID	Intersection	Impacted Peak Hour(s)	Mitigation Strategies	Impact Significance after Mitigation
52	Fair Oaks Lane and Middlefield Road	АМ	Signalize intersection	Less-than-significant after mitigation (LTS)
53	Watkins Avenue and Middlefield Road	AM and PM	Signalize intersection	Less-than-significant after mitigation (LTS)
58	Merrill Street and Santa Cruz Avenue	РМ	Signalize intersection	Less-than-significant after mitigation (LTS)

Source: Appendix D, Transportation Analysis

^a Less-than-significant after mitigation but a secondary impact is produced at Intersection #29 (9th Avenue and S Railroad Avenue). After mitigation, the delay increases by more than four seconds at Intersection #29.

^b Addition of through lanes along Central Expressway and Alma Street may reduce the impact, but the addition of through lanes is subject to right-of-way constraints and is therefore infeasible.

^c Implementation of a grade separated crossing may reduce the impact but is subject to fiscal and temporal constraints. Therefore this mitigation is considered infeasible for purposes of this document.

^d Grade separated interchanges are under study but have yet to be approved or funded.

^e Less-than-significant after mitigation but a secondary impact is produced at Intersection #20 (California Drive and Oak Grove Avenue). After mitigation, the delay increases by more than four seconds at Intersection #20.

1

2 While the Proposed Project would have an adverse contribution to cumulative traffic delays at 3 certain locations, the Proposed Project is only a small overall contributor compared with the effects 4 of general growth along the Peninsula. This is shown by the 2040 No Project conditions which in 5 many cases indicate a substantial decline in traffic level of service from 2013 conditions with a 6 lesser contribution to delays above the 2040 No Project conditions shown by the 2040 Project 7 conditions. Further as noted above, the net effect of the Proposed Project is to reduce regional daily 8 VMT which produces benefits at many intersections, roadways, and freeways away from the at-9 grade crossings and Caltrain stations.

Thus, any mitigation to address <u>overall</u> cumulative traffic impacts is the responsibility of all
 cumulative contributors to the future conditions, including local jurisdictions, future development,
 as well as other rail services that plan increases in the Caltrain corridor, in addition to Caltrain.

13 As described in Mitigation Measure TRA-CUMUL-1, Caltrain will work with local jurisdictions, 14 transportation funding agencies, and state and federal agencies to support traffic improvements 15 over time as funding becomes available. While the recommended mitigation below, where feasible 16 to implement, would help to reduce cumulative traffic impacts, it will take time to implement it, is 17 funding limited and may only be partially implementable in the future, and it may not be feasible to 18 reduce all cumulative traffic impacts to a less than significant level, thus the Proposed Project is 19 considered to make a fair-share considerable contribution to significant cumulative traffic impacts, 20 even with mitigation. Caltrain will fund and implement the signal and minor roadway measures 21 proposed in Table 4-17. Other longer-term improvements will have to be implemented in concert 22 with local, regional, state, and federal partners as funding becomes available.

- As to secondary environmental impacts of Mitigation Measure TRA-CUMUL-1, the environmental
- 24 effects of the minor roadway improvements such as traffic signal optimization and roadway

- geometry changes would likely be limited in scale and nature. Caltrain will work with other parties
 when implementing this measure to apply the relevant construction mitigation measures identified
- 3 in this EIR to these minor improvements.

As to roadway major widenings or grade separations, the design and feasibility of such potential
future mitigations are unknown and unstudied at this time, and, thus, the specific environmental
impacts cannot be identified. Such major improvements will need to have their own environmental
review as appropriate²⁰, as they can have substantial environmental impacts depending on their
design and location and their construction can be highly disruptive and, thus, as a conservative
assumption, their secondary environmental impacts are considered significant and unavoidable.

- 10Mitigation Measure TRA-CUMUL-1: Implement a phased program to provide traffic11improvements to reduce traffic delays near at-grade crossings and Caltrain stations
- 12The proposed signalization and minor roadway mitigations in Table 4-18 will be fully funded by13Caltrain as they are directly related to the Proposed Project impact compared to 2040 No14Project conditions. The performance standard for the project impacts compared to the No
- 15 <u>Project conditions are the significance criteria used in this EIR.</u>
- 16Other long-term mitigation, such as grade separations, cannot be committed to by Caltrain at17this time due to funding limitations, but Caltrain will work with local jurisdictions and funding18partners to support such improvements as funding becomes available. JPB will coordinate with19local jurisdictions during the design phase of roadway mitigation measures that affect roadways20under local jurisdiction.
- 21 Caltrain, in cooperation with local agencies and other parties, will support a phased program 22 seeking to improve local roadway conditions along the Caltrain corridor near at-grade crossings 23 and Caltrain stations where cumulative impacts have been identified and where the Proposed 24 Project makes an adverse contribution to traffic delays. Separate from the specific Table 4-18 25 mitigation, given that there are multiple contributors to cumulative traffic conditions, Caltrain is 26 only responsible to fund its fair share for other necessary improvements with local jurisdictions, 27 future land use development as well as other rail services responsible to fund their fair share as 28 well. Fair share shall be determined by cumulative contributions to future traffic levels or delays 29 at identified significant cumulatively affected intersections and roadways determined using 30 traffic modelling.
- 31In the long run, where adequate funding is available, there are a variety of technically feasible32The following traffic improvements that would help to reduce cumulative traffic delays at33intersections near at-grade crossings and Caltrain stations including, but not limited to the34following options:
- Traffic signal optimization: Signal timing optimization can be performed to reduce delay at grade crossings. This can include optimizing the cycle time, splits, and phasing. In addition, for closely spaced intersections, optimizing the offset and better signal coordination can also reduce delay. Signal optimization was considered is proposed as a mitigation measure at a number of study intersections as shown in <u>Table 4-18 Table 4-17</u>. <u>Caltrain will fund and</u> implement the signalization in Table 4-18 as these impacts are directly related to Proposed Project impacts as they are identified relative to 2040 No Project conditions.

²⁰ As noted above, grade separations are statutorily exempt from CEQA.

1	 Roadway Geometry Changes: Changing the roadway geometry can also help reduce
2	intersection delay. This can include changing the roadway width by widening the street or
3	changing the existing geometry configuration through restriping. Intersection #43 (Main
4	Street and Middlefield Road) and Intersection #64 (El Camino Real and Alma Street and
5	Sand Hill Road) are examples of where roadway geometry could be altered as a mitigation
6	measure to reduce intersection delay. More detailed information can be found Roadway
7	changes are proposed in Table 4-18 Table 4-17. Caltrain will fund and implement the
8	roadway improvements in Table 4-18 as these impacts are directly related to Proposed
9	Project impacts as they are identified relative to 2040 No Project conditions.
10	• Grade Separations: Given the costs and disruption of major roadway widenings and grade
11	separations ²¹ , Caltrain cannot commit at this time to a comprehensive program of
12	improvements that would address all cumulative impacts in the future, because it does not
13	have the identified funding and does not expect to receive sufficient funding in the
14	foreseeable future. However, Caltrain, in cooperation with local jurisdictions, transportation
15	funding agencies, and state and federal agencies, will support incremental grade separations
16	at locations of cumulative traffic impacts over time as funding becomes available. Caltrain
17	will work with local, state, and federal partners to establish priorities for roadway
18	improvements grade separations to be implemented as funding becomes available. Caltrain
19	will also work with other rail parties to seek funding participation from multiple parties on
20	a fair-share basis in proportion to traffic contributions <u>or project contributions to traffic</u>
21	<u>delays.</u>
22	• Road Closures: One option for managing local traffic is to close roadways at grade crossings
23	and reroute traffic via alternative roadways. This option may not be feasible or acceptable to
24	local jurisdictions at many, if not all locations.
25	This mitigation is funding limited as it relates to major road widenings and grade separations
26	and will likely take many decades to implement. <u>As noted above, the JPB is committed to</u>
27	implementing the improvements shown in Table 4-18 in a phased program as needed to address
28	the Proposed Project's effects on local traffic.
29	Transit Services
30	As described in Section 3.14, Transportation and Traffic, the Proposed Project would not conflict or
31	create inconsistences with adopted transit plans, guidelines, policies or standards adopted by
32	project area cities, counties, the MTC, or the State of California. The Proposed Project has a beneficial
33	effect on transit plans as it implements a long-planned for increase in Caltrain service and
34	modernization. <u>Table 4-19 shows the modelled ridership for the Caltrain system in 2040 (from</u>

Appendix D). Table 4-20 shows the modelled ridership for connecting transit systems in 2040 (from
 Appendix I).

²¹ While grade separations are a technically feasible way to reduce cumulative traffic impacts at the at-grade locations, it is a highly expensive mitigation strategy. As discussed above, Caltrain supports future efforts at grade separation where acceptable to local communities and where local, state, and federal funding can be obtained to fund these improvements. However, using an average assumed cost of \$50 to \$100 million per crossing (grade separations can cost much more sometimes), grade separating all existing 42 at-grade crossings would cost \$2.1 to \$4.2 billion. Grade separating only 17 locations that are nearest the 17 significant unavoidably impacted intersections noted above could cost \$850 million to \$1.7 billion. The budget for the Proposed Project is \$1.225 billion by comparison. Thus, Caltrain cannot commit to a comprehensive program of grade separations at this time.

1	<u>The amount of Caltrain ridership to the Transbay Transit Center will depend on the amount of</u>
2	<u>Caltrain service to the TTC. The system-wide ridership model evaluation (Appendix I) was</u>
3	<u>conducted assuming that two trains per peak hour per direction would go to the TTC. This</u>
4	assumption of two trains is based on the operational studies to date by Caltrain given the current
5	TTC design of 3 platforms for HSR and two platforms for Caltrain. This assumption was for EIR
6	<u>evaluation purposes only and does not limit the number of trains that may travel to TTC. TJPA has</u>
7	also conducted ridership studies and has found higher levels of ridership for the TTC with increasing
8	service levels. The comparison of potential ridership at the 4 th and King Station and the TTC with
9	varying service levels is shown in Table 4-21.

10 Table 4-19. Daily Ridership Projections, 2040 No Project and Project Scenarios^a

Station	Existing Conditions	2040 No Project	2040 Project
Transbay Transit Center	<u>N/A</u>	<u>N/A</u>	<u>8,530 (2 trains to TTC)</u>
4 th and King	<u>10,790</u>	<u>16,560</u>	<u>15.230</u>
22nd Street	<u>1,310</u>	<u>2,860</u>	<u>3,290</u>
<u>Bayshore</u>	<u>200</u>	<u>1,040</u>	<u>1,700</u>
<u>South SF</u>	<u>360</u>	<u>1,000</u>	<u>1,200</u>
<u>San Bruno</u>	440	<u>960</u>	<u>1,200</u>
<u>Millbrae</u>	<u>3.260</u>	<u>6,500</u>	<u>8.960</u>
<u>Broadway</u>	<u>-</u>	<u>0</u>	<u>440</u>
<u>Burlingame</u>	<u>790</u>	<u>1,320</u>	<u>1,440</u>
<u>San Mateo</u>	<u>1,570</u>	<u>2,530</u>	<u>3,280</u>
<u>Hayward Park</u>	<u>330</u>	<u>1,510</u>	<u>1,420</u>
<u>Hillsdale</u>	<u>2,320</u>	<u>4,040</u>	<u>6,000</u>
<u>Belmont</u>	<u>510</u>	<u>820</u>	<u>1.090</u>
<u>San Carlos</u>	<u>1,140</u>	<u>1,890</u>	<u>1.900</u>
<u>Redwood City</u>	<u>2,620</u>	<u>5,170</u>	<u>5,670</u>
<u>Atherton</u>	<u>-</u>	<u>0</u>	<u>430</u>
<u>Menlo Park</u>	<u>1,500</u>	<u>2,180</u>	<u>2,140</u>
<u>Palo Alto</u>	<u>5,470</u>	<u>9,820</u>	<u>13,540</u>
<u>California Avenue</u>	<u>1,290</u>	<u>1,990</u>	<u>1.500</u>
<u>San Antonio</u>	<u>680</u>	<u>1,110</u>	<u>1.280</u>
Mountain View	<u>3,880</u>	<u>6,700</u>	<u>9,570</u>
<u>Sunnyvale</u>	<u>2,270</u>	<u>3,480</u>	<u>4,630</u>
<u>Lawrence</u>	<u>700</u>	<u>1,410</u>	<u>1,750</u>
<u>Santa Clara</u>	<u>820</u>	<u>950</u>	<u>930</u>
College Park ^b	<u></u>	=	
<u>San Iose Diridon</u>	<u>3,490</u>	<u>6.640</u>	<u>10.600</u>
<u>Tamien</u>	<u>810</u>	<u>1.360</u>	<u>1,880</u>
<u>Total</u>	<u>46,560</u>	<u>81,820</u>	<u>109,590</u>

Note: Daily Ridership is presented as passenger boardings, defined as the number of passengers who board a train at a given station (not boardings plus alightings). Numbers may not match totals due to rounding.

a Excludes boardings south of Tamien Station.

b No service increases are proposed at the College Park Station and ridership at this station is very low at present (118 boardings/day). While College Park boardings are included in overall system ridership estimates, no analysis of localized traffic around this station was conducted given the low level of boardings and lack of proposed service increases.

<u>Source: Appendix D</u>

1 Table 4-20. Estimated Daily Ridership, Proposed Project and No Project Alternative

<u>Operator</u>	2013 Observed	2040 No Project	2040 Project (& DTX/TTC)			
<u>Caltrain</u>	47,100	<u>83,900</u>	<u>111,100</u>			
BART	<u>366,600</u>	<u>678,900</u>	<u>676,900</u>			
SamTrans Bus (Local and BRT)	<u>39,800</u>	<u>103,200</u>	<u>100,000</u>			
VTA Light Rail	<u>34,600</u>	<u>129,300</u>	<u>129,900</u>			
<u>VTA Bus</u>	<u>103,100</u>	246,100	<u>247,100</u>			
(Local and BRT)						
MUNI Metro	<u>173,500</u>	<u>252,200</u>	<u>250,100</u>			
<u>MUNI Bus</u>	<u>531.700</u>	<u>736,600</u>	<u>740,200</u>			
<u>Shuttles (Caltrain + Private)</u>	<u>NA</u>	<u>20,700</u>	<u>27,000</u>			
<u>Total</u>	<u>1,297,700</u>	<u>2,311,600</u>	<u>2,332,600</u>			
Source: Appendix I, Ridership Technical Memorandum						

2

5

Table 4-21. Comparison of Potential Caltrain Ridership to TTC with Varying Service Level Assumptions (Boardings and Alightings by Station)

			Transbay			
		<u>4th and King/</u>	<u>Transit</u>	<u>Total of 2</u>		
	<u>Service</u>	<u>4th and Townsend</u>	<u>Center</u>	<u>Stations</u>		
Cambridge Systematics	<u>6 trains to 4th and King</u>	<u>30,900</u>	<u>N/A</u>	<u>30,900</u>		
<u>(2009) (1)</u>	6 trains to 4th and Townsend and to TTC	<u>17,100</u>	<u>31,500</u>	<u>48,500 (2)</u>		
PCEP DEIR System-	6 trains to 4th and King	<u>31,782</u>	<u>N/A</u>	<u>31,782</u>		
wide Ridership	<u>4 trains to 4th and King</u>	<u>29,058</u>	<u>17,053</u>	<u>46,112 (2)</u>		
<u>Modelling (2014) (3)</u>	2 trains to 4th and Townsend and TTC					
Notes:						
For 2030. Estimates prepared in 2008 based on pre-recession growth forecasts.						
Totals may not match due to rounding.						
For 2040. Estimates prepared in 2013 based on post-recession growth forecasts.						

Below, potential cumulative effects on transit infrastructure and other cumulative transit projects
 are discussed.

8 Need for Transit Infrastructure due to Ridership Increase

9 Cumulative growth in the region will increase demand for increased transit service. The Proposed

10 Project is one of many projects in the planning phase to address that increased demand. Table 4-3

11 includes a number of key other transit projects as well, but there are many other regionally

12 significant transit improvement efforts not included in Table 4-3 because they are in locations more

13 distant from the Caltrain ROW.

- 14 One concern is that the Proposed Project, might result in increased ridership not only for Caltrain
- 15 but also for other transit systems. The increase in ridership on other systems alone is not a concern
- 16 for the CEQA evaluation, unless that increase in induced ridership would result in changes in
- 17 physical conditions such as through the construction of additional transportation infrastructure to

1 address the increased ridership. As discussed in Section 3.14, Transportation and Traffic, the 2 Proposed Project is not expected to result in a significant change in ridership for other transit 3 services that would result in the need for new transportation infrastructure. As shown in Appendix 4 I, *Ridership Technical Memorandum*, Table 4-20, compared with 2040 No Project conditions, the 5 Proposed Project is expected to slightly lower ridership on BART, SamTrans, and Muni MUNI Metro 6 and slightly increase ridership on VTA light rail (0.5 percent), VTA bus (0.4 percent) and Muni-MUNI 7 bus (0.5 3 percent). Like Caltrain, other transit providers must plan for their future needs and 8 construct the facilities to meet their system rider demands as feasible given funding availability. The 9 Proposed Project would also contribute substantially to increases in Caltrain and private shuttles. 10 Where the Proposed Project would result in increased bus ridership (VTA, Muni MUNI, and 11 shuttles), it is not expected to require substantial new facilities to support the increase, although it 12 would contribute to the need for bus shelters, stops, and maintenance facilities. Where the Proposed 13 Project would contribute to VTA light-rail ridership, it may contribute to the need for additional 14 light-rail infrastructure, which might result in environmental impacts during construction.

15 Because infrastructure improvements for transit services other than Caltrain and their funding are 16 outside the responsibility of the JPB, the responsibility for managing the environmental effects of 17 any additional transit facilities or service that might be necessary to meet future cumulative 18 demands lies with each transit operator. For future improvements that may be necessary to 19 accommodate increased Caltrain shuttle service due to increased ridership from the Proposed 20 Project, such as shuttle bus stops, shelters, or other facilities, Caltrain will be required to complete 21 the appropriate state (and federal if required) environmental review for such improvements and 22 shall adopt feasible mitigation for any significant environmental impacts thus identified. For future 23 improvements that may be necessary to accommodate increased other transit service due to 24 increased ridership from the Proposed Project, the responsible transit operations will be required 25 complete the appropriate state (and federal if required) environmental review for such 26 improvements and shall adopt feasible mitigation for any significant environmental impacts thus 27 identified.

At this time, it appears unlikely that the relatively modest increases in ridership for other transit
 services resultant from the Proposed Project would result in the construction of additional transit
 infrastructure that might have significant physical impacts on the environment and thus the
 Proposed Project's contribution to cumulative need for transit infrastructure is less than
 considerable.

33 Potential Conflicts between Proposed Project and Other Transit System Projects

Caltrain routinely coordinates with other transit system providers to facilitate Caltrain and other
 system transit projects and to avoid conflicts between planning for different systems. Caltrain has
 coordinated and is continuing to coordinate with CHSRA on the HSR project, TJPA on the DTX
 project, BART on the Silicon Valley Extension and other projects and has not identified any conflicts
 between the Proposed Project and these projects that would hinder their completion as proposed.
 Similarly, Caltrain is taking into account the future service plans of other passenger rail operators
 when planning for the South Terminal improvements.

- 41 At this time, only three potential conflicts between the Proposed Project and other proposed transit
- 42 projects have been identified. If conflicts could not be resolved, there is the potential for significant
- 43 impacts in the loss of transit service which could then result in increased vehicle traffic and
- 44 resultant traffic congestion and air quality impacts (as well as possibly other environmental effects).

- 1 However, as discussed below, each of the potential conflicts appears manageable without impeding 2 athen transit analyzed (anthen smarting of substantial new anxiety and (athen
- 2 other transit projects/service and/or the creation of substantial new environmental effects.
- 3 *DTX*

4 As described above, the DTX project's 2004 FEIS/EIR included proposes a reconfiguration of the San 5 Francisco 4th and King <u>Street station</u> yard from six at-grade platforms (12 tracks) to three at-grade 6 platforms (six tracks) at 4th and King, in the southern portion of the railyard; permanent 7 realignment of approach tracks south of the 4th and King Station within the Caltrain right-of-way 8 bordering 7th Street, and a new underground station at 4th and Townsend streets. Subsequent to 9 the 2004 FEIS/EIR, the platform and track reconfiguration at the railyard was removed from the 10 DTX project scope during the Preliminary Engineering phase. TIPA clarified in its comment letter on the PCEP DEIR that the railyard platform reconfiguration 11 12 under the DTX project is limited only to work necessary to create space for DTX construction. 13 consistent with the current DTX scope. Based on this clarification, construction of the DTX project 14 would not require platform modifications either for existing Caltrain service or for proposed 15 Caltrain electrification service. If such reconfiguration were to be desirable in the future for other 16 purposes, a separate environmental review involving Caltrain (and possibly other parties) may be 17 warranted to evaluate impacts of surface station and/or track reconfiguration at the 4th and King 18 Street Station. At present, no plans or funding have been identified to implement the surface station 19 and track reconfiguration. 20 The DTX project could result in two effects to the electrified Caltrain railyard and its operations. 21 First, the DTX project could result in temporary disturbances to the north side of the railyard • 22 during construction. Caltrain has coordinated with TJPA and identified that DTX construction 23 may require temporary relocation of OCS infrastructure (poles and wires) in certain portions of 24 the railyard during construction. If funding is identified and surface station reconfiguration and 25 associated approach track relocation is carried out before DTX construction, then no track relocation at the railyard would be required as part of the DTX construction. In this scenario, 26 27 DTX construction would not impact the OCS poles and wires that would be installed for the 28 reconfigured station design. 29 • Second, as noted previously, the DTX project also requires realignment of approach tracks south 30 of the 4th and King Station within the Caltrain ROW bordering 7th Street. This work would 31 require permanent relocation of the OCS poles and wires along with the realigned tracks. 32 Temporary or permanent relocation of OCS poles and wires associated with 4th and King Station 33 reconfiguration (if not completed prior to DTX construction), would involve a minor increase in 34 DTX cost compared to the overall DTX construction effort. 35 As described above, Caltrain ridership to the TTC will depend on Caltrain service to the TTC. 36 Although the modeling for this EIR assumed two trains per peak hour to the TTC and fourth to the 37 4th and King Station, this assumption was for EIR evaluation purposes only. Because the project 38 limits for the PCEP end at the 4th and King Station, the exact level of service to TTC is outside the 39 PCEP's scope and is dependent on ultimate resolution of the TTC design, which is a matter to be 40 resolved between TIPA and Caltrain (and other parties) (which is also outside the scope of the 41 PCEP). The PCEP project would bring up to 6 Caltrain EMU trains per peak hour per direction to the 42 4th and King Station. The total number of trains that could proceed all the way to TTC shall be 43 determined in the future and will depend on ultimate platform, track design, and operational

- parameters at TTC, that are yet to be determined. The PCEP does not preclude a greater number of
 trains travelling to TTC.
- 3 <u>Therefore, there is no substantial conflict between the PCEP and the DTX/TTC projects.</u>
- 4 <u>Caltrain Fourth and King Terminal Platform Reconfiguration</u>

5 If the DTX platform reconfiguration project could have been be completed before the Proposed 6 Project, then electrification would only need to be applied to the six tracks at the station itself. 7 However given funding constraints, full platform reconfiguration will happen after 2020 it appears 8 likely that the DTX project will be completed sometime after 2019 and, thus, that the Proposed 9 Project will electrify the 12 existing tracks at the station. This will likely mean that the DTX project 10 platform reconfiguration will have additional construction effort to remove and relocate electrical 11 infrastructure at the 4th and King Station/Yard to match the new configuration sometime after 2020 12 2019. Given the scale of the DTX project, the additional effort will be an additional cost, but a limited one by comparison to the cost of DTX overall. Given the uncertainty as to DTX funding and timing, 13 14 the electrification of the 4th and King Station as is will allow for the commencement of electrified 15 service with all of its identified benefits without an uncertain delay that might occur if funding for 16 platform reconfiguration DTX takes some time to secure. Environmentally, the additional effort to 17 remove and relocate the poles and wires at the station would be a minor increase in terminal 18 reconfiguration DTX-construction effort overall. given the need for DTX to construction substantial tunneling, underground station infrastructure, and platform reconfiguration. 19

- 20 Relocation of OCS poles and wires would not be a major impediment to future station platform 21 reconfiguration. The estimated cost to electrify the entire 4th and King Station and yard is \$13.5 22 million. This cost would fall on the Proposed Project. If and when the 4th and King Station platforms are reconfigured, assuming the TIPA 2004 EIS/EIR reconfiguration design, the cost to electrify the 23 reconfigured tracks and platforms would be \$7 million. This \$7 million additional cost is not 24 25 considered an insurmountable financial hurdle to platform reconfiguration, regardless of who 26 ultimately implements the reconfiguration. Caltrain would prefer to electrify the 4th and King 27 Station after reconfiguration to help avoid additional cost as well as disruption to its riders, but at 28 this time due to funding limitations that does not appear likely.²² Caltrain will continue to 29 coordinate with TIPA to examine if there is an opportunity to coordinate construction of the
- 30 Proposed Project and station reconfiguration to minimize the need for additional work.
- 31 SFMTA 22-Fillmore Electric Trolley Bus Re-Routing to 16th Street

SFMTA is proposing to re-route the 22-Fillmore electric trolley bus (ETB) from its current route
 crossing over the Caltrain ROW at 18th Street to an at-grade crossing at 16th Street. The installation
 of the direct current 600-volt OCS for the electric trolley bus at 16th Street creates a conflict with the
 proposed installation of the 25 kVA alternative current OCS as part of the Proposed Project.

- 36 The ETBs have an auxiliary power unit (APU) that can operate the bus without electrical power for
- 37 short distances. While it would be technically feasible for the ETB to pull down the collector poles
- prior to driving through the 16th street rail crossing (to avoid contacting the Caltrain 25 kVA OCS
- 39 wire), this is considered unacceptable from both a safety and an operational standpoint. A bus
- 40 stopping to disconnect and re-attach the collector poles while on a railroad crossing is not safe and a

²² The Proposed Project does not include adequate funding for any station improvements or reconfiguration other than installation of electrification infrastructure.

20

21

22

23

24

31

32

33

34

35

36

- bus stopping before and after the railroad crossing would delay bus service times and create traffic
 safety issues.
- In order to manage the conflict to allow the SFMTA project and the Proposed Project to both go
 forward, Mitigation Measure TRA-CUMUL-2 is proposed. With implementation of this mitigation,
- 5 both projects would be able to proceed and provide their improved transit benefits.
- 6Mitigation Measure TRA-CUMUL-2: Implement technical solution to allow electric trolley7bus transit across 16th Street without OCS conflicts in cooperation with SFMTA
- 8 The JPB, in cooperation with SFMTA, will implement a technical solution to allow operation of
 9 the ETB at the 16th street crossing as well as the Caltrain electrification.
- 10Two feasible options for the SFMTA at-grade trolley crossing at 16th Street underneath the I-11280 viaduct have been identified, both of which would involve a short phase break of the12Caltrain OCS. Both options would include a short gap in the Caltrain OCS to allow the ETB OCS to13be installed through the intersection. The short section of the ETB OCS would not be energized14to avoid any potential for contact between energized parts of the Caltrain OCS and the ETB OCS.15The options for equipment to facilitate Caltrain operations through the Caltrain OCS gap are as16follows:
- Option #1: Installation of a track-mounted transponder that automatically communicates
 with special on-board equipment to open the main circuit breaker and preclude current
 from reaching the car.
 - As a Caltrain consist approaches the 16th street crossing, the engineer would reduce the power draw and the track-mounted transponder would instruct the individual car to open its main breaker. Power drawn from pantographs outside the "zero-power zone" will allow the train to move through the crossing without slowing down. After clearing the crossing, the main breaker will close, and the power draw can be ramped up again.
- 25 o Electric Trolley Buses will operate normally at the crossing, as the collector poles glide
 along the contact wires up to 6" above the 25kV Caltrain OCS wires. Buses will
 encounter a roughly 6-foot-long (the width of the Caltrain pantograph) non-energized
 portion of contact wire at the crossing of each track, but can coast through that gap on a
 continuous wire structure. This type of movement is a part of normal operations in San
 Francisco.
 - This type of OCS wire structure has been used previously in Seattle and in Europe.
 - Option #2: Installation of a vacuum circuit breaker (VCB), which removes the requirement for special on-board equipment.
 - The VCB solution has only been available for about 15 years and has not been implemented on a large scale yet. This solution has been utilized in newer installations in China.
- Caltrain will need to obtain regulatory clearance from the CPUC for either of these solutions. The
 CPUC has not yet released regulations for 25kV traction power systems. The rulemaking process
 is ongoing. Caltrain, in cooperation with SFMTA will work with the CPUC to obtain approval of a
 technical solution for the 16th Street crossing.

- The placement of the ETB overhead wires needs to be identified by SFMTA in coordination with
 Caltrain as the ETB needs to cross in the lane with the overhead wires in order to avoid any
 power interruption for the bus while crossing the rail line.
- The following issues will be resolved during design of the improvement: wire height for the 22 Fillmore OCS, reliability of the Caltrain on-board (transponders), or off-board equipment.
 (vacuum circuit breakers), and emergency operating procedures in case of failure.
- In addition, Caltrain will work with SFMTA to identify any design, maintenance, or emergency
 contingency considerations important to the design of the crossing system to minimize
 additional maintenance effort or materials for SFMTA during operations and to identify
 emergency response actions in the event of any wire entanglement at the crossing.
- 11 BART Millbrae Tail Tracks
- As described above, the BART Millbrae Tail Track project would extend the existing tail tracks at the
 BART Millbrae Station 200 to 300 feet southward on BART property. In this area, the OCS would be
 installed within the Caltrain ROW so there should be no conflicts with the BART extension project.²³
- 15 **Pedestrian Facilities**
- 16 Cumulative projects could also affect pedestrian walkways and bike paths that cross the Caltrain
 17 ROW or are directly adjacent to the Caltrain ROW. Blended Service improvements would have the
 18 greatest potential to affect such facilities if passing tracks are proposed outside the Caltrain ROW.
 19 For example, the Embarcadero bike path is parallel to the Caltrain ROW and in Palo Alto and the
 20 Middle 3 passing track option would include this portion of Palo Alto. Whether or not passing tracks
 21 affect bicycle and pedestrian facilities would depend on location and design, which are unknown at
 22 this time.
- 23 As discussed in Section 3.14, *Transportation and Traffic*, the Proposed Project would add increased 24 pedestrian volume to existing pedestrian facilities due to increased ridership. The existing 25 pedestrian facilities have been evaluated and are capable of accommodating an increase in 26 pedestrian traffic with the exception of pedestrian facilities around the San Francisco 4th and King 27 Station. Future planned pedestrian facilities are designed around the Proposed Project's existing 28 alignment. Planned pedestrian facilities will be constructed to accommodate Caltrain's existing 29 alignment. Therefore the Proposed Project would not contribute to cumulative impacts on 30 pedestrian facilities at locations other than the 4th and King Station.
- 31 At the 4th and King Station, due to increased Caltrain ridership (with or without the Proposed 32 Project) in combination with increased transit ridership on connecting services including the 33 Central Subway and the proposed Embarcadero Streetcar extension, as well as general growth in the 34 4th and King Station vicinity, the capacity of some of the pedestrian facilities will be exceeded, 35 resulting in congested walkways and crosswalks around the station and queuing to cross local 36 streets. Because the Proposed Project would increase Caltrain ridership compared with No Project 37 conditions, the Proposed Project would contribute considerably to pedestrian usage of the 4th and 38 King Station area. Thus, the Proposed Project will contribute considerably to a cumulative 39 pedestrian facility impact at 4th and King Station.

²³ As discussed in Section 3.5, *Electromagnetic Fields and Electromagnetic Interference*, during final design Caltrain will assess the potential for EMI between the Caltrain OCS and BART signal and communication systems and address it through design features such as s filters, capacitors, and inductors.

- 1 As discussed in Section 3.14, *Transportation and Traffic*, the Proposed Project would only contribute
- 2 to this impact between when the Proposed Project begins operations in <u>2020</u> 2019 and when
- 3 DTX/TTC becomes operational. At that point, with ridership shifting to TTC, the Proposed Project
- 4 would no longer have a considerable contribution to pedestrian usage because the Proposed 5 Project's contribution would be less than under No Project conditions
- 5 Project's contribution would be less than under No Project conditions.
- 6 Mitigation Measure TRA-3b (discussed in Section 3.14, *Transportation and Traffic*) would require
- 7 the JPB and the City and County to plan for and implement necessary pedestrian facility
- 8 improvements to the 4th and King Station and adjacent pedestrian facilities in City street rights-of-
- 9 way. Implementation of this mitigation measure would reduce the Proposed Project's contribution
- 10 to a cumulative impact to a less than significant level.

11 Bicycle Facilities

- 12 The Proposed Project, in combination with other cumulative projects may also increase future
- demand for bicycle facilities however, most plans in the project area account for increased bicycle
- 14 volumes through added bicycle infrastructure. The Proposed Project does not change the alignment
- and does not impede any existing or planned bicycle projects because the new improvements are
- 16 limited to overhead infrastructure and the TPFs (which do not affect bicycle facilities).
- 17 For the Caltrain system itself, the increase in ridership over time will likely increase the demand for
- 18 bicycle facilities at Caltrain stations. Given that bike trains often operate at capacity during peak
- periods under existing conditions, it is possible that capacity issues may continue in future years.
 Any unmet on-board demand for bikes-on-board could be accommodated through the provision of
- increased bike parking at stations. This would allow passengers to safely and securely park their
 bikes before boarding the train. If a passenger is in need of a bike to egress from their destination
 station, they may also be able to use Bay Area Bike Share or travel by another mode.
- As explained in Section 3.14, *Transportation and Traffic*, Caltrain's *Bicycle Access and Parking Plan*,
 includes a long-term plan to increase bicycle parking supply for a variety of user needs, improving
 station access for bicyclists, working with cities to improve station bike access, as well as
 considering other station-side concepts.
- 28 Mitigation Measure TRA-4b, in Section 3.14, *Transportation and Traffic*, would require Caltrain to
- 29 continue implementation of its current planning to improve bicycle facilities at Caltrain stations
- over time to meet potential increased demand for such facilities. Thus, with mitigation, the Proposed
 Project would not contribute considerably to any significant cumulative impacts on bicycle facilities.

32 Emergency Vehicle Access

- 33 Cumulative projects would affect existing emergency vehicle access if they result in constrictions on
- 34 the ability for emergency responders to reach their destinations. This could occur due to physical
- 35 constraints and/or generation of traffic congestion which could impede emergency vehicles.
- 36 However, peak period traffic congestion generally does not result in delay for emergency vehicles,
- 37 which have right-of-way and often utilize multi-lane major arterials for access. Emergency vehicles
- 38 are permitted to use transit-only lanes or other vehicle-restricted lanes if necessary.
- 39 The increase of cumulative rail traffic along the Caltrain ROW including HSR, ACE, Capitol Corridor,
- 40 DRC, the Coast Daylight and freight could result in increased gate down times at the at-grade
- 41 crossings along the Caltrain ROW. As discussed above, due to cumulative growth in traffic over time
- 42 due to both the land use projects (included in Table 4-3) as well as general growth in the region (as

- 1 shown by projections in Table 4-2), traffic conditions are expected to substantially decline over the
- 2 next few decades both at the at-grade crossings of the Caltrain ROW but also generally throughout
- 3 the region (in spite of substantial investments in transit). With this cumulative growth in traffic,
- 4 emergency response times during peak hours may be adversely affected.
- 5 Despite these localized traffic delay impacts, emergency vehicle response times are a function of 6 travel along the entire path from their base to the incident location. The Proposed Project overall
- 7 would substantially reduce overall vehicle miles travelled in the Peninsula corridor by
- 8 approximately 235,000 miles/day in 2020 and 619,000 miles/day in 2040 (compared with No
- 9 Project Conditions) which would substantially improve congestion on a broad general basis. Most of
- 10 the VMT reductions would be during peak hours, which is especially important in reducing
- 11 congestion. The broad-based congestion improvement is expected to more than offset the localized
- 12 effects at individual at-grade crossings and near Caltrain stations and result in a net improvement
- 13 (compared with No Project Conditions) in the emergency response times.
- 14 As discussed in Section 3.8, Hazards and Hazardous Materials, the Proposed Project's new OCS 15 would not pose an impediment to routine emergency vehicle access.

16 Station Parking/Access

- 17 As described in Section 3.14, *Transportation and Traffic*, the Proposed Project does not interfere
- 18 with the implementation of Caltrain's Comprehensive Access Program Policy Statement or Bicycle
- 19 *Access and Parking Plan.* The Proposed Project would also increase both vehicular and pedestrian 20 traffic around Caltrain stations but locations with high vehicle volumes are signalized and allow
- 21 pedestrians to cross safely. No additional new at-grade crossings are planned with the Proposed
- 22 Project and the implementation of CBOSS PTC further improves safety. Under cumulative conditions,
- 23 there would be a further increase in traffic and pedestrian volumes by 2040, but a similar conclusion
- 24 applies and the Proposed Project would not contribute considerably to any cumulative access safety
- 25 impacts.
- 26 The remainder of this section concerns station parking and access facilities.
- 27 Modeling of potential parking demand was completed for informational purposes based on
- 28 behavioral forecasts by Fehr & Peers (see Appendix D, Transportation Analysis). Actual parking
- 29 demand will fluctuate based on day and month based on peoples changing mode of access to
- 30 Caltrain. The parking supply and demand forecasted for 2040 is shown in Table 4-22 19. Parking
- 31 supply remains the same with and without the project while parking demand increases.
- 32 Without the Proposed Project, 2040 ridership will still increases, causing parking demand that will 33 exceed Caltrain supply at 11 stations. At some stations, this parking deficit will likely be absorbed by 34 existing non-Caltrain lots and on-street parking at stations such as San Mateo, Hillsdale and San Jose 35 Diridon. Four stations will have demand that exceeds both Caltrain and nearby non-Caltrain parking supply. At the Mountain View and Sunnyvale Stations, the demand will exceed the Caltrain and non-36 37 Caltrain parking supply by more than 100 spaces.
- 38 The cumulative parking demand presented in this analysis does not take into account parking 39
- demand from High-Speed Rail or proposed TOD developments. TOD development could increase or
- 40 decrease local parking demand depending on their specific design and approach to shared parking.
- 41 HSR parking impacts will need to be assessed as part of subsequent environmental evaluation by
- 42 CHSRA as parking demand is highly tied to the specific timing, mode of access and schedule for HSR
- 43 service, all of which are not known in sufficient detail at this time.

	Ex	isting	2040 without Project			2040 with Project		
Station	Caltrain Lot Utilization	Caltrain Lot Parking Supply	Parking Demand	Parking Surplus & Deficitª	Excess Parking Demand ^b	Parking Demand	Parking Surplus & Deficitª	Excess Parking Demand ^b
4th and King	-	0	169	-169	39	77	-77	0
22nd Street	-	0	514	-514	0	779	-779	157
Bayshore	13%	38	54	-16	0	114	-76	0
South SF	51%	74	75	-1	1	113	-39	39
San Bruno	22%	201	215	-14	0	304	-103	0
Millbrae ^c	<u>80-</u> 79%	490	332	158	0	455	35	0
Broadway ^d	8%	122	-	-	-	35	87	0
Burlingame	30%	69	55	14	0	74	-5	0
San Mateo	20%	42	190	-148	0	359	-317	0
Hayward Park	3%	210	28	182	0	37	173	0
Hillsdale	86%	513	615	-102	0	1,112	-609 ^e	503
Belmont	20%	375	82	293	0	135	240	0
San Carlos	32%	207	210	-3	0	243	-36	0
Redwood City	46%	553	331	222	0	588	-35	0
Atherton ^d	-	96	-	-	-	44	52	0
Menlo Park	33%	155	82	73	0	118	37	0
Palo Alto	87%	350	232	118	0	393	-43	43
California Avenue	31%	169	52	117	0	59	110	0
San Antonio	33%	193	47	146	0	115	78	0
Mountain View	97%	336	811	-475	119	1,379	-1,043	687
Sunnyvale	103%	391	750	-359	296	1,291	-910 ^f	847
Lawrence	30%	122	105	17	0	143	-21	0
Santa Clara	62%	190	33	157	0	32	158	0
$College Park^{g}$								
San Jose Diridon	99%	576	239	337	0	380	196	0
Tamien	98%	275	853	-578	0	1,205	-930	301
Total Excess Demand				455			2,578 2,577	

1 Table 4- 22 19. Existing and Future 2040 Cumulative Parking Supply at Caltrain Stations

Source: Appendix D, Transportation Analysis

^a High parking surplus can be attributed to changes in land use where parking currently exists in some cases

^b Excess Park and Ride demand beyond non-Caltrain lot and on-street parking

^c Includes shared parking with BART.

^d No weekday service at present. Weekday service would be restored with Proposed Project but not with No Project.

- ^e Includes potential loss of 10 spaces due to PS-4, Option 1.
- ^f Includes potential loss of 10 spaces due to PS-6, Option 2.
- ^g There is no Caltrain lot at the College Park Station. Parking is on the street. Given limited ridership and no plans to change service levels, parking demand was not evaluated at this location.

2

1 The increase is greater with the Proposed Project due to increased ridership. As shown in Table 4-2 22 19, the majority of parking deficits could be absorbed by on-street parking and/or non-Caltrain 3 lots where space is available.²⁴ In 2040 with the Proposed Project, parking demand will exceed the 4 Caltrain and Non-Caltrain parking supply at seven stations, five of which will have demands that 5 exceed the supply by more than 100. 6 At the 4th and King, Hayward Park, Santa Clara, San Jose Diridon and Tamien Stations, parking 7 demand decreases from the 2020 to 2040. This demand decrease can be attributed to planned 8 cumulative future transit-oriented development, contributing to increasing riders who access 9 Caltrain via transit, walking and bicycling. It should be noted that land use changes in the station 10 area contributing to parking demand decrease may decrease the parking supply as well. 11 Subsequently, this planned development may result in lower parking surplus. 12 At most stations where impacts occur with the Proposed Project, they also occur without the project, though to a lesser extent. 13 14 An area of substantial change for the future is the area around the San Jose Diridon Station. The 15 cumulative analysis of parking for the Diridon Station Area has been recently assessed in the certified 2014 Final EIR for the DSAP, which includes transit demand. In the FEIR for the DSAP, the 16 17 City of San Jose specifically noted in response to comments from Arena Management that the DSAP 18 EIR analysis of full buildout included BART and rail electrification (City of San Jose 2014b). The 19 DSAP EIR's analysis of cumulative parking demand is incorporated by reference for the PCEP EIR. 20 The DSAP proposes to meet demand generated by existing and future development by requiring that 21 new development provide off-street parking, primarily through structured or underground garages. The DSAP projects future off-street parking ratios that would ultimately be achieved with build-out 22 23 of the DSAP and completion of the planned transit facilities, including BART and High Speed Rail. 24 Already a major transit hub, Diridon Station is anticipated to become one of the busiest multi-modal 25 stations both in California and the western United States with the BART extension to Silicon Valley 26 and the High Speed Rail to San Francisco and Los Angeles (City of San Jose 2014b). 27 In addition to these major investments, the DSAP also plans for a dense network of bicycle and 28 pedestrian facilities that will further improve access to the Plan area from the surrounding 29 communities. Given the planned high level of transit, bicycle, and pedestrian accessibility, it is 30 anticipated that more people will travel to the Diridon area using an alternative mode of 31 transportation than by driving alone, thereby necessitating the need for less parking than is currently required in Downtown for office/R&D and hotel uses(City of San Jose 2014b). 32 33 The parking demand for transit services accounted for by the DSAP under build-out conditions is 34 projected to range from 1,350 to 2,200. The DSAP does not propose to supply new parking facilities 35 specifically for transit users. Rather, the parking demand would be met through surplus spaces to be 36 provided in the new structures associated with future development (City of San Jose 2014b). 37 To continue to meet parking demand generated by the Arena, the existing 1,400-space (approximately) surface lot would remain under build-out conditions. In addition, the DSAP includes 38 39 a 900-space, 2 to 3 level parking structure to provide additional shared parking for the general 40 public. The garage would be located at the northeast corner of St. John Street and Montgomery Street, north of the Arena (City of San Jose 2014b). 41

²⁴ There could be competition for excess parking locations with future residential or commercial development.

- 1 Based on the projected parking ratios, maximum development levels, and projected transit parking
- 2 <u>demand, the total recommended parking supply in the DSAP area would be approximately 11,950</u>
- 3 spaces. As described above, parking would be supplied by future development in the form of
- 4 <u>structured or underground facilities and would provide a modest surplus of just over 600 spaces</u>
- 5 when full-build out is achieved over the 30-year life of the DSAP (City of San Jose 2014b). Thus,
- 6 while the PCEP does not propose to add any additional parking facilities as part of the project or as
 7 mitigation, the DSAP has providing an overall approach to considering and addressing cumulative
- mitigation, the DSAP has providing an overall approach to considering and addressing cumulative
 parking taking into account planned development and planned transit and has provided for meeting
- 9 <u>that demand</u>.
- Caltrain's 2010 Comprehensive Access Program Policy Statement, emphasizes station access by
 walking, transit, and bicycling over automobile access at most stations. The policy targets different
 access strategies at different stations based on the station characteristics and access opportunities.
 For example, the San Francisco 4th and King Station is a transit center where the access priority for
 autos is the lowest priority after transit, walking and bicycle. At intermodal connectivity and
 neighborhood circulator stations, auto access is not a priority. At auto-oriented stations, auto access
 is the primary priority access mode followed by biking.
- 17 Since some of the parking deficits identified above are at stations where providing automobile 18 access is not a priority, provision of substantial additional parking facilities at these stations would 19 conflict with Caltrain's *Comprehensive Access Program Policy Statement*. Where parking deficits are 20 at auto-oriented stations, provision of additional auto parking would be a priority, where feasible. 21 The *Comprehensive Access Program Policy Statement* is implemented by Caltrain in cooperation with 22 local jurisdictions as part of Caltrain's long-term planning and capital improvement program; 23 however access improvements are implemented on a funding available basis. Caltrain also works 24 with local jurisdictions, other transit agencies, and local, state and federal funding partners to fund 25 improvements to access to Caltrain stations via alternatives to automobiles including transit 26 connections, bicycle and walking. Where future investments in these access modes are realized, they 27 will help to reduce some of the excess parking demand. Caltrain is also working with many local 28 jurisdictions concerning transit-oriented developments including exploring shared parking 29 opportunities where appropriate.
- However, despite these efforts, given the funding limitations and long-term nature of Caltrain's
 implementation of its *Comprehensive Access Program Policy Statement*, it is likely that not all of the
 parking deficits will be addressed when the Proposed Project is in operation.
- A parking deficit in and of itself, or the need to find a parking space off-site, while inconvenient is not
 inherently a significant physical impact on the environment. Some station users unaware of the
 parking deficits may circle²⁵ but experienced station users will modify their behavior to take into
- 36 account the parking deficits and take alternative actions. Those actions may include arriving earlier,
- 37 using other nearby stations with available parking²⁶, using the kiss and ride, using parking areas
- 38 further from the station, or accessing the station via other modes such as transit, biking or walking.
- 39 At the extreme, lack of vehicle parking could result in some riders deciding to use an alternative
- 40 transit system, carpool, or drive to their destination alone. This could result in lower Caltrain

²⁵ While circling vehicles may result in additional vehicle emissions, traffic and traffic noise, additional circling is not likely result in substantial additional criteria pollutant emissions, traffic, or noise around Caltrain stations above the thresholds used in this EIR.

²⁶ For example, users of the Hillsdale Station could utilize the nearby Hayward Park and Belmont Stations, which are forecasted to have a parking surplus in 2040.

- 1 ridership than estimated in this EIR. As an unrealistic worst-case example, if the system deficit of
- 2 approximately 2,100 spaces in excess of the Proposed Project were to mean 2,100 fewer Caltrain
- 3 riders, then 2040 ridership would be 2 percent less than predicted. However, given that the
- 4 Proposed Project would still result in a substantial ridership increases (approximately 25,000 in
- 5 2040 compared with the No Project conditions) even in this worst-case situation, the environmental
- 6 consequences would be less than significant as the Proposed Project benefits to regional traffic,
- 7 noise, air quality, and greenhouse gases would still be substantial (though slightly smaller). In this
- 8 scenario, the localized traffic impacts around the stations with parking deficits would be slightly
- 9 better than with full ridership.
- 10The other potential impact of a parking deficit in and around Caltrain stations would be the potential11increased demand for additional off-site parking facilities, the construction of which might result in12other secondary environmental impacts. However, as described above, Caltrain expects that the13dominant response to parking deficits, such as they actually occur, will be behavioral change on the14part of the commuting public, rather than the speculative construction of new off-site parking15facilities.
- 16 Thus, while the Proposed Project may contribute to a cumulative parking deficit, even with
- 17 implementation of its access program, as described above this is not considered to result in a
- 18 significant environmental impact and thus the Proposed Project would not contribute considerably
- 19 to a cumulatively significant impact related to air quality, noise, traffic or greenhouse gas emissions
- 20 or the secondary impacts of construction of parking facilities.

21 Impact to Freight Service

- 22 Cumulative rail service increases along the Caltrain corridor could <u>have impacts upon affect</u> existing
- 23 freight service <u>in two ways: 1) through time constraints due to the requirements for temporal</u>
- 24 separation between Proposed EMUs and freight trains in the FRA waiver, if applicable; and 2)
- 25 through <u>the interaction of potential height restrictions due to OCS installation with future proposals</u>
- 26 <u>by freight operators to use freight equipment taller than today's freight equipment</u>.
- As discussed in Chapter 2 and Section 3.14, Transportation and Traffic, the Proposed Project
 presumes that temporal separation will not be required and thus that changes to freight operational
 windows will not be necessary. Thus, this analysis focused on potential constraints on freight
 heights.

31 The existing levels of freight are approximately 3 round-trip trains per day in the Caltrain corridor 32 north of Santa Clara. On an average day there are an estimated 150 loaded cars per day hauled on 33 the Caltrain corridor and tonnage per loaded car ranges from 85 to 115 tons with an average of 100 34 tons of cargo per railcar (Greenway pers. comm.). This is only a rough estimate and daily averages 35 can vary substantially based on economic conditions, customer needs, type of freight cargo being 36 handled, equipment available and other factors. Based on these assumptions, on average 37 approximately 15,000 tons of freight is being hauled on the Caltrain corridor per day. Assuming 38 truck loads of 20 to 25 tons, this amount of rail freight is equivalent to that which could be carried

- 39 by 600 to 750 trucks loads.
- 40 Local daily freight moves along the Caltrain corridor in length vary from approximately 5 to 7 miles
1 ("South City Local" from the Port of San Francisco to South San Francisco²⁷) to 16 to 18 miles

- 2 ("Broadway" from South San Francisco to the Port of Redwood City) to 35 to 38 miles ("Mission Bay"
- 3 from South San Francisco to San Jose Newhall Yard) in length. Freight hauling from more distant
- 4 locations would have much larger hauling length. While the exact ton-miles per day hauled along the
- 5 Caltrain corridor on average each day is not known, if the daily average of 150 loaded rail cars is
- 6 evenly divided between the three daily moves, then the average freight service could be estimated
- 7 as approximately 300,000 ton-miles.

8 Cumulative Impacts on Freight Service due to Cumulative Increase of Rail Service and Constrained 9 Operational Windows

- 10 The Proposed Project would result in restriction of freight to midnight to 5 a.m. (compared with
- 11 approximately 8 p.m. to 5 a.m. at present²⁸) along the portion of the Caltrain corridor north of Santa
- 12 Clara (north of CP Coast) due to the temporal separation requirements of the FRA waiver. As
- 13 discussed in Section 3.14, *Transportation and Traffic*, while inconvenient and requiring change in
- 14 freight operational practices north of Santa Clara, the compression of freight service hours to
- 15 midnight to 5 a.m. would not be expected to result in a diversion of freight hauling from freight
- 16 trains to trucks (or other modes) at existing levels of freight service.
- 17 The FRA waiver requirements cannot be altered by the JPB on its own; only FRA can decide if
- 18 temporal separation should be required or not for alternately compliant light-weight EMUs. If FRA
- 19 decides that temporal separation is not required in the current rule-making, then it would likely be
- 20 feasible to accommodate the moderate increases in freight included in this analysis without
- 21 diversion to truck or other modes.
- Operations of Amtrak, ACE, DRC and Capitol Corridor would not constrain freight as these services
 operate FRA-compliant vehicles and primarily operate during the day (ACE and Capitol Corridor
 only operate south of Santa Clara where there are dedicated freight tracks).
- The FRA-compliant vehicles are heavier and have the structural strength to operate on the same
 tracks as freight without the temporal separation (BART 2008).
- 27 Blended Service is proposed to operate between 5 a.m. and 12:30 a.m. This would further constrain
- 28 freight operating hours by an additional 30 minutes north of CP coast compared with the Proposed
- 29 Project, given the temporal separation requirements of the FRA waiver, if applicable. With Blended
- 30 Service, freight would be limited to 4.5 hours between 12:30 a.m. to 5:00 a.m. between Santa Clara
- 31 and San Francisco.
- At present, approximately three round-trip trains operate in this part of the Caltrain corridor and
 this could increase to perhaps six round-trip trains by 2040. For this analysis it was assumed that

²⁷ The San Francisco to South San Francisco round trip is not presently completed in a single night. The long-haul trains used on the Caltrain corridor are six-axle trains and the Quint Street Lead can only handle four-axle trains. As a result, the trains making this trip must make an equipment change in mid-trip (from a six-axle locomotive to a four-axle locomotive and vice versa). This change involves many hours related to charging the brake system with air, brake testing and a crew change. Thus, the round-trip takes 24 hours at present.

²⁸-As explained in Section 3.14, *Transportation and Traffic,* the Trackage Rights Agreement (TRA) provides that between midnight and 5 a.m., at least one main track will always be in service for freight. It also provides at least one 30-minute headway window between 10 a.m. and 3 p.m. for freight service. In practice today, freight commonly runs between 8 p.m. and 5 a.m., with occasional daytime service. Freight service hours are not limited by the TRA on the UP-owned MT-1 track between CP Coast and CP Lick (Santa Clara to south of Tamien Station). The FRA waiver requirements would not apply on the UPRR-owned MT-1.

- 1 the daily number of freight trains would double and the increase in service would mirror the pattern
- of daily moves at present. Thus, instead of 1 train daily making the moves discussed above, there
 would be two.
- 4 If freight round trips could not be completed in a single night using a single train consists, then trips
- 5 may need to be staggered over several nights (as is done on the South City Local at present).
- 6 Alternatively, additional trains operating in each direction (one –way transit per night) or lengthier
- 7 trains could be employed in order to maintain the same level of service as a round-trip that could be
- 8 completed in the same night. Another potential response could be routing of freight via rail other
- 9 Bay Area ports (such as at Richmond or Oakland). Such operational changes could affect scheduling
- 10 convenience, cost, and/or competitiveness for freight operators.
- 11Given the low levels of current freight operations on the corridor, the existing freight levels can be12accommodated even with a more constrained operational window and thus a significant cumulative13effect on existing freight service due to Blended Service is not considered likely. However, if freight14rail demand along the San Francisco Peninsula substantially increases in the future, the additional
- 15 freight rail service may be more challenging to accommodate with the small operational window
- 16 and, thus, some freight may be diverted to truck or other modes or diverted to other ports.
- A smaller operational window is more likely to affect the longer freight moves. The South City Local
 already operates over a two night window due to equipment constraints and, thus, is not likely to be
 significantly affected by the constrained operational window. The more lengthy moves, particularly
 from South San Francisco to San Jose, would be more susceptible to time issues. For this analysis, a
 base case was analyzed consisting of diverting the freight of a daily round trip train from South San
 Francisco to San Jose to trucks and a more extreme case of diverting all new freight (three daily
 round trips over existing freight levels).
- 24 Cumulative Impacts on Freight Service due to Changes in Freight Heights and Vertical Clearances
- The Proposed Project would lower the effective vertical clearance at a number of locations (such as
 tunnels and overhead structures such as bridges) along the Caltrain corridor by up to several feet
 due to installation of the OCS. The Proposed Project would include minor modifications at three of
 the San Francisco tunnels and at four roadway overpasses to ensure that adequate vertical clearance
 is provided to accommodate existing freight heights.
- 30 As discussed above, there is a potential that freight service in the future may desire to use higher 31 freight vehicles than are currently operating on the Caltrain corridor. While the Proposed Project 32 would provide adequate vertical clearance for existing freight vehicles (see discussion in Section 33 3.14, Transportation and Traffic), it may not accommodate potential future freight vehicles that 34 could otherwise operate today if the OCS were not installed. Because existing freight would be 35 accommodated, this would not be an impact over baseline. However, there is a potential for a 36 cumulative impact when combining the effect of lowered vertical clearance to accommodate with 37 the OCS with a change in potential freight train height in the future.
- Table 4-23 shows the resultant effective vertical clearances with the Proposed Project and identifies
 whether vertical clearances with the project would be less than existing effective vertical clearances.
- 40 <u>As shown in Table 4-23, if current freight equipment is used, then there would be no impact. If</u>
- 41 <u>higher equipment is proposed, it would be constrained compared to existing conditions, north of the</u>
- 42 San Francisquito Bridge to Bayshore and at the Lafayette Pedestrian Overpass.

1 Table 4-23. Changes in Effective Vertical Clearance with the Proposed Project OCS

						Effective Vertical	Clearance with OCS	<u>Lower than</u> Existing Effective
			Existing E	ffective Clearan	<u>ce(1)</u>	<u>Lineeuve vertieuv</u>	<u>2)</u>	<u>Clearance?</u>
				Existing	Allowable			
		<u>TRA Clearance</u>	Effective Clearance	<u>Freight</u>	<u>Plate Height /</u>	<u>Effective</u>	<u>Allowable Plate</u>	
<u>Milepost</u>	<u>Bridge</u>	<u>(CL)</u>	<u>Over CL</u>	<u>Heights</u>	<u>Plate (3)</u>	<u>Clearance</u> Over CL	<u>Height / Plate (3)</u>	<u>(Y/N)</u>
<u>0.52</u>	Signal	<u>N/A</u>	<u>22.48 (MT-1)</u>	<u>15.50 / C</u>	<u>15.50 / C</u>	<u>20.44 (MT-1)</u>	<u>15.50 / C (4)</u>	<u>N</u>
	Cantilever		<u>23.70 (MT-2)</u>			<u>21.66 (MT-2)</u>		
<u>0.70</u>	Signal	<u>N/A</u>	<u>27.59 (MT-3)</u>	<u>15.50 / C</u>	<u>15.50 / C</u>	<u>25.55 (MT-3)</u>	<u>15.50 / C (4)</u>	<u>N</u>
	Cantilever		<u>28.07 (Lead Track)</u>			<u>26.03 (Lead</u>		
<u>0.88</u>	<u>Signal</u> Captilovor	<u>N/A</u>	<u>25.45 (MT-1)</u>	<u>15.50 / C</u>	<u>15.50 / C</u>	$\frac{23.41 (MT-1)}{22.55 (MT-2)}$	<u>15.50 / C (4)</u>	<u>N</u>
4.4.0		NT / A	<u>25.59 [M1-2]</u>	15 50 / 0		<u>23.55 [M1-2]</u>		
<u>1.10</u>	Signal Bridge	<u>N/A</u>	<u>25.45 (MT-1)</u>	<u>15.50 / C</u>	<u>15.50 / C</u>	$\frac{22.74 (MT-1)}{22.64 (MT-2)}$	<u>15.50 / C (4)</u>	<u>N</u>
	C: 1.D.:1		<u>25.59 [M1-2]</u>	15 50 / 0		<u>22.64 [MT-2]</u>	15 50 / 6 (4)	NT
	Signal Bridge	<u>N/A</u>	<u>23.12 (MT-1)</u>	<u>15.50 / C</u>	<u>15.50 / C</u>	<u>21.08 (MT-1)</u>	<u>15.50 / C (4)</u>	<u>N</u>
1.00		04.05	<u>23.12 (M1-2)</u>	15 50 / 0		<u>21.08 [M1-2]</u>		
<u>1.29</u>	Mariposa	21.25	<u>20.51</u>	<u>15.50 / C</u>	<u>15.50 / C</u>	<u>18.47</u>	<u>15.50 / C (4)</u>	<u>N</u>
<u>1.33</u>	<u>Tunnel 1</u>	<u>21.92 (MT-1)</u>	<u>20.80 (MT-1)</u>	<u>15.50 / C</u>	<u>15.50 / C</u>	<u>17.00 (MT-1)</u>	<u>15.50 / C (4)</u>	<u>N</u>
		<u>21.50 (MT-2)</u>	<u>20.60 (MT-2)</u>			<u>17.00 (MT-2)</u>		
<u>1.72</u>	<u>22nd St.</u>	<u>20.50</u>	<u>19.92</u>	<u>15.50 / C</u>	<u>15.50 / C</u>	<u>16.84</u>	<u>15.50 / C (4)</u>	<u>N</u>
<u>1.87</u>	Signal	<u>N/A</u>	<u>24.81 (MT-1)</u>	<u>15.50 / C</u>	<u>15.50 / C</u>	<u>22.77 (MT-1)</u>	<u>15.50 / C (4)</u>	<u>N</u>
	<u>Cantilever</u>		<u>24.89 (MT-2)</u>			<u>22.85 (MT-2)</u>		
<u>1.90</u>	<u>23rd St.</u>	<u>21.00</u>	<u>20.25</u>	<u>15.50 / C</u>	<u>15.50 / C</u>	<u>17.17</u>	<u>15.50 / C (4)</u>	<u>N</u>
<u>1.93</u>	<u>Tunnel 2</u>	<u>21.74 (MT-1)</u>	<u>20.70 (MT-1)</u>	<u>15.50 / C</u>	<u>15.50 / C</u>	<u>17.00 (MT-1)</u>	<u>15.50 / C (4)</u>	<u>N</u>
		<u>21.33 (MT-2)</u>	<u>20.60 (MT-2)</u>			<u>17.00 (MT-2)</u>		
<u>3.13</u>	<u>Oakdale</u>	<u>20.50</u>	<u>22.68</u>	<u>17.08 / F</u>	<u>17.08 / F</u>	<u>20.64</u>	<u>17.08 / F (5)</u>	<u>N</u>
<u>3.19</u>	<u>Tunnel 3</u>	<u>21.33 (MT-1)</u>	<u>20.80 (MT-1)</u>	<u>17.08 / F</u>	<u>17.08 / F</u>	<u>18.00 (MT-1)</u>	<u> 17.08 / F (5)</u>	<u>N</u>
		<u>21.17 (MT-2)</u>	<u>20.80 (MT-2)</u>			<u>18.00 (MT-2)</u>		
4.15	Paul Ave	19.83	<u>19.83</u>	<u>17.08 / F</u>	<u>17.08 / F</u>	17.79	<u>17.08 / F (5)</u>	N

			Existing Effective Clearance(1)		Effective Vertical Clearance with OCS (2)		<u>Lower than</u> <u>Existing Effective</u> <u>Clearance?</u>	
<u>Milepost</u>	<u>Bridge</u>	<u>TRA Clearance</u> (<u>CL)</u>	<u>Effective Clearance</u> <u>Over CL</u>	<u>Existing</u> <u>Freight</u> <u>Heights</u>	<u>Allowable</u> <u>Plate Height /</u> <u>Plate (3)</u>	<u>Effective</u> <u>Clearance Over CL</u>	<u>Allowable Plate</u> <u>Height / Plate (3)</u>	<u>(Y/N)</u>
<u>4.27</u>	<u>Tunnel 4</u>	<u>21.08 (MT-1)</u> 21.08 (MT-2)	<u>20.20 (MT-1)</u> 20.10 (MT-2)	<u>17.08 / F</u>	<u>17.08 / F</u>	<u>18.00 (MT-1)</u> <u>18.00 (MT-2)</u>	<u>17.08 / F (5)</u>	<u>N</u>
5.10	<u>Signal Bridge</u>	<u>N/A</u>	23.17 (MT-1) 23.08 (MT-2) 23.33 (MT-3) 23.24 (MT-4) 23.60 (Lead Track)	<u>18.92 / > F</u>	<u>20.25 / Н</u>	21.13 (MT-1) 21.04 (MT-2) 21.29 (MT-3) 21.20 (MT-4) 21.56 (Lead Track)	<u>18.92 / >F (6)</u>	Ϋ́
<u>5.48</u>	<u>Signal Bridge</u>	<u>N/A</u>	28.18 (MT-1) 28.36 (MT-2) 28.20 (MT-3) 28.52 (MT-4)	<u>18.92 / > F</u>	<u>20.25 / Н</u>	26.14 (MT-1) 26.32 (MT-2) 26.16 (MT-3) 26.48 (MT-4)	<u>18.92 / >F (6)</u>	Ϋ́
5.83	<u>Signal Bridge</u>	<u>N/A</u>	27.36 (MT-1) 27.42 (MT-2) 27.55 (MT-3) 27.57 (MT-4) 27.57 (Lead track)	<u>18.92 / > F</u>	<u>20.25 / H</u>	25.32 (MT-1) 25.38 (MT-2) 25.51 (MT-3) 25.53 (MT-4) 25.53 (Lead Track)	<u>18.92 / >F (6)</u>	Ϋ́
<u>6.29</u>	<u>Signal Bridge</u>	<u>N/A</u>	27.68 (MT-1) 27.61 (MT-2) 27.90 (MT-3) 27.87 (MT-4) 28.06 (Lead track)	<u>18.92 / > F</u>	<u>20.25 / H</u>	25.64 (MT-1) 25.57 (MT-2) 25.86 (MT-3) 25.83 (MT-4) 26.02 (Lead Track)	<u>18.92 / >F (6)</u>	Ϋ́
<u>6.95</u>	<u>Signal Bridge</u>	<u>N/A</u>	28.10 (MT-1) 28.03 (MT-2) 27.91 (MT-3) 28.01 (MT-4)	<u>18.92 / > F</u>	<u>20.25 / H</u>	26.06 (MT-1) 25.99 (MT-2) 25.87 (MT-3) 25.97 (MT-4)	<u>18.92 / >F (6)</u>	Y

			Existing Effective Clearance(1)		Effective Vertical Clearance with OCS [2]		<u>Lower than</u> <u>Existing Effective</u> <u>Clearance?</u>	
				Existing	Allowable			
<u>Milepost</u>	<u>Bridge</u>	<u>TRA Clearance</u> (CL)	<u>Effective Clearance</u> <u>Over CL</u>	<u>Freight</u> Heights	<u>Plate Height /</u> <u>Plate (3)</u>	<u>Effective</u> <u>Clearance</u> Over CL	<u>Allowable Plate</u> <u>Height / Plate (3)</u>	<u>(Y/N)</u>
<u>8.24</u>	<u>Signal</u> <u>Cantilever</u>	<u>N/A</u>	<u>28.09 (MT-1)</u> <u>27.94 (MT-2)</u>	<u>18.92 / > F</u>	<u>20.25 / H</u>	<u>26.05 (MT-1)</u> <u>25.90 (MT-2)</u>	<u>18.92 / >F (6)</u>	<u>Y</u>
<u>8.60</u>	<u>Oyster Point</u> <u>Parkway</u>	<u>N/A</u>	<u>22.19</u>	<u>18.92 / > F</u>	<u>20.25 / H</u>	20.15	<u>18.92 / >F (6)</u>	Ϋ́
<u>9.10</u>	<u>Signal Bridge</u>	<u>N/A</u>	<u>21.59 (MT-1)</u> <u>21.64 (MT-2)</u>	<u>18.92 / > F</u>	<u>20.25 / H</u>	<u>19.55 (MT-1)</u> <u>19.60 (MT-2)</u>	<u>18.92 / >F (6)</u>	Y
<u>13.71</u>	<u>Signal Bridge</u>	<u>N/A</u>	29.15 (MT-1) 29.10 (MT-2) 29.02 (MT-3)	<u>18.92 / > F</u>	<u>20.25 / Н</u>	27.11 (MT-1) 27.06 (MT-2) 26.98 (MT-3)	<u>18.92 / >F (6)</u>	<u>Y</u>
<u>14.14</u>	<u>Signal Bridge</u>	<u>N/A</u>	28.32 (MT-1) 28.40 (MT-2) 28.20 (MT-3)	<u>18.92 / > F</u>	<u>20.25 / Н</u>	26.28 (MT-1) 26.36 (MT-2) 26.16 (MT-3)	<u>18.92 / >F (6)</u>	Ϋ́
<u>26.20</u>	<u>Signal Bridge</u>	<u>N/A</u>	<u>28.08 (MT-1)</u> 28.06 (MT-2) 28.09 (MT-3)	<u>18.92 / > F</u>	<u>20.25 / H</u>	26.04 (MT-1) 26.02 (MT-2) 26.05 (MT-3)	<u>18.92 / >F (6)</u>	Ϋ́
<u>26.35</u>	<u>Signal</u> <u>Cantilever</u>	<u>N/A</u>	<u>27.74 (MT-2)</u> <u>27.62 (MT-4)</u>	<u>18.92 / > F</u>	<u>20.25 / Н</u>	<u>25.70 (MT-2)</u> <u>25.58 (MT-4)</u>	<u>18.92 / >F (6)</u>	Y
27.12	<u>Signal Bridge</u>	<u>N/A</u>	27.60 (MT-1) 27.62 (MT-2) 27.58 (MT-3) 27.70 (MT-4)	<u>18.92 / > F</u>	<u>20.25 / H</u>	25.56 (MT-1) 25.58 (MT-2) 25.54 (MT-3) 25.66 (MT-4)	<u>18.92 / >F (6)</u>	Ϋ́
<u>29.69</u>	<u>San</u> Francisquito	<u>21.75</u>	<u>21.05</u>	<u>18.92 / > F</u>	<u>20.25 / H</u>	<u>19.11</u>	<u>18.92 / >F</u>	Y
<u>34.00</u>	<u>San Antonio</u> <u>Ave.</u>	<u>N/A</u>	<u>22.14</u>	<u>18.92 / > F</u>	<u>20.25 / H</u>	<u>19.62</u>	<u>18.92 / >F (6)</u>	Ϋ́
36.50	<u>Hwy 85</u>	<u>N/A</u>	22.14	<u>18.92 / > F</u>	<u>20.25 / H</u>	20.10	<u>18.92 / >F (6)</u>	<u>Y</u>
<u>36.88</u>	<u>Whisman Rd.</u>	<u>N/A</u>	22.47	<u> 18.92 / > F</u>	<u>20.25 / H</u>	20.43	<u>18.92 / >F (6)</u>	<u>Y</u>

								Lower than
			Existing Effective Clearance(1)		Effective vertical clearance with OCS		<u>Existing Effective</u> Clearance?	
				Evicting	Allowable	L		<u>orearance:</u>
		TRA Clearance	Effective Clearance	<u>Existing</u> Freight	Plate Height /	Effective	Allowable Plate	
<u>Milepost</u>	<u>Bridge</u>	<u>(CL)</u>	<u>Over CL</u>	<u>Heights</u>	<u>Plate (3)</u>	<u>Clearance</u> Over CL	<u>Height / Plate (3)</u>	<u>(Y/N)</u>
38.60	<u>Mathilda Ae.</u>	<u>N/A</u>	<u>22.37</u>	<u>18.92 / > F</u>	<u>20.25 / H</u>	<u>20.33</u>	<u>18.92 / >F (6)</u>	<u>Y</u>
<u>39.40</u>	<u>Pedestrian</u> <u>Overpass</u>	<u>N/A</u>	<u>21.85</u>	<u>18.92 / > F</u>	<u>20.25 / H</u>	<u>19.81</u>	<u>18.92 / >F (6)</u>	Y
<u>39.46</u>	<u>Signal Bridge</u>	<u>N/A</u>	<u>27.86 (MT-1)</u>	<u>18.92 / > F</u>	<u>20.25 / H</u>	<u>25.82 (MT-1)</u>	<u>18.92 / >F (6)</u>	<u>Y</u>
			<u>27.75 (MT-2)</u>			<u>25.71 (MT-2)</u>		
			<u>27.93 (MT-3)</u>			<u>25.89 (MT-3)</u>		
			<u>27.71 (MT-4)</u>			<u>25.67 (MT-4)</u>		
<u>40.14</u>	<u>Signal Bridge</u>	<u>N/A</u>	<u>29.28 (MT-1)</u>	<u>18.92 / > F</u>	<u>20.25 / H</u>	<u>27.24 (MT-1)</u>	<u>18.92 / >F (6)</u>	<u>Y</u>
			<u>29.22 (MT-2)</u>			<u>27.18 (MT-2)</u>		
			<u>29.38 (MT-3)</u>			<u>27.34 (MT-3)</u>		
			<u>29.44 (MT-4)</u>			<u>27.40 (MT-4)</u>		
40.75	<u>Lawrence</u>	<u>N/A</u>	22.13	<u>18.92 / > F</u>	<u>20.25 / H</u>	<u>20.09</u>	<u>18.92 / >F (6)</u>	<u>Y</u>
	<u>Expressway</u>							
<u>40.90</u>	<u>Signal Bridge</u>	<u>N/A</u>	<u>27.17 (MT-1)</u>	<u>18.92 / > F</u>	<u>20.25 / H</u>	<u>25.13 (MT-1)</u>	<u>18.92 / >F (6)</u>	<u>Y</u>
			<u>27.15 (MT-2)</u>			<u>25.11 (MT-2)</u>		
			<u>27.29 (MT-3)</u>			<u>25.25 (MT-3)</u>		
			<u>27.24 (MT-4)</u>			<u>25.20 (MT-4)</u>		
<u>41.51</u>	<u>Signal Bridge</u>	<u>N/A</u>	<u>27.82 (MT-1)</u>	<u>18.92 / > F</u>	<u>20.25 / H</u>	<u>25.78 (MT-1)</u>	<u>20.25 / H</u>	<u>N</u>
			<u>27.80 (MT-2)</u>			<u>25.76 (MT-2)</u>		
			<u>27.81 (MT-3)</u>			<u>25.77 (MT-3)</u>		
			<u>27.91 (MT-4)</u>			<u>25.87 (MT-4)</u>		
<u>42.50</u>	<u>San Tomas</u> Expressway	<u>N/A</u>	<u>22.37</u>	<u>18.92 / > F</u>	<u>20.25 / H</u>	<u>21.33</u>	<u>20.25 / H</u>	<u>N</u>
<u>43.65</u>	<u>Lafayette</u> <u>Pedestrian</u> <u>Overpass</u>	<u>N/A</u>	22.25	<u>18.92 / > F</u>	<u>20.25 / Н</u>	20.21	<u>18.92 / >F</u>	Y
45.90	<u>I-880</u>	<u>N/A</u>	<u>22.46</u>	<u>20.25 / H</u>	<u>20.25 / H</u>	20.42	<u>20.25 / H</u>	<u>N</u>
46.15	Hedding Ave.	<u>N/A</u>	22.07	<u>20.25 / H</u>	<u>20.25 / H</u>	20.25	<u>20.25 / H (7)</u>	<u>N</u>

								Lower than
			<u>Existing</u> Ef	fective Clearand	<u>ce(1)</u>	Effective Vertical Clearance with OCS (2)		<u>Clearance?</u>
<u>Milepost</u>	<u>Bridge</u>	<u>TRA Clearance</u> (CL)	Effective Clearance Over CL	<u>Existing</u> <u>Freight</u> <u>Heights</u>	<u>Allowable</u> <u>Plate Height /</u> <u>Plate (3)</u>	<u>Effective</u> <u>Clearance Over CL</u>	<u>Allowable Plate</u> <u>Height / Plate (3)</u>	<u>(Y/N)</u>
46.34	<u>Signal</u> <u>Cantilever</u>	<u>N/A</u>	<u>24.06 (MT-2)</u>	<u>20.25 / H</u>	<u>20.25 / H</u>	<u>22.02 (MT-2)</u>	<u>20.25 / H</u>	<u>N</u>
<u>46.50</u>	<u>Signal</u> <u>Cantilever</u>	<u>N/A</u>	<u>27.23 (MT-2)</u> <u>27.50 (MT-3)</u>	<u>20.25 / Н</u>	<u>20.25 / H</u>	<u>25.19 (MT-2)</u> <u>25.46 (MT-3)</u>	<u>20.25 / H</u>	<u>N</u>
<u>47.0</u>	Cahill Station	<u>15.67</u>	<u>Structure does not</u> <u>exist</u>	<u>20.25 / Н</u>	<u>20.25 / H</u>	<u>N/A</u>	<u>N/A</u>	<u>N</u>
<u>47.05</u>	<u>Signal Bridge</u>	<u>N/A</u>	27.88 (MT-2) 28.05 (MT-3) 28.13 (Lead Track)	<u>20.25 / H</u>	<u>20.25 / H</u>	25.84 (MT-2) 26.01 (MT-3) 26.09 (Lead <u>Track)</u>	<u>20.25 / H</u>	N
47.30	<u>Signal Bridge</u>	<u>N/A</u>	<u>23.56 (MT-2)</u> <u>23.44 (MT-3)</u>	<u>20.25 / Н</u>	<u>20.25 / H</u>	<u>21.52 (MT-2)</u> 21.40 (MT-3)	<u>20.25 / H</u>	<u>N</u>
47.89	<u>San Carlos</u> <u>Ave.</u>	<u>22.17</u>	<u>21.53</u>	<u>20.25 / H</u>	<u>20.25 / H</u>	<u>20.25</u>	<u>20.25 / H (7)</u>	N
<u>49.13</u>	<u>Signal</u> Cantilever	<u>N/A</u>	<u>23.08 (MT-2)</u>	<u>20.25 / H</u>	<u>20.25 / H</u>	<u>21.04 (MT-2)</u>	<u>20.25 / H</u>	<u>N</u>
<u>50.55</u>	<u>Signal</u> <u>Cantilever</u>	<u>N/A</u>	<u>27.76 (MT-2)</u>	<u>20.25 / Н</u>	<u>20.25 / H</u>	<u>25.72 (MT-2)</u>	<u>20.25 / H</u>	N
50.59	<u>Curtner Ave.</u>	<u>N/A</u>	<u>21.99</u>	<u>20.25 / H</u>	<u>20.25 / H</u>	<u>20.25</u>	<u>20.25 / H (7)</u>	<u>N</u>
<u>50.65</u>	<u>Signal</u> <u>Cantilever</u>	<u>N/A</u>	<u>27.72 (MT-2)</u>	<u>20.25 / Н</u>	<u>20.25 / H</u>	<u>25.68 (MT-2)</u>	<u>20.25 / H</u>	<u>N</u>
<u>51.08</u>	<u>Private</u> Overpass	<u>N/A</u>	<u>21.96</u>	<u>20.25 / H</u>	<u>20.25 / H</u>	20.25	<u>20.25 / H</u>	N
51.64	<u>Signal</u> <u>Cantilever</u>	<u>N/A</u>	<u>25.24 (MT-2)</u>	<u>20.25 / H</u>	<u>20.25 / H</u>	<u>23.20 (MT-2)</u>	<u>20.25 / H</u>	N

								Lower than
						Effective Vertical	Clearance with OCS	Existing Effective
			<u>Existing E</u>	ffective Clearan	<u>ce(1)</u>	<u>(</u>	<u>2)</u>	<u>Clearance?</u>
				<u>Existing</u>	<u>Allowable</u>			
		<u>TRA Clearance</u>	Effective Clearance	Freight	<u> Plate Height /</u>	<u>Effective</u>	Allowable Plate	
<u>Milepost</u>	<u>Bridge</u>	<u>(CL)</u>	<u>Over CL</u>	<u>Heights</u>	<u>Plate (3)</u>	Clearance Over CL	<u>Height / Plate (3)</u>	<u>(Y/N)</u>
Notes:								
Existing e	ffective clearan	<u>ce is defined as t</u>	<u>he existing clearance n</u>	neasured over t	the centerline of	the track minus 6 in	<u>ches of dynamic env</u>	<u>elope per Caltrain</u>
<u>Standards</u>			-				-	
Effective v	vertical clearand	ce with OCS is de	fined as existing cleara	nce measured	over the centerli	ne of the track minu	s 1.5 feet of OCS stru	<u>cture depth and</u>
<u>1.04 feet c</u>	of electrical clea	arance envelope.	Includes Proposed Pro	ject notching/lo	owering at sever	al tunnels and track	lowering at 4 under	passes (see
Section 3.	<u>14)</u>							
Allowable	Plate Height /	Plate takes into a	account for clearance r	estrictions dow	nstream. Allowa	<u>ble Plate Height / Pl</u>	ate at tunnels are no	t constrained by
measurem	ent over cente	r line of track but	t by the tunnel walls. P	late Heights are	e as defined by A	AR: Plate C = 15.50';	Plate F = 17.08'; Pla	te H = 20.25'. Due
to the sha	pe of the tunne	ls, a vehicle with	a height greater than I	<u>Plate C, 15.50' ca</u>	an clear through	the tunnels dependi	ng on the width of t	<u>ne vehicle.</u>
Effective v	vertical clearand	ce North of Tunn	el 3 is constrained by '	Funnels 1 and 2	. Design conside	rations from the pro	<u>ject will maintain cl</u>	earance for a Plate
<u>C</u>								
Effective v	vertical clearand	ce from Bayshore	e to the Ouint Street Le	ad to the Port o	of SF is constraine	ed by Tunnels 3 and	4. Design considerat	<u>ions</u> from the
<u>project wi</u>	<u>ll maintain clea</u>	arance for a Plate	<u>F.</u>					
Effective v	vertical clearand	ce from Bayshore	e to the Butterhouse Sp	our at MP 41.4 r	restricted to 18.9	2' due to San Francis	squito Bridge clearai	nce. Actual
<u>physical c</u>	learance with (OCS may be highe	r than effective clearar	<u>nce.</u>				
<u>Project de</u>	<u>sign to provide</u>	Plate H clearanc	<u>e.</u>					
<u>Analysis a</u>	ssumes that M	T-1 South of CP C	oast at MP 44.0 (MP 4	3.4) is not electi	rified and thus th	<u>iere's no change to e</u>	xisting MT-1 clearar	<u>ce or impact to</u>
freight tra	ffic South of CF	<u>Coast.</u>						

1

1The potential restriction of the ability to utilize higher freight trains would most likely result in the2continued use of freight equipment similar to that used at present which would conform to the3clearances provided with the Proposed Project. This could potentially mean reliance on longer4trains using lower cars for future expanded freight service. Alternatively, freight could be diverted to5other modes (such as truck) or to other destinations (such as the Port of Oakland or Port of6Richmond).

7 At present, approximately three round-trip <u>freight</u> trains operate in this part of the Caltrain corridor.

- 8 and, This could increase to perhaps four round-trip trains by 2020²⁹ and as shown in Table 4-8
- 9 perhaps six round-trip <u>freight</u> trains by 2040. Since the existing freight can be accommodated by the
- Proposed Project, the maximum potential diversion to other modes would be three round-trip
 freight trains by 2040. It is probable that the additional trains would just use lower train cars similar
- 12 to existing freight trains and no diversion would occur due to changes in height. The South City Local
- 13 would likely not be affected because tunnel heights already heavily constrain potential equipment
- and the Proposed Project would accommodate existing freight heights. It is also likely that any
 additional mid-Peninsula freight moves could also be accommodated by using freight equipment
- 16 similar to existing freight equipment. Thus, a base case was analyzed assuming that the freight
- 17 associated with one future daily round-trip train from South San Francisco to San Jose might be
- 18 diverted to trucks because of Proposed Project height changes with the OCS <u>in 2020</u>. A more
- extreme case of diverting all new freight (three daily round trips over existing freight levels) to
 trucks was also analyzed for 2040.

21Analysis of Environmental Effects due to Potential Diversion of Small Amounts of Freight from Rail to22Trucks

Business effects by themselves would not be considered environmental impacts, unless somehow
the change in train operations would result in secondary physical environmental impacts. Such
effects would only occur if there was a diversion of freight from rail to trucks (or other modes)
which would then result in secondary environmental impacts such as additional traffic, noise,
criteria pollutant emissions or GHG emissions compared with rail freight operations, which are
discussed below.

29 Traffic

30 If the freight associated with one additional South San Francisco–San Jose freight train with 50

loaded cars were diverted to trucks (assuming 100 tons of cargo per railcar), then the

approximately 5,000 tons of freight would need to be carried by 200 to 250 trucks. Assuming an 80
 mile round trip for trucks, the additional regional miles would be 16,000 to 20,000 miles.

34 As discussed in Section 3.14, *Transportation and Traffic*, and this section, the Proposed Project

- would lower Regional VMT by 235,000 miles in 2020 and 619,000 miles in 2040 (with Caltrain Full
- 36 Electrification) compared with No Project conditions. The VMT reduction would particularly benefit
- 37 traffic congestion on major arterials and freeways used for longer-distance commutes. The resulting
- 38 reduction in regional VMT emissions would be vastly larger than the potential increased truck traffic
- 39 if the freight from the one example daily freight train from South San Francisco to San Jose were
- 40 diverted to trucks. This conclusion would hold even if the amount of diverted freight daily consisted

²⁹ The cumulative growth in freight for Table 4-8 was assumed to be 4 percent per year. At this rate, by 2020, freight could increase from 3 to 4 round-trip trains on the Redwood City to San Francisco segment.

- 1 of all three new daily trains. As a result, the diversion of limited amounts of freight from train to
- 2 truck is not identified as a significant cumulative regional traffic impact as the positive regional
- traffic benefits of the Proposed Project would vastly outweigh the likely regional traffic effects of
 potential diversion of small amounts of freight traffic.
- + potential diversion of small amounts of freight traine.
- However, the diversion of freight from one round trip train to truck could result in 200 to 250
 additional truck trips per weekday along the congested San Francisco Peninsula <u>by 2020</u>. Diversion
- additional truck trips per weekday along the congested san Francisco Pennisula <u>by 2020</u>. Diversion
 of freight from three round trip trains would add 600 to 750 truck trips per weekday <u>by 2040</u>.
- 8 Without knowing specific routing and timing, it is difficult to make conclusions about the impact on
- 9 traffic congestion. Where truck routing is during peak hours on localized intersections with failing
- 10 conditions that the Proposed Project does not benefit, additional truck traffic potentially diverted
- 11 from the Caltrain corridor could contribute to significant cumulative localized traffic impacts.
- 12 Noise
- 13 For noise, there is a tradeoff between freight train noise along the Caltrain ROW and truck noise 14 along truck haul routes. While train noise would be lowered along the Caltrain corridor, truck noise 15 would be increased along haul routes. Existing freight train noise crosses through a mix of 16 residential, commercial, and industrial areas along the Caltrain corridor between San Jose and San 17 Francisco. Without knowing specific truck routing and timing (day or night), it is difficult to make 18 site-specific conclusions about the sensitive receptors affected by potentially increased truck traffic. Regionally, the diversion of freight to trucks is unlikely to result in substantial increase in the 19 20 number of sensitive receptors along truck haul routes compared with the relatively high number of 21 sensitive receptors affected by freight noise along the Caltrain corridor already. However, it is 22 possible that there may be localized noise increased due to diverted freight truck traffic and, thus, 23 that diverted truck hauling could contribute to potential cumulative noise along new truck haul 24 routes.

25 Air Quality

- 26 Freight trains are considered more efficient than trucks for long-hauling of materials and thus result 27 in less overall criteria pollutant emissions on a ton-mile basis. For example, a recent study of 28 increasing freight rail transport for goods from the Salinas Valley concluded that criteria pollutants 29 could be reduced by 12 to 45 percent (depending on the pollutant) compared with current hauling 30 by truck (Transystems 2011). The EPA has noted that, on a ton-mile basis, trains are 2 to 4 times 31 more fuel efficient and have one-half to one-third the NOx emissions compared with trucks (USEPA 32 2010). One comparison of trains vs. trucks described that railroads carry 455 ton-miles/gallon of 33 diesel vs. 105 ton-miles/gallon of diesel for trucks (Brown and Hatch 2002).
- As an example, the additional freight train trip per day carrying 5,000 tons (50 loaded cars) one-way
- 35 from San Francisco to San Jose (distance of 37 miles/185,000 ton-miles) could not be
- accommodated, the daily increase due to truck emissions was estimated as approximately <u>102</u>101
- to 204 202 pounds (lbs) of NO_x (using EPA assumptions noted above) which would easily exceed the
 BAAQMD's daily threshold of 54 lbs/day for NOx. ³⁰
- 39 As discussed in Section 3.2, *Air Quality*, the Proposed Project would lower NOx emissions by
- 40 <u>5662,400 lbs/day in 2020 and 1,400 1,600 lbs/day in 2040 (with Caltrain Full Electrification)</u>
- 41 compared with No Project conditions. This reduction in NO_x emissions would be vastly larger than

³⁰ Calculations are provided in Appendix B, *Air Quality and Greenhouse Gas Analysis Technical Data*.

- 1 the potential increased NO_X emissions if the example daily freight trip from South San Francisco to
- 2 San Jose were diverted to trucks <u>for 2020</u>. <u>For 2040</u>, this conclusion would hold even if the amount
- 3 of freight diverted daily were two to three times larger than estimated above for the single daily trip.
- 4 In addition, as noted above, freight will continue to be able to use freight equipment of the same
- 5 <u>heights as at present, and thus the likelihood of substantial diversion of freight to trucks is</u>
- 6 <u>considered very low.</u> As a result, no significant cumulative impact to air quality is identified due to
- 7 the potential diversion of limited amounts of train freight to trucks.

8 Greenhouse Gas Emissions

As noted above, freight trains are considered more efficient than trucks for long-hauling of materials
and thus result in less overall greenhouse gas emissions on a ton-mile basis. For example, the recent
study of increasing freight rail transport for goods from the Salinas Valley cited above also
concluded that greenhouse gas emissions could be reduced by 59 percent compared with current
hauling by truck (Transystems 2011). The EPA has also noted that, on a ton-mile basis, trains emit
one-third the GHG emissions of trucks (USEPA 2010).

- If the example daily haul trip (described above for the air quality analysis) was diverted daily for a
 period of over one year <u>in 2020</u>, annual GHG emissions (using EPA estimate of one-third GHG
 emissions for freight rail vs. trucks and assuming 260 days/year) would increase by approximately
 2,500 metric tons of CO2e (MT CO₂e) per year due to diversion from freight rail to trucks.³¹
- 19 As discussed in Section 3.6, *Greenhouse Gas Emissions and Climate Change*, the Proposed Project 20 would lower annual GHG emissions by approximately 79,000 68,000 MT CO2e /year in 2020 and 21 189,000 177,000 MT CO2e/year in 2040 (with full Caltrain electrification) compared with No Project 22 conditions. This reduction in GHG emissions would be vastly larger than the potential increased GHG 23 emissions if the example daily trip from South San Francisco to San Jose were diverted to trucks. 24 This conclusion would hold even if the amount of freight diverted daily were two to three times 25 larger than estimated above by 2040. As a result, although adverse, no significant cumulative impact 26 to greenhouse gas emissions is identified due to the potential diversion of limited amounts of train
- 27 freight to trucks.

28 Conclusion

- 29 As described above, the actual potential for diversion of freight is considered low and the low levels
- 30 of existing and future freight can likely be accommodated even with more constrained operational
- 31 windows and the changes in heights due to the Proposed Project OCS. Even if limited diversion of
- 32 freight from trains occurs, it is not likely to result in significant secondary regional traffic, air quality
- 33 or greenhouse gas emissions impacts because of the positive effects of the Proposed Project.
- However, there is the potential for localized noise and traffic effects as a result of diverting some
 future increases in freight carried by rail to trucks because of changes in the operational window or
 lowered vertical height due to the OCS. This is considered a potentially significant cumulative impact
- 37 on localized noise and localized traffic.
- 38 Relative to operational windows, the FRA waiver requirements for temporal separation are not
- 39 under the control of Caltrain. Constraining operational windows for Caltrain and other passenger
- 40 railroads to allow for untrammeled freight access from 8 p.m. to 5 a.m. would be counterproductive

³¹ Calculations are provided in Appendix B, Air Quality and Greenhouse Gas Analysis Technical Data.

- 1 to the Proposed Project's purpose of expanding passenger rail service and would only result in
- 2 additional air quality and greenhouse gas emissions and regional traffic. Thus, impacts associated
- 3 with smaller operational windows relative to future potential freight increases is considered
 4 cumulatively significant and unavoidable.
- To manage the potential constraint on future freight hauling along the Caltrain corridor due to
 lowered vertical clearances, Mitigation Measure TRA-CUMUL-3 is proposed. With implementation of
 this mitigation, freight hauling heights would not be limited by installation of the OCS.
- 8 Caltrain evaluated the feasibility of providing additional vertical clearance at the San Francisquito 9 bridge. Due to the nature of the existing truss structure, gains in vertical clearance could only be 10 made by rebuilding the existing bridge. San Francisquito Bridge is a historic bridge and rebuilding or 11 replacing the bridge would result in the loss of its historic character. Costs would be an estimated 12 \$48 million with a project duration of 6.5 years). Construction would require disruption to both 13 passenger and freight rail unless a temporary bridge were built. Construction of a temporary bridge 14 and/or replacement of the existing bridge would disturb San Francisquito Creek which is habitat for 15 listed steelhead and California red-legged frog. Construction would not be allowed to use access 16 from the east side of the ROW due to the presence of the "El Palo Alto" redwood tree. Disturbance on 17 the west side would result in disturbance of riparian vegetation. Despite the cost and environmental damage, replacement of the bridge would only result in a minimal gain in vertical clearance (from 18 19 19' to 20.25'). Existing freight Santa Clara to Bayshore only uses 18.92' height freight cars at present 20 and there is no reason that additional trains in the future could not use the same equipment to serve 21 customers along the Corridor. Given the cost and environmental impact and the minimal height gain, 22 Caltrain does not propose to rebuild this bridge as part of Mitigation Measure TRA-CUMUL-3.
- 23 An alternative approach to the San Francisquito Bridge vertical clearance would be to provide a 24 short "neutral section" in which the OCS would have a non-electrified segment through the bridge. 25 This approach has been used for several short areas of electrified railroads in the UK in areas of 26 constrained overhead clearance, but has only been recommended for low speed, low frequency 27 branch lines (Network Rail 2013, Network RUS Alternative Solutions). Mitigation Measure TRA-28 CUMUL-3 requires assessment of the feasibility of a neutral section for the San Francisquito Bridge 29 location. If a neutral section is feasible while supporting project service objectives and safety, then 30 Mitigation Measure TRA-CUMUL-3 would require the use of neutral section at the San Francisquito 31 Bridge location as necessary to accommodate actual freight use of Plate H equipment north of Santa 32 Clara (as noted previously, at present freight operators are not using Plate H equipment north of San 33 lose).
- 34 However, if a neutral section is not feasible at San Francisquito Bridge, freight heights from 35 Bayshore (MP 5.5) to the Butterhouse Spur (MP 41.4) would be limited to 18.92' (Plate F+) which is the height of current equipment, but is less than the existing effective clearance on this segment of 36 37 approximately 20.25' (Plate H). There are no freight spurs from the San Francisquito Bridge (MP 38 29.7) to the Butterhouse Spur (MP 41.4), so Mitigation Measure TRA-CUMUL-3 only includes 39 improvements south of the Butterhouse Spur if a neutral section is not feasible at the San 40 Francisquito Bridge. 41 Thus, with Mitigation Measure TRA-CUMUL-3, vertical clearances from the south end of the project
- 41 Thus, with Mitigation Measure TKA-COMOL-3, Vertical clearances from the south end of the project
 42 (MP 52.0) to the Butterhouse Spur (MP 41.4) would allow Plate H equipment similar to today's
 43 existing effective conditions. If Plate H clearance cannot be provided at the San Francisquito Bridge
 44 observation of the provided at the San Francisquito Bridge
 44 observation of the provided at the San Francisquito Bridge
- 44 through use of a neutral section, from the Butterhouse Spur to Bayshore, Plate F+ (18.92')

1 2 3 4	equipment could be used the same as under today's operations, but Plate H equipment could not be used. North of Bayshore, the project's proposed tunnel improvements would provide the same effective vertical clearance as present, and no additional tunnel improvements are included as mitigation.
5 6 7 8	If Plate H clearance cannot be provided at the San Francisquito Creek Bridge through use of a neutral section, Mitigation Measure TRA-CUMUL-3 would be limited to track lowering at the Lafayette Pedestrian Overpass (MP 43.65) to provide Plate H clearance to allow Plate H clearance to be able to access the Butterhouse Spur.
9 10 11 12 13 14 15 16 17 18 19 20 21	The residual cumulative impact would be a future constraint on train equipment to existing freight heights from the Butterhouse Spur to Bayshore to Plate F+ (18.92') instead of the current possible Plate H (20.25') clearance. While it is not likely that freight will be diverted to truck modes due to this change, given that existing Plate H equipment is not used on this portion of the corridor, it is possible there might be a mode shift for some of the future freight growth. As discussed above, this would not be a significant regional traffic, air quality or GHG emissions cumulative impact, but might result in some localized noise or traffic impacts, depending on location of truck haul routes, timing, and intensity. This is considered a significant and unavoidable impact, primarily due to the concerns described above concerning the San Francisquito Bridge. As noted in Mitigation Measure TRA-CUMUL-3, additional site improvements may be necessary in the future to accommodate higher freight heights. Potential additional track lowering and minor notching improvements would likely have similar effects to the Proposed Project's minor notching/track lowering activities at three tunnel and bridge locations.
22 23 24 25 26 27	However, if Plate H clearance can be provided at the San Francisquito Bridge through use of a neutral section, then Mitigation Measure TRA-CUMUL-3 would require track lowering and/or neutral sections (if feasible) at additional locations to allow Plate H equipment operation from San Jose to Bayshore. In this scenario, Plate H clearance would be provided from San Jose to Bayshore, similar to that available today (but not utilized) and there would not be a potential for shift of freight from rail to truck modes and this impact would be mitigated to a less than significant level.
28 29 30 31 32 33 34 35 36	However, potential modifications for this mitigation could be more extensive than those included in the Proposed Project and may or may not be feasible. For example, while track lowering and complete rebuild of the tunnel portals are technically feasible to rectify potential tunnel impediments, these solutions are costly and would results in major disruptions to existing operations and to the character of the San Francisco tunnels, which are historic resources. Similarly, modification at other historic bridges or underpasses, such as the San Francisquito Creek bridge, could result in greater impacts related to cultural resources than under the Proposed Project. Given that potential future modifications are not defined at this time, secondary physical impacts are considered potentially significant and unavoidable.
37 38 39 40	Mitigation Measure TRA-CUMUL-3: As warranted, Caltrain and freight operators will partner to provide <u>Plate H clearance as feasible between San Jose and Bayshore-site</u> improvements to restore existing effective vertical height clearances along the Caltrain corridor.
41 42 43	Caltrain and freight operators share responsibility for the potential constraints that may occur due to the combination of a change in freight operating equipment and the installation of the OCS.

1	Bayshore to Butterhouse Spur (MP 41.4)
2 3 4 5 6	If freight operators identify a plan to operate freight railcars along the Caltrain corridor between Bayshore and the Butterhouse Spur (MP 41.4) that would be hindered by the OCS installation compared with existing conditions, then Caltrain and freight operators shall evaluate the feasibility to provide Plate H effective vertical height clearances where needed along this segment of the Caltrain corridor.
7 8 9 10 11	The evaluation shall first include a feasibility assessment of a "neutral section", or unelectrified segment, for the San Francisquito Bridge. If the use of a "neutral section" is feasible without compromising project service improvement objectives or safety, then a combination of track lowering and "neutral sections" (if feasible) shall be used to provide Plate H clearance between Bayshore and the Butterhouse Spur (MP 41.4).
12 13 14 15 16	Based on current analysis (see Table 4-23) apart from San Francisquito Bridge, additional vertical clearance height would be required at the following locations to support Plate H equipment: Oyster Point Parkway (MP 8.60, +0.1'), Signal Bridge (MP 9.10, +0.7'), San Antonio Avenue (MP 34.0, +0.63'), Highway 85 (MP 36.5, +0.15'), Pedestrian Overpass (MP 39.40, +0.44') and Lawrence Expressway (MP 40.75, +.16').
17 18 19	If a "neutral section" is not feasible at the San Francisquito Bridge and thus the entire segment would be constrained by the low point at the San Francisquito Bridge, then no further improvements are required between Bayshore and the Butterhouse Spur.
20	Butterhouse Spur (MP 41.4) to MP 52.0
21 22 23 24 25	If freight operators identify a plan to operate freight railcars along the Caltrain corridor <u>between</u> <u>MP 52.0 and the Butterhouse Spur (MP 41.4)</u> that would be hindered by the OCS installation compared with existing conditions, then Caltrain and freight operators shall implement site improvements to restore effective vertical height clearances where needed along the Caltrain corridor.
26 27 28 29 30	Based on current analysis, the only proposed improvement in addition to the Proposed Project tunnel notching/track lowering at the four San Francisco tunnels and the track lowering at Hedding Avenue (MP 46.15), San Carlos Avenue (MP 47.89), Curtner Avenue (MP 50.59), a private overpass (MP 51.08), would be track lowering at the Lafayette Pedestrian Overpass (MP 43.65).
31 32 33 34	Possible solutions to rectify the reduction in existing clearance at the tunnels can include deeper notching, track lowering, combination of notching and track lowering, or a complete rebuild of the tunnel portal. Probing of tunnel lining will determine the existing condition of tunnel linings and the necessary solution to rectify the impediments.
35	Both Segments
36 37 38 39 40	Track lowering is a possible solution to rectify the reduction in clearance at constrained bridge overcrossings, but further study will be required to determine the condition of track subgrade in each specific area and to locate existing utilities that may impact the track lowering. If it is determined existing utilities are in the way of potential track lowering, the existing utilities will have to be relocated in order to achieve the desired clearance.

- 1This mitigation is limited to site improvements designed to restore existing effective vertical2clearance only. The effective vertical clearance shall be defined not only by the individual3vertical clearance at a particular constraint point, but also by the constraints along the corridor4leading to that constraint point. For example, Tunnel 4 today has lower clearances than Tunnel 25or Tunnel 3 and effectively limits the height of trains that can transit through Tunnels 2 through64. This mitigation is limited to restoring effective vertical clearance that can actually be used7taking into account all constraints along the corridor.
- 8 Caltrain and the freight operators shall apportion any cost pursuant to the existing agreement9 between the parties.
- Presuming that any identified improvements will be implemented by an entity that is subject to
 CEQA, those improvements would need to be analyzed for their environmental impacts, as
 warranted, to determine if any additional significant impacts beyond those disclosed in this EIR
 for clearance improvements (e.g., those described in Chapter 2, *Project Description*).
- 14 Environmental clearance shall be obtained, if necessary and required, prior to construction of
- 15 any additional site improvements.
- All relevant mitigation included in this EIR would apply to any additional construction necessary
 to implement this mitigation measure.

4.2 Significant and Unavoidable Environmental Impacts

- 19 Impacts related to the following topics would remain significant and unavoidable with the20 implementation of mitigation.
- Construction
- Cultural Resources As described in Section 3.2, *Cultural Resources*, due to tunnel
 modifications necessary to provide heights for Caltrain and freight rail cars, the
 modifications to historic San Francisco Tunnel 4 may be significant and unavoidable even
 with mitigation.
 - Noise—As described in Section 3.11, *Noise and Vibration*, although project mitigation would reduce noise in many locations, given nighttime construction it may not always be possible to reduce construction noise to a less-than-significant level.
- Operations

26

27

28

- 30•Aesthetics—As described in Section 3.1, Aesthetics, although project mitigation would31reduce tree removal/trimming effects in many locations, it may not always be possible to32replace trees in locations that would avoid significant changes in localized visual character33at individual parcels affected by tree removal/pruning. As described in Section 4.1,34Cumulative Impacts, the Proposed Project would also contribute considerably to cumulative35effects on local visual character, relative to tree removals/pruning.
- Hydrology and Water Quality As described in Section 3.9, *Hydrology and Water Quality*, the
 Caltrain ROW, including new Proposed Project facilities may be subject to future flooding
 associated with sea level rise. Although project mitigation may be able to reduce the
 potential impacts of future flooding on the Proposed Project, given that effective coastal
 flooding mitigation requires the involvement of multiple parties beyond Caltrain, at this

1		time it cannot be concluded that future flooding impacts to the Caltrain system will be fully
2		avoided. As described in Section 4.1, <i>Cumulative Impacts</i> , this would also be considered a
3		potential considerable contribution to a significant cumulative impact. As described in
4		Section 3.9, <i>Hydrology and Water Quality</i> , given the <i>Ballona Wetlands</i> decision, it is unknown
5		whether or not the impacts of sea level rise on a project are properly considered significant
6		impacts under CEQA and thus this EIR discloses this impact for disclosure purposes in case
7		they are.
8	0	Noise—As described in Section 4.1, Cumulative Impacts, with cumulative passenger and
9		freight rail increases along the Caltrain corridor there would be significant noise increases
10		affecting sensitive receptors. Where mitigation is not feasible to reduce the Proposed
11		Project's noise contribution, the Proposed Project would also contribute to cumulative noise
12		impacts at a number of locations.
13	0	Transportation and Traffic: As described in Section 3.14, Transportation and Traffic,
14		although project mitigation would reduce localized traffic impacts at a number of affected
15		locations, it would not be feasible to reduce all localized traffic impacts with mitigation. As
16		described in Section 4.1, <i>Cumulative Impacts</i> , the Proposed Project would also have a
17		considerable contribution to a significant cumulative impact on localized traffic conditions,
18		even with mitigation, and a potentially significant cumulative impact related to localized
19		traffic and noise resulting from the diversion of limited amounts of freight from rail to truck
20		modes (although diversion of freight to trucks is an unlikely impact).

4.3 Significant and Irreversible Environmental Changes

The Proposed Project would involve installation of OCS and TPFs along the 51-mile project corridor,
 which would require the use of materials such as steel and copper, as well as fossil fuels, during
 construction. The source metals used, unless they come from recycled materials, would represent an
 irreversible use of resources. Fossil fuels used during construction would also represent an
 irreversible use of oil and natural gas.

The Proposed Project also would require electrical energy to power the new EMUs. Section 4.5,
 Energy, documents the Proposed Project's energy consumption.

29 The Proposed Project would require electrical energy to power new EMUs. While the Proposed

30 Project would use far more electricity than the present Caltrain system uses, the Proposed Project

31 would use far less diesel fuel. When calculating the overall energy consumption (on a British

32 Thermal Unit - BTU basis), the Proposed Project would consume far less energy directly than the

33 current system does (see Table 4-20 below). The difference in energy consumption can be

- 34 attributed to the relative efficiency of electric powered vehicles and the relative inefficiency of 25 discel neuronal architeles
- 35 diesel-powered vehicles.
- 36 The continued diesel use, albeit substantially lower with the Proposed Project, would continue use
- 37 of non-renewable fossil fuels. To the extent that electricity supplying the Proposed Project comes
- 38 from renewable sources (hydropower, sun, wind, geothermal), it would not represent an
- 39 irreversible use of resources. To the extent that electricity supplying the Proposed Project comes
- 40 from non-renewable sources (natural gas, coal, nuclear), it would represent an irreversible use of
- 41 those resources.

- Permanent visual alterations would result from the Proposed Project, comprising the introduction
 of poles and wires, and TPFs. Additionally, trees and mature vegetation would be removed and
 pruned. Some trees and vegetation would not be replaced on-site, resulting in a physical and
 aesthetic permanent change in certain locations. As documented in Section 3.1, *Aesthetics*, these
 physical changes would alter views from residential or business areas in various locations along the
 corridor, but they would not significantly obscure a scenic view or vista. However, even with
 mitigation, some local visual character would be permanently altered.
- 8 The Proposed Project would also introduce a new source of EMF along the project alignment. As 9 detailed in Section 3.5, *Electromagnetic Fields and Electromagnetic Interference*, the Proposed 10 Project would likely increase the level of EMF along the perimeter of the Caltrain ROW and at locations that passengers and workers frequent, such as passenger stations, on-board passenger 11 coaches and locomotives, and at the perimeter of electrical substations. The EMF environment 12 13 resulting from the Proposed Project would have field levels similar to those in the vicinity of 14 moderate voltage utility transmission and distribution lines, but unlike the utility environment, the 15 EMF fields from electrified Caltrain operations would be highest only during peak revenue 16 operations, lessening during lower volume periods to become nominal during the late night when 17 train service is discontinued and/or only line maintenance is proceeding. The field strengths are 18 below ranges identified as levels of concern for human health effects. While the Proposed Project 19 would permanently change the EMF field levels along the corridor as long as electrified trains 20 utilized the corridor, this change is not irreversible. If a new preferable power source were 21 identified in the future that replaced electrified service, then the EMF fields from the electrified service would be removed. 22

23 **4.4 Growth-Inducing Impacts**

- 24 CEQA requires a consideration of a project's capacity to induce growth.
- 25 Growth inducement would occur if the amount of population or employment growth projected to
- 26 occur as a result of the Proposed Project would exceed planned levels. Increased development and
- 27 growth in an area are dependent on a variety of factors, including employment and other
- opportunities, availability of developable land, and availability of infrastructure, water, and power
 resources.
- 30A growth inducement analysis was conducted for the Proposed Project, as described in Section 3.12,31Population and Housing. This analysis determined that the Proposed Project's changes in travel time32savings would have little to no effect on the overall growth pressures in the project corridor because33Caltrain serves only developed areas within a well-established rail corridor and the Proposed
- 34 Project would not extend this corridor or provide access to undeveloped areas.

35 4.5 Energy

Under the Proposed Project, use of EMUs for approximately 75 percent of Caltrain's fleet for service
 between San Francisco and San Jose would require electrical energy to power the new EMUs and
 would increase electricity demand. Table 4-24 summarizes the annual direct energy consumption
 associated with the new EMUs under the Proposed Project by year 2020 and with full electrification
 in 2040 and compares this energy consumption to the existing Caltrain system and No Project

- 1 <u>conditions for 2020 and 2040. The overall energy consumption is calculated on a British Thermal</u>
- 2 <u>Unit (BTU) basis and accounts for both train operation and idling. Transmission and distribution</u>
- 3 loses for electricity are included in electricity totals as well as direct electricity consumption.

4 Table 4-24. Annual Direct Energy Consumption

<u>Scenario</u>	<u>Train Fuel Use</u>	<u>Diesel</u> (gallons)ª	<u>Electricity</u> (kwh)	<u>Direct</u> <u>Energy Use</u> (<u>million</u> <u>BTUs)^b</u>	<u>Avoided</u> <u>VMT</u> gallons/year	<u>Net Direct</u> <u>Energy Use</u> <u>Million BTU</u> (w/ VMT <u>reduction)</u>	
Existing	All diesel with electricity for shore power at terminal	4,452,984	4,214,860	<u>633,346</u>	<u>0</u>	<u>633,346</u>	
<u>No Project</u> <u>(2020)</u>	All diesel with electricity for shore power at terminals	<u>5,599,784</u>	<u>4,214,860</u>	<u>792,751</u>	<u>0</u>	<u>792,751</u>	
Proposed	<u>SF – SJ: 75% EMUs/</u>	<u>1,073,711</u>	88,817,309	<u>452,290</u>	<u>-1,718,058</u>	<u>237,533</u>	
<u>Project</u> (2020)	<u>25% Diesel</u>						
	<u>Gilroy – SJ: 100% Diesel</u>						
<u>No Project</u> <u>(2040)</u>	All diesel with electricity for shore power at terminals	<u>5,725,108</u>	<u>4,214,860</u>	<u>810,171</u>	<u>0</u>	<u>810,171</u>	
<u>Fully</u>	<u>SF – SJ: Electrified</u>	<u>146,615</u>	112,027,827	<u>402,618</u>	<u>-2,952,584</u>	<u>33,545</u>	
<u>Electrified</u> (2040)	<u>Gilroy – SJ: Diesel</u>						
^a Fuel use f ^b BTU facto	from Appendix B, <i>Air Quali</i> ors from USEPA 2004: Dies	<u>ty and Greenl</u> el—139.000	<i>house Gas Analy</i> BTU/gallon; El	vsis Technical I lectricity—3,4	<u>Data.</u> 12 BTU/kwh.		
While Propos the ele and Sa <u>As sho</u>	 <u>While the Proposed Project would use far more electricity than the present Caltrain system, the Proposed Project would use far less diesel fuel. As stated in Section 3.13, <i>Public Services and Utilities,</i> the electricity use in 2040 would be approximately 0.5% of the total electricity demand in San Mateo and Santa Clara Counties. ³²</u> <u>As shown in Table 4-24, the Proposed Project would consume substantially less energy directly than</u> 						
<u>the cur</u> vehicle	<u>rent system does since it</u> es. The difference in energ	<u>would repla</u> v consumpt	ice diesel-pow ion can be attr	<u>ered vehicles</u> ributed to the	relative efficie	<u>powerea</u> encv of electric-	
power	ed vehicles and the relativ	ve inefficien	cy of diesel-po	wered vehicle	es. The Propos	ed Project	
<u>itself w</u>	vould represent an efficient	nt transport	ation option as	s compared to	o the existing (<u>Caltrain system.</u>	
<u>Overal</u> Project	l, there would be no signi t's direct energy consump	ficant physic tion, becaus	cal environmen e the project v	ntal impact as vould lower c	ssociated with overall energy	<u>the Proposed</u> consumption.	
³² By way of would be 27	f comparison, the estimated 7 million kWh/year (City of N	<u>annual electri</u> Menlo Park 20	icity demand of)11). The Apple	<u>the Facebook I</u> Campus 2 proi	<u>Menlo Park cam</u> lect in Cuperting	<u>pus project</u> o would have a	

would be 27 million kWh/year (City of Menlo Park 2011). The Apple Campus 2 project in Cupertino would have a projected electricity demand of 142 million kWh/year, but expects to supply the majority of this power from onsite photovoltaic and fuel cell systems with the remainder from off-site renewable energy direct access power (City of Cupertino 2012).

5

15 16

1	The project represents a lowering of energy use in the transportation sector compared to existing
2	and No Project conditions and thus there is no need per Appendix F of the CEQA guidelines to
3	consider alternatives with lower transportation energy use or to consider mitigation relative to
4	transportation energy use.
5	The physical environmental impacts associated with the energy infrastructure system are described
6	in Section 3.13, Public Services and Utilities. The Proposed Project's increase in electricity demand
7	would be supported by the Pacific Gas and Electric (PG&E) existing transmission and generation
8	system. Section 3.2, Air Quality, also describes the emissions associated with the Proposed Project's
9	electricity consumption, whereby the Proposed Project emissions would be lower than the existing
10	Caltrain system condition in both 2020 and 2040. The difference in emissions would be a direct
11	result of the Proposed Project, which would consume less diesel fuel than the existing Caltrain
12	system and would operate energy-efficient EMUs. Section 3.7, Greenhouse Gas Emissions and Climate
13	Change, states that the Proposed Project would substantially reduce operational Caltrain system
14	greenhouse gas emissions even with the increased electricity demand, as the electric vehicles would
15	<u>be more energy efficient than the diesel-powered vehicles. In both cases, the Proposed Project</u>
16	would introduce an environmental benefit relative to emissions.